MIL-F-60042B (PA)
14 MARCH 1975
SUPERSEDING
MIL-F-60042A
6 September 1973

MILITARY SPECIFICATION

FUZE, BASE DETONATING, M578
PARTS - WITH DETONATOR

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the parts and sub-assemblies for one type fuze designated as Fuze, Base Detonating, M578 Parts, with Detonator.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-P-116 - Preservation, Methods of
MIL-D-45441 - Detonator, Stab, M61 Assembly Loading
MIL-A-48078 - Ammunition, Standard Quality Assurance Provision, General Specification for

STANDARDS

FEDERAL

Federal Test Methods Standard No. 151 - Metals; Test Methods

FSC: 1390

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-STD-331 - Fuze and Fuze Components, Environmental and Performance Tests For

DRAWINGS

PICATINNY ARSENAL

8796522 - Marking Diagram and Sealing for Wooden Packing Boxes
8886433 - Fuze, Base Detonating, M578, Parts with Detonator
8887101 - Box, Fiber for Fuze, BD, M578
8887102 - Box, Packing, Ammunition for Fuze, BD, M578

3. REQUIREMENTS

3.1 Materials. - The materials shall be in accordance with applicable drawings and specifications.

3.2 Parts and Assemblies. - The parts and assemblies shall comply with all requirements of Drawing 8886433 and with all requirements specified in applicable specifications.

3.3 Embrittlement of Springs. - The segment spring, creep spring, and safety plunger spring shall not break when pulled to the minimum point of permanent distortion.

3.4 Jolt and Jumble. - The assembly (dwg. 8886433) shall comply with the requirements of Standard MIL-STD-331, Test Nos. 101.1 and 102.1.

3.5 Transportation Vibration. - The assembly (dwg. 8886433) shall comply with the requirements of Standard MIL-STD-331, Test No. 104, Procedure II. After the fuzes are subjected to transportation vibration, the arming delay assembly and the locking segment and striker needle assembly shall meet the arm, disarm and arming time requirements of 3.8.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:19Z
Check the source to verify that this is the current version before use.

3.6 Workmanship. - All parts and assemblies shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust, corrosion products and other foreign material. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. All required markings shall be neat and sharply defined.

3.7 Proving Ground

3.7.1 Arming Safety. - The fuze (dwg. 8886434) shall not function within sixteen (16) feet minimum from the muzzle of the gun.

3.7.2 Functioning. - The fuze (dwg. 8886434) shall arm within 150 feet maximum from the muzzle of the gun.

3.8 Spin Tests

3.8.1 Arming Delay Assembly - Arming, Non-Arm and Arming Time. - When the loaded arming delay assembly is spun about its axial center to the specified speeds, the assembly shall be armed or disarmed with arming time as follows:

RPM	SHUTTER POSITION	ARMING TIME
6,500 Min.	Disarmed	
9,000 - 100	Armed	.036 to .080 Sec
15,000 - 200	Armed	.020 to .040 Sec.

NOTE: Alternate Timing Requirement, - The Arming Time Test at 9,000 RPM is an alternate to the test at 15,000 RPM.

3.8.2 Locking Segment and Striker Needle Assembly.

3.8.2.1 Non-Arming. - Locking segment shall not open when spun at 6000 RPM (min.).

3.8.2.2 Arming. - Locking segment shall be fully open when spun at 8500 RPM (max.), returning to the fully closed position on cessation of spin.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

3.9 First Article Inspection. - This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspection and Standard Quality Assurance Provisions. - Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of the detail specification.

4.2 Classification of Inspections. - The following types of inspection shall be conducted on this item:

a. First Article or Initial Production Inspection.
b. Production Quality Conformance Inspection.

4.3 First Article Inspection

4.3.1 Submission. - The contractor, prior to initiation of regular production, shall submit a First Article Sample to a Government approved facility as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2. The First Article Sample shall consist of 100 fuze assemblies (with detonators) and 50 complete sets of parts (i.e. 50 each of every component and sub-assembly). An additional submission, for Ballistic Tests at Proving Ground, of one hundred fifty (150) metal parts assemblies with detonators that have been inspected for compliance with the drawings and this specification shall be assembled to complete rounds for which the fuze is standard. The assemblies shall not be submitted for ballistic testing prior to acceptance of the sample at the contractor's plant unless otherwise directed by the Contracting Officer.

4.3.2 Inspection to be Performed. - The First Article Sample assemblies and components shall be inspected for conformance with any or all of the requirements of this specification including proving grounds tests, and any or all of the requirements of the applicable drawings (see Table 1). All inspections listed in Table 1 shall be classified Major unless otherwise specified.

4.3.3 Rejection. - See MIL-A-48078 (PA). In the ballistic tests, if a premature burst occurs or one or more fuzes fail to comply with the requirements of 3.7.1, the initial production sample shall be rejected. In addition, if two or more fuzes fail to comply with 3.7.2, the initial production lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

TABLE 1 -- FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE		SHEET 1 OF 8		DRAWING NUMBER
	Fuze, Base Detonating, M578 Parts, Assemblies and Subassemblies				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Fuze Body (Dwg. 8886429)				
	Examination for Defects	50		3.2/3.6	4.4.2.1
	Booster Lead Cup (Dwg. 9276737)				
	Examination for Defects	50		3.2/3.6	4.4.2.2
	Disc Cover (Dwg. 9276736)				
	Examination for Defects	50		3.2/3.6	4.4.2.3
	Alignment Screw (Dwg. 8860739)				
	Examination for Defects	50		3.2/3.6	4.4.2.4
	Spring, Segment (Dwg. 8860744)				
	Examination for Defects	50		3.2/3.6	4.4.2.5
	Embrittlement Test	50		3.3	4.5.1
	Segment (Dwg. 8860745)				
	Examination for Defects	50		3.2/3.6	4.4.2.6

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

TABLE 1 -- FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 8		DRAWING NUMBER
	Fuse, Base Detonating, M578 Parts, Assemblies and Subassemblies				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Plate, Segment Holder (Dwg. 8860746)				
	Examination for Defects	50		3.2/3.6	4.4.2.7
	Holder, Segment (Dwg. 8860742)				
	Examination for Defects	50		3.2/3.6	4.4.2.8
	Pin, Holder (Dwg. 8860743)				
	Examination for Defects	50		3.2/3.6	4.4.2.9
	Segment Holder Assembly (Dwg. 8860741)				
	Examination for Defects	50		3.2/3.6	4.4.2.10
(a)	Striker Locking Segment Assembly--Prior to Assembling Cover (Dwg. 8860740)				
	Examination for Defects	50		3.2/3.6	4.4.2.11
	Cover (Dwg. 8860747)				
	Examination for Defects	50		3.2	4.4.2.12

NOTES:

(a) To be performed at contractor's facility.

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

TABLE 1 -- FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE: Fuze, Base Detonating, M578 Parts, Assemblies and Subassemblies		SHEET 3 OF 8		DRAWING NUMBER: See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Segment, Striker Locking Assembly (Dwg. 8860740)				
	Examination for Defects	50		3.2/3.6	4.4.2.13
	Spring, Creep (Dwg. 8860750)				
	Examination for Defects	50		3.2/3.6	4.4.2.14
	Embrittlement Test	50		3.3	4.5.1
	Body, Striker (Dwg. 8860748)				
	Examination for Defects	50		3.2/3.6	4.4.2.15
	Ring, Retaining (Dwg. 8861063)				
	Examination for Defects	50		3.2/3.6	4.4.2.16
	Needle, Striker (Dwg. 9207461/8860749)				
	Examination for Defects	50		3.2/3.6	4.4.2.17
	Locking Segment and Striker Needle Assy. (Dwg. 8860738)				
	Examination for Defects	50		3.2/3.6	4.4.2.18
	Non-Arming Spin Test	50		3.82	4.5.2.1
	Arming Spin Test	50		3.82	4.5.2.2

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 202640-26104:192
Check the source to verify that this is the current version before use.

8

TABLE 1 -- FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
	Fuze, Base Detonating, M578 Parts, Assemblies and Subassemblies	4 OF 8	See Below
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Body, Delay (Dwg. 8860754) Examination for Defects	50		3.2/3.6	4.4.2.19
	Shaft, Shutter (Dwg. 8860755) Examination for Defects	50		3.2/3.6	4.4.2.20
	Plate, Locking (Dwg. 8860773) Examination for Defects	50		3.2/3.6	4.4.2.21
	Pin, Spring (Dwg. 8860756) Examination for Defects	50		3.2/3.6	4.4.2.22
	Strip, Retaining Plunger (Dwg. 8860764) Examination for Defects	50		3.2/3.6	4.4.2.23
	Delay Body Assembly (Dwg. 8860753) Examination for Defects	50		3.2/3.6	4.4.2.24

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

TABLE 1 -- FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE		SHEET 5 OF 8		DRAWING NUMBER
	Fuze, Base Detonating, M578 Parts, Assemblies and Subassemblies				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Pinion (Dwg. 8860759)				
	Examination for Defects	50		3.2/3.6	4.4.2.25
	Escape Wheel (Dwg. 8860758)				
	Examination for Defects	50		3.2/3.6	4.4.2.26
	Hardness Test	30		3.2	4.5.4
	Escape Wheel and Pinion Assembly (Dwg. 8860757)				
	Examination for Defects	50		3.2/3.6	4.4.2.27
	Load and Torque Test	50		3.2	4.5.5
	Shutter (Dwg. 8860770)				
	Examination for Defects	50		3.2/3.6	4.4.2.28
	Pin, Shutter (Dwg. 8860772)				
	Examination for Defects	50		3.2	4.4.2.29
	Weight (Dwg. 8860771)				
	Examination for Defects	50		3.2	4.4.2.30

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

TABLE 1 -- FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 6 OF 8		DRAWING NUMBER See Below
	Fuze, Base Detonating, M578 Parts, Assemblies and Subassemblies				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Shutter Assembly Loaded (Dwg. 8860769) Examination for Defects	50		3.2/3.6	4.4.2.31
	Plate, Cover (Dwg. 8860762) Examination for Defects	50		3.2	4.4.2.32
	Pivot-Tube (Dwg. 8860763) Examination for Defects	50		3.2/3.6	4.4.2.33
	Plate, Cover, Assembly (Dwg. 8860761) Examination for Defects	50		3.2/3.6	4.4.2.34
	Pallet (Dwg. 8860760) Examination for Defects	50		3.2/3.6	4.4.2.35
	Segment, Timing (Dwg. 8860766) Examination for Defects	50		3.2/3.6	4.4.2.36

NOTES:

Source: https://assist.dla.mil -- Downloaded: 20261[illegible]
Check the source to verify that this is the current version before use.

TABLE 1 -- FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE		SHEET 7 OF 8		DRAWING NUMBER
	Fuze, Base Detonating, M578 Parts Assemblies and Subassemblies				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Spring, Plunger, Safety (Dwg. 8860767)				
	Examination for Defects	50		3.2/3.6	4.4.2.37
	Embrittlement Test	50		3.3	4.5.1
	Washer, Segment, Timing (Dwg. 8860765)				
	Examination for Defects	50		3.2/3.6	4.4.2.38
	Plunger, Safety (Dwg. 8860768)				
	Examination for Defects	50		3.2/3.6	4.4.2.39
(b)	Arming Delay Assembly, Loaded (Dwg. 8860752)				
	Examination for Defects	50		3.2/3.6	4.4.2.40
	Non-Arming Test	50		3.8.1	4.5.3.1
	Arming Test	50		3.8.1	4.5.3.2
	Arming, Delay Time Test	50		3.8.1	4.5.3.3
(a)	Fuze Assembly, Prior to Assembling Alignment Screw, and Loaded Arming Delay Assy. (Dwg. 8886433)				
	Examination for Defects	50		3.2/3.6	4.4.2.41

NOTES: (b) Loaded with Detonators
(a) To be performed at Contractor's Facility

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

TABLE 1 -- FIRST ARTICLE SAMPLE

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE			SHEET 8 OF 8	DRAWING NUMBER
	Fuze, Base Detonating, M578 Parts, Assemblies and Subassemblies				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
(a) (b)	Fuse Assembly, Prior to Assembling Booster Leadcup (Dwg. 8886433)				
	Examination for Defects	50		3.2/3.6	4.4.2.42
(b)	Fuse Metal Parts Assembly (Dwg. 8886433)				
	Examination for Defects	50		3.2/3.6	4.4.2.43
	Jolt Test	50		3.4	4.4.3.3
	Jumble Test	50		3.4	4.4.3.3
	Transportation Vibration	50		3.5	4.4.3.4
	Washer, Detonator (Dwg. 9204556)				
	Examination for Defects	50		3.2	4.4.2.49
	Fuze, Base Detonating -- M578-Loaded with Booster Lead and Booster into Loaded Rounds (Dwg. 8886434 Assembled into Complete Round M393)				
	Arming Safety Test	150	(c)	3.7.1	4.5.6.1
	Functioning Test	150	(d)	3.7.2	4.5.6.2
	Washer, Striker (Dwg. 8860751)				
	Examination for Defects	50		3.2	4.4.2.52

NOTES:
(a) To be Performed at Contractor's plant
(b) Loaded with Detonators
(c) 4.4.3.7.1
(d) 4.4.3.7.2
(e) At Proving Ground

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

4.4 Quality Conformance Inspection

4.4.1 Inspection Lot Formation. - Inspection lots shall comply with lot formation provisions of MIL-A-48078. Each lot shall contain detonators of one interfix lot from one manufacturer.

4.4.2 Examination. - See MIL-F-48078.

a. Sampling Plans. - Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, level II.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:19Z
Check the source to verify that this is the currentversion before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER 8886429
4.4.2.1	Fuse Body		NEXT HIGHER ASSEMBLY 8886433

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major A					
101	Concentricity of outside diameter with pitch diameter of external thread		0.40%	3.2	Gage
102	Concentricity of arming delay assembly cavity with internal thread		0.40%	3.2	Gage
103	Concentricity of locking Segment and Striker Needle Assy Cavity with Internal Thread		0.40%	3.2	Gage
104	Concentricity of Locking Segment and Striker Needle Assembly Cavity		0.40%	3.2	Gage
Major B					
131	Pitch Diameter of External Thread		0.40%	3.2	Gage
132	Major Diameter of External Thread		0.40%	3.2	Gage
133	Diameter of striker ball cavity, min.		0.40%	3.2	Gage
Minor					
201	Pitch Diameter of Internal Thread		0.65%	3.2	Gage
202	Minor Diameter of Internal Thread		0.65%	3.2	Gage
203	Depth of Internal Thread, max.		0.65%	3.2	Gage
204	Length of Engagement of Internal Thread, min.		0.65%	3.2	Gage
205	Length of Internal Chamfer, min.		0.65%	3.2	Gage
206	Concentricity of Internal Thread with Outside diameter		0.65%	3.2	Gage
207	Perpendicularity of Internally Threaded End of Body with Outside Diameter		0.65%	3.2	Gage

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil - Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 8886429
4.4.2.1	Fuze Body				NEXT HIGHER ASSEMBLY 8886433
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
208	Diameter of Locking Segment and Striker Needle Assembly Cavity		0.65%	3.2	Gage
209	Diameter of Locking Segment and Striker Needle Assembly Pilot Cavity		0.65%	3.2	Gage
210	Diameter of Striker Ball Cavity, max.		0.65%	3.2	Gage
211	Concentricity of Striker Ball Cavity with locking Segment and Striker Needle Assembly Cavity		0.65%	3.2	Gage
212	Pitch Diameter of Alignment Screw Hole		0.65%	3.2	Gage
213	Minor Diameter of Alignment Screw Hole		0.65%	3.2	Gage
214	Outside Diameter		0.65%	3.2	Gage
215	Depth of Bottom of Striker Ball Cavity		0.65%	3.2	Gage
216	Depth of Bottom of Locking Segment and Striker Needle Assembly Pilot Cavity		0.65%	3.2	Gage
217	Length of Locking Segment and Striker Needle Assembly Pilot Cavity		0.65%	3.2	Gage
218	Overall Length		0.65%	3.2	Gage
219	Length from Face of Body to End of External Thread		0.65%	3.2	Gage
220	Length of Engagement of External Thread, min.		0.65%	3.2	Gage
221	Surface Finish		0.65%	3.2/3.6	Visual/Gage (See 6.4)
222	Chamfer Missing		0.65%	3.2	Visual
223	Location of Alignment Screw Hole.		0.65%	3.2	Gage
224	Diameter of External Thread Pilot		0.65%	3.2	Gage
225	Protective Finish Missing or Damaged		0.65%	3.2/3.6	Visual
226	Marking Misleading or Unidentifiable		0.65%	3.2/3.6	Visual
227	Evidence of Poor Workmanship		0.65%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.2	Booster Lead Cup	1	2	9276737
				NEXT HIGHER ASSEMBLY 8886433

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major A					
101	Thickness of Bottom Lead Cavity		0.40%	3.2	Gage
102	Flatness of Base		0.40%	3.2	Gage
Minor					
201	Pitch Diameter of Thread		0.65%	3.2	Gage
202	Major Diameter of Thread		0.65%	3.2	Gage
203	Diameter of Lead Charge		0.65%	3.2	Gage
204	True Position of Lead Charge Cavity with Thread		0.65%	3.2	Gage
205	Depth of Booster Pellet Cavity		0.65%	3.2	Gage
206	Diameter of Booster Pellet Cavity		0.65%	3.2	Gage
207	Runout of Booster Pellet Cavity with Thread		0.65%	3.2	Gage
208	True Position of Thread Pilot at Base End		0.65%	3.2	Gage
209	Thickness of Bottom of Booster Pellet Cavity		0.65%	3.2	Gage
210	Diameter of Thread Pilot at Base End		0.65%	3.2	Gage
211	Diameter of Cover Disc Cavity		0.65%	3.2	Gage
212	Length of Thread Pilot at Base End		0.65%	3.2	Gage
213	Length from Base End to Shoulder		0.65%	3.2	Gage
214	Width Across Wrench Flats		0.65%	3.2	Gage
215	Chamfer Missing or Incorrect		0.65%	3.2	Visual
216	Surface Finish		0.65%	3.2/3.6	Visual-Gage (see 6.4)
217	Radii		0.65%	3.2	Visual
218	Perpendicularity of Base		0.65%	3.2	Gage
219	Protective Finish Missing or Damaged		0.65%	3.2/3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 9276737
4.4.2.2	Booster Lead Cup				NEXT HIGHER ASSEMBLY 8886433
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
220	Evidence of Poor Workmanship		0.65%	3.6	Visual
221	Outside Diameter		0.65%	3.2	Gage

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.3	Disc, Cover	1	1	9276736
				NEXT HIGHER ASSEMBLY 8886433

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major B					
131	Thickness		0.40%	3.2	Gage
Minor					
201	Diameter		0.65%	3.2	Gage
202	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil - Downloaded: 202610-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.4	Alignment Screw		8860739
			NEXT HIGHER ASSEMBLY 8886433

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major	None Defined				
Minor					
201	Total Length		0.65%	3.2	Gage
202	Pitch Diameter of Thread		0.65%	3.2	Gage
203	Major Diameter of Thread		0.65%	3.2	Gage
204	Diameter of Shank		0.65%	3.2	Gage
205	Length to Thread Shoulder		0.65%	3.2	Gage
206	Chamfer Missing		0.65%	3.2	Visual
207	Protective Finish Missing or Damaged		0.65%	3.2	Visual
208	Evidence of Poor Workmanship		0.65%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.5	Spring, Segment	1	1	8860744
				NEXT HIGHER ASSEMBLY: 8860740

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Embrittlement Test	10	100%	3.3	4.5.1
Major B					
131	Length of Coiled Section. - Max.		0.40%	3.2	Gage
Minor					
201	Inside Diameter		0.65%	3.2	Gage
202	Length of Short Tang		0.65%	3.2	Gage
203	Length of Long Tang		0.65%	3.2	Gage
204	Protective Coat Missing or Damaged		0.65%	3.6	Visual
205	Evidence of Poor Workmanship		0.65%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil - Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.6	Segment				8860745
					NEXT HIGHER ASSEMBLY 8860740
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major A					
101	Profile		0.40%	3.2	Gage
Major B					
131	Location of Pivot and Spring Holes		0.40%	3.2	Gage
132	Diameter of Pivot Hole		0.40%	3.2	Gage
133	Finish Improper		0.40%	3.6	Visual-Gage (see 6.4)
134	Burrs		0.40%	3.6	Visual
Minor					
201	Thickness		0.65%	3.2	Gage
202	Evidence of Poor Workmanship		0.65%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

MIL-F-60042B (PA)

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET OF	DRAWING NUMBER
4.4.2.7	Plate, Segment Holder		1 1	8860746
				NEXT HIGHER ASSEMBLY 8860740

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major A					
101	Concentricity of Hole with Outside Diameter		0.40%	3.2	Gage
Major B					
131	Flatness		0.40%	3.2	Gage
132	Surface Finish		0.40%	3.6	Visual-Gage (see 6.4)
133	Burrs		0.40%	3.6	Visual
Minor					
201	Length of Slots		0.65%	3.2	Gage
202	Width of Slots		0.65%	3.2	Gage
203	Diameter of Center Hole		0.65%	3.2	Gage
204	Outside Diameter		0.65%	3.2	Gage
205	Chamfer		0.65%	3.2/3.6	Visual
206	Location of Slots with Respect to Outside Diameter		0.65%	3.2	Gage
207	Protective Finish Missing or Damaged		0.65%	3.6	Visual
208	Evidence of Poor Workmanship		0.65%	3.6	Visual

NOTES;

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil - Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER 8860742
4.4.2.8	Holder, Segment				NEXT HIGHER ASSEMBLY 8860741
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major A					
101	Perpendicularity of Rear Surface with Striker Cavity		0.40%	3.2	Gage
102	Ends Not Parallel		0.40%	3.2	Gage
103	Concentricity of Striker Bore with Large Outside Diameter		0.40%	3.2	Gage
104	Concentricity of Segment Cavity with Outside Dia.		0.40%	3.2	Gage
105	Concentricity of Striker Hole with Outside Dia.		0.40%	3.2	Gage
Major B					
131	Concentricity of Small Outside Dia. with Large Outside Dia.		0.40%	3.2	Gage
132	Dia. of Segment Cavity		0.40%	3.2	Gage
133	Depth of Segment Cavity, min.		0.40%	3.2	Gage
134	Dia. of Holder Pin Hole, max.		0.40%	3.2	Gage
135	Location of Holder Pin Hole		0.40%	3.2	Gage
136	Location of Segment Spring Hole		0.40%	3.2	Gage
137	Location of Segment Spring Anchor Hole		0.40%	3.2	Gage
138	Finish of Striker Bore		0.40%	3.2/3.6	Visual-Gage (see 6.4)
139	Finish of Segment Cavity		0.40%	3.2/3.6	Visual-Gage (See 6.4)
140	Burrs		0.40%	3.2	Visual
Minor					
201	Diam. of Striker Bore		0.65%	3.2	Gage

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 2 OF 2	DRAWING NUMBER
4.4.2.8	Holder, Segment		8860742
			NEXT HIGHER ASSEMBLY
			8860741

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
202	Diameter of Segment Cavity		0.65%	3.2	Gage
203	Depth of Segment Cavity, max.		0.65%	3.2	Gage
204	Diameter of Striker Hole		0.65%	3.2	Gage
205	Diameter of Holder Pin Hole, min.		0.65%	3.2	Gage
206	Diameter of Segment Spring Hole		0.65%	3.2	Gage
207	Diameter of Small outside diameter		0.65%	3.2	Gage
208	Diameter of Inside Counterbore		0.65%	3.2	Gage
209	Concentricity of Inside Counterbore with Outside Diameter		0.65%	3.2	Gage
210	Depth of Inside Counter Bore		0.65%	3.2	Gage
211	Overall Length		0.65%	3.2	Gage
212	Depth of Segment Spring Clearance Hole		0.65%	3.2	Gage
213	Thickness at Base of Striker Cavity		0.65%	3.2	Gage
214	Depth of Holder Pin Holes		0.65%	3.2	Gage
215	Outside Diameter		0.65%	3.2	Gage
216	Diameter of Segment Spring Anchor Holes		0.65%	3.2	Gage
217	Depth of Segment Spring Anchor Holes		0.65%	3.2	Gage
218	Evidence of Poor Workmanship		0.65%	3.6	Visual
219	Protective Finish Missing or Damaged		0.65%	3.6	Visual
220	Diameter of Retaining Ring Groove		0.65%	3.2	Gage
221	Location of Retaining Ring Groove		0.65%	3.2	Gage
222	Width of Retaining Ring Groove		0.65%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.9	Pin, Holder	1 OF 1	8860743
			NEXT HIGHER ASSEMBLY: 8860741

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major B					
131	Diameter, min		0.40%	3.2	Gage
132	Finish of Diameter		0.40%	3.2/3.6	Visual-Gage (See 6.4)
Minor					
201	Diameter, max.		0.65%	3.2	Gage
202	Length		0.65%	3.2	Gage
203	Chamfer		0.65%	3.2	Gage

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:19Z
Check the source to verify that this is the currentversion before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.10	Segment Holder Assembly	1 OF 1	8860741
			NEXT HIGHER ASSEMBLY 8860740

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major B					
131	Protrusion of Holder Pin		0.40%	3.2	Gage
Minor					
201	Holder Pin Loose or Missing		0.65%	3.2/3.6	Visual-Manual
202	Evidence of Poor Workmanship		0.65%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil - Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.11	Striker Locking Segment Assembly, Prior to Assembling Cover				8860740
					NEXT HIGHER ASSEMBLY 8860738
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major B					
131	Distance between segments and centerline when held in armed position, min.		0.40%	3.2	Gage
132	Spring improperly assembled		0.40%	3.2	Visual
Minor					
201	Evidence of Poor Workmanship		0.65%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

12

Source: https://assist.dla.mil - Downloaded: 2026-10-26T04:49Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.12	Cover	1	1	8860747
				NEXT HIGHER ASSEMBLY 8860740

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major:	None Defined				
Minor:					
201	Length		0.65%	3.2	Gage
202	Thickness		0.65%	3.2	Gage
203	Inside Diameter		0.65%	3.2	Gage
204	Diameter of Hole		0.65%	3.2	Gage
205	Concentricity of Hole		0.65%	3.2	Gage
206	Radii		0.65%	3.2	Visual-Gage
207	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.13	Segment, Striker Locking Assembly				8860740
					NEXT HIGHER ASSEMBLY
					8860738
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major B					
131	Functional Concentricity of Striker Needle Hole With Striker Assembly Cavity		0.40%	3.2	Gage
Minor					
201	Cover Crimp Incomplete		0.65%	3.2	Visual
202	Length, max.		0.65%	3.2	Gage
203	Any Component Improperly Assembled		0.65%	3.2	Visual
204	Evidence of Poor Workmanship		0.65%	3.2/3.6	Visual
205	Diameter, max.		0.65%	3.2	Gage

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.14	Spring, Creep		8860750
			NEXT HIGHER ASSEMBLY 8860738

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Load at Assembled Length, min.	10	100%	3.2	Gage
2	Embrittlement Test		100%	3.3	4.5.1
Major B					
131	Solid Height, max.		0.40%	3.2	Gage
132	Inside Diameter, min.		0.40%	3.2	Gage
133	Outside Diameter, max.		0.40%	3.2	Gage
Minor					
201	Load at Compressed Length, max.		0.65%	3.2	Gage
202	Evidence of Poor Workmanship		0.65%	3.6	Visual
203	Protective Finish Missing or Damaged		0.65%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 20261010-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8860748
4.4.2.15	Body, Striker				NEXT HIGHER ASSEMBLY 8860738
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major B					
131	Total Length		0.40%	3.2	Gage
132	Vent Holes Missing		0.40%	3.2	Visual
133	Flange Radius Missing		0.40%	3.2	Visual
Minor					
201	Diameter of Flange		0.65%	3.2	Gage
202	Diameter of Shank		0.65%	3.2	Gage
203	Length from Head End to Face of Flange		0.65%	3.2	Gage
204	Thickness of Flange		0.65%	3.2	Gage
205	Length of Thread, min.		0.65%	3.2	Gage
206	Diameter of Creep Spring Cavity		0.65%	3.2	Gage
207	Depth of Creep Spring Cavity		0.65	3.2	Gage
208	Diameter of Vent Holes		0.65%	3.2	Gage
209	Chamfer Missing		0.65%	3.2	Visual
210	Evidence of Poor Workmanship		0.65%	3.6	Visual
211	Pitch Diam. of Thread		0.65%	3.2	Gage
212	Minor Diameter of Thread		0.65%	3.2	Gage
213	Concentricity of Flange Diam. with Pitch Diam. of Thread		0.65%	3.2	Gage
214	Concentricity of Shank with Pitch Diameter		0.65%	3.2	Gage

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.16	Ring, Retaining		8861063
			NEXT HIGHER ASSEMBLY 8860738

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major	None Defined				
Minor					
201	Diameter		0.65%	3.2	Gage
202	Thickness		0.65%	3.2	Gage
203	Evidence of Poor Workmanship		0.65%	3.6	Visual-Gage

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.17	Needle, Striker		9207461/8860749
			NEXT HIGHER ASSEMBLY 8860738

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major B					
131	Profile of Point		0.40%	3.2	Gage
132	Diameter of Shank, max.		0.40%	3.2	Gage
Minor					
201	Concentricity of Shank With Pitch Diameter of Thread		0.65%	3.2	Gage
202	Pitch Diameter of Thread		0.65%	3.2	Gage
203	Major Diameter of Thread		0.65%	3.2	Gage
204	Length of Thread		0.65%	3.2	Gage
205	Total Length		0.65%	3.2	Gage
206	Dia. of Shank, min.		0.65%	3.2	Gage
207	Depth of Slot		0.65%	3.2	Gage
208	Width of Slot		0.65%	3.2	Gage
209	Finish Improper		0.65%	3.2	Visual-Gage (see 6.4)
210	Evidence of Poor Workmanship		0.65%	3.6	Visual
211	Diameter of Slotted End, max. (When Applicable)		0.65%	3.2	Gage

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8860738
4.4.2.18	Locking Segment and Striker Needle Assembly				NEXT HIGHER ASSEMBLY 8886433
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Creep Spring Missing		100%	3.2	Manual
2	Non-Arming Spin Test		100%	3.8.2	4.5.2.1
Major A					
101	Arming Spin Test	(a)		3.8.2	4.5.2.2
Major B					
131	Length of Striker Needle Protrusion		0.40%	3.2	Gage
132	Striker Body Bound (After Curing of Needle Thread Sealing Compound)		0.40%	3.2	Manual
133	Striker Needle Loose or Damaged		0.40%	3.2	Visual-Manual
Minor					
201	Evidence of Poor Workmanship		0.65%	3.6	Visual

NOTES: (a) 4.4.3.1.1.1, 4.4.3.1.1.2

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
4.4.2.19	Body, Delay				8860754
					NEXT HIGHER ASSEMBLY
					8860753
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major A					
101	Location of Shutter Cavity, Safety Plunger Slot, Locking Plate Recess and Armed Position Stop		0.40%	3.2	Gage
102	Location of Shutter Shaft Hole		0.40%	3.2	Gage
103	Diameter of Shutter Shaft Hole, max.		0.40%	3.2	Gage
104	Diameter of Cover Plate Location Holes		0.40%	3.2	Gage
105	Location of Cover Plate Location Holes		0.40%	3.2	Gage
106	Location of Escape Wheel and Pinion Assembly Cavity Hole		0.40%	3.2	Gage
107	Location of Escape Wheel and Pinion Bearing Hole		0.40%	3.2	Gage
108	Diameter of Escape Wheel and Pinion Bearing Hole		0.40%	3.2	Gage
109	Location of Spring Pin Hole		0.40%	3.2	Gage
110	Diameter of Spring Pin Hole, max.		0.40%	3.2	Gage
111	Location of Plunger Retaining Strip Slot		0.40%	3.2	Gage
112	Location of Pivot Tube Hole		0.40%	3.2	Gage
Major B					
131	Thickness of Body		0.40%	3.2	Gage
132	Depth of Shutter Cavity		0.40%	3.2	Gage
133	Depth of Safety Plunger Slot		0.40%	3.2	Gage
134	Depth of Timing Assembly Cavity		0.40%	3.2	Gage
135	Depth of Escape Wheel and Pinion Assembly Cavity		0.40%	3.2	Gage
136	Porosity in Pinion Bearing Area		0.40%	3.2/3.6	Visual
137	Improper Surface Finish		0.40%	3.2/3.6	Visual-Gage

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 8860754
4.4.2.19	Body, Delay				NEXT HIGHER ASSEMBLY 8860753
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
138	Diameter of Escape Wheel and Pinion Cavity, min.		0.40%	3.2	Gage
139	Diameter of Pivot Tube Hole, max.		0.40%	3.2	Gage
Minor					
201	Location of Threaded Holes		0.65%	3.2	Gage
202	Pitch Dia. of Threaded Holes		0.65%	3.2	Gage
203	Width of Plunger Retaining Strip Slot		0.65%	3.2	Gage
204	Height of Bottom of Safety Plunger Retaining Strip Slot Above Safety Plunger Slot		0.65%	3.2	Gage
205	Length of Safety Plunger Retaining Strip Slot		0.65%	3.2	Gage
206	Outside Diameter		0.65%	3.2	Gage
207	Distance to Base of Locating Slot		0.65%	3.2	Gage
208	Width of Locating Slot		0.65%	3.2	Gage
209	Symmetry of Locating Slot With Outside Dia.		0.65%	3.2	Gage
210	Height of Armed Position Stop		0.65%	3.2	Gage
211	Depth of Cover Plate Locating Holes		0.65%	3.2	Gage
212	Dia. of Escape Wheel and Pinion Cavity, max.		0.65%	3.2	Gage
213	Diameter of Spring Pin Hole, Min.		0.65%	3.2	Gage
214	Evidence of Poor Workmanship		0.65%	3.6	Visual
215	Diameter of Shutter Shaft Hole, Min.		0.65%	3.2	Gage

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8860755
4.4.2.20	Shaft, Shutter				NEXT HIGHER ASSEMBLY 8860753
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major A					
101	Diameter Below Head		0.40%	3.2	Gage
Major B					
131	Small Diameter		0.40%	3.2	Gage
132	Length of Diameter Below Head, max.		0.40%	3.2	Gage
Minor					
201	Total Length Below Head		0.65%	3.2	Gage
202	Length of Diameter Below Head, min.		0.65%	3.2	Gage
203	Thickness of Head		0.65%	3.2	Gage
204	Diameter of Head		0.65%	3.2	Gage
205	Concentricity of Diameter Below Head		0.65%	3.2	Gage
206	Radii		0.65%	3.2/3.6	Visual
207	Chamfers Missing		0.65%	3.2/3.6	Visual
208	Finish		0.65%	3.6	Visual/Gage (See 6.4)

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.21	Plate, Locking	1 OF 1	8860773
			NEXT HIGHER ASSEMBLY: 8860752

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major A					
101	Location of Hole		0.40%	3.2	Gage
Major B					
131	Burr		0.40%	3.6	Visual
132	Width, max.		0.40%	3.2	Gage
133	Thickness, max.		0.40%	3.2	Gage
134	Surface Finish		0.40%	3.6	Visual-Gage (See 6.4)
135	Diameter of Hole, min.		0.40%	3.2	Gage
136	Clearance at Inside Edge of Hole, min.		0.40%	3.2	Gage
Minor					
201	Inside Length		0.65%	3.2	Gage
202	Length of Short Tab		0.65%	3.2	Gage
203	Length of Long Tab		0.65%	3.2	Gage
204	Diameter of Hole, max.		0.65%	3.2	Gage
205	Clearance at Inside Edge of Hole, max.		0.65%	3.2	Gage

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8860756
4.4.2.22	Pin, Spring				NEXT HIGHER ASSEMBLY 8860753
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major B					
131	Diameter of Head, max.		0.40%	3.2	Gage
132	Diameter of Body, max.		0.40%	3.2	Gage
133	Radius Missing		0.40%	3.2/3.6	Visual
134	Finish		0.40%	3.6	Visual-Gage (See 6.4)
Minor					
201	Diameter of Body, min.		0.65%	3.2	Gage
202	Length		0.65%	3.2	Gage
203	Thickness of Head		0.65%	3.2	Gage
204	Diameter of Head, min.		0.65%	3.2	Gage

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.23	Strip, Retaining Plunger	1 OF 1	8860764
			NEXT HIGHER ASSEMBLY: 8860752

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major	None Defined				
Minor					
201	Thickness		0.65%	3.2	Gage
202	Width		0.65%	3.2	Gage
203	Length		0.65%	3.2	Gage
204	Evidence of Poor Workmanship		0.65%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8860753
4.4.2.24	Delay Body Assembly				NEXT HIGHER ASSEMBLY 8860752
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major B					
131	Component Loose		0.40%	3.2/3.6	Manual
132	Length of Spring Pin Protrusion, max.		0.40%	3.2	Gage
Minor					
201	Length of Spring Pin Protrusion, min.		0.65%	3.2	Gage
202	Height of Shutter Shaft Head, max.		0.65%	3.2	Gage
203	Evidence of Poor Workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:10Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8860759
4.4.2.25	Pinion				NEXT HIGHER ASSEMBLY 8860757
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major A					
101	Total Composite Error		0.40%	3.2	Gage
102	Concentricity of Escape Wheel Shaft Dia. with Cover Plate Bearing Diameter		0.40%	3.2	Gage
103	Tooth Profile		0.40%	3.2	Gage
104	Diam. of Delay Body Bearing Surface		0.40%	3.2	Gage
105	Diam. of Cover Plate Bearing Surface		0.40%	3.2	Gage
Major B					
131	Length of Delay Body Bearing Surface		0.40%	3.2	Gage
132	Length of Cover Plate Bearing Surface		0.40%	3.2	Gage
133	Thickness of Shoulder at Delay Body Bearing End		0.40%	3.2	Gage
134	Length From Face of Shoulder At Delay Body Bearing End of End of Pinion Teeth		0.40%	3.2	Gage
135	Length, From Face of Shoulder At Delay Body Bearing End to Face of Shoulder at Cover Plate Bearing End		0.40%	3.2	Gage
136	Burrs		0.40%	3.6	Visual
137	Finish Improper		0.40%	3.6	Visual-Gage (See 6.4)
Minor					
201	Dia. of Shoulders Adjacent to Bearing Surface		0.65%	3.2	Gage
202	Width of Escape Wheel Shoulder		0.65%	3.2	Gage

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8860758
4.4.2.26	Escape Wheel				NEXT HIGHER ASSEMBLY 8860757
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major A					
101	Profile of Teeth and Wheel Including Position of Teeth		0.40%	3.2	Gage
Major B					
131	Thickness		0.40%	3.2	Gage
132	Incorrect Number of Teeth		0.40%	3.2	Visual
133	Burr		0.40%	3.2/3.6	Visual
134	Hardness Test	30		3.2	4.5.4
Minor					
201	Evidence of Poor Workmanship		0.65%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.27	Escape Wheel and Pinion Assembly		8860757
			NEXT HIGHER ASSEMBLY 8860752

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Load and Torque Test	(a)		3.2	4.5.5
Major A					
101	Perpendicularity of Escape Wheel Face With Shaft		0.40%	3.2	Gage
102	Concentricity of Escape Wheel Diam. with pinion		0.40%	3.2	Gage
103	Stake Missing or Not Full 360 Degrees		0.40%	3.2	Visual
Minor					
201	Evidence of poor Workmanship		0.65%	3.6	Visual

NOTES: (a) 4.4.3.5

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil - Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
4.4.2.28	Shutter		8860770
			NEXT HIGHER ASSEMBLY 8860769

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major A					
101	Profile		0.40%	3.2	Gage
102	Concentricity of Flash Hole with Detonator Cavity		0.40%	3.2	Gage
103	Location of Detonator Cavity		0.40%	3.2	Gage
104	Location of Pivot Hole		0.40%	3.2	Gage
105	Location of Locking Plate Slot		0.40%	3.2	Gage
106	Location of Shutter Pin Holes		0.40%	3.2	Gage
Major B					
131	Thickness, max.		0.40%	3.2	Gage
132	Location of Weight Cavity		0.40%	3.2	Gage
133	Diam. of Pivot Hole		0.40%	3.2	Gage
134	Width of Safety Plunger Slot, min.		0.40%	3.2	Gage
135	Width of Locking Plate Slot, min.		0.40%	3.2	Gage
136	Diameter of Shutter Pin Holes		0.40%	3.2	Gage
137	Thickness at Base of Detonator Cavity		0.40%	3.2	Gage
138	Thickness From Base to Bottom of Locking Plate Slot, max.		0.40%	3.2	Gage
Minor					
201	Diameter of Detonator Cavity		0.65%	3.2	Gage
202	Diameter of Flash Hole Cavity		0.65%	3.2	Gage

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE	SHEET 2 OF 2	DRAWING NUMBER
4.4.2.28	Shutter		8860770
			NEXT HIGHER ASSEMBLY 8860769

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
203	Diam. of Weight Cavity		0.65%	3.2	Gage
204	Width of Safety Plunger Slot, max.		0.65%	3.2	Gage
205	Diameter of Shutter Pin Holes, min.		0.65%	3.2	Gage
206	Depth of Shutter Holes		0.65%	3.2	Gage
207	Thickness, min.		0.65%	3.2	Gage
208	Depth of Locking Plate Slot max.		0.65%	3.2	Gage
209	Width of Locking Plate Slot, max.		0.65%	3.2	Gage
210	Chamfer Missing		0.65%	3.6	Visual
211	Evidence of Poor Workmanship		0.65%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 20261010-20104.19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.29	Pin, Shutter		8860772
			NEXT HIGHER ASSEMBLY 8860769

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major B					
131	Diameter, min.		0.40%	3.2	Gage
Minor					
201	Diameter, max.		0.65%	3.2	Gage
202	Length		0.65%	3.2	Gage
203	Chamfer Missing		0.65%	3.2	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.30	Weight		8860771
			NEXT HIGHER ASSEMBLY
			8860769

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major	None Defined				
Minor					
201	Length		0.65%	3.2	Gage
202	Diameter		0.65%	3.2	Gage

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 20261020-261041 9Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8860769
4.4.2.31	Shutter Assembly, Loaded				NEXT HIGHER ASSEMBLY 8860752
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major B					
131	Projection of Shutter Pin		0.40%	3.2	Gage
132	Pin Loose		0.40%	3.2	Manual
133	Weight Improperly Staked		0.40%	3.2	Visual
134	Detonator Improperly Staked		0.40%	3.2	Visual
135	Weight or Any Other Material Above Flush		0.40%	3.2	Visual
136	Detonator Washer Missing		0.40%	3.2	Visual
Minor					
201	Evidence of Poor Workmanship		0.65%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

05

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER 8860762
4.4.2.32	Plate, Cover				NEXT HIGHER ASSEMBLY 8860761
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major A					
101	Location of Escape Wheel and Pinion Assembly Bearing Hole		0.40%	3.2	Gage
102	Flatness		0.40%	3.2	Gage
103	Diam. of Locating Bosses		0.40%	3.2	Gage
104	Location of Locating Bosses		0.40%	3.2	Gage
105	Diameter of Pivot Tube Hole, max.		0.40%	3.2	Gage
106	Diameter of Escape Wheel and Pinion		0.40%	3.2	Gage
Minor					
201	Thickness		0.65%	3.2	Gage
202	Protrusion of Locating Bosses		0.65%	3.2	Gage
203	Diam. of Pivot Tube Hole Counterbore		0.65%	3.2	Gage
204	Concentricity of Pivot Tube Hole Counterbore with Pivot Tube Hole		0.65%	3.2	Gage
205	Diameter of Screw Hole		0.65%	3.2	Gage
206	Location of Screw Holes		0.65%	3.2	Gage
207	Chamfer Missing		0.65%	3.2	Visual
208	Outside Diameter		0.65%	3.2	Gage
209	Concentricity of Outside Dia. with Pivot Tube Hole		0.65%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 8860762
4.4.2.32	Plate, Cover				NEXT HIGHER ASSEMBLY 8860761
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
210	Diameter of Shutter Shaft Head Hole		0.65%	3.2	Gage
211	Width of Locating Slot		0.65%	3.2	Gage
212	Symmetry of Locating Slot		0.65%	3.2	Gage
213	Diameter of Pivot Hole, min.		0.65%	3.2	Gage
214	Thickness from Bottom of Pivot Tube Counterbore to Bottom Face, max.		0.65%	3.2	Gage
215	Locating Boss Fails to Withstand Minimum Load		0.65%	3.2	Load Test

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

52

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.33	Pivot, Tube		8860763
			NEXT HIGHER ASSEMBLY 8860761

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major A					
101	Concentricity of Small Diam.		0.40%	3.2	Gage
102	Diameter of Ends		0.40%	3.2	Gage
Major B					
131	Thickness of Flange		0.40%	3.2	Gage
132	Concentricity of Flange		0.40%	3.2	Gage
133	Diameter of Hole, min.		0.40%	3.2	Gage
134	Length of Ends		0.40%	3.2	Gage
135	Finish		0.40%	3.2	Visual-Gage (See 6.4)
Minor					
201	Diameter of Flange		0.65%	3.2	Gage
202	Diameter of hole, max.		0.65%	3.2	Gage
203	Radii of Chamfer missing		0.65%	3.2	Gage
204	Evidence of Poor Workmanship		0.65%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8860761
4,4,2,34	Plate, Cover, Assembly				NEXT HIGHER ASSEMBLY 8860752
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major A					
101	Perpendicularity of Face with Pivot Tube		0.40%	3.2	Gage
102	Load Test of Pivot		0.40%	3.2	Test
103	Crimp Not Full 360 Degrees		0.40%	3.2	Visual
Major B					
131	Height of Pivot Tube Shoulder Above Cover Plate max.		0.40%	3.2	Gage
132	Inside Diameter of Pivot Tube, min.		0.40%	3.2	Gage
Minor					
201	Evidence of Poor Workmanship		0.65%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.35	Pallet		8860760
			NEXT HIGHER ASSEMBLY 8860752

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major A					
101	True Position of Hole		0.40%	3.2	Gage
102	Profile		0.40%	3.2	Gage
Major B					
131	Diameter of Hole		0.40%	3.2	Gage
132	Thickness		0.40%	3.2	Gage
133	Surface Finish		0.40%	3.2	Visual-Gage (See 6.4)
134	Radii, max.		0.40%	3.2	Visual
135	Burrs		0.40%	3.6	Visual
Minor					
201	Evidence of Poor Workmanship		0.65%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8860766
4.4.2.36	Segment, Timing				NEXT HIGHER ASSEMBLY 8860752
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major A					
101	Location of Gear Teeth		0.40%	3.2	Gage
102	Total Composite Error		0.40%	3.2	Gage
103	Location of Striker Needle Slot Including Concentricity with Pivot Hole		0.40%	3.2	Gage
104	Profile of Outside Surface Including Drive Slot and Gear Teeth		0.40%	3.2	Gage
105	Concentricity of Outside Dia. with Pivot Hole		0.40%	3.2	Gage
106	Profile of Striker Needle Slot		0.40%	3.2	Gage
Major B					
131	Location of Drive Hole		0.40%	3.2	Gage
132	Location of Drive Slot		0.40%	3.2	Gage
133	Diameter of Drive Hole		0.40%	3.2	Gage
134	Incorrect Number of Teeth		0.40%	3.2	Visual
135	Burrs		0.40%	3.6	Visual
136	Thickness, max.		0.40%	3.2	Gage
Minor					
201	Thickness, min.		0.65%	3.2	Gage
202	Evidence of Poor Workmanship		0.65%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.37	Spring, Plunger, Safety		8860767
			NEXT HIGHER ASSEMBLY 8860752

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Embrittlement Test		100%	3.3	4.5.1
Major B					
131	Solid Height, max.		0.40%	3.2	Gage
132	Outside Diameter, max.		0.40%	3.2	Gage
133	Inside Diameter, min.		0.40%	3.2	Gage
Minor					
201	Bare Spot in Protective Coating		0.65%	3.6	Visual
202	Evidence of Poor Workmanship		0.65%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.38	Washer, Segment, Timing		8860765
			NEXT HIGHER ASSEMBLY 8860752

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major B					
131	Thickness, max.		0.40%	3.2	Gage
Minor					
201	Thickness, min.		0.65%	3.2	Gage
202	Diameter of Hole		0.65%	3.2	Gage
203	Diameter		0.65%	3.2	Gage
204	Evidence of Poor Workmanship		0.65%	3.6	Visual

NOTES:

57

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B(PA)

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
4.4.2.39	Plunger, Safety		8860768
			NEXT HIGHER ASSEMBLY
			8860752

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major A					
101	Location of Stud, max.		0.40%	3.2	Gage
102	Location of Spring Cavity		0.40%	3.2	Gage
Major B					
131	Diameter of Stud, max.		0.40%	3.2	Gage
132	Diameter of Spring Cavity, min.		0.40%	3.2	Gage
133	Chamfer Missing		0.40%	3.2	Gage
134	Sharp or Burred Edges or Corners		0.40%	3.2	Gage
135	Width, max.		0.40%	3.2	Gage
136	Thickness, max.		0.40%	3.2	Gage
137	Width to Retaining Strip Recess, max.		0.40%	3.2	Gage
138	Thickness to Retaining Strip Recess, max.		0.40%	3.2	Gage
139	Overall Length, max.		0.40%	3.2	Gage
140	Depth of Spring Cavity, min.		0.40%	3.2	Gage
Minor					
201	Overall Length		0.65%	3.2	Gage
202	Length Excluding Stud		0.65%	3.2	Gage
203	Depth of Spring Cavity, max.		0.65%	3.2	Gage
204	Diameter of Stud, min.		0.65%	3.2	Gage
205	Diameter of Spring Cavity		0.65%	3.2	Gage
206	Width, min.		0.65%	3.2	Gage

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil - Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B(PA)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.4.2.39	Plunger, Safety				8860768
					NEXT HIGHER ASSEMBLY
					8860752
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
207	Thickness, min.		0.65%	3.2	Gage
208	Width to Retaining Strip Recess, min.		0.65%	3.2	Gage
209	Thickness to Retaining Strip Recess, min.		0.65%	3.2	Gage
210	Protective Finish Missing or Contains Bare Stop		0.65%	3.6	Visual
211	Evidence of Poor Workmanship		0.65%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B(PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.40	Arming Delay Assembly, Loaded				8860752
					NEXT HIGHER ASSEMBLY
					8886433
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Non-Arming		100%	3.8.1	4.5.3.1
2	Arming Delay Time	(b)	100%	3.8.1	4.5.3.3
Major A					
101	Arming	(a)		3.8.1	4.5.3.2
102	Arming Delay Time	(b)	100%	3.8.1	4.5.3.3
Major B					
131	Any Component Except Screw Above Flush		0.40%	3.2	Gage
132	Protrusion of Safety Plunger Retaining Strip, max.		0.40%	3.2	Gage
133	Detonator Missing or Inverted		0.40%	3.2	Visual
134	Any Component Missing		0.40%	3.2	Visual
Minor					
201	Screw Above Flush		0.65%	3.2	Visual
202	Evidence of Poor Workmanship		0.65%	3.6	Visual
203	Thickness, max.		0.65%	3.2	Gage

NOTES: (a) 4.4.3.2.1.1, 4.4.3.2.1.2
(b) 4.4.3.2.2

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B(PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.41	Fuze Assembly, Prior to Assembling Alignment Screw and Loaded Arming Delay Assembly				8886433
					NEXT HIGHER ASSEMBLY
					8886433
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major B					
131	Any Component Missing or Damaged		0.40%	3.2	Visual
132	Evidence of Poor Workmanship		0.40%	3.6	Visual
Minor	None Defined				

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B(PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.42	Fuze Assembly, Prior to Assembling Booster Lead Cup				8886433
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Shutter in Armed Position		100%	3.2	Visual
Major B					
131	Alignment Screw Loose		0.40%	3.2	Manual
132	Any Component Missing		0.40%	3.2	Visual
Minor					
201	Evidence of Poor Workmanship		0.65%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B(PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.43	Fuze Metal Parts Assembly				8886433
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Jolt	(a)		3.4	4.4.3.3
2	Jumble	(a)		3.4	4.4.3.3
3	Transportation Vibration	(a)		3.5	4.4.3.4
Major A					
101	Transportation Vibration	(b)		3.5	4.4.3.4
Major B					
131	Any Component Damaged to the Extent that Function may be Impaired		0.40%	3.2	Visual
Minor					
201	Evidence of Poor Workmanship		0.65%	3.6	Visual
202	Any Component Missing		0.65%	3.2	Visual

NOTES:
(a) 4.4.3.3.1 and 4.4.3.3.2
(b) 4.4.3.4

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B(PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.44	Box, Fiber, Prior to Sealing				8887101
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major	None Defined				
Minor					
201	Any Packing Material Missing		0.65%	3.2	Visual
202	Separator Damaged to Extent that Fuzes Touch Each Other		0.65%	3.2	Visual
203	Fuze Missing		0.65%	3.2	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B(PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.45	Sealed Box, Fiber				8887101
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major	None Defined				
Minor					
201	Carton Torn, Cut or Punctured		0.65%	3.2	Visual
202	Sealing Strip Fails to Completely Seal Box		0.65%	3.2	Visual
203	Marking Misleading or Unidentifiable		0.65%	3.2	Visual
204	Contents Loose		0.65%	3.2	Manual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B(PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.46	Sealed Barrier Bag				8887101
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major B					
131	Seal Improper or Incomplete		0.40%	3.2	Visual
132	Bag Punctured, Torn or Cut		0.40%	3.2	Visual
133	Heat Seal Test	(a)		3.2	Spec. MIL-P-116
Minor	None Defined				

NOTES:

(a) MIL-P-116

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B(PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.47	Packing Box, Prior to Sealing				8887102
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major B 131	Carton Missing		0.40%	3.2	Visual
Minor	None Defined				

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B(PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.48	Packing Box, Sealed		8887102
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major B					
131	Box Broken, Board Loose or Protruding Nail		0.40%	3.2	Visual
132	Strapping Missing, Broken or Loose		0.40%	3.2	Visual-Manual
Minor					
201	Marking Misleading or Unidentifiable		0.65%	3.2	Visual
202	Strapping Improperly Engaged or Mislocated		0.65%	3.2	Visual
203	Contents Loose		0.65%	3.2	Manual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B(PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.49	Washer, Detonator				9204556
					NEXT HIGHER ASSEMBLY
					8860769
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major	None Defined				
Minor					
201	Outside Diameter		0.65%	3.2	Gage
202	Inside Diameter		0.65%	3.2	Gage
203	Thickness		0.65%	3.2	Gage
204	Concentricity		0.65%	3.2	Gage

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

PROVING GROUND

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B(PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8886434 assembled into complete rounds M393
4.4.2.50	Fuze, Base Detonating, M578 -- Loaded with Booster Lead and Booster and Assembled into Loaded Round M393				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical 1	Arming Safety	(a)		3.7.1	4.5.6.1
Major A 101	Functioning	(b)		3.7.2	4.5.6.2

NOTES:
(a) 4.4.3.7.1
(b) 4.4.3.7.2

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B(PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8865554
4.4.2.51	Detonator, Stab				NEXT HIGHER ASSEMBLY 8860769
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major A 101	Check for Deterioration Test	(a)		3.2	MIL-D-45441C (MU)
Minor	None Defined				

NOTES:
(a) 4.4.3.6

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B(PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.52	Washer, Striker				8860751
					NEXT HIGHER ASSEMBLY
					8860738
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major B					
131	Diameter of Hole, max.		0.40%	3.2	Gage
Minor					
201	Diameter of Hole, min.		0.65%	3.2	Gage
202	Thickness		0.65%	3.2	Gage
203	Outside Diameter		0.65%	3.2	Gage
204	Protective Finish Missing or Contains Bare Spot		0.65%	3.2.3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil — Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60042B(PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.53	Disc, Cover				9276736
					NEXT HIGHER ASSEMBLY
					8886433
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major B					
131	Thickness		0.40%	3.2	Gage
Minor					
201	Diameter		0.65%	3.2	Gage
202	Evidence of Poor Workmanship		0.65%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. - When arming and non-arming tests are specified herein, the non-arming test shall be performed after the performance of the arming test in all cases.

4.4.3.1 Locking Segment and Striker Needle Assembly (see dwg. 8860738).

4.4.3.1.1 Arming. - Major A Defect (See 3.8.2).

4.4.3.1.1.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with the acceptance criteria specified herein, 450 sample assemblies shall be selected from each lot for this test. If five (5) or more assemblies fail to comply with the requirement specified, the lot shall be rejected. The test shall be performed as specified in 4.5.2.2.

4.4.3.1.1.2 After three consecutive lots have met the criteria specified in 4.4.3.1.1.1, 150 sample assemblies shall be selected from each lot for this test. If two (2) or more assemblies fail to comply with the requirement specified, the lot shall be rejected. The test shall be performed as specified in 4.5.2.2.

4.4.3.2 Arming Delay Assembly. (see dwg. 8860752).

4.4.3.2.1 Arming - Major A Defect(See 3.8.1).

4.4.3.2.1.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with the acceptance criteria specified herein, 450 sample assemblies shall be selected from each lot for this test. If five (5) or more assemblies fail to comply with the requirement specified, the lot shall be rejected. The test shall be performed as specified in 4.5.3.2.

4.4.3.2.1.2 After three consecutive lots have met the criteria specified in 4.4.3.3.2.1, 150 sample assemblies shall be selected from each lot for this test. If two (2) or more assemblies fail to comply with the requirement specified, the lot shall be rejected. The test shall be performed as specified in 4.5.3.2.

4.4.3.2.2 Arming Delay Time

- Critical Defect: If arming time is less than the minimum specified in drawing.
- Major A Defect: If arming time is greater than the maximum specified in drawing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

This test shall be performed 100%. Any assembly which fails to comply with the requirement specified shall be classed defective and removed from the lot. The test shall be performed as specified in 4.5.3.3. using test equipment in accordance with 4.4.4.

4.4.3.3 Jolt and Jumble. (see 3.4). - Fuze Assembly dwg. 8886433. Jolt - Critical Defect, Jumble - Critical Defect

4.4.3.3.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with the acceptance criteria specified, a sample of 36 assemblies shall be selected from each lot for these tests. The assemblies shall be subjected to the Jolt Test specified in Standard MIL-STD-331, except that after test, the assemblies shall not be disassembled but shall be subjected to the Jumble Test specified in Standard MIL-STD-331. The assemblies shall then be disassembled to determine compliance with the applicable requirement. If any assembly fails to comply with the requirement, the lot shall be rejected. Assemblies subjected to these tests shall not be returned to the lot.

4.4.3.3.2 After three consecutive lots have met the criteria specified in 4.4.3.3.1, a sample of 12 assemblies shall be selected from each lot for these tests. Acceptance and rejection criteria shall be as specified in 4.4.3.3.1.

4.4.3.4 Transportation Vibration (see 3.5) (Fuze Assembly Dwg. 8886433). Defect classification is as shown in the following:

CRITICAL DEFECT	MAJOR DEFECT A
1. Breakage of, damage to or loosening of any part likely to result in safety hazard during Transportation Vibration (TV) Test.	1. Breakage of, damage to or loosening of any part not likely to result in safety hazard during Transportation Vibration (TV) Test.
2. Detonator functioning during Transportation Vibration Test.	2. Failure to arm during Spin Tests following the Transportation Vibration Test.
3. Assembly arms during Transportation Vibration	3. Arming Delay Time greater than maximum as specified on drawing during Spin Test and after TV Test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

4. Failure of Non-Arming Test.

5. Arming Delay Time less than minimum as specified on drawing during Spin Test and after TV Test.

4.4.3.4.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with the acceptance criteria specified, a sample of 30 assemblies shall be selected from each lot for this test. The assemblies shall be subjected to the test specified in Standard MIL-STD-331. The assemblies shall then be disassembled and the components visually examined for evidence of damage. The locking segment and striker needle assembly and the loaded arming delay assembly shall be subjected to the applicable tests specified in 4.5.2 and 4.5.3. If any assembly fails to comply with a requirement of Standard MIL-STD-331, or a component of the assembly fails the respective arming, non-arming or arming delay test, the lot shall be rejected. Assemblies subjected to this test shall not be returned to the lot.

4.4.3.4.2 After three consecutive lots have met the criteria specified in 4.4.3.4.1, a sample of ten assemblies shall be selected from each lot for this test. Acceptance and rejection criteria shall be as specified in 4.4.3.4.1.

4.4.3.5 Escape Wheel and Pinion Assembly Load and Torque Test (see dwg. 8860757) - Critical Defect.

4.4.3.5.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with the acceptance criteria specified herein, 150 sample assemblies shall be selected from each lot for this test. If one or more assemblies fail to comply with the requirement specified, the lot shall be rejected. The test shall be performed as specified in 4.5.5.

4.4.3.5.2 After three consecutive lots have met the criteria specified in 4.4.3.5.1, 50 sample assemblies shall be selected from each lot for this test. If one or more assemblies fail to comply with the requirement specified, the lot shall be rejected. The test shall be performed as specified in 4.5.5.

4.4.3.6 Check Test for Deterioration of Detonator (dwg. 8865554) - Major A Defect. - If the total elapsed time between the acceptance of any detonator lot and assembly of that lot into fuze lots exceeds two years, or if the detonators have

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

been subjected to adverse conditions, however brief, at any time since previous tests, the detonator lot shall be check tested as specified in the applicable detonator specification immediately before the detonator lot is assembled into fuzes. This test shall be performed by the supplier on detonators selected by the Government Inspector at the facility assembling the detonators into the fuze. The test shall be conducted at Government expense without cost to the supplier who loaded the detonator or the supplier assembling the detonator into the fuze, and shall not constitute a basis for rejection against either supplier except where deterioration has occurred as a direct result in carelessness in handling, storage, etc., permitted while the detonator lot was under the responsibility of either supplier.

4.4.3.7 Proving Ground. - Fuze Assembly Dwg. 8886434 Assembled Into Complete Round M393.

4.4.3.7.1 Arming Safety (see 3.7.1) - Critical Defect.

4.4.3.7.1.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with the applicable requirement, 75 sample fuze assemblies shall be randomly selected from each lot for this test. If one or more assemblies fail to comply with the applicable requirement, the lot shall be rejected. The test shall be performed as specified in 4.5.6.1.

4.4.3.7.1.2 After three consecutive lots have complied with the criteria of 4.4.3.7.1.1, 25 sample fuze assemblies shall be randomly selected from each lot for this test. If one or more fuzes fail to comply with the applicable requirement, the lot shall be rejected. If any lot fails to meet the applicable requirement, the sampling plan of 4.4.3.7.1.1 above shall be reinstated for three consecutive acceptable lots. The test shall be performed as specified in 4.5.6.1.

4.4.3.7.2 Functioning (see 3.7.2) - Major A Defect

4.4.3.7.2.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with the applicable requirement, 75 fuze assemblies shall be randomly selected from each lot for this test. If two or

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:19Z
Check the source to verify that this is the current version before use.

more fuze assemblies fail to comply with the applicable requirement, the lot shall be rejected. The test shall be performed as specified in 4.5.6.2.

4.4.3.7.2.2 After three consecutive lots have complied with the criteria of 4.4.3.7.2.1, 25 sample fuze assemblies shall be randomly selected from each lot for this test. If two or more fuze assemblies fail to comply with the applicable requirement, the lot shall be rejected. If one fuze assembly fails to comply with the applicable requirement, a second group of 50 fuze assemblies shall be selected and tested. If the combined number of failures in both the first and second sample is two or more, the lot shall be rejected. If any lot fails to meet the applicable requirement, the sampling plan of 4.4.3.7.2.1 above shall be reinstated for three consecutive acceptable lots. The test shall be performed as specified in 4.5.6.2.

4.4.4 Inspection Equipment. - The inspection equipment required to perform the examination and tests prescribe herein is described in the Paragraph Reference/Inspection Method column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment design in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Test Methods and Procedures

4.5.1 Embrittlement of Springs. - The creep and safety plunger springs shall be pulled to the minimum point of permanent distortion. The segment spring shall be twisted to the minimum point of permanent distortion in the direction simulating function. The equipment used to perform this test shall be in accordance with 4.4.4, and springs tested shall not be returned to the lot.

4.5.2 Locking Segment and Striker Needle Assembly (see 3.8.2).

4.5.2.1 Non-Arming. - The locking segment and striker needle assembly shall be placed in a suitable holding device that will apply the compressive load. The holding device with the locking segment and striker needle assembly shall then be spun at the required non-arming speed and observed for compliance with the drawing requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

4.5.2.2 Arming. - The locking segment and striker needle assembly shall be tested as specified in 4.5.2.1 except that rotation shall be at the required arming speed.

4.5.3 Loaded Arming Delay Assembly (see 3.8.1). - Since the arming delay assembly contains a loaded detonator, adequate safety precautions should be taken to protect personnel testing the assembly.

4.5.3.1 Non-Arming. - The loaded arming delay assembly shall be tested in a manner similar to that specified in 4.5.2.1.

4.5.3.2 Arming. The loaded arming delay assembly shall be tested as specified in 4.5.3.1 except that rotation shall be at the required arming speed.

4.5.3.3 Arming Delay Time. - When the arming time interval is determined by the low or high speed rotation method, the loaded arming delay assembly shall be tested in a device similar to that specified in 4.5.3.1, a timer of sufficient accuracy to record a millisecond shall be used to time the interval between start of rotation and the engagement of the locking plate in the recess. For both the low speed and the high speed rotation, the rotating device must be modified with a mechanism to restrain the safety plunger until the specified rotation speed is attained. The timer shall time the interval between release of the loaded shutter assembly by the safety plunger and the engagement of the locking plate in the recess. The loaded arming delay assembly shall be observed for compliance with the requirement.

4.5.4 Hardness Test of Escape Wheel, Timing Segment, Sleeve and Pallet. - The parts shall be tested as specified in Method 243.1 of Federal Test Method Standard 151a.

4.5.5 Escape Wheel and Pinion Assembly Load and Torque Test. - The escape wheel and pinion assembly shall be placed in a suitable supporting fixture and the load applied without impact. Prior to the torque test, the escape wheel shall be marked so that any movement on the pinion may be seen. The assembly shall be examined after test, both manually and visually, under not less than four (4) power magnification for compliance with the requirements. Assemblies subjected to this test shall be scrapped.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

4.5.6 Proving Ground Testing. - The metal parts assemblies shall be sent to a Government designated facility to be loaded with a lead charge and booster and assembled into rounds (M393) for which the fuzes are standard. The firings shall be conducted in accordance with the applicable Acceptance Test Procedure.

4.5.6.1 Arming Safety. - The loaded rounds (M393) shall be fired through a four (4) inch thick wood bursting screen placed at the required distance from the gun. The rounds shall be observed for compliance with the applicable requirement.

4.5.6.2 Functioning. - The loaded rounds shall be fired as specified in 4.5.6.1 except that the target screen shall be placed at the functioning distance from the gun. The rounds shall be observed for compliance with the applicable requirements.

5. PREPARATION FOR DELIVERY

5.1 Preservation and Packaging

5.1.1 Level C. - The fuze assemblies shall be preserved and packaged in accordance with dwg. 8887101.

5.2 Packing

5.2.1 Level C. - The packaged fuze assemblies shall be packed in accordance with dwg. 8887102.

5.2.2 The packing box shall be marked in accordance with dwg. 8796522.

6. NOTES

6.1 Intended Use. - The fuze covered by this specification is intended for use in the M393 complete round.

6.2 Ordering Data. - See 6.1 of MIL-A-48078 (PA).

6.3 Submission of Design for Approval. - See 6.2 of MIL-A-48078. Submit equipment designs, as required to Commander, Picatinny Arsenal, ATTN: SARPA-QA-T-T, Bldg. 92 Dover, New Jersey 07801.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:19Z
Check the source to verify that this is the current version before use.

6.4 Visual Examination Qualification. - When compliance with the applicable requirements is in doubt as a result of visual examination, this characteristic may be measured or gaged to determine acceptability.

6.5 Proving Ground Tests. - All fuze assemblies shall be:

a. Visually inspected for the shutter in the armed position (prior to loading).

b. Visually inspected for component missing (prior to loading).

c. Inspected for flatness of the booster lead cup as follows: After loading of the lead charge, booster pellet and closing disc, the bottom surface of the booster lead cup shall be inspected for flatness. Flatness shall not exceed .002 inches.

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 1390-A-055

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

COMMANDER
Picatinny Arsenal
ATTN: SARPA-QA-A
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:19Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.