MIL-F-60043A (MU)
2 May 1968
SUPERSEDING
MIL-F-60043 (MU)
dated 1 June 1964

MILITARY SPECIFICATION

FUZE, BASE DETONATING, (M62A2)
METAL PARTS FOR

1. SCOPE

1.1 This specification covers the metal parts for one type of base detonating artillery fuze designated as Fuze, BD, M62A2.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550 - Ammunition and Special Weapons, General Specification for.
MIL-I-45607 - Inspection Equipment, Supply and Maintenance of

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105).
MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-1167 - Ammunition Data Card
MIL-STD-1168 - Lot Numbering of Ammunition
MIL-STD-1169 - Packaging, Packing and Marking for Shipment of Inert Ammunition Components
MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures for Inspection by Attributes.

FSC: 1390

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

DRAWINGS

ORDNANCE CORPS

8886414 - Fuze, Base Detonating, M62A2 Assembly

PUBLICATIONS

ORDNANCE CORPS

ET-9200353 - Index of Inspection Equipment Lists

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material.-Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Parts.-The parts shall comply with all requirements specified on Drawing (dwg.) 8886414, other reference drawings, and with all requirements specified in applicable specifications.

3.3 Position of firing pin.-The firing pin point shall not rotate or wobble on its longitudinal axis in a circle greater than .075 inch, maximum diameter when tested as specified in 4.4.1.

3.4 Embrittlement of springs (spring, slider; spring, retaining; and spring, safety pin).-The springs shall not break or permanently deform when extended or compressed to the point of maximum (max.) load or deflection when tested as specified in 4.4.5.

3.5 Arming and Non-Arming (Slider; inert loaded)

3.5.1 Non-Arming.-The slider shall not arm when spun at 2400 revolutions per minute (rpm) minimum (min.).

3.5.2 Arming.-The slider shall arm when spun at 3600 rpm, max.

3.6 Workmanship.-All parts shall be fabricated and finished in a thorough, workmanlike manner and all manufacturing, processing, and assembling operations shall be correctly performed. All parts shall be clean and free of burrs, sharp edges, unblended radii, surface defects, cracks, chips, slivers, cuts, dirt, grease, rust, and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. All required markings shall be neat, legible and sharply defined.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:19Z
Check the source to verify that this is the current version before use.

3.7 First Article Inspection.-This specification makes provisions for first article inspection. Requirements for submission of first article samples by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

4.1 General quality assurance provisions.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL-STD-109 in order to define terms used herein. The provisions of Specification MIL-A-2550 shall apply.

4.1.1 Submission of product.-At the time the completed lot of product is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all of the quality assurance provisions specified within this specification.
b. Number of units of product inspected.
c. Results obtained, by defect code, for all inspections performed.
d. Drawing, specification number and date, together with an identification and date of changes.
e. Certificates of conformance on all material purchased by the contractor when such material is controlled by Government or commercial specifications referenced in any of the contractual documents.
f. Number of items in the lot.
g. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

4.2 First Article Inspection

4.2.1 Submission.-The contractor shall submit a first article sample as designated by the contracting officer for evaluation in accordance with the provisions of 4.2.2. The first article sample shall consist of twenty-five (25) complete sets of parts and assemblies (i.e., 25 each of every component and subassembly) except that quantities for the following shall be:

Two hundred twenty-five (225) percussion plunger assemblies

Two hundred twenty-five (225) assemblies, each consisting of body, slider spring, retaining screw and slider which is loaded with an inert material for the charge, which have been produced by the contractor or furnished by a supplier and which have been manufactured using the same production processes, procedures and equipment which will be used in fulfilling the contract. All parts and materials including packaging and packing shall be obtained from the same source of supply as will be used in regular production. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract and submit a record of this inspection with the sample, including statements of findings for materials, processes and tests. A sample containing known defects will not be submitted unless specifically authorized by the Contracting Officer. A first article sample or portion thereof as directed by the contracting officer shall also be submitted whenever there is a lapse in production for a period in excess of 90 days or whenever a change occurs in manufacturing process, material used, drawing or specification such as to significantly affect product uniformity as determined by the Government.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

4.2.2 Inspection to be performed.-Assemblies and components will be subjected by the Government to any or all of the examinations or tests specified in 4.3.2 and 4.3.3 of this specification and any or all requirements of the applicable drawings.

4.2.3 Rejection.-If any component or subassembly fails to comply with any of the applicable requirements, the initial production sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of a component in the sample to comply with any of the stated requirements. In the event of rejection, the Government reserves the right to require the contractor to take corrective action and submit a new first article sample or portion thereof. Until a first article sample is accepted, the contractor is in no way authorized by the Government to initiate regular production unless otherwise directed by the contracting officer.

4.3 Inspection Provisions

4.3.1 Lot formation.-The term "lot" as used throughout this specification refers to an inspection lot, which is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance of the lot with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the lot has been produced by one manufacturer in one unchanged process, in accordance with the same drawings, same drawing revisions, same specifications and same specification revisions. Changes to the process, specification, or drawings not affecting safety, performance, interchangeability, or storage, as determined by the Government, shall not be deemed to alter the homogeneity of the lot. Inspection lots shall comply with MIL-STD-105. Unless otherwise approved by the contracting officer, the inspection lot size of end items deliverable under the contract shall be not less than the smallest weekly estimate of quantities contractually scheduled for production during the contract period nor more than the largest monthly quantity contractually scheduled for delivery during the contract period. Inspection lots of components or subassemblies, other than the items of delivery, shall be homogeneous and of a size mutually convenient to both the contractor and the Government inspector. Lot numbering, as required, shall be in accordance with MIL-STD-1168.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:19Z
Check the source to verify that this is the current version before use.

4.3.2 Examination.-Inspection for Critical defects (and Major defects, when so specified), shall be 100 percent. Sampling plans and procedures for Major and Minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the procuring activity. Also, at the option of the procuring activity, AQL's and sampling plans may be applied to individual characteristics listed using an AQL of 0.65 percent for each Minor defect and an AQL of 0.40 percent for each Major defect, except where 100 percent inspection is specified. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.3.4.

4.3.2.1 Housing, Plunger (see dwg. 8837317, covering a detail of dwg. 8886414).

Categories	Defects	Method of Inspection	Code No. (see 6.2)
Critical: None defined.			
Major: None defined.			
Minor:	AQL 2.5 percent		
201.	Total length	Gage	01001
202.	Base thickness	Gage	01007
203.	Outside diameter	Gage	01003
204.	Inside diameter	Gage	01004
205.	Diameter of hole	Gage	01005
206.	Evidence of poor workmanship (see 3.6)	Visual	01006

4.3.2.2 Fulcrum, firing pin (see dwg. 8837321, covering a detail of dwg. 8886414).

Categories	Defects	Method of Inspection	Code No.
Critical: None defined.			
Major:	AQL 0.40 percent		
101.	Diameter, max.	Gage	02001
102.	Plating damaged exposing base metal	Visual	02002
Minor:	AQL 1.0 percent		
201.	Length	Gage	02003
202.	Evidence of poor workmanship (see 3.6)	Visual	02004

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

4.3.2.3 Pin, firing (see dwg. 8837318, covering a detail of dwg. 8886414).

Categories	Defects	Method of Inspection	Code No.
Critical: None defined.			
Major:	AQL 1.0 percent		
101.	Profile of firing pin point	Gage	03001
102.	Height of firing pin point, max.	Gage	03002
103.	Diameter of fulcrum pin hole, min.	Gage	03003
104.	Location of fulcrum pin hole	Gage	03004
105.	Alignment of firing pin point with fulcrum pin hole	Gage	03005
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.6)	Visual	03007

4.3.2.4 Pin, safety (see dwg. 8837320, covering a detail of dwg. 8886414).

Categories	Defects	Method of Inspection	Code No.
Critical: None defined.			
Major:	AQL 0.65 percent		
101.	Large diameter, max.	Gage	04001
102.	Total length, max.	Gage	04002
103.	Length of small diameter shaft	Gage	04003
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.6)	Visual	04004

4.3.2.5 Body, plunger, (see dwg. 8837316, covering a detail of dwg. 8886414).

Categories	Defects	Method of Inspection	Code No.
Critical: None defined.			

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

Major:	AQL 0.40 percent		
101.	Distance to bottom of firing pin slot, max.	Gage	05001
102.	Location of firing pin fulcrum hole	Gage	05002
Minor:	AQL 1.5 percent		
201.	Total length	Gage	05003
202.	Width of firing pin slot	Gage	05004
203.	Chamfer missing	Visual	05005
204.	Evidence of poor workmanship (see 3.6)	Visual	05006

4.3.2.6 Percussion plunger assembly (see drawing 8837315, covering a detail of dwg. 8886414.)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 1.0 percent		
101.	Total length including firing pin in armed position	Gage	06001
102.	Total length of assembly in unarmed position	Gage	06002
103.	Outside diameter of housing, max.	Gage	06003
104.	Firing pin point damaged	Gage	06004
105.	Any component missing or improperly assembled	Visual	06005
Minor:	AQL 2.5 percent		
201.	Stake of firing pin fulcrum missing	Visual	06006
202.	Stake of body pin missing	Visual	06007
203.	Plating damaged exposing base metal	Visual	06008
204.	Coating of plunger housing incomplete	Visual	06009
205.	Evidence of poor workmanship (see 3.6)	Visual	06010

4.3.2.7 Spring, restraining (see dwg. 8837325, covering a detail of dwg. 8886414.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 1.0 percent		
101.	Load at test height, max.	Gage	07001
102.	Load at assembled height, min.	Gage	07002
103.	Solid height, max.	Gage	07003
104.	Plating damaged exposing base metal	Visual	07004
105.	Evidence of poor workmanship (see 3.6)	Visual	07005
Minor:	AQL 1.5 percent		
201.	Outside diameter, max.	Gage	07006
202.	Inside diameter, min.	Gage	07007
203.	Winding not left hand	Visual	07008

4.3.2.8 Holder, detonator (see dwg. 8837323, covering a detail of dwg. 8886414).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 1.0 percent		
101.	Pitch diameter of thread	Gage	08001
102.	Major diameter of thread	Gage	08002
103.	Length of thread pilot, min.	Gage	08003
104.	Inside diameter of firing pin hole	Gage	08015
105.	Concentricity of firing pin hole with pitch diameter of thread	Gage	08005
106.	Diameter of detonator cavity, min.	Gage	08006
107.	Depth of detonator cavity	Gage	08007
108.	Total length	Gage	08008
109.	Thread not full	Visual	08009
Minor:	AQL 2.5 percent		
201.	Diameter of thread pilot	Gage	08010
202.	Location of wrench holes	Gage	08011
203.	Depth of wrench hole	Gage	08012
204.	Wrench hole missing	Gage	08013
205.	Evidence of poor workmanship (see 3.6)	Visual	08014

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

4.3.2.9 Slider (see dwg. 8837314, covering a detail of dwg. 8886414.)

Categories	Defects	Method of Inspection	Code No.
Critical: None defined.			
Major:	AQL 1.0 percent		
101.	Length of boss, max.	Gage	09001
102.	Distance from shoulder to charge cavity	Gage	09002
103.	Diameter of charge cavity, min.	Gage	09003
104.	Diameter of pilot	Gage	09004
105.	Alignment of pilot with shoulder	Gage	09005
106.	Alignment of charge cavity with pilot	Gage	09006
107.	Finish improper	Visual	09007
Minor:	AQL 4.0 percent		
201.	Total length, max.	Gage	09008
202.	Length of shoulder, max.	Gage	09009
203.	Diameter of shoulder	Gage	09010
204.	Diameter of boss	Gage	09011
205.	Length of boss, min.	Gage	09012
206.	Diameter of gas check cavity	Gage	09013
207.	Depth of gas check cavity,min.	Gage	09014
208.	Distance from shoulder to gas check cavity	Gage	09015
209.	Alignment of gas check cavity with pilot and charge cavity	Gage	09016
210.	Radii missing	Visual	09017
211.	Evidence of poor workmanship (see 3.6)	Visual	09018

4.3.2.10 Spring, slider, (see dwg. 8837322, covering a detail of dwg. 8886414).

Categories	Defects	Method of Inspection	Code No.
Critical: None defined.			

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

Categories	Defects	Method of Inspection	Code No.
Major:	AQL 0.65 percent		
101.	Solid height, max.	Gage	10001
102.	Plating damaged exposing base metal	Visual	10002
103.	Evidence of poor workmanship (see 3.6)	Visual	10003
Minor:	AQL 1.5 percent		
201.	Outside diameter, max.	Gage	10004
202.	Inside diameter, min.	Gage	10005
203.	Winding not left hand	Visual	10006

4.3.2.11 Screw, retaining (see dwg. 8837312, covering a detail of dwg. 8886414).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 1.0 percent		
101.	Depth of slider shoulder counterbore	Gage	11001
102.	Depth of spring cavity, min.	Gage	11002
103.	Distance from open end to end of thread, min.	Gage	11003
104.	Length of thread pilot	Gage	11004
105.	Pitch diameter of thread, max.	Gage	11005
106.	Major diameter of thread, max.	Gage	11006
107.	Thread not full	Visual	11007
Minor:	AQL 4.0 percent		
201.	Total length	Gage	11008
202.	Pitch diameter of thread, min.	Gage	11009
203.	Major diameter of thread, min.	Gage	11010
204.	Diameter of slider shoulder counterbore	Gage	11011
205.	Diameter of spring cavity	Gage	11012
206.	Depth of spring cavity, max.	Gage	11013
207.	Diameter of thread pilot	Gage	11014
208.	Distance between wrench notches	Gage	11015
209.	Wrench notch missing	Visual	11016
210.	Finish improper	Visual	11017
211.	Evidence of poor workmanship		

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

4.3.2.12 Head (see dwg. 8886415 covering a detail of dwg. 8886414).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 1.5 percent		
101.	Pitch diameter of shell thread	Gage	12001
102.	Major diameter of shell thread	Gage	12002
103.	Pitch diameter of body thread	Gage	12003
104.	Major diameter of body thread	Gage	12004
105.	Distance from start of shell thread to flange, min.	Gage	12007
106.	Shell thread undercut, max.	Gage	12008
107.	Concentricity of body thread with shell thread	Gage	12009
108.	Concentricity of flange with shell thread	Gage	12010
109.	Concentricity of percussion plunger cavity with shell thread	Gage	12011
110.	Perpendicularity of body thread with face of flange	Gage	12012
111.	Perpendicularity of body thread with plunger cavity end	Gage	12013
112.	Depth of percussion plunger cavity, min.	Gage	12014
113.	Diameter of percussion plunger cavity	Gage	12015
114.	Distance from plunger cavity end to flange, min.	Gage	12016
115.	Diameter of flange	Gage	12017
116.	Distance from plunger cavity end to shoulder, min.	Gage	12019
117.	Caulking groove angle missing	Visual	12021
118.	Metal defects (crack or break)	Visual	12022
119.	Shell thread not full	Visual	12023
Minor:	AQL 4.0 percent		
201.	Distance from start of shell thread to flange, max.	Gage	12024
202.	Diameter of shell thread pilot, max.	Gage	12025
203.	Body thread undercut, max.	Gage	12026
204.	Length of body thread pilot	Gage	12027
205.	Diameter of body thread pilot, max.	Gage	12028

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

206.	Distance from plunger cavity end to shoulder, max.	Gage	12029
207.	Depth of plunger cavity, max.	Gage	12030
208.	Diameter of caulking groove at flange	Gage	12031
209.	Length of caulking groove	Gage	12032
210.	Total length	Gage	12034
211.	Depth of spanner holes, max.	Gage	12038
212.	Distance between spanner holes.	Gage	12039
213.	Diameter of spanner holes	Gage	12040
214.	Plating damaged exposing base metal	Visual	12041
215.	Evidence of poor workmanship (see 3.6)	Visual	12042

4.3.2.13 Body (see dwg. 8837310, covering a detail of dwg. 8886414).

Categories	Defects	Method of Inspection	Code No.
Critical	None defined.		
Major:	AQL 2.5 percent		
101.	Pitch diameter of head thread.	Gage	13001
102.	Minor diameter of head thread, min.	Gage	13002
103.	Pitch diameter of detonator holder thread	Gage	13003
104.	Minor diameter of detonator holder thread, min.	Gage	13004
105.	Pitch diameter of retaining screw thread	Gage	13005
106.	Minor diameter of retaining screw thread, min	Gage	13006
107.	Pitch diameter of booster cup thread	Gage	13007
108.	Major diameter of booster cup thread	Gage	13008
109.	Outside diameter, max.	Gage	13009
110.	Length of perfect head thread, min.	Gage	13010
111.	Depth of head cavity	Gage	13011
112.	Depth to bottom of detonator cavity from shoulder of head cavity	Gage	13012
113.	Depth to bottom of detonator cavity from shoulder of holder cavity	Gage	13013

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

1. Scope. This specification covers portable electric circuit saws

114.	Length of perfect detonator holder thread, min.	Gage	13014
115.	Concentricity of head thread with outside diameter including perpendicularity with bottom of head cavity	Gage	13015
116.	Concentricity of head thread with detonator cavity	Gage	13016
117.	Concentricity of detonator holder thread with outside diameter including perpendicularity with bottom of detonator holder cavity	Gage	13017
118.	Distance from bottom of head cavity to centerline of slider cavity	Gage	13018
119.	Distance from body centerline to retainer screw thread undercut, max.	Gage	13019
120.	Concentricity of booster cup thread with outside diameter	Gage	13020
121.	Diameter of slider cavity, min.	Gage	13021
122.	Total length	Gage	13022
123.	Alignment of slider cavity with slider shoulder cavity	Gage	13023
124.	Finish of slider cavity improper	Visual	13024
125.	Material defective (crack or splits)	Visual	13025

Minor: AQL 4.0 percent

201.	Diameter of detonator cavity	Gage	13026
202.	Diameter of lead hole	Gage	13027
203.	Diameter of slider shoulder cavity	Gage	13028
204.	Depth of slider shoulder cavity	Gage	13029
205.	Diameter of slider cavity, max.	Gage	13030
206.	Depth of slider cavity	Gage	13031
207.	Depth of retaining screw thread cavity, min.	Gage	13032
208.	Distance from booster end to shoulder, min.	Gage	13033
209.	Diameter of booster cup thread pilot, max.	Gage	13034
210.	Length of booster cup thread pilot, min.	Gage	13035
211.	Booster cup thread undercut, max.	Gage	13036
212.	Diameter of booster cavity	Gage	13037

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

213.	Depth of booster cavity	Gage	13038
214.	Plating damaged exposing base metal	Gage	13040
215.	Staking notch missing or incorrectly located	Visual	13041
216.	Evidence of poor workmanship (see 3.6)	Visual	13042

4.3.2.14 Cup, booster, (see dwg. 8837313, covering a detail of dwg. 8886414).

Categories	Defects	Method of Inspection	Gage
Critical:	None defined.		
Major:	AQL 1.0 percent		
101.	Outside diameter, max.	Gage	14001
102.	Pitch diameter of thread, min.	Gage	14002
103.	Length of perfect thread, min.	Gage	14004
104.	Thickness at bottom, max.	Gage	14005
105.	Concentricity of outside diameter with threads	Gage	14006
106.	Crack or break	Visual	14007
Minor:	AQL 2.5 percent		
201.	Outside diameter, min.	Gage	14008
202.	Pitch diameter of thread, max.	Gage	14009
203.	Minor diameter of thread, max.	Gage	14010
204.	Thickness at bottom, min.	Gage	14011
205.	Depth to bottom	Gage	14012
206.	Finish improper	Visual	14013
207.	Evidence of poor workmanship (see 3.6)	Visual	14014

4.3.2.15 Spring, safety pin (see dwg. 8837326, covering a detail of dwg. 8886414).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.40 percent		
101.	Solid height, max.	Gage	15001
102.	Evidence of poor workmanship (see 3.6)	Visual	15002
Minor:	AQL 1.5 percent		
201.	Outside diameter, max.	Gage	15003
202.	Inside diameter, min.	Gage	15004
203.	Winding not left hand	Visual	15005

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

4.3.3 Testing

4.3.3.1 Non-arming test of percussion plunger assembly (see dwg. 8837315), Critical Defect, Code No. 06011.-This test shall be performed 100 percent. If any plunger assembly fails to comply with the requirements specified on the applicable drawing, the assembly shall be classed defective and removed from the lot. The test shall be performed as specified in 4.4.1.

4.3.3.2 Arming test of percussion plunger assembly (see dwg. 8837315), Major Defect, Code No. 06012.-Sampling plans for this test shall be in accordance with MIL-STD-105, Code letter L, and an AQL of 0.25 percent. Testing shall be performed as specified in 4.4.2.

4.3.3.3 Arming and non-arming test of slider

4.3.3.3.1 Arming test (see 3.5.2), Major Defect, Code No. 09020.-Using the samples specified in 4.3.3.3.1, the items shall be tested as specified in 4.4.4. An AQL of 0.25 percent shall apply to this test.

4.3.3.3.2 Non-arming test (see 3.5.1), Critical Defect, Code No. 09019.-The sampling plan for this test shall be in accordance with MIL-STD-105, single sampling, Code Letter L, and an AQL of 0.65 percent. Bodies, sliders, slider springs, and retaining screws shall be selected from each lot of parts and assembled using an inert material for the charge. The test shall be conducted as specified in 4.4.3.

4.3.3.4 Embrittlement of springs (safety pin, dwg. 8837326; restraining, dwg. 8837325; and slider, dwg. 8837322), Major Defect.-A sample of 50 springs each shall be selected from the lot for this test. If one or more springs in any of the samples fail to comply with 3.4, when tested as specified in 4.4.5, that lot of springs shall be rejected. Code Nos.-Safety pin spring--15006; restraining spring--07009; slider spring--10007.

4.3.4 Inspection Equipment.-Index of Inspection Equipment List Number ET-9200353 identifies the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in paragraph 6.3.

4.3.4.1 Government rights to documentation.-Inspection equipment drawings and lists provided and revised in accordance with the requirements of the ET may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey and whenever inspection equipment drawings are needed.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:19Z
Check the source to verify that this is the current version before use.

4.3.4.2 Supply and maintenance.-Supply and maintenance of the equipment listed in the ET shall be in accordance with Specification MIL-I-45607.

4.3.4.3 Government use of contractor's inspection equipment.-The contractor shall make available to the Government all inspection equipment necessary for determining conformance with contract requirements. Personnel for operating the equipment and verification of its accuracy shall be supplied by the contractor for the performance of examination or test by the Government.

4.4 Test methods and procedures

4.4.1 Arming of percussion plunger assembly.-Equipment specified in 4.3.4 shall be used. Each assembly shall arm when spun at, and not exceeding the arming speed specified on the applicable drawing. Arming shall be evidenced by rotation of the firing pin on the fulcrum to the armed (ready-to-fire) position where the point of the firing pin rotates on its longitudinal axis within a circle not greater than .075 inches maximum diameter. Check manually to see that the firing pin lock functions.

4.4.2 Non-arming of percussion plunger assembly.-Each percussion plunger assembly in the lot shall be subjected to this test using equipment specified in 4.3.4. Each assembly shall not arm when spun at, and at not less than the non-arming speed of rotation specified on the applicable drawing. Non-arming of the percussion plunger assembly shall be evidenced by observing that the firing pin has not been released from the safety-pin locked position in the armed (ready-to-fire) position. This test shall be performed after the arming test.

4.4.3 Non-arming test of slider.-The slider shall not arm when the body assembly is spun at, and at not less than the non-arming speed of rotation specified in 3.5.1. Test equipment specified in 4.3.4 shall not be used. Non-arming shall be determined by observation from the head end of the body that the inert charge in the slider is not visible through the detonator flash hole.

4.4.4 Arming test of slider.-The body with inert loaded slider, slider spring and retaining screw shall be rotated at the arming speed specified in 3.5.2. Arming shall be determined by observation from the head end of the body that the inert charge of the slider is in line with the detonator and flash hole. Equipment specified in 4.3.4 shall be used.

4.4.5 Embrittlement of springs.-The springs shall be tested in such a manner as to simulate functioning; i.e., by pulling a tension coil spring, bending a flat spring or compressing a compression spring until the maximum limits of the functional travel are met. No permanent distortion or breakage shall result.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:19Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Preservation and Packaging

5.1.1 Level C.-The metal parts for Fuze, Base Detonating, M62A2 shall be preserved and packaged in accordance with Standard MIL-STD-1169.

5.2 Packing

5.2.1 Level C.-The metal parts for Fuze, Base Detonating, M62A2 shall be preserved and packed in accordance with Standard MIL-STD-1169.

5.3 Marking.-Marking shall be in accordance with MIL-STD-1169.

6. NOTES

6.1 Ordering data.-Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Data cards.-Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.

6.2 Inspection code numbers.-The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government.

6.3 Inspection equipment.-The contractor shall design inspection equipment as required by the inspection Equipment Lists (EL) referenced on the applicable ET in accordance with the instructions of paragraphs 6.3.1 through 6.3.5.

6.3.1 Inspection equipment lists (EL).-Inspection equipment lists indicate the availability of inspection equipment designs by showing in the "number" column of the list of inspection equipment (Form SMUPA 1010) the numbers of drawings or Federal Stock numbers of existing equipment designs, or codes as indicated in paragraph 6.3.2. Design action required of the contractor is described in paragraphs 6.3.3 and 6.3.4. The contractor will be required to prepare detailed drawings in accordance with 6.3.4 for all the equipment coded as "Contractor Design" in the number column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

6.3.2 Inspection equipment list codes.-The inspection equipment as defined in 6.3.3 and 6.3.4 will be designated in the EL by the following codes:

CD - Contractor design on controlled contractor format and/or commercial equipment.
MU - Army design, mandatory for use.

6.3.3 Army designs.-Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for an item of inspection equipment. Army designs fall into two basic classifications: mandatory (designated "MU") and non-mandatory (indicated by drawing or Federal Stock Number). When an inspection equipment list references mandatory Army designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with non-mandatory designs, and with the approval of the Government, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.4 Contractor designs.-Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finish, notes, operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Unless otherwise specified, contractor designs may be developed on the format the contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above, subject to the following controls: All submitted contractor designs shall conform to MIL-D-1000, Category E, Form 2. Legibility and reproducibility shall permit conventional making of clearly understandable, high contrast reproductions. Contractors shall submit three copies of final designs as a flat set. Designs shall be submitted for approval as specified in 6.3.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

6.3.5 Submission of contractor designs.-All submitted designs shall contain a reference to the applicable five digit Code Number contained in Section 4 of this specification and the appropriate component or assembly drawing number and revision letter to which the specific design applies. Unless otherwise specified on the EL, all designs of equipment for inspection of defects classified as critical and major shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND1. All other designs of inspection equipment shall be approved by the inspection element of the agency administering the contract; submission shall be as directed by the contracting officer. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion da for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will be accomplished normally within one month after receipt.

6.4 Visual examination.-When compliance with the applicable requirements is in doubt, as a result of visual examination, the characteristic may be measured or gaged to determine acceptability.

Custodian:
Army-MU

Preparing Activity:
Army-MU

Project Number: 1390-A642

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:19Z
Check the source to verify that this is the currentversion before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION

ORGANIZATION *(Of submitter)*	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 APR 63 1426 REPLACES NAVSHIPS FORM 4863, WHICH IS OBSOLETE C-8270

Source: https://assist.dla.mil -- Downloaded: 20261O-26T04:19Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
Picatinny Arsenal
ATTN: SARPA-AD-E-C-3
Dover, NJ 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:19Z
Check the source to verify that this is the current version before use.