MIL-I-55667C
5 January 1977
SUPERSEDING
MIL-I-55667B(EL)
15 April 1970

MILITARY SPECIFICATION

IGNITOR
FOR
SEARCHLIGHT, INFRARED,
28-VOLT, 110-AMPERE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the ignitor for searchlights, infrared, 28-volt, 110-ampere.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

QQ-S-781	- Strapping, Steel, and Seals
PPP-B-585	- Boxes, Wood, Wirebound
PPP-B-601	- Boxes, Wood, Cleated-Plywood
PPP-B-621	- Boxes, Wood, Nailed and Lock-Corner
PPP-B-636	- Boxes, Shipping Fiberboard
PPP-F-320	- Fiberboard, Corrugated and Solid, Sheet Stock (Container Grade) and Cut Shapes

MILITARY

MIL-P-116	- Preservation-Packaging, Methods of
MIL-M-10304	- Meters, Electrical Indicating, Panel Type Ruggedized, General Specification for
MIL-P-11268	- Parts, Materials and Processes Used in Electronic Communication Equipment

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Cdr, USA Electronics Command, ATTN: DRSEL-RD-TS-S, Ft Monmouth, NJ 07703 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 5855

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:18Z
Check the source to verify that this is the current version before use.

MIL-M-13231	- Marking of Electronic Items
MIL-P-19644	- Plastic Molding Material (Polystyrene Foam Expanded Bead)
MIL-P-26514	- Polyurethane Foam, Rigid or Flexible for Packaging
MIL-R-52446	- Radiation Source, Infrared, 2.2 KW for Searchlight, Infrared, 28-Volt, 110-Ampere

STANDARDS

FEDERAL

FED-STD-356	- Commercial Packaging of Supplies and Equipment
FED-STD-595	- Colors

MILITARY

MIL-STD-22	- Welded-Joint Design
MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	- Marking for Shipment and Storage
MIL-STD-171	- Finishing of Metal and Wood Surfaces
MIL-STD-252	- Classification of Visual and Mechanical Defects for Equipment, Electronic, Wired and other Devices
MIL-STD-810	- Environmental Test Methods

DRAWINGS

ELECTRONICS COMMAND

SC-DL-613827	- Ignitor for Searchlight, Infrared, 28-Volt, 110-Ampere

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI)

Y32.16-1975 Reference Designations for Electrical and Electronic Parts and Equipments

(Application for copies should be addressed to the American Standards Institute, 1430 Broadway, New York, NY 10018.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:18Z
Check the source to verify that this is the current version before use.

AMERICAN WELDING SOCIETY

Standard Qualification Procedure

(Application for copies should be addressed to the American Welding Society, 2501 NW 7th Street, Miami, Florida 33125.)

NATIONAL BUREAU OF STANDARDS

Handbook H28 - Screw-Thread Standards for Federal Services.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, DC 20402.)

3. REQUIREMENTS

3.1 Description. The ignitor shall be a booster-starter ignitor utilizing an ignition circuit housed and wired in such a manner that only the input and output and ignitor connector need be attached to permit operation.

3.2 Construction. The ignitor shall be constructed in accordance with SC-DL-613827 and as specified herein.

3.3 First article. When specified in the contract or purchase order, the contractor shall furnish first article units in accordance with 4.3.

3.4 Parts and materials. Parts and materials shall be as specified herein and as shown on the applicable drawings. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification and shall conform to MIL-P-11268.

3.5 Operational and environmental.

3.5.1 Operation. The ignitor shall operate under all conditions as specified herein. The ignitor shall develop a high voltage ionization potential of not less than 18 kilovolt (kV) ac peak at a frequency between 3 and 10 megahertz (MHz). The ac input to the ignitor shall be 70-110 volts ac (root mean square (rms) value of an essentially square wave) at a frequency of 350 hertz (Hz) plus or minus 50 Hz. The input impedance of the ignitor shall be such that a maximum of 4.0 amperes rms is drawn from the ac source. The ignitor shall conduct through to a 2.2 kW radiation source conforming to MIL-R-52446 or its equivalent load value a maximum external plasma voltage of 150 volts dc at a maximum current of 50 amperes. The ignitor shall conduct through to the radiation source or its equivalent a maximum external sustaining voltage of 28 volts dc at a maximum current of 100 amperes. Both the dc plasma voltage and dc sustaining voltage shall be applied to the same dc input terminals with the switching performed externally.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:18Z
Check the source to verify that this is the current version before use.

3.5.2 Vibration. The ignitor shall not be damaged (see 6.3) by sustained vibration at frequencies varying from 10 to 55 hertz at an amplitude of 0.03 inch (0.06 inch total excursion).

3.5.3 Mechanical shock. The ignitor shall not be damaged by mechanical shocks using a half-sine shock pulse method 516 of MIL-STD-810 of 5 g's (see 6.3) minimum with each shock having a duration of 12 milliseconds, plus or minus 1 millisecond in a vertical plane and 23.5 g's minimum with each shock having a duration of 9 milliseconds, plus or minus 1 millisecond in a horizontal plane.

3.5.4 Altitude. The ignitor shall operate as specified herein at 8,000 feet above sea level with ambient temperature maintained at plus 35°C.

3.5.5 Altitude transportation. The ignitor shall not be damaged by transportation in unpressurized military aircraft at any altitude to 40,000 feet above sea level at corresponding temperature for this altitude.

3.5.6 Storage temperatures.

3.5.6.1 High temperature storage. The ignitor shall not be damaged by storage at an ambient temperature of plus 68°C with relative humidity controlled.

3.5.6.2 Low temperature storage. The ignitor shall not be damaged by storage at an ambient temperature of minus 62°C with relative humidity uncontrolled.

3.5.7 Operating temperatures.

3.5.7.1 High temperature operation. The ignitor shall operate as specified herein at any ambient temperature from plus 23°C to plus 85°C with humidity controlled between 90 to 98 percent.

3.5.7.2 Low temperature operation. The ignitor shall operate as specified herein at any ambient temperature from plus 23°C to minus 54°C with humidity uncontrolled.

3.5.8 Life. The ignitor shall operate as specified herein a minimum of 3,000 consecutive times without failure.

3.5.9 Wiring. The ignitor wiring shall be bundled into harnesses and supported by insulated cable clamps. All wiring shall be mounted to avoid any sharp corners or possibility of damage from contact with high temperature surfaces. Wiring shall contain no defects when examined in accordance with MIL-STD-252.

3.6 Treatment and painting. The ignitor housing shall be cleaned, treated and painted in accordance with MIL-STD-171 and in accordance with FED-STD-595, Color No. 37038. The color shall be lusterless black.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:18Z
Check the source to verify that this is the currentversion before use.

3.7 Identification and marking. Identification and marking shall be in accordance with MIL-M-13231 and ANSI Y32.16-1975. The output terminals shall be marked, "Warning, High Voltage and Amperage Output".

3.8 Workmanship. All parts, components and assemblies of the ignitor including forgings, molded parts, stampings, seals, welded parts and machined surfaces shall be clean and free from sand, dirt, pits, sprues, scale, flux and other harmful extraneous material. External surfaces shall be free from burrs, sharp edges and corners, except when sharp edges and corners are required.

3.8.1 Screw threads. Screw threads shall conform to National Bureau of Standards Handbook H-28. Mating threaded aluminum surfaces shall be treated prior to assembly with a silicon lubricant that shall withstand temperatures from minus 62°C to plus 177°C.

3.8.2 Welded design. Welded joint design shall conform to MIL-STD-22. Welding shall conform to standard welding practices as prescribed by the American Welding Society (Standard Qualification Procedure).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Parts and materials inspection. The supplier is responsible for insuring that parts and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards as specified herein.

4.2 Classification of inspection. Inspection shall be classified as follows:

a. First article inspection (see 4.3).
b. Inspections covered by subsidiary documents (see 4.4).
c. Quality conformance inspection (see 4.5).
d. Packaging inspection (see 4.7).

4.3 First article. Unless otherwise specified in the contract or purchase order, the first article inspection shall be performed by the contractor (see 6.2).

4.3.1 Inspection. Each ignitor shall be examined in accordance with Table I. One or more defects shall be cause for rejection of that ignitor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:18Z
Check the source to verify that this is the current version before use.

TABLE I Inspection.

Defects	Requirement paragraph
MAJOR	
101. Parts and Materials not as specified.	3.4
102. Wiring not as specified in MIL-STD-252.	3.5.9
MINOR	
201. Dimensions not as specified	3.2
202. Treatment and painting not as specified	3.6
203. Identification markings not as specified	3.7
204. Workmanship not as specified	3.8
205. Screw threads not as specified	3.8.1
206. Welded joint not as specified	3.8.2

4.3.2 Tests. Upon successful completion of the examination specified in 4.3.1 each first article ignitor shall be subjected to all tests in Table II. Tests may be conducted in any sequence. Failure of any test shall be cause for rejection.

TABLE II First article inspection.

Inspection	Requirement paragraph	Test paragraph
Operation	3.5.1	4.6.1
Vibration	3.5.2	4.6.2
Mechanical shock	3.5.3	4.6.3
Altitude	3.5.4	4.6.4
Altitude transportation	3.5.5	4.6.5
High temperature storage	3.5.6.1	4.6.6.1
Low temperature storage	3.5.6.2	4.6.6.2
High temperature operation	3.5.7.1	4.6.7.1
Low temperature operation	3.5.7.2	4.6.7.2
Life	3.5.8	4.6.8

4.4 Inspections covered by subsidiary documents. The ignitor shall be inspected under the applicable subsidiary documents as part of the inspection required by this specification, and the inspection requirement specified in the contract or purchase order (see 4.3.1 and Table I).

4.5 Quality conformance inspection.

4.5.1 Examination. Each ignitor shall be examined as specified in Table I. Presence of any defect shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:18Z
Check the source to verify that this is the current version before use.

4.5.2 Tests.

4.5.2.1 Group A inspection. Each ignitor shall be tested in accordance with Table III. Failure of the test shall be cause for rejection.

TABLE III Group A inspection.

Inspection	Requirement paragraph	Test paragraph
Operation	3.5.1	4.6.1

4.5.2.2 Group B inspection. Group B inspection shall be conducted on ignitors selected from units which have passed the examination and tests in 4.5.1 and 4.5.2.1. Sampling shall be in accordance with MIL-STD-105, AQL 2.5 percent defective, inspection level S-3. Tests shall be conducted in accordance with Table IV and may be performed in any sequence.

TABLE IV Group B inspection.

Inspection	Requirement paragraph	Test paragraph
Vibration	3.6.2	4.6.2
Altitude	3.6.4	4.6.4

4.5.2.3 Group C inspection. This inspection shall consist of the tests specified in Table V and shall be performed on sample units that have been subjected to and met Group A and B inspection. Sample units shall be selected in accordance with 4.5.2.3.1.

4.5.2.3.1 Sampling for Group C inspection. One sample ignitor shall be selected at random by the Government for all inspections in Table V from the monthly specified quantity produced (see 6.2) or each 100 ignitors, whichever occurs first. The first sample selected shall be at the start of the contract from the first quality conformance inspection lot.

TABLE V Group C inspection.

Inspection	Requirement paragraph	Test paragraph
Operation	3.5.1	4.6.1
Mechanical shock	3.5.3	4.6.3
Altitude transportation	3.5.5	4.6.5
High temperature storage	3.5.6.1	4.6.6.1
Low temperature storage	3.5.6.2	4.6.6.2
High temperature operation	3.5.7.1	4.6.7.1
Low temperature operation	3.5.7.2	4.6.7.2

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:18Z
Check the source to verify that this is the current version before use.

4.5.3 Group C failures. Actions required relative to Group C failures shall be as specified in the contract or purchase order (see 6.2).

4.5.4 Reinspection of Group B and C sample units. Unless otherwise specified, sample units which have been subjected to and passed both Group B and C reinspection may be accepted on contract or order provided all damage is repaired and the sample units are resubjected to and pass Group A inspection.

4.6 Test methods. Tests required to determine compliance with the requirements of this specification shall be conducted in accordance with the test procedures specified herein. The tolerance on all voltages shall be plus or minus 0.5 volt. The tolerance on all currents shall be plus or minus 1.0 ampere. All meters used during tests shall have been calibrated within 30 days prior to the start of testing, and thereafter as required, and at intervals not to exceed 6 months. Tests shall be monitored by direct-reading, laboratory - type meters accurate within 1.0 percent and connected to indicate in the most accurate portion of the range. Voltage, current, vibration frequency and amplitude, and mechanical shock forces shall be recorded using recording instruments, accurate within 3.0 percent with a damping factor not greater than 3 as defined in MIL-M-10304. All tests shall be conducted at room temperature (see 6.3) unless otherwise specified in the individual test procedure. Test facilities, chambers, and apparatus used in conducting tests specified herein shall meet the requirements of MIL-STD-810.

4.6.1 Operation. The operational test for ignitors shall be conducted in 3 steps as follows:

a. Connect the ignitor to an approved ac source of 70-110 volts rms of an essentially square wave as measured by an iron vane type (or other true rms reading instrument) voltmeter. Place in series with the input a true rms reading ammeter. Terminate the output of the ignitor in a calibrated spark gap having needle point electrodes. Calibrate the spark gap in the room that the test is to be performed by reducing the separation of the electrodes until a monitored dc potential of 18 kV just causes breakdown. Cycle the ignitor for 10 cycles; each cycle consisting of 3 seconds "ON" and 30 seconds "OFF". Failure of the spark to jump the electrodes shall constitute failure of this test.

b. Connect an approved source of 150 volts dc to the dc input and check for proper conduction through to a 2.2 kW radiation source socket or its equivalent. Apply ac power and cycle the ignitor as indicated in a. Any failure as outlined in a, shall constitute failure of this test.

c. Connect an approved source of 28 volts dc, 100 amperes to the dc input terminals. Connect a 0.2 ohm 4500 minimum watt load across the output terminals. Allow the 100 amperes current to pass through the ignitor for a minimum of 4 hours. At the end of this test period remove the resistive load within two

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:18Z
Check the source to verify that this is the current version before use.

minutes and connect the ignitor as indicated in a above and repeat the tests outlined in a. Failure to pass 100 amperes for 4 hours minimum or failure to meet any test in a above shall constitute failure of this test.

4.6.2 Vibration. Mount the ignitor on a vibration table. Vibrate the ignitor in the vertical and horizontal planes at an amplitude of 0.03 inch, (0.06 inch total excursion, plus or minus 10 percent). Vary the frequency uniformly from 10 to 55 Hz. Continue the vibration for not less than 90 minutes in each plane, and during this time note the frequency and magnitude of resonant points. Vibrate the ignitor for 15 minutes at each of the resonant frequencies noted. When no resonant frequencies are observed, vibrate the ignitor for 30 minutes at 55 Hz and 0.06 inch amplitude total excursion. Operate the ignitor. Any evidence of damage or failure of the ignitor to operate as specified in 4.6.1 shall constitute failure of this test.

4.6.3 Mechanical shock. Mount the ignitor on a rigid, non-resonant fixture by its mounting points and mount the fixture to the shock table. Subject the ignitor to 12 shock. The maximum g value shall be reached in 3 milliseconds, plus or minus 0.5 millisecond. This test shall be conducted in 2 steps as follows:

a. Six shocks shall be applied perpendicular to the horizontal axis each shock having a duration of 9 milliseconds, plus or minus 1.0 millisecond, at a minimum of 23.5 g's.
b. Six shocks shall be applied perpendicular to the vertical axis each shock having a duration of 12 milliseconds, plus or minus 1.0 millisecond, at a minimum of 5 g's. Failure of the ignitor to operate as specified in 4.6.1, or any evidence of damage shall constitute failure of this test.

4.6.4 Altitude. The ignitor shall be placed in the test chamber. The air pressure in the test chamber shall be reduced to the value corresponding to 8,000 feet above sea level and ambient air temperature maintained at plus 35°C. The ignitor shall be operated. Operation shall consist of continuous cycling for 1 hour at rated power. Failure of the ignitor to cycle continuous for 1 hour at rated power or any evidence of damage shall constitute failure of this test.

4.6.5 Altitude transportation. The ignitor shall be placed in a test chamber and the air pressure in the chamber shall be reduced to the value corresponding to 40,000 feet above sea level with corresponding temperature for this altitude. The chamber shall be maintained at this pressure and temperature for 4 hours. At the end of 4 hours the chamber air pressure and temperature shall be returned to the value corresponding to sea level. The ignitor shall be examined for damage. Any evidence of damage shall constitute failure of this test.

4.6.6 Storage temperatures.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:18Z
Check the source to verify that this is the current version before use.

4.6.6.1 High temperature storage. The ignitor shall be stored in a test chamber at an ambient temperature of plus 68°C with humidity controlled at 90 to 98 percent for 12 hours. At the conclusion of the storage period the ignitor shall be examined for damage. Any evidence of damage shall constitute failure of this test.

4.6.6.2 Low temperature storage. The ignitor shall be placed in the test chamber and exposed to an ambient temperature of minus 62°C with humidity uncontrolled for a period of 12 hours. At the conclusion of the exposure period the ignitor shall be examined. Any evidence of damage shall constitute failure of this test.

4.6.7 Operating temperatures .

4.6.7.1 High temperature operation. The ignitor shall be placed in a test chamber and subjected to two, 12 hour cycles of exposure with relative humidity controlled at 90 to 98 percent. Each cycle shall consist of the following:

a. Two hours at plus 85°C.
b. Decrease within 1 hour to plus 23°C and maintain for 1 hour.
c. Increase within 1 hour to plus 85°C and maintain for 2 hours.
d. Decrease within 1 hour to plus 23°C and maintain for 1 hour.
e. Increase within 1 hour to plus 85°C and maintain for 2 hours.

Immediately upon completion of 2 cycles, the ignitor shall be tested at plus 85°C in accordance with 4.6.1. Failure of the ignitor to operate as specified or any evidence of damage shall constitute failure of this test.

4.6.7.2 Low temperature operation. The ignitor shall be placed in a test chamber and exposed to an ambient temperature of minus 54°C for a period of 8 hours. During the last 30 minutes of the 8 hour period the ignitor shall be operated. Failure of the ignitor to operate as specified in 4.6.1 or evidence of damage shall constitute failure of this test.

4.6.8 Life. Connect the ignitor as specified in 4.6.1 a, operate the ignitor for 3,000 consecutive cycles. Each cycle shall consist of 3 seconds "ON" and 30 seconds "OFF". Failure of the ignitor to operate as specified in 4.6.1 shall constitute failure of this test.

4.7 Packaging inspection. The inspection of the preservation-packaging and interior package marking shall be in accordance with the group A and B quality conformance inspection requirements of MIL-P-116. The inspection of the packing and marking for shipment and storage shall be in accordance with the quality assurance provisions of the applicable container specification and the marking requirements of MIL-STD-129.

5. PACKAGING

5.1 Preservation. Preservation shall be level A, B or Commercial, as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:18Z
Check the source to verify that this is the current version before use.

5.1.1 Level A.

5.1.1.1 Cleaning. Ignitor for Searchlight, Infrared 28 Volt, 110-Ampere shall be cleaned in accordance with process C-1 of MIL-P-116.

5.1.1.2 Drying. Ignitor for Searchlight, Infrared 28 Volt, 110-Ampere shall be dried in accordance with the applicable procedures of MIL-P-116.

5.1.1.3 Preservative application. No preservative required.

5.1.1.4 Unit packing. Unit packing shall be in accordance with the methods prescribed in MIL-P-116 as specified herein.

5.1.1.4.1 Technical literature. Each technical literature shall be unit packed method IC-1.

5.1.1.4.2 Ignitor for Searchlight, Infrared 28 Volt, 110-Ampere. Each unit shall be individually unit packed method III as follows: cushion each unit on all surfaces with cells or pads or both fabricated of fiberboard conforming to PPP-F-320, type CF, class weather-resistant, variety SW, grade W5c, designed to protect all projections and absorb the shock of impact in handling and transit. As an alternate, cushioning material may be fabricated of plastic molding material conforming to MIL-P-19644 or polyurethane foam conforming to MIL-P-26514. Place each cushioned item within a close-fitting fiberboard box conforming to PPP-B-636, W5c. Place the technical literature, unit packed as specified in 5.1.1.4.1, on top of the contents, directly under the lid of the box. Close the box in accordance with appendix of the box specification.

5.1.2 Level B. Cleaning, drying, preservative application and unit packing shall be as specified in 5.1.1.

5.1.3 Commercial Preservation. Preservation shall be in accordance with FED-STD-356.

5.2 Packing. Packing shall be level A, B or Commercial, as specified (see 6.2). Shipping containers for level A and B shall be capable of stacking and supporting superimposed loads during shipment and storage without damaging the container(s) or its contents.

5.2.1 Level A. A quantity of Ignitor for Searchlight, Infrared 28 Volt, 110-Ampere, unit packed as specified in 5.1, shall be packed within a close-fitting box conforming to PPP-B-601, overseas type; PPP-B-621, style 4, class 2; or PPP-B-585, style 2 or 3, class 3. When the gross weight exceeds 200 pounds, or the container length and width is 48 x 24 inches or more and the weight exceeds 100 pounds, 3 x 4 inch skids, laid flat, shall be applied in accordance with the requirements of the container specification, or if not specified in the specification, in a manner which will adequately support the item and facilitate the use of material handling equipment. Closure and strapping shall be in accordance with the applicable container specification or appendix thereto except that metal strapping shall conform to QQ-S-781, type I, finish a.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:18Z
Check the source to verify that this is the current version before use.

5.2.2 Level B. A quantity of Ignitor for Searchlight, Infrared 28 Volt, 110-Ampere, unit packed as specified in 5.1, shall be packed within a close-fitting box conforming to PPP-B-601, domestic type; PPP-B-621, style 4, class 1, or PPP-B-585, style 2 or 3, class 3. When the gross weight exceeds 200 pounds, or the container length and width is 48 x 24 inches or more and the weight exceeds 100 pounds, 3 x 4 inch skids, laid flat, shall be applied in accordance with the requirements of the container specification, or if not specified in the specification, in a manner which will adequately support the item and facilitate the use of material handling equipment. Closure and strapping shall be in accordance with the applicable container specification or appendix thereto.

5.2.3 Commercial packing. Packing shall be in accordance with FED-STD-356.

5.3 Marking.

5.3.1 Military marking. In addition to an special marking required by the contract or order, interior packs and exterior shipping containers shall be marked in accordance with MIL-STD-129.

5.3.2 Commercial marking. In addition to any special marking required by the contract or order, interior packs and exterior shipping containers shall be marked in accordance with FED-STD-356.

6. NOTES

6.1 Intended use. The ignitor is intended for igniting radiation sources used in searchlight, infrared, 28-volt, 110-ampere.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number and date of this specification and any amendment thereto.
b. Level A, level B or Commercial preservation and packing (see section 5).
c. Actions required relative to Group C failure (see 4.5).
d. Schedule for First Article Testing (see 4.3).
e. When the rough handling test is required.
f. Environmental. Environmental pollution prevention measures are contained in the packaging material specifications referenced herein. Refer to material specifications or preparing activity for recommended disposability methods.

6.3.1 Damage. Damage is defined as deformation, loosening, breakage, corrosion, or change of fit of any component or part.

6.3.2 "g". g is defined as an acceleration or deceleration of 32.17 feet per second per second.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:18Z
Check the source to verify that this is the currentversion before use.

6.3.3 Room temperature. Room temperature is defined as +23°C plus or minus 3°C.

Custodians:
Army - EL
Navy - EC

Preparing Activity:
Army - EL

Project No. 5855-0014

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:18Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION MIL-I-55667C IGNITOR FOR SEARCHLIGHT, INFRARED, 28-VOLT, 110-AMPERE

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

ESC-FM 1068-68

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:18Z
Check the source to verify that this is the currentversion before use.

FOLD

Department of the Army
Headquarters
U.S.Army Electronics Command
Fort Monmouth, New Jersey 07703

POSTAGE AND FEES PAID

OFFICIAL BUSINESS

Commanding General
U.S.Army Electronics Command
ATTN: ~~AMSELX~~ DRSEL-RD-TS
Fort Monmouth, New Jersey 07703

To detach this form, cut along this line

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:18Z
Check the source to verify that this is the current version before use.