MIL-P-60049A (PA)
29 April 1974
SUPERSEDING
MIL-P-60049 (MU)
27 July 1964 and
MIL-P-60048 (MU)
27 July 1964
(see 6.6)

MILITARY SPECIFICATION

PRIMER, STAB M26
PARTS FOR,
LOADING, ASSEMBLING AND PACKING

*This specification is approved for use by all Departments and Agencies in the Department of Defense.

1. SCOPE

1.1 This specification covers the parts for, loading, assembling and packing for one type of primer designated as Primer, Stab, M26

*2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-P-116 - Preservation, Methods of
MIL-A-2550 - Ammunition, General Specification For.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105).

FSC: 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-650 - Explosives: Sampling, Inspection and Testing
MIL-STD-1168- Lot Numbering of Ammunition
MIL-STD-1235- Single and Multilevel Continuous Sampling and Procedures and Tables For Inspection by Attributes

DRAWINGS

U.S. ARMY PICATINNY ARSENAL

PRODUCT AND PACKAGING DRAWINGS

8795837 - Primer, Stab M26 Assembly
9258182 - Box, Set-Up, Packing, Ammunition, Inner for Small Explosive Components
9258183 - Box, Set-Up, Packing, Ammunition
9258184 - Box, Packing, Ammunition for Small Explosive Components

INSPECTION EQUIPMENT DRAWINGS

8816367 - Holder, Firing Pin
8827828 - Sleeve, Alternate
8827829 - Ball, Steel
9200012 - Pin Firing
9200443 - Sleeve, Centering
9200444 - Firing Assembly
9202650 - Disc, Steel

(Copies of specifications, standards, and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer).

*3. REQUIREMENTS

3.1 Material. - Materials shall be in accordance with applicable drawings and specifications.

3.2 Primers. - The primers shall comply with all requirements specified on drawing (dwg. 8795837, and with all requirements specified in applicable specifications.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

3.3 Moisture content

3.3.1 Primer mixture. - The moisture content of the primer mixture used in loading the primers shall not exceed 0.30 percent.

3.4 Functioning.- The primers shall function on the first attempt under an applied energy of 5.92 inch ounces, and shall cause a high order report when fired against the steel disc.

3.5.2 Waterproofness. - The primers shall be waterproof as evidenced by normal functioning after being immersed under a minimum (min.) of 2 inchs of water for a minimum of 48 hours at a temperature of 75° Farenheit (F) plus or minus 5 degrees.

3.6 Workmanship. - All parts and assemblies shall be fabricated and loaded in a thorough, workmanlike manner. they shall be free of burrs, sharp edges, cracks, dirt, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat and sharply defined. All packing components shall be dry.

3.6 First article inspection. - This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

*4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to MIL-STD-109 to define terms used herein. The provisions of MIL-A-2550 shall apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

4.1.1 Submission of Product.-At the time each completed lot of items deliverable under the contract is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted.

a. A statement that the lot complies with all of the quality assurance provisions specified in this specification.
b. Drawing and specification number and date, together with identification and date of changes thereto.
c. A statement that all material purchased by the contractor meets requirements, when such material is controlled by Government or commercial specifications referenced in any of the contractual documents, and that certificates of conformance are on file and available for review.
d. Number of items in the lot.
e. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agents authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

*4.2 First Article Inspection

4.2.1 Submission.-Prior to the start of regular production the contractor shall submit a first article sample (see 6.1c) to a Government approved facility as designated by the contracting officer for evaluation in accordance with the provisions of 4.2.2 and 4.2.3. The first article sample shall consist of three hundred forty (340) loaded primers and 50 complete sets of parts (i.e., 50 each of every component),which have been produced by the contractor or funished by a supplier and which have been manufactured using the same production processes, procedures and equipment which will be used in fulfilling the contract. All parts and materials including packaging and packing shall be obtained from the same source of supply as will be used in regular production. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract and submit a record of this inspection with the sample, including a certificate of

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

conformance for materials. A sample containing known defects will not be submitted unless specifically authorized by the Contracting Officer. A first article sample, or portion thereof, as directed by the Contracting Officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days or whenever a change occurs in manufacturing process, material used, drawing or specification such as to significantly affect product uniformity as determined by the Government.

4.2.2 Inspections to be performed.-Assemblies and components will be subjected by the Government to any or all of the examinations and tests specified in this specification and any or all requirements of the applicable drawings.

4.2.3 Rejection. - If any component or subassembly fails to comply with any or all of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of an inert component or subassembly to comply with any of the stated requirements.

4.2.4 Loaded Primers. - A sample of three hundred forty (340) loaded primers shall be submitted in accordance with 4.2.1 and tested as specified in 4.3.3.2 and 4.3.3.3.

*4.3 Inspection provisions

4.3.1 Lot formation.-The term "inspection lot" as used in this specification is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer in one unchanged process using the same materials and methods in accordance with the same drawings, same drawing revisions, same specifications and same specification revisions and complies with the provisions for submission of product as specified in MIL-STD-105. Changes to the process, specifications, or drawings not affecting safety, performance, interchangeability, or storage, as determined by the Government, shall not be deemed to alter the homogeneity of an inspection lot. All material submitted for inspection in accordance with this specification shall comply

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

with the homogeneity criteria specified herein regardless of the type of sampling procedure which is being applied to determine conformance with requirements. Lot numbering, as required, shall be in accordance with MIL-STD-1168. Each inspection lot of loaded primer assemblies shall contain:

a. Parts of one lot interfix number from one supplier.
b. Primer mixture consisting of batches, blended by the same process, each ingredient being from not more than 2 lots from one manufacturer.

*4.3.2 Examination.-The examinations listed in the following subparagraphs shall be performed on inspection lots (see 4.3.1) of the components or assemblies designated in the applicable paragraph headings. Inspection for critical defects (and major defects, when so specified) shall be 100 percent. Sampling plans for major and minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the Government. Instead of applying the AQL's designated herein to the groups of major and minor defects listed, the contractor may elect to apply an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. When this method is elected, it shall be applied to all of the major and minor defects listed in the applicable sub-paragraph of this section, except where 100 percent inspection is specified, and be documented as part of the contractor's inspection system. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.3.4.

4.3.2.1 Disc (see dwg. 8838132 covering a detail of dwg. 8795837).

Categories	Defects	Method of Inspection	Code No. (see 6.2)
Critical:	None defined		
Major:	AQL 0.40 percent		
101.	Diameter	Gage	01001
102.	Thickness	Gage	01002
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.6)	Visual	01003

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

4.3.2.3 Cup (see dwg. 8805653 covering a detail of dwg. 8795837).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 1.00 percent		
101.	Thickness through bottom	Gage	02001
102.	Length	Gage	02002
103.	Outside diameter	Gage	02003
Minor:	AQL 1.50 percent		
201.	Diameter of flange (when applicable) max.	Gage	02004
202.	Inside diameter, min.	Gage	02005
203.	Evidence of poor workmanship (see 3.6)	Visual	02006

4.3.2.4 Primer Assembly (see dwg. 8795837)

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Cup split or cracked	Visual	04001
Major:	AQL 0.65 percent		
101.	Outside diameter.....	Gage	04002
102.	Length.....	Gage	04003
103.	Identification color missing or incorrect	Visual	04004
Minor:	AQL 1.50 percent		
201.	Seal incomplete	Visual	04005
202.	Disc wrinkled or bulged	Visual	04006
203.	Crimp less than 360 degrees ..	Visual	04007
204.	Evidence of poor workmanship (see 3.6)	Visual	04008

4.3.2.5 Box, set-up, inner, after loading and prior to closing slide cover (see dwg. 9258182).

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Filler and cushion assembly missing	Visual	05001

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

2.	Filler and cushion assembly improperly assembled	Visual	05002
3.	Stiffener missing	Visual	05003
4.	Slide cover assembled reversed .	Visual	05004
Major:	AQL 0.40 percent		
101.	Release paper missing	Visual	05005
Minor:	AQL 1.00 percent		
201.	Marking missing, incomplete or illegible	Visual	05006
202.	Evidence of poor workmanship (see 3.6)	Visual	05007

4.3.2.6 Box, set-up, outer, with innner set-up boxes assembled and prior to assembling top and sealing strip (see dwg. 9258183).

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Red surfaces on inner set-up boxes do not alternate on same side of outer set-up box	Visual	06001
2.	Stiffener not facing one direction	Visual	06002
Major:	None defined		
Minor:	AQL 1.00 percent		
201.	Marking missing, incomplete or illegible	Visual	06003
202.	Evidence of poor workmanship (see 3.6)	Visual	06004

4.3.2.7 Box, packing, ammunition prior to assembling cover and strapping (see dwg. 9258184).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.65 percent		
101.	Bags containing set-up boxes damaged	Visual	07001

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:19Z
Check the source to verify that this is the currentversion before use.

102.	cushioning material incomplete or missing from around outer set-up boxes	Visual	07002
103.	Marking missing, misleading or unidentified.....	Visual	07003
104.	Barrier bag seal incomplete or improperly positioned.....	Visual	07004
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.6)	Visual	07005

4.3.2.8 Box, packing, ammunition (see dwg. 9258184).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.65 percent		
101.	Strapping missing, broken loose, or improperly fastened	Visual/ Manual	08001
102.	Box damaged	Visual	08002
103.	Marking missing, incomplete or illegible	Visual	08003
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.6)	Visual	08004

4.3.3 Testing

4.3.3.1 Moisture content of primer mixture (see 3.3.1) - Major defect - Code No. 04009. - The moisture content of the primer mixture shall be determined for each lot at the time of loading. A sample shall be selected and tested as specified in 4.4.1. If the moisture content is in excess of the percentage specified and loading has not yet begun, the lot of primer mix shall be rejected. If loading has begun, action on the unloaded primer mix shall be as specified above and all primers loaded with the questionable primer mix shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

4.3.3.2 Functioning (see 3.4) - Major Defect - Code No. 04010. - A sample of 315 primers shall be selected at random from each lot. If 3 or more primers fail to comply with the requirements specified, the lot shall be rejected. If one or two defects are found, a second sample of 315 shall be selected at random and tested. If, in the combined first and second sample, a total of 4 or more defects are found, the lot shall be rejected. The test shall be performed as specified in 4.4.3 using test equipment as specified in 4.3.4 and 4.4.3.

4.3.3.3 Waterproofness (see 3.5) - Major defect - Code No. 04011. - a sample of 25 primers shall be selected at random from each lot. If one or more detonators fail to comply with the requirement specifeid, the lot shall be rejected. The test shall be performed as specified in 4.4.3, using test equipment specified in 4.3.4 and 4.4.3.

4.3.3.4 Composition of primer mixture (see dwg. 8796462) - Major Defect - Code No. 04012. - A sample of approximately 0.5 grams shall be selected from each batch or blend of batches of primer mixture and tested as specified in 4.4.2. The batch or blend of batches shall be rejected if one or more of the requirements are not met.

4.3.3.5 Heat seal test of sealed bag (see dwg. 9258183) - Major Defect - Code No. 08005. - Sampling, acceptance criteria, and test procedures for this test shall be as specified in MIL-P-116.

*4.3.4 Inspection Equipment. - Inspection equipment required to perform the inspections prescribed in this specification is identified in the examination (4.3.2) and Test Method (4.4) paragraphs herein. See 6.3 for details concerning responsibilities for inspection equipment design and approval.

4.4 Test Methods and Procedures

4.4.1 Moisture content of the primer mixture. - The moisture content of the primer mixture shall be determined in accordance with MIL-STD-650, Method 101.6 except that the drying temperature shall be 60 plus or minus 5 degrees C. and only 0.40 to 0.70 grams of ignition mixture shall be dried.

4.4.2 Composition

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

4.4.2.1 Potassium chlorate

4.4.2.1.1 Preparation of solutions

4.4.2.1.1.1 Solution No. 1. - To approximately 800 ml of distilled water in a 1-liter amber glass reagent bottle, 40 gm of potassium sulfocyanate shall be added. The reagent bottle and contents shall be sealed with a rubber stopper and shaken until the solid material has been dissolved. To this solution, 1.0 gm of lead thiocyanate, 1.0 gm of antimony sulfide, and 1.0 gm of lead azide shall be added. Again the reagent bottle shall be stoppered, and the contents vigorously shaken for several minutes, then allowed to stand overnight. Portions of the saturated solution shall be filtered before use.

4.4.2.1.1.2 Solution No. 2. - to approximately 400 ml of distilled water in a 1/2 - liter amber glass reagent bottle, 1.0 gm of lead thiocyanate, 1.0 gm of antimony sulfide, and 1.0 gm of lead azide shall be added. The reagent bottle shall be sealed with a rubber stopper, and the contents vigorously shaken for several minutes, then allowed to stand overnight. Portions of the saturated solution shall be filtered before use.

4.4.2.1.2 Procedure. - A portion of approximately 1.0 gm of a sample shall be accurately weighed directly into a tared 30-ml sintered glass crucible of medium porosity. From a burette, 3.0 ml of Solution No. 1 shall be added to the crucible. The solution shall be swirled for exactly 1 minute, care being taken that no liquid be spilled, then aspirated with suction, and the bottom of the crucible wiped dry with tissue paper. The washing shall be continued, using one more 3.0 ml portion, two 2.0 ml. portions, and two 1.0 ml portions, making a total of 12.0 ml in all. the crucible shall be removed, and the bottom of the crucible, the funnel, the adapter, and the suction flask washed with water. The test tube shall be placed in the flask and the stem of the filtering funnel inserted into it. As above, the curcible and contents shall be washed with one 1.0 ml portion of Solution No. 1. The solution shall be aspirated with suction, and the filtrate caught in the test tube. The test tube shall be removed, 1.0 ml of distilled water added, then tested for the chlorate ion, as follows:

The tube shall be inclined at an angle of about 45 degrees. About 0.5 ml of a solution containing 1.0 gm of diphenylamine in 100 gm of concentrated sulfuric acid shall be run down the

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:19Z
Check the source to verify that this is the currentversion before use.

side of the tube from a dropper so that there will be two distinct layers. If an appreciable amount of chlorate ion is present, a distinct blue ring shall be visible at the border of the two layers. On shaking the tube, the ring disappears, but the contents assume a blue coloration, which shall last several seconds, depending on the amount of chlorate ion present. If only a trace of chlorate ion is present, the blue ring may not form, but upon shaking the test tube, a slight bluish coloration shall appear momentarily throughout the solution, and last only a fraction of a second. If a definite blue ring forms, the washing shall be repeated as before, using one 1.0 ml portion of Solution No. 1, and finally a 0.5 ml portion of the same solution, as needed, depending upon the outcome of the tests for the chlorate ion. (Usually a total of 14.0 or 14.5 ml of Solution No. 1 shall be sufficient). After the removal of potassium chlorate has been completed, the inside of the crucible shall be washed with 1.0 ml of Solution No. 2, and aspirated immediately. The bottom of the crucible shall be wiped dry with tissue paper, and the crucible dried in an oven at 80 degrees plus or minus 1 degree C. for 30 minutes, cooled in a desiccator, and weighed. The percentage of potassium chlorate shall be calculated as follows:

$$\text{Potassium chlorate, percent} = \frac{B \times 100}{W}$$

Where:

B = Loss in weight of the contents of the crucible
W = Weight of the sample on a moisture-free basis.

4.4.2.2 Antimony sulfide

4.4.2.2.1 Preparation of solution of ferric ammonium sulfate. - To approximately 120 ml of distilled water in a 1/2-liter reagent bottle, 125 gm of ferric ammonium sulfate shall be added. The reagent bottle shall be stoppered, vigorously shaken for several minutes, and then allowed to stand overnight. Portion so the saturated solution shall be filtered before use.

4.4.2.2.2 Procedure. - A portion of approximately 1 gm of the sample shall be accurately weighed directly into a tared 30-ml sintered glass curcible of medium porosity. a 5.0 ml portion of 1 percent nitric acid shall be added, and the crucible constantly swirled for 1 minute, in order that all the ingredients of the

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

powder except antimony sulfide be dissolved. Care shall be taken that none of the liquid be spilled. The mixture shall be filtered by applying suction, employing a vacuum flask. the crucible shall be removed from the adapter, and the bottom wiped dry with tissue paper. The washing operation shall be repeated, using 5.0 ml of 1 percent nitric acid each time, and the contents swirled for exactly 1 minute. After a total of 40 ml of 1 percent nitric acid has been used, the crucible shall be removed, and the bottom of it washed with water. The funnel, the funnel adapter, and the vacuum flask shall be washed with water, and the filtrate and washings discarded. About 1 ml of a saturated solution of ferric ammonium sulfate shall be placed in the flask. The contents of the crucible shall be treated as before with 5.0 ml of 1 percent nitric acid, and filtered by means of suction into the flask. If the liquid in the flask turns red, due to the presence of the sulfocyanate ion in the filtrate, the washing of the contents in the crucible shall be repeated with additional 5.0 ml portions of 1 percent nitric acid, unitl a negative test for the sulfocyanate ion has been affected. (Usually a total of 50 ml shall be sufficient.) The crucible and contents shall be rinsed with alcohol and then with ether. The solution shall be aspirated until the odor of ether can no longer be detected. The crucible and contents shall be dried in an oven at 80 degress plus or minus 1 degree C. for 30 minutes, cooled in a desiccator, and weighed. The percentage of antimony sulfide shall be calculated as follows:

$$\text{Antimony sulfide, percent} = \frac{A \times 100}{B}$$

Where:

A = Weight of residue in the crucible.
B = Weight of sample on a moisture-free basis.

4.4.2.3 Lead azide. - the lead azide content shall be determined using the (Eudiometer) method and apparatus in MIL-STD-650 Method No. 407.1.

4.4.2.4 Lead sulfocyanate. - The percentage of lead sulfocyanate in the sample shall be calculated on a moisture free basis by subtracting from 100 the sum of the percentages of potassium chlorate, antimony sulfide, and lead azide.

*4.4.3 Functioning. - The primer shall be assembled to the applicable test equipment and a steel ball weighing a maximum of 3.95 ounces shall be dropped from a maximum height of

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

1 1/2 inches on the firing pin of the test set-up. A primer that fails to fire or fails to fire with a high order report shall be classed defective. Method of Inspection shall be in accordance with dwgs. 8816367, 8827828, 8827829, 8827934, 9200012, 9200443, 9200444 and 9202650.

4.4.3.2 Waterproofness. - The primer shall be immersed under water as specified for the time specified. Within one hour after removal from the water the primer shall be subjected to the sensitivity test specified in 4.3.3.2. Any primer which fails to fire shall be classed defective.

*5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.

5.1.1 Level C. - Packaging shall be as specified on dwgs. 9258182 and 9258183.

5.2 Packing

5.2.1 Level C. - Packing shall be as specified on dwg. 9258184.

5.3 Marking. - Marking of all packaging and packing shall comply with dwgs. 9258182, 9258183, and 9258184.

*6. NOTES

6.1 Ordering data.-Procurement documents shall specify the following:

a. Title, number and date of this specification.
b. Data cards. - Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.
c. Provisions for submission of first article samples.

6.2 Inspection code numbers.-The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government. They should be cited as references on drawings of equipment designs submitted by the contractor to the Government for approval (see 6.3.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

6.3 Inspection Equipment Designs.-Inspection equipment designs are of two types - Government Special Inspection Equipment (SIE) designs and contractor designs. SIE designs are designated by drawing numbers under the "Method of Inspection" headings in Section 4. Design responsibility for all other inspection equipment is assigned to the contractor. The contractor need not furnish any design when a complete Government SIE design is provided. Unless otherwise specified, however, the contractor may submit alternate or modified contractor designs of SIE in accordance with 6.3.2 and 6.3.3 should he elect to do so.

6.3.1 SIE designs.-SIE designs may consist of any of the following:

a. Detailed drawings which completely depict all information necessary for the fabrication and use of the item of inspection equipment.

b. A source control drawing or a specification control drawing as defined in MIL-STD-100.

c. An envelope drawing, as defined in MIL-STD-100, which establishes the criteria which a detailed design shall meet. When envelope drawings are specified, the contractor shall prepare designs which comply with the criteria therein.

6.3.2 Contractor designs.-Contractor designs are required for all inspection equipment for which SIE designs are not specified and may include commercial equipment which the contractor proposes to use. (Commercial equipment is defined as unmodified equipment which is cataloged and available for purchase by the general public). Contractor designs shall include appropriate operating instructions, calibration procedures and maintenance procedures. Commercial equipment shall be fully described by catalog listings or other means which provide sufficient information to permit identification and evaluation by the Government and may include illustrations and engineering data. Designs shall be prepared for any special fixture(s) required to be used with commercial equipment, or with SIE designs if not otherwise covered thereby (see 6.3.1c). Designs shall be of the category and form (per MIL-D-1000) specified in the Contract Data Requirements Lists (DD Form 1423). The contractor is referred to MIL-HDBK-204, "Inspection Equipment Design" for guidance. The specification number and the applicable five digit defect code number (or other specific identifying information) from Section 4 of this specification shall be referenced on each contractor design together with the component or assembly drawing number and revision letter to which the specific design applies.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:19Z
Check the source to verify that this is the current version before use.

6.3.3 Submission of Designs for Approval.-Contractor designs shall be approved by the Government prior to fabricating or procuring the equipment. Designs shall be submitted for approval to Commander, Picatinny Arsenal, ATTN: SARPA-QA-A-M, Dover, New Jersey 07801 in accordance with the stipulations, time frame and distribution specified in the Contract Data Requirements List (DD Form 1423) or in the contract. The contractor must include in his submission of designs a listing of any and all Government SIE designs which will be utilized. Partial submission of inspection designs is permissible and encouraged. However, the completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will normally be accomplished within one month after receipt.

6.4 Check test for possible deterioration. - The following test is designed to prevent major ammunition items being loaded with primers that may have deteriorated. This test shall be performed on primers from each lot which has been stored under normal conditions for more than two years, or under adverse conditions for any period of time. If the specification for the ammunition item into which the primers are loaded does not require a check test, the contracting officer shall insert into the contract a check test performance provision. the contracting officer will arrange for the contractor to be reimbursed for expenses incurred in the performance of the deterioration check test.

6.4.1 Functioning. - A sample of 315 primers shall be selected at random from each lot. If 4 or more primers fail to comply with the requirement specified, the lot shall be rejected. If more than one defective is found, a second sample of 315 shall be selected at random and tested. If in the combined first and second sample a total of 5 or more defectives are found, the lot shall be rejected. The test shall be performed as specified in 4.4.3 using test equipment as specified in 4.3.4 and 4.4.3.

6.5 The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

6.6 Supersession data. - This specification includes the requirements of MIL-P-60048 (MU) dated 27 July 1964.

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 1375-A-090

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:19Z
Check the source to verify that this is the currentversion before use.

FOLD

Department of the Army
Headquarters, Picatinny Arsenal
Dover, New Jersey 07801

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

Commander
Picatinny Arsenal
ATTN: SARPA-QA-A
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.