MIL-T-58070A(AV)
3 April 1970
SUPERSEDING
MIL-T-58070(MO)
23 April 1964

MILITARY SPECIFICATION

TESTER SET, CYLINDER COMPRESSION

1. SCOPE

1.1 This specification covers a cylinder compression tester set for aircraft reciprocating engines.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

QQ-B-626	Brass, Leaded and Non-Leaded: Rod, Shaped, Forgings, and Flat Products with Finished Edges (Bar and Strip)
QQ-C-502	Copper Rods and Shapes, and Flat Products with Finished Edges (Flat Wire, Strips and Bars)
TT-E-489	Enamel, Alkyd, Gloss, (for Exterior and Interior Surfaces)
TT-P-636	Primer Coating, Alkyd, Wood and Ferrous Metals
TT-P-664	Primer Coating, Synthetic, Rust-Inhibiting, Lacquer-Resisting
PPP-B-591	Boxes, Fiberboard, Wood-Cleated
PPP-B-601	Boxes, Wood, Cleated-Plywood
PPP-B-636	Box, Fiberboard
PPP-B-640	Boxes, Fiberboard, Corrugated, Triple, Wall

FSC 4920

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-T-704	Treatment and Painting of Materiel
MIL-R-3065	Rubber, Fabricated Parts
MIL-L-6082	Lubricating Oil; Aircraft Reciprocating Engine (Piston)
MIL-H-9850	Hinge, Butt, Continuous, Piano

STANDARDS

FEDERAL

FED. TEST METHOD STD. NO. 151	Metals; Test Methods
FED-STD-595	Colors

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	Marking for Shipment and Storage
MIL-STD-130	Identification Marking of US Military Property
MIL-STD-143	Specifications and Standards Order of Precedence for the Selection of
MIL-STD-417	Rubber Compositions, Vulcanized, General Purpose, Solid (Symbols and Tests)
MS33586	Metals, Definition of Dissimilar

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications.--The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

NATIONAL BUREAU OF STANDARDS

Handbook H28	Screw-Thread Standards for Federal Services

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington 25, D. C.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Compression tester set.--The portable cylinder compression tester set shall consist of nine dial-indicating gages each complete with a valve assembly, flexible extension, and adapters; a carrying case; and a repair kit.

3.1.1 First article.--When specified (see 6.2), the supplier shall furnish one complete tester set for first article inspection. The first article may be either a pre-production model or an initial production item which conforms to this specification. In either case, the approved first article and the production items shall be identical and in accordance with the terms of the contract. Approval of the first article shall not relieve the supplier of the responsibility to furnish equipment in accordance with this specification.

3.2 Materials.--Materials shall be as specified herein. wnen specifications and standards are not specifically designated, selection shall be in accordance with MIL-STD-143.

3.3 Construction.--All parts susceptible to wear, breakage, or distortion shall be accessible for replacement, adjustment, and repair.

3.3.1 Standard parts.--AN or MIL standard parts shall be used whenever they are suitable for the purpose, and shall be identified on the drawings by their part numbers. Commercial utility parts such as screws, bolts, nuts, and cotter pins, etc., may be used provided they have suitable properties and are replaceable by AN or MIL standard parts without alteration.

3.3.2 Metals.--Metals shall be of the corrosion-resistant type, or treated to resist corrosion due to fuels, salt spray, or atmospheric conditions apt to be met in storage or normal service. Unless protected from corrosion due to electrolytic action, dissimilar metals shall not be used in intimate contact with each other. Dissimilar metals are defined in MS33586.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

3.3.3 Fastening devices.--All screws, pins, bolts, and similar fastening devices shall be installed with a means for preventing loss of tightness. If such parts are subject to removal or adjustment, they shall not be swaged, peened, staked, or otherwise permanently deformed.

3.3.4 Threaded parts.--Threaded parts shall conform to Handbook H28, as applicable. The Unified fine thread series shall be used for threaded parts less than 1/4-inch diameter. The Unified or American National coarse thread series shall be used for threaded parts 1/4-inch diameter and larger; however, the Unified fine thread series may be employed for these sizes when applicable. Pipe threads shall conform to the American National taper pipe thread series.

3.3.5 Interchangeability of parts.--Components shall be interchangeable (without requiring modification for replacement) with similar components furnished under the same contract or order.

3.4 Components.--

3.4.1 Tester.--Each tester shall consist of a dial-indicating pressure gage, valve assembly, flexible extension, and adapters.

3.4.1.1 Gage.--The gage shall be of Bourdon tube type embodying the following characteristics:

3.4.1.1.1 Operating mechanism.--The Bourdon tube shall be of phosphor bronze, beryllium copper, or stainless steel, and shall be soldered in the socket, or threaded and soldered. The end opposite the socket end shall be sealed by a plug, soldered, or threaded and soldered.

3.4.1.1.2 Stem.--The Bourdon tube and operating mechanism of the gage shall be supported by a stem secured to the housing in such a manner that working or twisting of the housing will not cause movement of the pointer. An integral wrench grip shall extend at least 1/4-inch outside the housing.

3.4.1.1.3 Dial.--The dial shall be 2-1/2-inch diameter, with a scale arc of not less than 270 degrees. Graduations and figures shall be black on a dull white background. The

Source: https://assist.dla.mil -- Downloaded: 20261O-26T04:19Z
Check the source to verify that this is the current version before use.

dial shall have a minimum scale range of 0 to 160 pounds per square inch gage (psig). The dial scale shall be graduated in increments of not more than 2 psig, with numerical markings at 20-psig intervals.

3.4.1.1.4 Pointer.--The pointer shall be plain, and black.

3.4.1.1.5 Housing.--The housing shall be of metal construction and shall have a threaded or screw-retained bezel to retain the crystal. The bezel shall be of the same material and finish as the housing. Openings shall be provided in the housing, or between the housing and stem, to relieve the pressure in event of gage failure.

3.4.1.1.6 Crystal.--The crystal shall be not less than 1/16-inch thick, and of shatterproof glass or transparent plastic material unaffected by oil or gasoline.

3.4.1.2 Valve assembly.--One end of the valve assembly shall screw onto, or into, the stem of the gage to form a pressuretight connection, and the other end shall be threaded to form a pressuretight connection with the flexible extension. The external wrench grip on the assembly shall be at least 3/8-inch wide. The assembly shall contain a check valve to trap the pressure admitted to the gage and a relief valve to release the trapped pressure and return the gage to zero. One valve may perform both these functions. The valve or valves shall be of oil-resistant material equal to, or exceeding type S, class SA of MIL-STD-417 under the requirements of MIL-R-3065. The valves shall operate satisfactorily after being immersed for 24 hours in lubricating oil conforming to MIL-L-6082. The loss of air pressure from the valve assembly during a 5-minute period with 160 psig trapped in the gage shall not exceed 5 psig.

3.4.1.3 Flexible extension.--Overall length of the flexible extension shall be 8 inches, plus or minus 1/8-inch. Each end of the extension shall provide a 3/4-inch wrench grip at least 1/4-inch wide. The end which attaches to the valve assembly shall be threaded to receive the valve assembly and form a pressuretight connection. The opposite end shall

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

be threaded to form a pressuretight connection with the 18-mm adapter. The flexible section of the extension shall be fabricated of oil-resistant rubber and shall contain soft annealed, twisted strands of copper core 5 inches long, with air space between each strand. The copper core shall be pliable to permit forming the hose to the desired shape, and rigid enough to support and position the gage as required for viewing. The hose shall be protected with a shield approximately 1 inch long at both ends around the inner or outer wall, to prevent the ends of the copper core from puncturing the hose when the flexible extension is bent to various shapes. The hose and fittings shall withstand a proof hydrostatic pressure of 300 psig for a 10-minute period, after being submerged 24 hours in oil conforming to MIL-L-6082. The flexible extension shall incorporate an arrangement that will permit 360-degree rotation of the gage for viewing.

3.4.1.4 Threaded adapters.--One 18-mm and one 14-mm adapter shall be furnished with each tester. Adapters shall be of quarter-hard or half-hard temper brass conforming to QQ-B-626. A felt filter shall be located inside the adapter or in the flexible extension, to prevent oil or carbon particles from entering the valve assembly. An integral 7/8-inch wrench grip at least 3/8-inch wide shall complement each adapter. The spark plug port end thread length shall be 3/8-inch, plus or minus 1/16-inch. The opposite end of the 18-mm adapter shall be threaded to receive the valve assembly or flexible extension; the opposite end of the 14-mm adapter shall be threaded to receive the spark plug port end of the 18-mm adapter and form a pressuretight connection therewith. Each adapter shall be identified by its size stamped or engraved thereon.

3.4.1.5 Washers.--Washers of metal or of oil-resistant rubber shall be used where necessary to effect a pressuretight connection. Metal washers shall be of copper, soft, in accordance with QQ-C-502 and rubber washers shall be in accordance with MIL-R-3065 and with MIL-STD-417.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

3.4.2 Repair kit.--A repair kit shall be furnished with each tester set. The kit shall contain three each of relief valves, check valves, felt filters, and replaceable washers. The parts container shall be constructed of metal or plastic and provide a suitable storage for the spare parts within the carrying case.

3.4.3 Carrying case.--The carrying case shall be approximately 14 inches wide by 16 inches long, and the overall height shall not exceed 3-1/2 inches. It shall be constructed of .032-inch steel and have a hinged lid, a positive type latch, and a carrying handle. The hinge shall be a continuous piano type conforming to MIL-H-9850. A rack or framework shall be attached inside the case to position and immobilize the individual testers and the components of the tester set.

3.5 Performance and product characteristics.--

3.5.1 Pressure.--All pressuretight connections shall withstand, without damage, maximum air pressures to which the scale is graduated, when tightened to 20 foot-pounds torque, plus or minus 1 foot-pound. (See 4.4.2.)

3.5.2 Accuracy.--The error in pressure indication at 80° F., plus or minus 10° F., with readings taken either in the increasing or decreasing direction, at any point above 20 percent and below 80 percent of the maximum pressure to which the scale is graduated, shall not exceed plus or minus 3 psig, and for the remainder of the scale the error shall not exceed plus or minus 4 psig. (See 4.4.3.)

3.5.3 Vibration.--The tester set, and all components thereof enclosed in the carrying case, shall be capable of withstanding without damage or change in accuracy, the tests specified in 4.4.4.

3.5.4 Shock.--The tester and all components thereof, when enclosed in the carrying case, shall withstand without damage or change in accuracy, the shock tests specified in 4.4.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

3.5.5 Temperature and humidity conditions.--

3.5.5.1 Storage.--The compression tester set and all components thereof shall be able to withstand storage without damage in temperatures specified in 4.4.1.1.1 and 4.4.1.1.2. Following the extreme exposures, and when stabilized at 80° F., the compression tester shall conform to the accuracy specified in 3.5.2.

3.5.5.2 Operating temperatures.--The compression tester set and all components thereof shall be able to withstand damage and to operate within the accuracy specified in 3.5.5.2.1 and 3.5.5.2.2, while being subjected to operating temperature from minus 25° F. to plus 115° F. as specified in 4.4.1.2.

3.5.5.2.1 Low.--When the tester is operated in an ambient air temperature of minus 25° F. the error in pressure indications shall not exceed plus or minus 5 psig at any point above 20 percent and below 80 percent of the maximum pressure to which the scale is graduated, and shall not exceed plus or minus 8 psig at scale readings for the remainder of the scale.

3.5.5.2.2 High.--When the tester is operated in an ambient air temperature of plus 115° F., the error in pressure indications shall not exceed plus or minus 5 psig at any point above 20 percent and below 80 percent of the maximum pressure to which the scale is graduated, and shall not exceed plus or minus 8 psig at scale readings for the remainder of the scale.

3.5.5.3 Humidity conditions.--The compression tester and all components thereof shall withstand without damage and operate within the accuracy specified in 3.5.2, after exposure to 20 hours of relative humidity between 93 and 97 percent at air temperatures from 80° F. to 85° F., followed by 4 hours of 100 percent relative humidity with condensation at 75° F. to 80° F. Air movement and radiation shall be negligible. (See 4.4.1.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

3.5.6 Endurance.--The compression tester shall exhibit no functional failure when subjected to 1,000 operating cycles each at pressures of 40, 80, 120, and 160 psig. The error in pressure indication at the finish of these operations shall not exceed plus or minus 3 psig at any point above 20 percent and below 80 percent of the maximum pressure to which the scale is graduated, and plus or minus 4 psig for the remainder of the scale in a temperature of 80° F., plus or minus 10° F. (See 4.4.8.)

3.6 Painting and finishing.--Housing and carrying case shall be painted and finished as follows:

3.6.1 Preparation of surfaces.--Surfaces to be painted shall be cleaned of all grease, oil, scale, rust, dirt, and other extraneous matter, and shall be dry.

3.6.2 Painting.--Painting shall be in accordance with MIL-T-704, except that the tester shall be finished with one coat of primer conforming to TT-P-636 or TT-P-664, followed by two coats of enamel conforming to TT-E-489. Color shall be No. 16187 (gray) as shown in FED-STD-595.

3.7 Identification of product.--The tester set shall be identified in accordance with MIL-STD-130.

3.8 Technical data.--Unless otherwise specified (see 6.2.2) operation and maintenance instructions, with a spare parts list, are required. One copy shall be packed with each tester set, and identified on a numbered DD Form 1664.

3.9 Workmanship.--Workmanship shall be of a quality that will produce a compression tester set assuring the highest degree of accuracy and durability. The tester set shall be clean, free of scratches, dents, pits, rust, and loose connections. External surfaces of the testers and carrying case shall be rounded or beveled to prevent injury during handling.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:19Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.--Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of examinations and tests.--Examinations and tests shall be classified as (1) first article (see 3.1.1) and (2) quality conformance (see 4.2.2).

4.2.1 First article.--Unless otherwise specified in 6.2, the first article shall be examined and tested as specified in 4.4 through 4.4.8. Failure of the first article to pass any examination or test shall be cause for rejection.

4.2.2 Quality conformance.--Conformance examinations and tests shall be as specified in 4.3 and 4.4.

4.3 Sampling.--From lots of 100, or a fraction thereof of the total number of individual tester sets submitted for acceptance at one time, tester sets shall be examined in accordance with MIL-STD-105, using the acceptable quality levels (AQL's) indicated in table I.

4.4 Conformance tests.--From each lot of tester sets which has passed the acceptance examination specified in 4.3, samples shall be selected for the following tests. Acceptance or rejection shall be based on an AQL of 4.0 percent defective:

(a) Pressure retention (see 4.4.2).
(b) Accuracy (see 4.4.3).

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:19Z
Check the source to verify that this is the current version before use.

4.4.1 Test methods.--

4.4.1.1 Storage.--

4.4.1.1.1 Low temperature.--The complete compression tester set shall be placed in an ambient air temperature of minus 60° F. to minus 65° F. for a 72-hour period. At the end of this time, this tester shall be removed and allowed to stabilize at an air temperature of 80° F., plus or minus 10° F. The tester shall then be inspected for evidence of damage and tested for accuracy in accordance with 4.4.3 (see 3.5.5.1).

4.4.1.1.2 High temperature.--The complete compression tester set shall be subjected to a 24-hour cycle of tests starting with 10 hours at 90° F., plus or minus 5° F., followed by 5 hours of steady increase to 150° F., to 155° F., 4 hours at 150° F., and 5 hours of steady decrease to 90° F., plus or minus 5° F. The tester shall then be inspected for evidence of damage and tested for accuracy in accordance with 4.4.3 (see 3.5.5.1).

4.4.1.2 Operating temperatures.--

4.4.1.2.1 Low.--The complete tester, after being subjected to temperatures specified in 3.5.5.2.1, shall be tested in accordance with the procedure in 4.4.3 to determine compliance with the accuracy limits specified in 3.5.5.2.1.

4.4.1.2.2 High.--The complete tester, after being subjected to temperatures specified in 3.5.5.2.2, shall be tested in accordance with the procedure in 4.4.3 to determine compliance with the accuracy limits specified in 3.5.5.2.2.

4.4.1.3 Humidity.--The complete tester, in the carrying case, shall be subjected to the humidity conditions specified in 3.5.5.3. At the conclusion of the humidity test, the tester shall be inspected for damage and tested for accuracy in accordance with 4.4.3 (see 3.5.5.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

TABLE I. -- Classification of defects in accordance with MIL-STD-105.

Category	AQL percent defective		Defects	Paragraph reference
CRITICAL:	None defined			
MAJOR:	2.5			
101		Parts inaccessible for repair		3.3
102		Corrosion or rust affect operation; materials not properly treated		3.3.2
103		Fastening devices inadequate		3.3.3
104		Threaded parts not as specified		3.3.4
105		Interchangeability not as specified		3.3.5
106		A component omitted		3.4
107		Operating mechanism not as specified		3.4.1.1.1
108		Stem not as specified		3.4.1.1.2
109		Gage dial range less than 0 to 160 psig		3.4.1.1.3
110		Valve(s) fail to operate		3.4.1.2
111		Valve assembly does not mate properly with gage or flexible extension assembly		3.4.1.2
112		Flexible extension connection does not mate properly with the threaded adapters		3.4.1.3
113		Washers do not provide pressure-tight connections as specified		3.4.1.5
114		Repair kit incomplete		3.4.2
MINOR	4.0			
201		Gage housing wrench grip not as specified		3.4.1.1.2
202		Dial background, figures, and scale graduations not as specified		3.4.1.1.3
203		Pointer color not as specified		3.4.1.1.4
204		Wrench grip on valve assembly not as specified		3.4.1.2
205		Flexible extension overall length and fittings not as specified		3.4.1.3
206		Carrying case not as specified		3.4.3
207		Treatment and painting not as specified		3.6
208		Identification marking not as specified		3.7
209		Workmanship inferior; surfaces not smooth and edges not rounded or beveled		3.9
210		Preparation for delivery not as specified		5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

4.4.1.4 Salt spray.--The complete tester set shall be subjected to the salt spray test for 32 hours, in accordance with method 811.1 of Federal Test Method Standard No. 151. At the end of this period, the tester set shall be washed free of salt particles, air-dried to remove surface moisture, and examined for evidence of damage (see 3.3.2).

4.4.2 Pressure retention.--An air pressure of 160 psig shall be applied to the gage and the valve assembly for 6 seconds, and after a 5-minute interval the pressure loss shall not exceed 5 psig.

4.4.3 Accuracy.--The gage, valve assembly, extension, and adapters shall be assembled and torqued to 20 foot-pounds, plus or minus 1 foot-pound (see 3.5.1). Accuracy of the tester shall be tested at all graduations with numerical markings throughout the entire range of scale by comparison with a standard air pressure measuring device having an overall accuracy of 1/4 of 1 percent. Accuracy shall be within the limits specified in 3.5.2.

4.4.4 Vibration.--The tester set with all components enclosed in the carrying case, shall be rigidly mounted on a vibration machine and subjected to vibrations (simple harmonic motion) with an amplitude of 0.030-inch (0.060-inch total excursion) at 10 to 40 cycles per second for 1/2-hour each, in the direction of each of the three major axes. The frequency shall be continually varied, with the entire range being accomplished once every 5 minutes. At the conclusion of the test, the tester set shall be examined for evidence of damage and tested for accuracy in accordance with 4.4.3 to determine compliance with 3.5.3.

4.4.5 Shock.--The tester set, with all components enclosed in the carrying case, shall be dropped three times on the bottom surface of the carrying case to a concrete floor from a height of 8 inches. On conclusion of the test, the tester set shall be examined for evidence of damage, and tested for accuracy in accordance with 4.4.3 to determine compliance with 3.5.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

4.4.6 Valves.--The valve or valves shall be completely immersed in lubricating oil conforming to MIL-L-6082 at a temperature of 80° F., plus or minus 10° F., for a 24-hour period. At the conclusion of the immersion period, the valve or valves shall be removed from the oil, cleaned, and reassembled to the tester. The tester shall be tested in accordance with 4.4.2 to determine compliance with 3.4.1.2.

4.4.7 Flexible extension.--The flexible extension shall be completely immersed in oil conforming to MIL-L-6082 at a temperature of 80° F., plus or minus 10° F., for a 24-hour period. At the conclusion of the immersion period the flexible extension shall be cleaned and subjected to a hydrostatic pressure of 300 psig. During and after the pressure test, the flexible extension shall be examined to determine compliance with 3.4.1.3.

4.4.8 Endurance.--At the conclusion of the oil-resistant valve test specified in 4.4.6, the compression tester shall be assembled as specified in 4.4.3. Air pressure shall be applied for approximately 1 second on and 5 seconds off, with the air pressure relieved by operating the compression tester relief valve once every cycle and prior to application of pressure for the next test cycle. The rate of cycling shall be approximately 10 cycles per minute for a total of 4,000 cycles, as specified in 3.5.6. Upon completion of this test, the tester shall be inspected for damage and tested in accordance with the accuracy procedure in 4.4.3 to determine compliance with the accuracy specified in 3.5.6.

4.4.9 Test report.--Unless otherwise specified (see 6.2.1), test reports are required, and shall be identified on a numbered DD Form 1664 (see 6.2.2).

4.5 Inspection of preparation for delivery.--The packaging, packing, and marking of the tester sets shall be inspected to determine conformance with section 5 of this specification.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:19Z
Check the source to verify that this is the currentversion before use.

5. PREPARATION FOR DELIVERY

5.1 Packaging.--Tester sets shall be packaged at level A or C, as specified (see 6.2).

5.1.1 Level A.--Tester sets shall be individually packaged in snug-fitting fiberboard containers conforming to class weather-resistant of PPP-B-636.

5.1.2 Level C.--Tester sets shall be individually packaged in a manner to prevent deterioration and damage during shipment from the supply source to the first receiving activity.

5.2 Packing.--Packing shall be at level A, B, or C, as specified (see 6.2.1).

5.2.1 Level A.--Tester sets packaged as specified in 5.1.1 shall be packed in exterior shipping containers conforming to oversea type of PPP-B-601. Gross weight of each container shall not exceed 200 pounds.

5.2.2 Level B.--Tester sets packaged as specified in 5.1.1 shall be packed in exterior shipping containers conforming to class II weather resistant of PPP-B-591 or class 2 of PPP-B-640. Gross weight of each container shall not exceed 200 pounds.

5.2.3 Level C.--Tester sets packaged as specified in 5.1.1 or 5.1.2 shall be packed in a manner to insure carrier acceptance and safe delivery to destination at the lowest applicable rate. Shipping containers shall comply with carrier rules and regulations applicable to the mode of transportation.

5.3 Marking.--In addition to any special marking required by the contract or order, marking shall be in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:19Z
Check the source to verify that this is the currentversion before use.

6. NOTES

6.1 Intended use.--This compression tester set is intended for use in testing the cylinder compression of aircraft reciprocating engines.

6.2 Ordering data.--Procurement documents should specify:

6.2.1 Procurement requirements.--

(a) Title, number, and date of this specification.

(b) Whether first article inspection and tests are required (see 3.1.1 and 4.2.1).

(c) Extent of technical data required (see 3.8 and 4.4.9).

(d) Level of preparation for delivery required (see 5.1 and 5.2).

(e) Whether special marking for shipment is required (see 5.3).

(f) Whether first article approval is required (see 6.3).

6.2.2 Contract data requirements.--Data specified in 3.8 and 4.4.9 will be delivered as identified on a numbered DD Form 1664 when specified on a DD Form 1423 incorporated in the contract.

6.3 First article.--When first article approval is required (see 3.1.1), the solicitations should include complete information concerning examination and test in accordance with 4.2.1.

Custodian:

Army -- Aviation Systems Command

Preparing Activity:

Army -- AV

Review Activities:

User Activities:

Project No. 4920-A274

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE | CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)* | DATE

DD FORM 1 JAN 66 1426 REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:19Z
Check the source to verify that this is the currentversion before use.

FOLD

POSTAGE AND FEES P

OFFICIAL BUSINESS

Commanding General
US Army Aviation Systems Command
ATTN: AMSAV-R-MN
PO Box 209
St. Louis, Missouri 63166

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.