The documentation and process conversion measures necessary to comply with this amendment shall be completed by 8 December 1988.

MILITARY SPECIFICATION

SEMICONDUCTOR DEVICE, DARLINGTON TRANSISTOR, NPN, SILICON,
POWER TYPES 2N6350, 2N6351, 2N6352, AND 2N6353
JAN, JANTX, AND JANTXV

This amendment forms a part of MIL-S-19500/472A(ER) dated 20 January 1983, and is approved for use within the U.S. Army Laboratory Command, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4 -

FIGURE 1, bottom view lower base (B2): Delete "B2" and substitute "B1".

PAGE 9

TABLE I, subgroup 3, low temperature operation, conditions column: Delete "65°C" and substitute "-65°C".

PAGE 12

TABLE II, subgroup 3, delete in its entirety and substitute:

Intermittent operation life	1037	Power shall be applied for the time necessary to achieve a 100°C -10°C +15°C minimum rise in T_J, 2000 cycles, t_{on} = 1 minute minimum (for TO-66) t_{on} = 30 seconds minimum (for TO-33) This test is intended to allow the case temperature to rise and fall appreciably as the junction is heated and cooled; thus, it is not appropriate to use a large heat sink or a high power short pulse. The power level, power-on time, and heat sink used, if any, shall be chosen to ensure that at the end of the heating cycle, the case temperature is not more than 15°C below the junction temperature.	5
Electrical measurements		See table IV steps 1, 2, 4, and 5.	

PAGE 14

TABLE III, subgroup 2, Thermal shock, condition column: Add "200 cycles".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:17Z
Check the source to verify that this is the current version before use.

PAGE 15

TABLE III, subgroup 6, delete in its entirety and substitute:

Intermittent operation	1037	Power shall be applied for the time necessary to achieve a 100°C -10°C +15°C minimum rise in T_J, 6000 cycles, t_{on} = 1 minute minimum (for TO-66) t_{on} = 30 seconds minimum (for TO-33) This test is intended to allow the case temperature to rise and fall appreciably as the junction is heated and cooled; thus, it is not appropriate to use a large heat sink or a high power short pulse. The power level, power-on time, and heat sink used, if any, shall be chosen to ensure that at the end of the heating cycle, the case temperature is not more than 15°C below the junction temperature.	5
Electrical measurements		See table IV steps, 1, 2, 3, and 5	

PAGE 16

TABLE IV, add the following:

5	Thermal resistance (junction to case)	3151	Base 1 shorted to base 2	$R_{\theta JC}$	(see 1.3)	°C/W

Custodians:
Army - ER

Review activities:
DLA - ES

Preparing activity:
Army - ER

Agent:
DLA - ES

(Project 5961-A938)

☆U.S. GOVERNMENT PRINTING OFFICE: 1988 — 506-033/91602

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:17Z
Check the source to verify that this is the current version before use.