The documentation and process conversion measures necessary to comply with this amendment shall be completed by 26 September 2001.

INCH-POUND

MIL-PRF-19500/599C
AMENDMENT 2
26 June 2001
SUPERSEDING
AMENDMENT 1
8 May 1998

PERFORMANCE SPECIFICATION SHEET

SEMICONDUCTOR DEVICE, QUAD, FIELD EFFECT TRANSISTORS,
P-CHANNEL, SILICON TYPE 2N7335
JAN, JANTX, JANTXV, JANS, JANHC, AND JANKC

This amendment forms a part of MIL-PRF-19500/599C, dated 30 December 1997 and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.2; delete “(MO-Q36AB)” and substitute “(MO-036AB)”.

PAGE 3

FIGURE 1; delete “LL_2” and substitute “LL_1”.

FIGURE 1, title; delete and substitute “FIGURE 1. Dimensions and configuration (MO-036AB).”

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:55Z
Check the source to verify that this is the current version before use.

PAGE 4

FIGURE 1, dimension table; delete and substitute:

“

Symbol	Dimensions				Notes
	Inches				
	Min		Millimeters		
	Min	Max	Min	Max	
BH	.105	.175	2.67	4.45	11
BL	.690	.770	17.53	19.56	
BW	.290	.325	7.37	8.26	
BW_1	.280	.310	7.11	7.87	10
LH	.025	.055	0.64	1.40	11
LL	.125	.175	3.18	4.45	11
LL_1	.000	.030	0.00	0.76	
LS	.300 TP		7.62 TP		5, 6
LS_1	.100 TP		2.54 TP		5, 6
LT	.008	.012	.203	.305	
LW	.015	.021	.381	.533	
LW_1	.038	.060	0.97	1.52	
N	14		14		8
R	.010	- - -	0.25	- - -	
S	.030	.095	0.76	2.41	
α	0°	15°	0°	15°	7

“

FIGURE 1 title, delete “(MO-Q36AB)” and substitute “(MO-036AB)”.

PAGE 5

FIGURE 2, note 3; delete “.005 inch” and substitute “±.005 inch”.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:55Z
Check the source to verify that this is the current version before use.

PAGE 7

* 4.3, Screen 12, JANTX and JANTXV, delete “Method 1042, test condition A”, and substitute “Method 1042, test condition A or accelerated, T_A = +175°C, t = 48 hours.”

PAGE 8

4.4.2.1, subgroup B5, conditions column; delete and substitute:

“ Accelerated steady-state gate stress, method 1042, condition B, T_A = +175°C, t = 24 hours. Test condition A, T_A = +175°C, t = 120 hours. Read and record $V_{BR(DSS)}$ (pre and post) at I_D = 1 mA.”

PAGE 11

TABLE I, subgroup 2, gate to source voltage (threshold), method column; delete “3404” and substitute “3403”.

PAGE 12

TABLE I, subgroup 3, gate to source voltage (threshold), method column; delete “3404” and substitute “3403”.

* TABLE I, subgroup 4, switching time test, delete R_g = 24Ω and substitute “R_g = 7.5Ω”

* TABLE I, subgroup 4, turn-off delay time, delete “turn-off delay time”, and substitute with “turn-off delay time, with a maximum limit of t_f = 70ns.”

* TABLE I, subgroup 4, Fall time, max limits column; delete “40” and substitute “80”.

PAGE 16

5.2, Marking; delete “MIL-STD-129” and substitute “MIL-PRF-19500”.

NOTE: The margins of this amendment are marked with asterisks to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - CR
Navy - NW
Air Force - 11
NASA - NA
DLA - CC

Review activities:
Army - AR, SM
Navy - AS, CG, MC
Air Force - 13, 19, 99

Preparing activity:
DLA - CC

(Project 5961-2244)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:55Z
Check the source to verify that this is the current version before use.