UU-C-620b
FEBRUARY 12, 1958

SUPERSEDING
Int. Fed. Spec. UU-C-00620 (GSA-FSS)
April 2, 1957, and
Fed. Spec. UU-C-620
September 13, 1946

FEDERAL SPECIFICATION

COVERS, HEADREST, PAPER, (DENTAL CHAIR)

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE

1.1 Scope. — This specification covers disposable paper covers suitable for use as a cover for headrests of operative chairs.

2. APPLICABLE SPECIFICATIONS AND STANDARDS

2.1 Specifications and standards.—The following specifications and standards, of the issues in effect on date of invitation for bids, form a part of this specification:

Federal Specifications:

V-T-276—Thread; Cotton.
UU-P-31—Paper; General Specifications and Methods of Testing.
DDD-S-751—Stitches; Seams; and Stitching.
PPP-B-636—Boxes, Fiber.

Federal Standards:

Fed. Std. No. 102—Preservation, Packaging and Packing Levels.

(Activities outside the Federal Government may obtain copies of Federal Specifications and Standards as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington 25, D. C.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, Seattle, and Washington, D. C.

(Federal Government activities may obtain copies of Federal Specifications and Standards and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 — Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 — Marking for Shipment and Storage.

3. REQUIREMENTS

3.1 Material.

3.1.1 *Paper.*—Paper for covers shall be creped, color white, of fully bleached chemical fiber. Paper shall be free from unbleached pulps or groundwood, and shall conform to the following physical requirements:

3.1.1.1 *Basis weight (creped).* — The weight on a basis of 500 sheets, 24 by 36 inches, shall be not less than 11 pounds.

3.1.1.2 *Tensile breaking strength (dry).*— The average minimum dry tensile strength

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

shall be 3 pounds per inch in the machine direction.

3.1.1.3 *Elongation.* — Unless otherwise specified, the average minimum percentage of elongation at rupture shall be 25 percent (1 inch to 1.25 inch) in the machine direction.

3.1.2 *Thread.*—Thread for stitching shall conform to type I, machine thread of a suitable ply and ticket number, as shown in table I of Federal Specification V–T–276. Color shall be white.

3.2 Construction and dimensions.—Covers shall be of the envelope type and shall be made of paper specified in 3.1.1. Covers shall measure 10 inches ± ¼ inch square, with closed corners rounded approximately 2.50 inches in radius. Three edges shall be over-edge stitched with thread as specified in 3.1.2, and the open end finished square. Stitches shall conform to class 500 and seams to type SSa–1 of Federal Specification DDD–S–751. There shall be a minimum of 6 stitches to the inch.

3.3 Workmanship.—Workmanship shall be first class throughout. Finished covers shall be free from holes, dirt, wrinkles, tears, or other defects which detract from their appearance or may impair their serviceability.

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 Sampling.—Sampling procedures shall be conducted in accordance with the procedures set forth in Military Standard MIL–STD–105. In addition, samples may be requested by the procuring activity for testing at Government laboratory.

4.2 Inspection. — Inspection may be made throughout the entire process of manufacture. The passing as satisfactory of any detail of construction or materials shall not relieve the contractor of responsibility for faulty workmanship or materials which may be discovered at any time prior to final acceptance. Final inspection of the finished article shall be made either at point of production or at point of delivery, as specified (see 6.2). In case of factory inspection, every facility shall be afforded inspectors, by the manufacturer, for the prosecution of their work.

4.3 Tests.—Tests shall be conducted in accordance with the applicable specifications, as necessary, to determine compliance with this specification.

4.3.1 *Basis weight.*—Basis weight shall be determined by method 110 of Federal Specification UU–P–31.

4.3.2 *Tensile breaking strength (dry) and elongation.*—Tensile breaking strength (dry) and elongation shall be determined by method 171 of Federal Specification UU–P–31, except that the test specimen shall be 1 inch wide instead of 2 inches.

4.3.3 *Groundwood and unbleached pulps.*—Tests for the presence of groundwood and unbleached pulp shall be determined by method 300 of Federal Specification UU–P–31, paragraph 7.3.

5. PREPARATION FOR DELIVERY

5.1 Packaging.

5.1.1 *Unit of issue.*—Two hundred fifty covers, as specified, constitutes one unit.

5.1.2 *Packaging quantities.*—The number of units of issue indicated in table I shall be packaged in each unit and exterior container, as applicable, for the required level of protection specified in procurement document.

TABLE I.—*Packaging quantities*

Federal Stock Number	Unit Package	Intermediate Package	Shipping Container
8540–518–4065	1 unit	Not required	12 units

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

5.1.2.1 *Packing variation permitted.* — If the required number of units to be shipped is less than the number of units specified to be overpacked in an exterior container, such units shall be packed in an exterior container of suitable size and design, acceptable to a common carrier, which will insure safe delivery to destination.

5.1.3 *Level A.*

5.1.3.1 *Unit package.*—Each unit shall be packaged in a box constructed in accordance with Federal Specification PPP–B–636, class 2, compliance symbol W5c or W5s. Carton shall be sealed with water resistant gummed tape.

5.1.4 *Level C.*—Units shall be packaged in standard commercial containers of the size and kind commonly used, which will afford the degree of protection required for shipment and use of the product for its intended purpose within the continental limits of the United States of America.

5.2 Packing.

5.2.1 *Level A.*—Exterior container shall be a box constructed in accordance with Federal Specification PPP–B–636, class 2, compliance symbol V3c or V3s. Closure shall comply with appendix thereto, except that strapping will not be required.

5.2.2 *Level C.* — The subject commodity shall be packed in substantial commercial containers of the type, size, and kind commonly used for the purpose, so constructed as to insure acceptance and safe delivery by common or other carriers, at the lowest rate, to point of delivery called for in the contract or purchase order.

5.3 Marking.

5.3.1 *Unit package.*—Each unit package shall be marked in accordance with section 5 of Military Standard MIL–STD–129.

5.3.2 *Shipping container.*—Shipping container shall be marked in accordance with Military Standard MIL–STD–129. Service color and service symbol markings are required only on direct shipments from the contractor's plant to overseas activities.

6. NOTES

6.1 Federal Standard No. 102 should be referred to for definitions and applications of the various levels of packaging protection for supplies and equipment.

6.2 Purchasers should exercise any desired options offered herein. (See 3.1.1.3, 4.2, 5.1, and 5.2).

6.3 It is believed that this specification adequately describes the characteristics necessary to secure the desired material, and that normally no samples will be necessary prior to award to determine compliance with this specification. If, for any particular purpose, samples with bids are necessary, they should be specifically asked for in the invitation for bids, and the particular purpose to be served by the bid sample should be definitely stated, the specification to apply in all other respects.

6.4 Federal specifications do not include all types, classes, grades, sizes, etc., of the commodities indicated by the titles of the specifications, or which are commercially available, but are intended to cover the types, etc., which are suitable for Federal Government requirements.

6.5 This specification covers the following item appearing in the Armed Services Medical Stock List:

8540–518–4065 — COVER, HEADREST, PAPER, 250s.

6.6 Transportation description.—Transportation description applicable to this item is:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

Doilies, paper (headrest covers).

Carload minimum weight 24,000 pounds, subject to Rule 34, Uniform Freight Classification.

Doilies, paper, not otherwise indexed by name.

Motor volume minimum weight, any quantity.

Notice. — When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

MILITARY INTEREST:
Army—M
Navy—Md
Air Force—AF.

☆ U. S. GOVERNMENT PRINTING OFFICE: 1958

Copies of this specification may be purchased for 5 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.