UU-M-650B
July 7, 1976
SUPERSEDING
UU-M-650A
April 27, 1967

FEDERAL SPECIFICATION

MOUNT, FILM SLIDE, PHOTOGRAPHIC (OVERHEAD PROJECTOR)

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers cardboard mounts for large transparencies. These mounts are intended to be used with type 1, size C overhead projectors conforming to Fed. Std. No. 73 and Federal Specification GG-P-661.

1.2 Classification. Mounts shall be of the following types, styles, and mask apertures, as specified (see 6.2).

1.2.1 Types.

Type I - Roll glazed pressboard (permanent mounts).
Type II - Calendered pressboard (permanent mounts).
Type III - Railroad board (semi-permanent mounts).

1.2.2 Styles and mask apertures.

Style A - Fileable in letter size cabinets
Mask aperture 7 1/2 by 9 1/2 inches (for 8 1/2 by 10-inch film).
Mask aperture 7 1/2 by 10 inches (for 8 1/2 by 11-inch film).
Mask aperture 8 by 10 inches (for 8 1/2 by 11-inch film).

Style B - Fileable in legal size cabinets
Mask aperture 5 1/4 by 8 inches (for 8 by 10-inch film).
Mask aperture 7 1/2 by 9 1/2 inches (for 8 by 10-inch film).

Style C - Fileable in special cabinets or store flat in legal size cabinets.
Mask aperture 7 1/2 by 9 1/2 inches (for 8 by 10-inch film).
Mask aperture 8 by 10 inches (for 8 1/2 by 11-inch film).
Mask aperture 9 by 9 inches (for 9 1/2 by 9 1/2-inch film).
Mask aperture 10 by 10 inches (for 10 1/2 by 10 1/2-inch film).
Mask aperture 7 5/8 by 9 5/8 inches (for 8 by 10-inch film).

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

GG-P-661 - Projector, Still Picture, Overhead; Attachments and Accessories.
UU-C-201 - Cardboard and Railroad Board (Manila and Wood).
UU-P-701 - Pressboard, Colored.
PPP-B-636 - Boxes, Shipping, Fiberboard.

Federal Standards:

Fed. Std. No. 73 - Projectors, Still Picture, Overhead; Attachments and Accessories.
Fed. Std. No. 123 - Marking for Shipment (Civil Agencies).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

American National Standards Institute, Inc., (ANSI) Publications:

Z 210.1 (ASTM E380-72) - Metric Practice Guide.

(Application for copies should be addressed to the American National Standards Institute, Inc., 1430 Broadway, New York, NY 10018.)

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

2.3 Conflict with referenced documents. Where the requirements stated in this specification conflict with any requirement in a referenced specification the requirements of this specification shall apply. Nature of conflict between the specification and the referenced specification shall be submitted in duplicate to the General Services Administration, Federal Supply Service, Mechanical and Electrical Division, Washington, DC 20406.

3. REQUIREMENTS

3.1 Mounts. Each mount shall consist of a simple die-cut cardboard frame to facilitate handling, projecting and filing large transparencies for use with overhead projectors.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

3.2 Material.

3.2.1 Type I. Mounts shall be cut from flat sheets of type I roll glazed pressboard in accordance with UU-P-701. The thickness shall be 0.030-inch ± 0.0015-inch. Procuring agency shall specify color of mounts (see 6.2).

3.2.2 Type II. Mounts shall be cut from flat sheets of type II calendered pressboard in accordance with UU-P-701. The thickness shall be 0.030-inch ± 0.0015-inch. Procuring agency shall specify color of mounts (see 6.2).

3.2.3 Type III. Mounts shall be cut from flat sheets of railroad board in accordance with UU-C-201. The thickness shall be 0.030-inch ± 0.0015-inch. Procuring agency shall specify color of mounts (see 6.2).

3.3 Dimensions.

3.3.1 Conversion. All dimensions are in inches. To convert the U.S. Customary Units (inch) to the metric SI Units (centimeter), multiply by 2.54 in accordance with the conversion principles outlined in ANSI Z210.1-1973.

3.3.2 Outside dimensions. The respective vertical and horizontal dimensions for each style of mount shall be:

Style A mount - 10 1/4 inches ± 1/16-inch by 12 inches ± 1/16-inch.
Style B mount - 10 1/4 inches ± 1/16-inch by 14 inches ± 1/16-inch.
Style C mount - 12 1/2 inches ± 1/16-inch by 13 7/8 inches ± 1/16-inch.

3.3.3 Masking aperture. Dimensions of the masking aperture, nominal transparency size accommodated and the location of the aperture for each style and type of mount shall conform to those shown in table I. All dimensions are in inches.

3.3.4 Aperture location. The masking aperture of style A mounts shall be centered with respect to the outside dimensions of the mount. The masking aperture of style B and C mounts shall be located to the right of the vertical center line of the mount to provide a wide margin for annotation purposes to the left of the aperture. The displacement shall be the distance indicated in table I. The horizontal center line of each mask aperture shall be centered with respect to the top and bottom edges of the mount.

3.4 Registration pin holes. Unless otherwise specified by the procuring agency (see 6.2), mounts shall be furnished without punched holes for pin registration of the mount on the projector stage.

3.4.1 Style A. If registration holes are required in these mounts, location, number of holes, dimensions and tolerances shall be specified in the invitation for bids (see 6.2).

3.4.2 Style B. These mounts shall be furnished without registration holes.

3.4.3 Style C. If registration holes are required in these mounts, location, number of holes, dimensions and tolerances shall be specified in the invitation for bids (see 6.2).

3.5 Trim. The mounts and apertures shall be cut square on four sides to the extent that the difference between the two diagonal measurements shall not exceed 1/16-inch. All mask apertures shall have rounded corners with a radius of 1/2-inch ± 1/16-inch. Outside corners of the mounts shall be square cut or rounded according to the manufacturer's commerical practice.

3.6 Tolerances. The tolerance on mount dimensions, mask aperture dimensions and mask aperture locations shall be ± 1/16-inch. Thickness tolerance for the material that the mount is constructed of shall be in accordance with the reference material specification for each type of mount (see 3.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

TABLE I - Mounts, Types I, II and III

Style	Clear aperture (inches)	Nominal film size (inches)	Aperture location right of center	File cabinet
A	7 1/2 by 9 1/2	8 by 10	centered	letter size
A	7 1/2 by 10	8 1/2 by 11	centered	letter size
A	8 by 10	8 1/2 by 11	centered	letter size
B	5 1/4 by 8	8 by 10	9/16 inch	legal size
B	7 1/2 by 9 1/2	8 by 10	1 inch	legal size
C	7 1/2 by 9 1/2	8 by 10	3/4 inch	special size
C	8 by 10	8 1/2 by 11	3/4 inch	special size
C	9 by 9	9 1/2 by 9 1/2	3/4 inch	special size
C	10 by 10	10 1/2 by 10 1/2	3/4 inch	special size
C	7 5/8 by 9 5/8	8 by 10	centered	special size

3.7 Grain. The grain of the card stock shall run vertically in the mount.

3.8 Curl. Mount shall lie flat under normal room conditions.

3.9 Writing qualities. Both surfaces of the mounts shall accept writing in fluid ink. Writing quality shall conform to the requirements of the appropriate material specification for each type of mount (see 3.2).

3.10 Imprinting. Unless otherwise specified by the procuring agency (see 6.2), mounts shall be furnished without imprinting and marking of any type.

3.11 Performance. When tested in accordance with 4.4.2.2, the mount shall show no evidence of deterioration or no dimensional change.

3.12 Workmanship. All edges of the mounts and mask apertures shall be cleanly cut. Mounts shall be clean and free from any defect that would affect their serviceability or impair their appearance.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling.

4.2.1 Visual examination. Samples from each lot of mounts shall be selected in accordance with the provisions set forth in MIL-STD-105. The acceptable quality level (AQL) at general inspection level I shall be 1.5 percent defective for major defects and 2.5 percent defective for minor defects.

4.2.2 Testing. Samples from each lot of mounts shall be selected in accordance with provisions set forth in MIL-STD-105 at inspection level S-2 with an acceptable quality level (AQL) of 2.5 percent defective.

4.2.3 Shipping container inspection. Samples of packed and marked containers ready for shipment shall be selected. The inspection level shall be S-3 with an acceptable quality level (AQL) of 4.0 percent defective. The lot size of the shipping containers shall be the number of shipping containers offered for delivery at one time. The sample unit shall be one shipping container.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

4.3 Inspection.

4.3.1 Visual examination. Examine each sample mount visually and measure it with gauges and scales for defects listed in table II.

TABLE II - Classification of defects

Requirement paragraph	Defect	Major AQL 1.5 percent defective	Minor AQL 2.5 percent defective
3.2.1, 3.2.2, 3.2.3	Type not as specified.	X	
3.3.2	Style not as specified.	X	
3.3.3	Dimensions of mask aperture not as specified.	X	
3.3.4	Aperture not properly located.	X	
3.4	Registration holes punches when not specified.	X	
3.4.1	Location, dimensions and tolerances of registration holes in style A mounts not as specified.	X	
3.4.2	Style B mounts furnished with registration holes.	X	
3.4.3	Location, dimensions and tolerances of registration holes in style C mounts not as specified.	X	
3.5	Aperture not square.	X	
3.5	Mount not square.	X	
3.5	Inside corner radius not as specified.		X
3.6	Mount and aperture dimensions not within specified tolerance.	X	
3.7	Grain does not run vertically in the mount.		X
3.8	Mount does not lie flat.		X
3.10	Printing missing (if required).	X	
	Printing not legible.	X	
	Printing not as specified.	X	
3.12	Mount dirty.		X
	Aperture not clean cut.	X	
	Mount edges not clean cut.		X

4.3.2 Tests. Samples selected in accordance with 4.2.2, shall be subjected to the performance test in 4.3.2.2 and the material test in 4.3.2.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

4.3.2.1 Test conditions. Unless otherwise specified, all tests required by this specification shall be made under ambient conditions of 24° ± 6°C (75° ± 10°F) and 50 percent ± 10 percent relative humidity.

4.3.2.2 Performance. The mounts shall be assembled with a transparency in place in the mask aperture. The transparency shall be projected onto a screen for a period of 15 minutes by utilizing a type 1, class C, projector conforming to Fed. Std. No. 73 and Federal Specification GG-P-661. The mount shall be inspected during and after projection to ensure that there has been no deterioration or dimensional change of the mount.

4.3.2.3 Material. Samples of each material selected for testing shall be tested for thickness, type of board and writing requirements in accordance with the applicable provisions of the appropriate material specification referenced herein.

4.3.3 Examination of preparation for delivery requirements. An examination shall be made to determine whether the packaging, packing and marking comply with the requirements of section 5 of this specification. Defects shall be scored in accordance with table III. For examination of interior packaging, the sample unit shall be one shipping container identical to each item being packed, fully prepared for delivery, selected at random just prior to the closing operations. Sampling shall be in accordance with MIL-STD-105. Defects of closure shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 with an AQL of 4.0 defects per hundred units.

TABLE III - Classification of preparation for delivery defects

Examine	Defects
Markings	Omitted; incorrect; illegible; improper size, location, sequence or method of application.
Material	Any component missing or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping, inadequate stapling or distortion of container.
Contents	Gross weight exceeds the requirements of the box specification.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B or C as specified (see 6.2).

5.1.1 Level A. Fifty mounts of like stock number shall be packaged in a close fitting box conforming to PPP-B-636, class weather-resistant, style optional. Close and waterproof seal each box in accordance with the appendix to PPP-B-636.

5.1.2 Level B. Fifty mounts of like stock number shall be packaged in a close-fitting box conforming to PPP-B-636, class domestic, style optional. Closure of boxes shall be in accordance with the appendix to PPP-B-636.

5.1.3 Level C. Mounts shall be packaged to insure protection against damage during shipment and safe delivery at destination while complying with the common carrier rules as a minimum.

5.2 Packing. Packing shall be level A, B or C as specified (see 6.2).

5.2.1 Level A. Mounts packaged as specified in 5.1 shall be packed in quantities as specified (see 6.2) in close-fitting boxes conforming to PPP-B-636, class weather-resistant, style RSC. Close, waterproof seal and strap each box in accordance with the appendix to PPP-B-636.

5.2.2 Level B. Mounts packaged as specified in 5.1 shall be packed in quantities as specified (see 6.2) in close-fitting boxes conforming to PPP-B-636, class domestic, style RSC. Closure of boxes shall be in accordance with method II of the appendix to PPP-B-636.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

5.2.3 Level C. Mounts packaged as specified in 5.1 shall be packed in containers in compliance with the National Motor Freight Classification rules or the Uniform Freight Classification rules.

5.3 Marking. Marking shall be in accordance with 5.3.1 or 5.3.2 as specified (see 6.2).

5.3.1 Civil agencies. Interior packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military agencies. Interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. These mounts are intended to facilitate handling, projecting and filing of large transparencies.

6.2 Order data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

(a) Title, number and date of this specification.
(b) Style and mask aperture required (see 1.2.2, 3.3.2 and table I).
(c) Type required (see 1.2.1, 3.2 and table I).
(d) Location, number, dimensions and tolerances for registration holes if required in style A mounts (see 3.4.1).
(e) Registration holes if required in style C mounts (see 3.4.3).
(f) Imprinting and marking details if required (see 3.10).
(g) Quantity of unit packages to be packed in each shipping container (see 5.2.1 and 5.2.2).
(h) Applicable levels of packaging and packing (see 5.1 and 5.2).
(i) Whether marking required is for civil or military agency (see 5.3).
(j) Color of mounts (see 3.2.1, 3.2.2 and 3.2.3).

Military Custodians:

Army - EL
Navy - AS
Air Force - 70

Review Activities:

Army - MI
Navy - MC, AS
Air Force - 70

Preparing Activity:

GSA-FSS

Civil Agency Coordinating Activities:

Commerce
CSC
DOT
EPA
Energy Research Dev. Adm.
FCC
GSA-FSS
HEW
HUD
Interior
Justice
Labor
NASA
Small Business Adm.
State
Treasury - IRS
USIA
USDA
VA

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See Section 2 of this specification to obtain extra copies and other documents referenced herein. Price 30 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.