UU-P-665B
March 28, 1974
SUPERSEDING
Fed. Spec. UU-P-665A
September 20, 1968

FEDERAL SPECIFICATION

PLATE, BAKING, PIE (PAPER)

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE

1.1 Scope. This specification covers one type of disposable, metal rimmed, paper plate for pie baking.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

UU-P-268	-	Paper, Kraft, Untreated, Wrapping
PPP-B-636	-	Boxes, Shipping, Fiberboard

Federal Standard:

FED-STD-123	-	Marking for Domestic Shipment (Civil Agencies)

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

FSC 7330

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

LAWS AND REGULATIONS:

Federal Food, Drug and Cosmetic Act

21 CFR 121 - Food Additives

(The Code of Federal Regulations (CFR) and the Federal Register (FR) are for sale on a subscription basis by the Superintendent of Documents, US Government Printing Office, Washington, DC 20402. When indicated, reprints of certain regulations may be obtained from the Federal Agency responsible for issuance thereof.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply:

National Motor Freight Traffic Association, Inc., Agent

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:21Z
Check the source to verify that this is the current version before use.

of the following types: ... The cutlery shall

3. REQUIREMENTS

3.1 Materials. Plate materials shall conform to subpart F of 21 CFR 121, and the Federal Food, Drug and Cosmetic Act, as applicable.

3.1.1 Paper. The body of the plate shall be made of paper, paperboard, or molded pulp. Coatings, additives, or after-treatments may be used to meet the specification requirements. Plates shall conform to 21 CFR 121.2526 for paper and paperboard in contact with aqueous and fatty foods. The use of reclaimed fibers for the plate stock is encouraged. Reclaimed fibers shall conform to 21 CFR 121.2546.

3.1.2 Metal. The metal shall be either stainless steel or steel, plated to resist corrosion.

3.2 Construction.

3.2.1 Body. The body of the plate shall be of molded or pressed construction with tapered sidewalls. The tapered sidewalls and rim shall be either plain, fluted, or otherwise embellished at the option of the supplier. When fluted or embellished sidewalls are used, they shall not prevent nesting of the plates or removal of the baked pie.

3.2.2 Rim. A smooth metal rim shall circumvent and be secured to the top of the plate.

3.3 Color. The plates shall be white in accordance with standard commercial practice and may vary in shade from ivory white through blue white.

3.4 Size. The plates shall have the dimensions and allowable tolerances specified in table I.

TABLE I - Dimensions (inches)

Over-all top diameter	9-5/8 ± 1/8
Inside top diameter	9 ± 1/8
Vertical depth	1-1/4 ± 1/8
Slant depth	1-1/2 ± 1/8
Thickness, minimum	0.020

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

at the back

3.5 Flame resistance. The body of the plate shall not burn, scorch, or deform when tested as specified in 4.3.2.

3.6 Rigidity. Plates shall withstand the baking process with minimum distortion and neither collapse nor show a deflection great enough to break the pie when tested as specified in 4.3.2.

3.7 Odor, taste, and discoloration. Plates shall not transfer any objectionable odor, impart any objectionable taste, or discolor the pie crust when tested as specified in 4.3.2.

3.8 Adherence. The plate shall not require greasing in preparation for baking and shall show no marked tendency to adhere to the pie crust after baking when tested as specified in 4.3.2.

3.9 Workmanship. The finished plates shall be clean and free from dirt, dust, slime spots, foreign matter, holes, tears, cuts, cracks, rough edges, buckled areas, and scuffed areas. The finished plates shall nest. The finished plates shall conform to the quality established by this specification. The occurrence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Certificate of compliance. Where certificates of compliance are submitted, the Government reserves the right to check test such items to determine the validity of the certification.

4.2 Inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated hereinafter.

4.2.1 Inspection of materials and components. In accordance with 4.1, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, or qualified in this specification or applicable purchase documents.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:21Z
Check the source to verify that this is the currentversion before use.

4.3 Inspection of the end item.

4.3.1 Examination of the end item. The end item shall be examined for the defects set forth in the applicable subparagraphs at the inspection levels and acceptable quality levels (AQLs) set forth in 4.3.1.4. Random samples shall be drawn from each lot of the and items for examination of visual, dimensional, and preparation for delivery defects. The lot size shall be expressed in units of plates for examination in 4.3.1.1 and 4.3.1.2 and in units of shipping containers for examination in 4.3.1.3.

4.3.1.1 Examination of the end item for visual defects. The sample unit for this examination shall be one plate.

Examine	Defect
Color	Not white.
Appearance	Not clean; presence of dirt, dust, slime spots, or foreign matter.
Workmanship	Any hole, tear, cut, or crack. Scuffs, scratches, blisters, or rough areas. Any evidence of delamination, malformation, or warpage. Rough edges. No metal rim; rim not firmly secured to plate. Sharp edges, splinters, plating peeling or loose.
Construction	Plates do not nest. Not molded or pressed construction.

4.3.1.2 Examination of the end item for defects in dimensions. The sample unit for this examination shall be one plate.

Examine	Defect
Over-all top diameter	Less than 9-1/2 inches or more than 9-3/4 inches.
Inside top diameter	Less than 8-7/8 inches or more than 9-1/8 inches.
Vertical depth	Less than 1-1/8 inches or more than 1-3/8 inches.
Slant depth	Less than 1-3/8 inches or more than 1-5/8 inches.

4.3.1.3 Examination of preparation for delivery requirements. An examination shall be made to determine that the packaging, packing, and marking complies with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully prepared for delivery except that it need not be closed. Defects of closure listed below shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

Examine	Defect
Marking (exterior)	Incorrect; incomplete; illegible; omitted; of improper size, location, sequence, or method of application.
Materials	Any nonconforming component; component missing, damaged, or otherwise defective.
Workmanship	Inadequate application of components, such as incomplete closure of container flaps, loose strapping, improper taping, or inadequate stapling. Bulged or distorted container.
Contents	Number of plates per shipping container is less than specified or indicated.

4.3.1.4 Inspection levels and acceptable quality levels (AQLs) for examination. The inspection levels for the purpose of determining the sample size and AQLs expressed as defects per one hundred units shall be as follows:

Examination paragraph	Inspection level	AQL
4.3.1.1	S-4	4.0
4.3.1.2	S-1	2.5
4.3.1.3	S-2	4.0

4.3.2 Testing of the end item. The end item shall be tested as specified in table III. The sample unit shall be one plate. The lot size shall be expressed in plates. The sample size shall be as indicated in table II. No more than one sample unit shall be taken from any one shipping container. All test reports shall contain the individual values utilized in expressing the final result. The lot shall be unacceptable if one or more sample units or the lot average fail to meet any test requirement specified.

TABLE II - Sampling for end item testing

Lot size (plates)	Sample size
800 or less	2
801 up to and including 22,000	3
22,001 or more	5

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS FOR TESTING OF THE END ITEM

TABLE III

CHARACTERISTIC	Specification Reference		Requirements Applicable To		Number Determinations Per Unit	Results Reported As		Inspect Level	AQL
	Requirement	Test Method	Individ Unit	Lot Aver		Pass or Fail	Numerically to Nearest		
Metal	3.1.2	1/							
Flammability and rigidity	3.5 and 3.6	4.4.1	X		1	X			
Adherence	3.8	4.4.2	X		1	X			
Odor, taste and discoloration	3.7	4.4.3	X		1	X			

1/ Unless otherwise specified, a certificate of compliance is required and will be acceptable for the requirement stated.

MIL-P-665B

AMXRE Form 598
8 February 1965

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

4.4 Test procedures.

4.4.1 Flammability and rigidity. Bake any pie which requires 465°F. and weighs at least 32 ounces until done. Remove the pie plate from the oven with a two tined fork, designed for this purpose, placed under the rim. The plate shall not burn or show marked scorch or discoloration. The pie shall not break or buckle (see 3.5 and 3.6).

4.4.2 Adherence. When the pie cools, run a knife under the crust on the rim. ~~Invert the baking plate on waxed paper or a flat plate.~~ Lift the baking plate and the pie should drop free (see 3.8).

4.4.3 Odor, taste, and discoloration. The odor, taste, and color shall be compared with a pie baked from the same ingredients in a glass baking dish at the same time (see 3.7).

5. PREPARATION FOR DELIVERY

5.1 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.1.1 Level A. Five hundred plates shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, grade V2s of PPP-B-636. Each container shall have the contents completely covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to grade B of UU-P-268. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V, and reinforced as specified in the appendix of PPP-B-636.

5.1.2 Level B. Five hundred plates shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. Each container shall have the contents completely covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to grade B of UU-P-268. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

5.1.2.1 When specified (see 6.2), the fiberboard shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of the container specification.

5.1.3 Level C. Plates shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with Uniform Freight Classification Rules or National Motor Freight Classification Rules, as applicable.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:21Z
Check the source to verify that this is the currentversion before use.

5.2 Marking.

5.2.1 Civil agencies. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with FED-STD-123.

5.2.2 Military requirements. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. Plates covered by this specification are intended for use in baking and dispensing pies where a disposable plate is required.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Selection of the applicable level of packing (see 5.1).
(c) When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.1.2.1).

Custodians:

Army - GL
Navy - SA
Air Force - 84

Review activities:

Army - MD
Navy - MS, YD

User activities:

Army - SM
Navy - MC, CG

Preparing activity:

Army - GL

CIVIL AGENCY COORDINATING ACTIVITIES:

GSA-FSS
VA-DMS

Project No. 7330-0354

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 15 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
US ARMY NATICK LABORATORIES
NATICK, MA 01760

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

STSNLT-EQS

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314



Commander
US Army Natick Laboratories
ATTN: STSNLT-EQS
Natick, Massachusetts 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

Plate, Baking, Pie (Paper) UU-P-665B

NAME OF ORGANIZATION AND ADDRESS	CONTRACT NUMBER
	MATERIAL PROCURED UNDER A ☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*	TELEPHONE NO.
	DATE

DD FORM 1426 REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.