UU-P-670D
March 21, 1974
SUPERSEDING
Fed. Spec. UU-P-670
August 27, 1968

FEDERAL SPECIFICATION

PLATES, PAPER, RECTANGULAR AND ROUND

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers disposable paper plates in rectangular and round forms (see 6.1).

1.2 Classification.

1.2.1 Types, grades and style. The plates covered by this specification shall be of the following types, grades, and styles as specified (see 6.2).

Type I - Round

Grade A	-	Molded pulp, extra water resistance and grease resistance
Grade B	-	Pressed board, standard water resistance
Grade C	-	Pressed board, extra water resistance and grease resistance
Grade E	-	Molded pulp, plastic laminated or coated, extra water resistance and grease resistance
Grade F	-	Pressed board, plastic laminated or coated, extra water resistance and grease resistance

Type II - Rectangular

Grade B	-	Pressed board, standard water resistance
Grade C	-	Pressed board, extra water resistance and grease resistance
Grade E	-	Molded pulp, plastic laminated or coated, extra water resistance and grease resistance

Style A	-	Noncompartmented
Style B	-	3 compartmented

FSC 7350

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specification:

PPP-B-636 - Boxes, Shipping, Fiberboard

Federal Standard:

FED-STD-123 - Marking for Domestic Shipment (Civil Agencies)

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, US Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads for 40" x 48" Pallets

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

LAWS AND REGULATIONS:

Federal Food, Drug, and Cosmetic Act:

21 CFR 121.2546 - Food additives - Pulp from Reclaimed Fiber
21 CFR 121.2526 - Components of Paper and Paperboard in Contact with Aqueous and Fatty Foods

(The Code of Federal Regulations (CFR) and the Federal Register (FR) are for sale on a subscription basis by the Superintendent of Documents, US Government Printing Office, Washington, DC 20402. When indicated, reprints of certain regulations may be obtained from the Federal Agency responsible for issuance thereof.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply:

National Motor Freight Traffic Association, Inc., Agent

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

3. REQUIREMENTS

3.1 Material. The paper plates shall be made of paperboard, or molded pulp and additives or after-treatments as required to meet the requirements of this specification. The materials, processes, and finished plates shall conform to the standard set forth in the Federal Food, Drug, and Cosmetic Act as amended and regulations issued thereunder (see 4.1.2). The maximum use of reclaimed fiber is encouraged provided the plates meet the requirements of this specification. The reclaimed fiber shall conform to the pertinent provisions concerning the use of pulp from reclaimed fiber in the Federal Food, Drug, and Cosmetic Act, Title 21 CFR 121.2546 (see 4.1.2). Plates shall conform to 21 CFR 121.2526 for paper and paperboard in contact with aqueous and fatty foods (see 4.1.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

3.2 Design. Paper plates shall be noncompartmented or compartmented, as specified (see 1.2 and 6.2). Compartmented plates shall have three (style B) compartments (see 1.2.1). The largest compartment shall cover approximately 50 percent of the eating surface of the plate. The two remaining compartments shall be approximately the same size. Ridges forming the compartments of plates shall run nonparallel to the outside edges of the plate.

3.3 Construction.

3.3.1 Paper plates (grades A, B, and C). Paper plates shall be of molded or pressed construction as specified (see 1.2.1). The rim may be embossed, fluted, or otherwise embellished provided any such feature does not prevent nesting of the plates. The plate base shall contain no corrugations or indentations that will cause the plate to tip, tilt, or rock when placed on a smooth surface.

3.3.2 Paper plates (grade E and F). Plastic coated plates shall be of molded construction for grade E and shall be of pressed construction for grade F. The thickness of the paper plate shall be not less than 0.022 inch and the entire top surface shall be coated with a clear plastic coating not less than 0.0001 inch thick.

3.4 Color. The paper plates shall be white in accordance with standard commercial practice and may vary in shade from cream white through blue white as specified (see 6.2). When procured for operational ration use, the entire plate shall be colored as specified (see 6.2).

3.5 Finish. The paper plates shall have a smooth pressed finish.

3.6 Sizes. The dimensions of the plates shall be as specified in table I. For compartmented plates, the rib height shall be at least equal to 35 percent of the plate depth. Dimensions shall be measured on an overall basis including width of rim or thickness of plate, as applicable. The food containing area, defined as the area of a horizontal plane located at a distance above the bottom surface of the plate equal to 2/3 of the plate depth, shall be not less than 60 percent of the area based on the overall dimensions of the plate.

3.7 Rigidity. The maximum deflection of the plates shall be as shown in table I when tested as specified in 4.3.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

TABLE I - Plate dimensions (inches) and maximum deflection

Type	Style	Diameter	Length	Width	Depth	Maximum Deflection		
						Grades		Grade
						E	A	B, C, F
I	A	4-1/2			1/2	-	3/16	3/8
I	A	4-1/2			1-23/32	-	1-13/32	1-19/32
I	A	5			1/2	-	3/16	3/8
I	A	6			1/2	-	3/16	3/8
I	A	7			1/2	-	3/16	3/8
I	A	8			5/8	-	5/16	1/2
I	A	8-3/4			7/8	7/32	-	-
I	A	9			3/4		7/16	5/8
I	A	10-1/2			7/8		9/16	3/4
I	B	10-1/4			7/8	-	9/16	3/4
II	B		9-3/4	9-3/4	7/8	-	-	3/4
II	B		10	8	7/8	-	-	3/4

Tolerances shall be as follows:

Diameter	- plus 1/2 inch, minus 1/4 inch
Length, width and depth	- plus or minus 1/4 inch

3.8 Water resistance. Plates shall show no total penetration of water, and for plastic coated or laminated plates, no ply separation or delamination more than 1/4 inch in any direction, or blister more than 1/4 inch in diameter, when in contact with water for the time and at the water temperature indicated in table II when tested as specified in 4.3.2. Total penetration is defined as the wetting and staining of the bond paper under the plate.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

TABLE II - Water resistance

	Time (minutes)	Water (temperature F)
Standard resistance (grade B)	15	150
Extra resistance (grades A and C)	30	160
Plastic coated (grades E and F)	30	160

3.9 Odor and taste. Plates shall not have any objectionable odor and shall not impart any objectionable taste to the test water when tested as specified in 4.3.2.

3.10 Grease resistance. Grease resistant plates (grades A, C, E and F) shall show no evidence of total penetration by oil when tested as specified in 4.3.2. Total penetration is defined as the wetting or staining of the bond paper under the plate.

3.11 Workmanship. All paper stock shall be protected from contamination during and after processing and shall be free from slime spots, dust, dirt, grease, oil or foreign matter. The rims of molded pulp plates, grades A and E, shall be free from wrinkles. The rims of grades B, C and F plates may exhibit wrinkles consistent with the industry's normal manufacturing process. Excessive wrinkles shall be avoided. Finished plates shall nest, be clean, and free from rough edges, buckled areas, scuffed areas, holes, tears, cuts, or cracks. The plastic coated plates shall be free from any blisters or wrinkles. The finished plates shall conform to the quality established by this specification. The occurence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Quality conformance inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated hereinafter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

4.1.2 Certificate of compliance. Where certificates of compliance are submitted the Government reserves the right to check test such items to determine the validity of the certification.

4.2 Component and material inspection. In accordance with 4.1 above, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

4.3 Inspection of the end item.

4.3.1 Examination of the end item. The end item shall be examined for the defects set forth in the applicable subparagraphs at the inspection levels and acceptable quality levels (AQLs) set forth in 4.3.1.5. Random samples shall be drawn from each lot of the end items for examination of visual, dimensional, count, and preparation for delivery defects. The lot size, for purposes of determining the sample size in accordance with MIL-STD-105, shall be expressed in units of 500 plates of the same type, style, grade, and size for examination in 4.3.1.1 and 4.3.1.2, in units of shipping containers for examination in 4.3.1.3, and in units of palletized unit loads for examination in 4.3.1.4.

4.3.1.1 Examination for visual defects. The sample unit for this examination shall be one plate. Both sides of the plate shall be examined.

Examine	Defect
Color	Not white, or not color specified, when applicable.
Appearance	Not clean; presence of slime spots, grease, oil, foreign matter, dust, dirt, or finger marks. Finish not pressed, or uniformly smooth.
Workmanship	Any hole, tear, cut, crack, scuffed, or buckled area. Any delamination (plastic coated or laminated plates only), blister, distortion, malformation or warpage. Any wrinkles or crease on rim of grades A and E plates. Excessive wrinkles on rims of grades B, C and F plates. Rough edges.
Construction	Not type or style specified. Plates do not nest; base not flat; plate tilts, tips or rocks when placed on a smooth surface. Not plastic coated as specified (see 3.3.2).
Design	Number or compartments not as specified (where applicable).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

4.3.1.2 Examination for defects in dimensions. The sample unit for this examination shall be one plate.

Examine	Defect
Dimensions	Any dimension varying from the dimensions specified by more than the allowable tolerance.
Area of compartments	Not in proportions specified.
Food surface area	Less than specified.

4.3.1.3 Examination of preparation for delivery requirements. An examination shall be made to determine that the packaging, packing, and marking complies with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully prepared for delivery with the exception that it need not be closed. Defects of closure listed below shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot.

Examine	Defect
Marking (exterior or interior)	Incorrect; incomplete; illegible; omitted; of improper size, location, sequence, or method of application.
Materials	Any nonconforming component; component missing, damaged, or otherwise defective.
Workmanship	Inadequate application of components; such as incomplete closure of container flaps; loose strapping, improper taping, or inadequate stapling.
Content	Average number of plates per shipping container is more or less than required (AQL not applicable). The lot shall be unacceptable if the average count per shipping container for all shipping containers examined is less than specified.

4.3.1.4 Examination for palletization. An examination shall be made to determine that the palletization complies with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one palletized unit load fully prepared for delivery. The lot size shall be the number of palletized unit loads in the end item inspection lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

Examine	Defect
Finished dimension	Length, width, or height exceeds specified maximum requirements.
Palletization	Not as specified. Pallet pattern not as specified. Interlocking of loads not as specified. Loads not bonded with required straps as specified.
Weight	Exceeds maximum load limits.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence or method of application.

4.3.1.5 Inspection levels and AQLs for examination. The inspection levels for determining the sample size and the AQLs expressed in defects per one hundred units shall be as follows:

Examination paragraph	Inspection level	AQL
4.3.1.1	II	4.0
4.3.1.2	S-3	2.5
4.3.1.3	S-2	4.0
4.3.1.4	S-1	6.5

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS FOR TESTING

TABLE III

CHARACTERISTIC	Specification Reference		Requirements Applicable To		Number Determinations Per Unit	Results Reported As		Inspect Level	AQL
	Requirement	Test Method	Individ Unit	Lot Aver		Pass or Fail	Numerically to Nearest		
Rigidity	3.7	4.4.1	X	-	1	-	1/8 inch		
Water resistance 1/									
Penetration	3.8	4.4.2	X	-	1	X			
Delamination (plastic coated or laminated plates only)	3.8	4.4.2	X	-	1		1/8 inch		
Odor and taste	3.9	4.4.3	X	-	1	X			
Grease resistance	3.10	4.4.4	X	-	1	X			

1/ Retain the water collected upon completion of this test for use in the performance of the odor and taste characteristics test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

4.3.2 Testing of the end item. The end items shall be tested for the applicable characteristics in table III. The lot size for purposes of determining the sample size shall be expressed in units of plates of the same type, grade, class, and size offered for inspection at one time. For grades A, C, E and F plates the sample unit shall be three plates for use in the following tests: one plate for rigidity, one plate for grease resistance, and one plate for combined water resistance, odor, and taste. For grade B plates the sample unit shall be two plates for use in the following tests: one plate for rigidity and one plate for water resistance, odor, and taste combined. The sample size shall be drawn at inspection level S-1.

4.4 Test procedures.

4.4.1 Rigidity.

4.4.1.1 Apparatus. The plate to be tested shall be held in a jig or clamp which shall support the underside of the plate over an area equal to one quarter of the overall plate area and hold the topside of the plate at a point on the rim centered over the back edge of the supporting surface directly under the rim. The bottom support shall be made of steel plate in the shape of a pointed wedge and may be designed to accommodate plates of different depths and sizes. The longer back edge of the support base shall be located at the edge of the test plate rim and the apex of the wedge shall be positioned directly under, but not beyond, the midpoint of the bottom of the test plate. The clamp or holddown shall be a vertically adjustable aluminum bar; one end of which shall contact the surface, acting as a clamp, with the opposite end provided with an opening to accommodate a weighted plunger, so that a weight may be applied at the rim of the plate diametrically opposite the point on the rim held by the clamp. The bar may be slotted for half its length so that the weighted plunger may be positioned laterally in order that different diameter plates may be tested.

4.4.1.2 Calculation. The total weight applied at the rim (including the plunger weight and added weights, as applicable), shall be equivalent to that of a uniformly dispersed load of 5.5 grams (g) per square inch area, based on the overall dimensions of the plate. This shall be calculated to the nearest 0.1g., as follows:

4.4.1.2.1 Round plates.

$$\text{Rim weight (grams)} = \frac{5.5 \times 3.1416 \times (\text{plate diameter in inches})^2}{4 \times 7.36^*}$$

* This constant is derived from a methematical calculation, based upon the equivalence of a uniformly distributed load to one concentrated at the rim, when the plate is loaded and tested in the apparatus described. Measurement of the plate deflection, upon application of the weighted plunger, may be facilitated by having the plunger graduated in units of 1/8-inch markings (see 6.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

4.4.1.2.2 Rectangular plates.

$$\text{Rim weight (grams)} = \frac{5.5 \times \text{length in inches} \times \text{width in inches}}{7.36}$$

4.4.1.3 Procedure.

4.4.1.3.1 Grades A, B, and C. Place the plate specimen eating surface upward, on the support wedge in such a position that the apex of the wedge is located at the midpoint of the bottom surface of the plate. Lower the bar clamp over the top of the plate so that it just makes contact with the plate rim. Apply the weight for the size plate being tested, as determined in 4.4.1.2, at the outer edge of the rim and measure the deflection of the plate caused by the weight to the nearest 1/8 inch. For the 8 by 10-inch plate, place the 10-inch side against the stops.

4.4.1.3.2 Grades E and F. Place the plate specimen eating surface upward, on the support wedge in such a position that the apex of the wedge is located at the midpoint of the bottom surface of the plate. Lower the bar clamp over the top of the plate so that it just makes contact with the plate rim. Apply a 100 gram total load on the outer edge of the rim and measure the deflection of the plate to the nearest 1/16-inch. The total deflection shall be not greater than specified in 3.8.

4.4.2 Resistance to water. Distilled water maintained at a temperature of 150° F ± 2° F (for standard) or 160° F ± 2° F (for extra), shall be poured onto the plate surface to a depth approximately equal to one-half the depth of the plate. The plate shall rest on a flat sheet of double face corrugated board or other suitable paper support, approximately 1/4 inch thick, with a sheet of clean white bond paper between the plate and supporting surface. After 15 minutes (for standard) or 30 minutes (for extra), the water in the test plate shall be drained into a clean flask and the test plate examined for evidence of delamination. Separation of plies extending more than 1/4 inch in diameter, shall be considered delamination. The bond paper and underside of the plate shall be examined for visible evidence of water leakage. Slight dampness of the paper due to condensation shall not be construed as a failure.

4.4.3 Odor and taste. The distilled water used in resistance to water test (4.4.2) shall be collected and allowed to stand in a clean stoppered flask or bottle for 2 hours. The odor and taste of the sample water shall be compared with that of freshly distilled water at the same temperature.

4.4.4 Resistance to grease. Place a mixture of 3.0 milliliters (ml) of corn oil, of the grade used for cooking, and 10 grams of clean, dry sand, of such a particle size that all of it will pass through a No. 20 U.S. Standard sieve, in a glass beaker of approximately 30 milliliter capacity and heat in an oven to 160 F ± 2 F. Remove the hot mixture from the oven and swirl the

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

beaker and contents to assure good mixing of the oil and sand. Cover the beaker with the plate to be tested, using the eating surface of the plate as the cover. Invert the plate and beaker and place the plate on a hard flat surface with a sheet of clean white bond paper directly under the plate, with the beaker in an inverted position over the sand and oil mixture. Allow the mixture to stand, as specified above, for 30 minutes. At the end of this test period, examine the bond paper and the underside of the plate for any evidence of staining.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C as specified (see 6.2).

5.1.1 Level A. Plates of one description only shall be nested in commercial quantities and then packaged in a paper or plastic bag or wrap. The bag or wrap shall be securely closed.

5.1.2 Level B. When specified, paper plates of one type, grade, style, and size shall be packaged in quantities of 50 or 100: in plastic or paper bag or wrap and sealed.

5.1.3 Level C. Plates shall be packaged to afford adequate protection against physical damage during shipment from the supply source to the first receiving activity. The supplier may use his standard practice when it meets this requirement.

5.2 Packing. Packing shall be level A, B or C as specified (see 6.2).

5.2.1 Level A. Plates of one description only, packaged as specified in 5.1, shall be packed in the quantities specified in table IV in a snug-fitting fiberboard shipping container conforming to style RSC, grade V2s of PPP-B-636. Each container shall be closed in accordance with method III, waterproofed in accordance with method V, and reinforced as specified in the appendix of PPP-B-636.

5.2.2 Level B. Plates of one description only, packaged as specified in 5.1, shall be packed in the quantities specified in table IV in a snug-fitting fiberboard shipping container conforming to style RSC, type CF (variety SW) or SF, class domestic, grade 200 of PPP-B-636. Each shipping container shall be closed in accordance with method II as specified in the appendix of the container specification.

5.2.2.1 When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of the container specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

TABLE IV - Quantity of plates per shipping container

Type I: Round Diameter (inches)	Type II: Rectangular Length (inches)	Width (inches)	Quantity per shipping container
4-1/2			2000
5			1000
6			1000
7			1000
8			500
8-3/4			500
9			500
10-1/4			500
10-1/2			500
	9-3/4	9-3/4	500
	10	8	500

5.2.3 Level C. Plates, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with Uniform Freight Classification Rules or National Motor Freight Classification Rules, as applicable.

5.3 Palletization (military requirements). When specified (see 6.2), plates of one description only, packed as specified in 5.2, shall be palletized in accordance with load type I of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer.

5.4 Marking.

5.4.1 Civil agencies. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with FED-STD-123.

5.4.2 Military requirements. In addition to any special marking required by the contract or order, interior packages, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. Paper plates covered by this specification are intended for use in dispensing and serving food where a disposable plate is required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents.

(a) Title, number, and date of this specification.
(b) Type, grade, style, size, and color desired (see 1.2, 3.2, and 3.4).
(c) Color of operational ration plate (see 3.4).
(d) Selection of the applicable levels of packaging and packing (see 5.1 and 5.2).
(e) When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
(f) When palletization is required (see 5.3).

6.3 An instrument as described in 4.4.1.1 may be obtained from the Single Service Institute, 250 Park Avenue, New York, NY 10017.

6.4 For overseas consignments the difference in shipping bulk of various plates may be a significant factor in assessing the overall cost of delivery, especially when overpacking is required.

6.5 Supersession data. Grade D has been deleted since requirements are now covered by Grade B.

Custodians:

Army - GL
Navy - SA
Air Force - 84

Review activities:

Army - MD
Navy - MS

Preparing activity:

Army - GL

CIVIL AGENCY COORDINATING ACTIVITIES:

GSA-FSS
VA-DMS

Project No. 7350-0161

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 20 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

Commander
U. S. Army Natick Laboratories
Attn: STSNL EPS
Natick, MA 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION

ORGANIZATION *(Of submitter)*

CITY AND STATE

CONTRACT NO.

QUANTITY OF ITEMS PROCURED

DOLLAR AMOUNT

$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*

DATE

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.