UU-P-680a
December 15, 1964

SUPERSEDING
Int. Fed. Spec. UU-P-00680 (GSA-FSS)
March 30, 1964

FEDERAL SPECIFICATION

PORTFOLIO, DOUBLE-POCKET, PRESENTATION

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers requirements for a double-pocket presentation portfolio for use in containing papers.

1.2 Classification.

1.2.1 *Type, size, and capacity.* The portfolio shall be of but one type, size (dimensions), and capacity (see 1.1, 3.3, and 3.4).

1.2.2 *Colors.* The portfolio shall be furnished in gray, tan, light blue, or dark blue colors, as specified in the invitation for bids, contract, or order (see 6.1).

2. APPLICABLE SPECIFICATIONS, STANDARDS, AND OTHER PUBLICATIONS

2.1 Specifications and standards. The following specifications and standards, of the issues in effect on date of invitation for bids, form a part of this specification to the extent specified herein:

Federal Specifications:

PPP-B-566—Boxes, Folding, Paperboard.
PPP-B-585—Boxes, Wood, Wirebound.
PPP-B-591—Boxes, Fiberboard, Wood-Cleated.
PPP-B-601—Boxes, Wood, Cleated-Plywood.
PPP-B-621—Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636—Box, Fiberboard.
PPP-B-640—Boxes, Fiberboard, Corrugated, Triple Wall.
PPP-B-665—Boxes, Paperboard, Metal Stayed (Including Stay Material).
PPP-B-676—Boxes, Set-Up, Paperboard.

Federal Standards:

Fed. Std. No. 102—Preservation, Packaging, and Packing Levels.
Fed. Std. No. 123—Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C. 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D. C., Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, and Seattle, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specification:

MIL-P-116—Preservation, Methods of.

Military Standards:

MIL-STD-105—Sampling Procedures

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

and Tables for Inspection by Attributes.

MIL-STD-129—Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following publications form a part of this specification to the extent specified hereinafter. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

Technical Association of the Pulp and Paper Industry (TAPPI)

Testing Methods, Recommended Practices Specifications:

T 401 m—Fiber Analysis of Paper and Paperboard.

T 402 m—Conditioning Paper and Paperboard for Testing.

T 403 m—Bursting Strength of Paper.

T 410 m—Basis Weight of Paper and Paperboard.

T 414 m—Internal Tearing Resistance of Papers.

(Copies of TAPPI Standards may be obtained from the Technical Association of the Pulp and Paper Industry, 360 Lexington Avenue, New York 17, New York.)

3. REQUIREMENTS

3.1 Material.

3.1.1 *Paper stock* shall be free from ground woodpulp. Colors shall be as specified in 1.2.2.

3.1.1.1 *Physical characteristics* shall conform to the requirements of table I when tested as specified in 4.4.

3.2 Construction. The portfolio shall be made of one-piece, die-cut construction, including the pockets and pocket flaps, and shall be made for use with sheets 11 by 8-1/2 inches or smaller. The portfolio shall be scored in the center for folding to the size specified in 3.3. Corners of the portfolio shall be round or square, or a combination of round and square. The portfolio shall be so constructed as to lie flat when fully open.

TABLE I.—*Physical characteristics*

Basis weight, 24 x 36 inches, 500 sheets, tolerance ± 5%	Average thickness, tolerance ± 0.0005 inch	Average bursting strength, (min.)	Tearing resistance (min.)	
			Machine direction	Cross direction
Pounds	*Inch*	*Points*	*Grams*	*Grams*
150	0.0105	70	190	235

3.2.1 *Pockets.* The portfolio shall have two interior pockets. The bottom portion of the portfolio shall be folded up and fastened along the center scoring in a manner to form two sections. Wire staples or other means of fastening in accordance with normal commercial practice shall be used. The outer edges of the two pocket sections shall be overlapped with a portion of the portfolio material which shall be glued or otherwise fastened to securely close the ends of the pockets in accordance with normal commercial practice. Width of the flaps (overlapping portion) on the pockets shall be 3/4 inch, with a tolerance of minus 1/8 inch and ends shall be rounded. Pockets shall be 4-15/16 inches deep by 9-1/2 inches wide, with a plus or minus tolerance of 1/8 inch in either direction.

3.3 Dimensions. When fully open, the overall outside dimensions of the portfolio shall be 11-11/16 inches high by 19 inches wide. When folded, the overall outside dimensions of the portfolio shall be 11-11/16 inches high by 9-1/2 inches wide. A plus or minus tolerance of 1/16 inch in any of the specified dimensions will be permitted.

3.4 Capacity. Each pocket of the portfolio as specified in 3.2.1 shall be capable of holding 3/8 inch of material. A minus tolerance of 1/16 inch will be permitted in the specified capacity.

3.5 Finish. The portfolio shall have an embossed, simulated leather grain.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

3.6 **Workmanship.** Portfolios shall be clean and free from cuts, scratches, breaks, holes, tears, lumps, creases, discoloration, and any other imperfections which affect the appearance or which might affect the serviceability. Edges shall be clean cut, even, and in accordance with normal commercial practice. Each portfolio shall be folded in a manner that when closed, all edges will be in even alignment.

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 **Supplier's responsibility.** Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified hereinafter. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements. (See 6.1.)

4.2 **Sampling.** (See 4.3.2.)

4.2.1 *Size of lot.* All portfolios of the same color, presented for delivery at one time, shall be considered a lot for the purposes of examination and tests.

4.2.2 *Sampling for visual and dimensional examination.* A random sample of the portfolios shall be taken from each lot in accordance with MIL-STD-105, inspection level I. Lot acceptance or rejection shall be based on an acceptable quality level (AQL) of 2.5 percent defective for major defects and 4.0 percent defective for minor defects. The sample unit shall be one portfolio.

4.2.3 *Sampling for tests.* Samples for test purposes shall be in accordance with level S-2 of MIL-STD-105, with an AQL of 1.0 percent defective. The sample unit shall be one portfolio.

4.3 **Examination.**

4.3.1 *Visual and dimensional examination.* Sample portfolios, taken in accordance with 4.2.2, shall be examined for the defects listed in table II. Any portfolio having one or move defects shall be considered a defective portfolio. If the number of defective portfolios exceeds the acceptance number for the sample, the lot represented by the sample shall be rejected.

TABLE II.—*Classification of defects (end item)*

Examine—	Defects	
	Major	Minor
Portfolio not one-piece, die-cut construction	X	
Size (dimensions) of portfolio not suitable for 11-x 8-1/2-inch size sheets	X	
Portfolio does not lie flat when fully open	X	
Number and construction of pockets not as specified	X	
Dimensions and capacity of pockets, within tolerances, not as specified.	X	
Width of flaps on pockets, within tolerance, not as specified	X	
Dimensions of portfolio, within tolerances, not as specified	X	
Portfolio not scored in center as specified	X	
Color not as specified		X
Finish not embossed, simulated leather		X
Workmanship:		
Portfolios contain uneven sides, tops, and bottoms; when closed all edges not in even alignment	X	
Defects—		
which might affect serviceability	X	
which affect appearance		X

4.3.2 *Examination for compliance with preparation for delivery requirements.* Examination shall be made to determine compliance with the packaging, packing, and marking requirements of section 5. Defects shall be scored in accordance with table III. For examination of contents, the sample unit shall be one shipping container fully prepared for delivery selected just prior to the closing operations. Defects of closure

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

listed shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be level II and the AQL shall be 4.0 defects per 100 units.

TABLE III.—*Examination of preparation for delivery*

Examine—	Defects
Markings (interior and exterior containers, as applicable).	Incorrect; omitted; illegible; improper size, location, sequence, or method of application.
Materials.	Wrong type, class, or other category of required specifications. Material missing, damaged, or defective, affecting serviceability.
Workmanship.	Wrong or careless means in placement and use of labeling (as applicable) and packaging and packing materials such as loose or partially attached labels; flaps of containers incompletely closed; loose or overtight straps, dangerous strap ends, protruding nails, and smeared adhesive.
Contents.	Quantities not as specified.
Closure of containers.	Not as specified.
Gross weight of shipping container.	In excess of specified weight. In excess of box limitation shown on boxmaker's certificate.

4.4 **Tests.** Samples obtained in accordance with 4.2.3 shall be subjected to the tests specified in table IV. If the number of defective portfolios exceeds the acceptance number for the sample, the lot represented by the sample shall be rejected.

TABLE IV.

Physical characteristic	TAPPI Standard Test Method[1]
Paper stock (fiber composition)	T 401 m
Atmospheric conditions	T 402 m
Bursting strength	T 403 m
Basis weight	T 410 m
Tearing resistance	T 414 m

[1] The TAPPI Standard test method stipulation of the number of samples to test, number of determinations to perform, or the number of results to report shall not apply.

5. PREPARATION FOR DELIVERY

For civil agency procurement, the definitions and applications of the levels of packaging and packing protection specified hereinafter shall be in accordance with Fed. Std. No. 102.

5.1 **Packaging.** Packaging shall be level A, B, or C, as specified (see 6.1).

5.1.1 *Level A.* Unless otherwise specified (see 6.1), 25 portfolios of like description shall be packaged together in accordance with method IC-2 of MIL-P-116.

5.1.2 *Level B.* Twenty-five portfolios of like description shall be packaged in a close-fitting box conforming to PPP-B-566, style IV, type A, class a; PPP-B-665, style A; or PPP-B-676, type I. Each box shall be closed in accordance with the appendix to the applicable box specification.

5.1.3 *Level C.* The portfolios shall be packaged in accordance with commercial practice.

5.2 **Packing.** Packing shall be level A, B, or C, as specified (see 6.1).

5.2.1 *Level A.* Portfolios of like description shall be packed in close-fitting boxes conforming to PPP-B-585, class 3; PPP-B-591, class II; PPP-B-601, type II, class weather resistant; PPP-B-621, class 2; PPP-B-636, class 2; or PPP-B-640, class 2, grade A. Boxes shall be closed in accordance with the appendix to the applicable box specification. The gross weight of the triple-wall fiberboard box and the wood boxes shall not exceed approximately 200 pounds. The gross weight of the fiberboard box (PPP-B-636) shall not exceed the weight limitations of the box specification. Strapping shall be in accordance with the appendix to the applicable box specification.

5.2.2 *Level B.* Ten packages of portfolios, packaged as specified in 5.1.2, shall be packed in a close-fitting box conforming

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

to PPP-B-636, class domestic, style RSC. The box shall be closed in accordance with the appendix to the box specification.

5.2.3 *Level C.* The portfolios shall be packed to insure carrier acceptance and safe delivery at destination in containers complying with the rules and regulations applicable to the mode of transportation.

5.3 **Standard pack (civil agency procurement).** The standard pack for civil agency procurement shall be as specified in 5.1.2 and 5.2.2 (see 6.1.1).

5.4 **Marking.**

5.4.1 *Civil agencies.* In addition to any special marking required by the contract or order, interior packages and exterior shipping containers shall be marked in accordance with Fed. Std. No. 123, and to indicate the color of the commodity. Unless otherwise specified, each shipping container shall be marked with the cube.

5.4.2 *Military activities.* In addition to any special marking required by the contract or order, interior packages and exterior shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 **Ordering data.** Purchasers should exercise any desired options offered herein (see 5.1.1) and procurement documents should specify the following:

(*a*) Title, number, and date of this specification.
(*b*) Color of portfolio required (see 1.2.2).
(*c*) Data; inspection responsibility if other than as specified in 4.1.
(*d*) Level of packaging and packing and any additional marking for shipment required (see 5.1, 5.2, and 5.4).

6.1.1 *Standard pack for civil agencies.* The standard pack requirements in 5.3 are intended for use in procurement of stores stock replenishments. Procuring officers should use the standard pack requirements when it is known that the material will be shipped from a supplier to a domestic warehouse, supply depot, or intermediate storage point for temporary storage, subsequent issue, or shipment to eventual user.

6.2 **Transportation data.** Transportation descriptions and minimum weights applicable to this commodity are:

Rail:

Pockets, letter or document, not otherwise indexed by name, paper.
Carload minimum weight 24,000 pounds, subject to Rule 34, Uniform Freight Classification.

Motor:

Portfolios, not otherwise indexed.
Truckload minimum weight 12,000 pounds, subject to Rule 115, National Motor Freight Classification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.