UU-S-600C
December 9, 1971
SUPERSEDING
UU-S-600B
January 25, 1965

FEDERAL SPECIFICATION

STENCIL, MARKING: PAPER, PRESSURE SENSITIVE

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers the requirements for a pressure-sensitive adhesive paper die-cut stencil.

1.2 Classification.

1.2.1 Types. Pressure-sensitive stencils shall be of the following types as specified (see 6.2).

Type I. Identification for intra-agency pool vehicles

U.S. GOVERNMENT	- 1" letters
	- 3/4" spacing
For Official Use Only	- 3/4" letters
	- 3/4" spacing
GENERAL SERVICES ADMINISTRATION	- 1" letters

Type II. Identification for interagency pool vehicles.

U.S. GOVERNMENT	- 1" letters
	- 3/4" spacing
For Official Use Only	- 3/4" letters
	- 3/4" spacing
INTERAGENCY MOTOR POOL	- 1" letters
	- 3/4" spacing
WASHINGTON, D.C.	- 1" letters
	- 3/4" spacing
GENERAL SERVICES ADMINISTRATION (or responsible operating agency)	- 3/4" letters

FSC 7520

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

Type III. Identification for departments or agencies.

U.S. GOVERNMENT	- 1" letters - 3/4" spacing
For Official Use Only	- 3/4" letters - 3/4" spacing
DEPARTMENT OF COMMERCE	- 1" to 1-1/2" letters - 3/4" spacing
BUREAU OF PUBLIC ROADS	- 1/2" letters

Type IV. Identification stencils, as required by using agencies (see 6.2).

Type V. Individual letters, numerals, or legends, as specified (see 6.2).

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

QQ-A-250/5	- Aluminum Alloy Alclad, 2024, Plate and Sheet.
QQ-S-766	- Steel Plate, Sheet, and Strip, Corrosion-Resisting.
TT-E-489	- Enamel, Alkyd, Gloss, (For Exterior and Interior Surfaces).
UU-P-268	- Paper, Kraft, Untreated, Wrapping.
PPP-B-566	- Boxes, Folding, Paperboard.
PPP-B-636	- Boxes, Shipping, Fiberboard.
PPP-B-676	- Boxes, Set-Up.
PPP-T-45	- Tape, Gummed, Paper, Reinforced and Plain, For Sealing and Securing.

Federal Standard:

FED-STD-123	- Marking for Domestic Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:21Z
Check the source to verify that this is the current version before use.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, Washington.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specifications:

MIL-P-7962	-	Primer Coating, Cellulose - Nitrate Modified Alkyd Type, Corrosion Inhibiting, Fast Drying (For Spray Application over Pretreatment Coating).
MIL-C-8514	-	Coating Compound, Metal Pretreatment, Resin-Acid.
MIL-A-8625	-	Anodic Coatings, for Aluminum and Aluminum Alloys.
MIL-L-19537	-	Lacquer; Acrylic - Nitrocellulose, Gloss (for Aircraft use).

Military Standards:

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	-	Marking for Shipment and Storage.
MIL-STD-147	-	Palletized and Containerized Unit Loads 40" x 48" Pallets, Skids, Runners, or Pallet Type Base.

(Copies of Military Specifications and Standards required by supplier in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

Technical Association of the Pulp and Paper Industry (TAPPI)

Testing Methods, Recommended Practices, Specifications of the Technical Association of the Pulp and Paper Industry

T402 os	-	Conditioning Paper and Paperboard for Testing.
T411 os	-	Thickness (Caliper) of Paper and Paperboard.
T404 ts	-	Tensile Breaking Strength of Paper and Paperboard.
T414 ts	-	Internal Tearing Resistance of Paper.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the Technical Association of the Pulp and Paper Industry, 360 Lexington Avenue, New York, New York 10017.)

National Motor Freight Traffic Association, Inc., Agent

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, D.C. 20036.)

Uniform Classification Committee, Agent

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 202, Union Station, 516 W. Jackson Blvd., Chicago, Illinois 60606.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Construction. The marking stencil shall consist of resin-impregnated or other suitably treated paper coated on one side with a pressure-sensitive adhesive and with a protective backing paper covering the adhesive.

3.2 Materials.

3.2.1 Stencil paper. The paper shall be uniform in formation and resin impregnated or suitably treated to insure compliance with the requirements of this specification.

3.2.2 Adhesive. The adhesive shall be a pressure-sensitive adhesive of the type that does not require moisture, heat, or other special preparation prior to application.

3.2.3 Backing sheet. The backing sheet shall be creped or flat back paper which shall remove easily without disturbing the die cut letters in the stencil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

3.3 Fabrication. The stencils shall be the type that produces complete letters or numbers. They shall not be of the conventional broken stencil type. Stencils shall have perforated holding ties to keep the cut-out portions and centers in place before removal. The stencil shall be uniformly coated on one side with a pressure-sensitive adhesive which is covered with a backing paper to protect the adhesive prior to use. The backing shall not become stuck to the adhesive to cause delamination or otherwise undue difficulty during removal.

3.4 Design.

3.4.1 Form. The stencils shall consist of single characters or numerals, or legends of one or more lines, as applicable to the stencil required. Letters and numerals shall be of the style designated as large commercial gothic.

3.4.2 Dimensions. No single stencil shall exceed 48 inches combined length and width.

3.4.2.1 Types I thru III. Stencils shall have the applicable legend and dimensions shown in 1.2.1. A tolerance of ± 1/32 inch shall be permitted.

3.4.2.2 Type IV. The height of the letters or numerals and the spacing between legend lines shall be as specified (see 6.2). A tolerance of ± 1/32 inch will be permitted.

3.4.2.3 Type V. The height of individual letters, numerals, and single line legends shall be as specified (see 6.2). A tolerance of ± 1/16 inch will be permitted.

3.5 Physical properties of the uncut stencil paper.

3.5.1 Thickness. The average thickness of the stencil paper after removal of the backing sheet, but including the adhesive thickness, shall be not more than 0.009 inch when tested as specified in table I.

3.5.2 Tearing resistance. The stencil paper shall show a minimum average tearing resistance of 100 grams in each direction when tested as specified in table I.

3.5.3 Adhesion. The stencil paper shall show a minimum adhesion value of 12 ounces per inch width when tested as specified in table I.

3.5.4 Accelerated stability. When tested as specified in table I, after storage for 1 week at 150° ± 1°F. and 85 ± 5 percent relative humidity, the stencil paper shall conform to the requirements specified in 3.5.2 and 3.5.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

3.6 Performance. The backing sheet shall be easily removed in one piece without tearing the stencil or disturbing the die cut letters in the stencil. Stencils shall adhere with out the need of moisture, heat, or special preparation prior to application. The cut-out portions of stencils shall be easily removed without tearing the remaining portions of the stencil. Stencils shall not be penetrated through to the protected surface by the marking materials. Stencils shall exhibit sufficient strength to permit removal of integral portions of the stencil as one piece from the marked surface after application of the marking materials, without tearing, delamination, or separation of the adhesive from the paper. Stencils shall produce sharp markings. Only slight indications of the presence of the perforated hold-ties shall be apparent after use. Compliance with these requirements shall be determined in accordance with table II.

3.7 Workmanship. Stencils shall be clean and free of holes, tears, creases, wrinkles and folds; foreign matter, sand, grit, lint, and dust. The stencils shall be trimmed clean and shall be free from ragged edges.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated hereinafter.

4.2.1 Inspection of materials and components. In accordance with 4.1 above, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications and standards, unless otherwise excluded, amended or qualified in this specification or applicable purchase documents. Each test report shall cover material tested within the period of the contract, or within 60 days prior to commencement of the contract.

4.2.1.1 Lot for components and materials testing. The lot shall consist of one shipment of stencil paper of the same description, manufactured by the same source under essentially the same condition, and identified as used in fabricating the end-item stencils in accordance with this specification. The sample unit shall consist of two pieces of material, each with an area of not less than 300 square inches and at least 12 inches in one dimension. The sample units shall be randomly selected from each lot in accordance with the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

Linear yards of paper in the lot	Sample size
1,000 or less	2
1,001 to 2,000	3
2,001 and over	4

4.2.1.2 Testing. The fully prepared stencil paper prior to cutting, consisting of the stencil paper, adhesive, and backing, shall be tested for the applicable characteristics specified in table I. Failure to pass any of the tests shall be cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:21Z
Check the source to verify that this is the current version before use.

TABLE I. Instructions for testing of components

Characteristic	Specification reference: Requirement	Specification reference: Test method	Requirements applicable to lot average	No. determinations per sample unit	Results reported as numerically to nearest 1/
Thickness	3.5.1	4.4.2	X	6	0.0005
Before accelerated stability:					
Tearing resistance:	3.5.2	4.4.1			
Machine direction			X	5	gram
Cross direction			X	5	gram
Adhesion	3.5.3	4.4.1.1	X	5	ounce per inch
After accelerated stability:	3.5.4				
Tearing resistance:	3.5.2	4.4.1			
Machine direction			X	5	gram
Cross direction			X	5	gram
Adhesion	3.5.3	4.4.1.1	X	5	ounce per inch

1/ Test reports shall include all values on which results are based.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T12:21Z
Check the source to verify that this is the current version before use.

4.3 Inspection on the end item.

4.3.1 Examination of the end item. The end item shall be examined in accordance with the classification of defects set forth in the subparagraphs hereunder at the inspection levels and AQL's set forth in 4.3.1.5. The lot, for purpose of determining the sample size, in accordance with MIL-STD-105, shall be expressed as indicated in the applicable examination paragraph.

4.3.1.1 Examination of the end item for defects in appearance and workmanship. The lot shall be expressed in units of unit packages of stencils submitted for delivery at one time. The sample unit shall be one stencil of a character, numeral, or legend, as applicable. Not more than one stencil shall be selected from any one package. Defects shall be as listed below.

Examine	Defect
Appearance and construction	Stencil not shape or design specified. Spacing of words and lines, as applicable, not as specified. Not uniformly coated on one side with pressure-sensitive adhesive. Not uniformly and smoothly covered on adhesive side with a paper backing. Cut-out portion not held intact by hold-ties. Cut-out portion not easily removed without tearing the stencil. Hold ties not completely removed.
Workmanship	Not clean; any mark or irregularity. Any hole, tear, crease, wrinkle, or fold in stencil. Any foreign matter; sand, grit, lint, or dust. Not trimmed clean; ragged edges.

4.3.1.2 Examination of the end item for dimensional defects. The sample unit for this examination shall be one stencil of each size character, numeral, or legend in any size lot. There shall be no failure to meet the dimensional tolerances specified. The lot shall be expressed in units of one character, legend, or numeral stencil, as applicable. Defects shall be as listed below.

Examine	Defect
Stencils, all types	Greater than 48 inches combined length and width.
Character and numeral height or spacing, types I thru IV	Varies by more than $\pm$ 1/32 inch from that specified.

Source: https://assist.dla.mil -- Downloaded: 20264Q-26T12:21Z
Check the source to verify that this is the currentversion before use.

Examine	Defect
Character and numeral height, type V	Varies by more than ± 1/16 inch from that specified.

4.3.1.3 Examination of the end item for defects in average count. The sample unit for this examination shall be one unit package of five stencils per package of any character, numeral, or legend in any size. The lot shall be expressed in units of unit packages of five stencils per package. Insofar as practicable, the sample unit shall include at least one package of each character, numeral, or legend. The average numeral of stencils per package shall be not less than the number specified.

4.3.1.4 Examination of preparation for delivery. An examination shall be made to determine that the packaging, packing, and marking complies with the section 5 requirements. Defects shall be as listed below. The sample unit shall be one shipping container, fully packed, selected just prior to the closing operation. Closed shipping containers shall be examined for closure defects. The lot shall be the number of shipping containers offered for inspection at one time.

Examine	Defect
Markings (exterior and interior)	Incorrect; incomplete; illegible; omitted; of improper size, location, sequence, or method of application.
Materials	Any nonconforming component; component missing, damaged, or otherwise defective.
Workmanship	Inadequate application of components, such as incomplete closure of container flaps; loose or inadequate sealing, strapping, or stapling. Bulged or distorted containers.
Contents	Number of stencils per unit package is more or less than required.
Weights	Weight of contents per shipping container, exceeds requirement.

4.3.1.4.1 Examination for palletization. When applicable, an examination shall be made to determine that the palletization complies with the section 5 requirements. Defects shall be as listed below. The sample unit shall be one palletized unit load fully prepared for delivery. The lot shall be the number of palletized unit loads in the end item inspection lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

Examine	Defect
Finished dimension	Length, width, or height exceeds specified maximum requirement.
Palletization	Not as specified. Pallet pattern not as specified. Interlocking of loads not as specified. Load not bonded with required straps as specified.
Weight	Exceeds maximum load limits.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence or method of application.

4.3.1.5 Inspection levels and AQL's for examinations. The inspection levels for determining the sample size and the AQL's expressed per one hundred units, shall be as follows:

Examination paragraph	Inspection level	AQL
4.3.1.1	S-4	2.5
4.3.1.2	S-4	4.0
4.3.1.3	S-3	-
4.3.1.4	S-2	4.0
4.3.1.4.1	S-1	6.5

4.3.2 Testing of the end item. The end item shall be tested for the characteristics specified in table II. The lot for the purpose of determining the sample size in accordance with MIL-STD-105, shall be expressed in units of unit packages of stencils. The sample size shall be S-2. The sample unit, insofar as practicable, shall consist of one stencil of each character, numeral, or legend, regardless of size. No more than one sample unit shall be taken from a package. The AQL shall be 1.5 expressed as defects per one hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

TABLE II. Instructions for testing the end item

Characteristic	Specification reference: Requirement	Specification reference: Test method	No. determinations per sample unit	Results reported as pass or fail
Backing sheet, easily removable	3.6	4.4.3.2	1	X
Stencil adheres by pressure application only	3.6	4.4.3.2	1	X
Cut-out portions easily removable	3.6	4.4.3.2.	1	X
Stencil not penetrated by finishing materials	3.6	4.4.3.2	1	X
Stencils removed easily after application of finishing material	3.6	4.4.3.2	1	X
Stencils produce sharp markings	3.6	4.4.3.2	1	X

4.4 Tests.

4.4.1 Test methods. The following tests shall be conducted in accordance with the methods specified in applicable test methods of the Technical Association of the Pulp and Paper Industry (TAPPI), after conditioning the specimens in accordance with TAPPI test T402 os, Conditioning Paper and Paperboard for Testing.

Requirement	Test method
Tearing resistance	T414 ts 1/
Adhesion	4.4.1.1 thru 4.4.1.1.3

1/ Denotes TAPPI test number.

4.4.1.1 Adhesion.

4.4.1.1.1 Test specimen. The test specimen shall be 203 ± 4 millimeters (8 inches) long and not more than 25.4 millimeters (1 inch) wide.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:21Z
Check the source to verify that this is the current version before use.

4.4.1.1.2 Apparatus. A pendulum-type tensile testing machine as described in T404 ts, a 5 x 2 x 1/16 inch stainless-steel plate polished to a No. 4 finish (commercial polish ground) as specified in QQ-S-766 and a 4-1/2 pound rubber-covered roller approximately 3-1/2 inches in diameter by 1-3/4 inches in width, the surface of which has a durometer hardness value with the range 70 - 80 shall be used.

4.4.1.1.3 Procedure. Before each test, wash the polished surface of the steel plate thoroughly with carbon tetrachloride, using a clean piece of lintless wiping tissue for each washing. After all traces of the carbon tetrachloride have evaporated, wipe the surface of the plate with a clean dry piece of the tissue. Apply the tape, adhesive side down, to the polished surface of the plate with a 5 inch section extending beyond one end of it. Press the tape down firmly by passing the roller twice over its surface in opposite directions at the rate of approximately 12 inches per minute, using the weight of the roller only. (Pumice, French talc, or a strip of paper may be applied to the adhesive side of the extended section of the tape to prevent adhesion during the rolling.) Immediately double-back the free end of the tape at an angle of 180° and peel 1 inch of the tape off the plate at the folded end. Clamp the adjacent end of the plate into the lower jaw of the pendulum-type tensile machine and the free end of the tape in the upper jaw. The pawls on the pendulum arm shall be taped back in an open position. The tensile tester shall be of such capacity that the test values will be read when the pendulum hangs between 9° and 45° from the vertical. After the first inch is removed from the plate during the test, the minimum tension required to remove the remainder of the tape, except for the final 1 inch, from the plate shall be taken as the adhesion value. The test shall be made with the stressing jaw moving at a speed of 12 inches per minute. The average adhesion value for not less than five specimens shall be reported in ounces per inch width to one decimal place.

4.4.2 Thickness. Two specimens 1 by 10 inches shall be cut from the sample selected as specified in 4.2.1. The paper backing shall be removed and the specimens lightly pressed on a sheet of cellophane 10 inches longer than the specimen. Thickness measurements shall be taken along the length of the specimen including the cellophane backing as specified in TAPPI test T411 os. The thickness of the cellophane protruding beyond the stencil also shall be taken. An equal number of measurements shall be taken on the cellophane, as were made on the specimen and substracted from the first reading taken. At least 3 determinations shall be made on each specimen and the results averaged.

4.4.3 Performance of the end item.

4.4.3.1 Preparation of test panels. The test panels used for this test shall be aluminum-clad aluminum alloy conforming to QQ-A-250/5, anodized in

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:21Z
Check the source to verify that this is the current version before use.

accordance with MIL-A-8625. The panels shall be finished as follows: Spray one coat of wash primer, in conformance with MIL-C-8514, to a dry film thickness of 0.0002 to 0.0003 inch and air dry for one hour. The test panels with the wash primer shall then be sprayed with control formula product of lacquer type primer conforming to MIL-P-7962 to a dry film thickness of 0.0003 to 0.0004 inch and air dried for one hour. Two spray coats of control formula lacquer conforming to MIL-L-19537 shall be applied over the primer with a 45-minute drying interval between coats to a total dry film thickness of 0.001 ± 0.0002 inch. After application of the lacquer, the film shall be air-dried for 2 hours and then force-dried at 180°F. for 1 hour.

4.4.3.2 Procedure. A panel or panels of adequate size to accommodate the stencils selected as specified in 4.3.2 shall be prepared as specified in 4.4.3.1. The stencils shall be applied by removing the backing and affixing the stencil to the panel. Apply, by spraying, an enamel conforming to class A of TT-E-489. The method of application and drying time shall be as specified in TT-E-489. Forty-eight hours after application of the enamel, the stencils shall be removed and the stencils, stenciling, and panel surfaces examined for conformance with the requirements specified in 3.6.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Unit packaging.

5.1.1.1.1 Single characters and numerals. Five stencils of one description only, shall be packaged in a commercial envelope. Closure of the envelope shall be in accordance with commercial practice.

5.1.1.1.2 Legends. Five or 25 stencils as specified (see 6.2), of one description only, shall be packaged in a commercial envelope. Closure of the envelope shall be in accordance with commercial practice. Alternatively, the stencils shall be evenly stacked flat on a fiberboard pad and then be completely wrapped with a sheet of 40-pound minimum basis weight kraft paper conforming to grade B of UU-P-268. The paper wrap shall be secured with 2-inch minimum width gummed paper tape conforming to type III, grade B of PPP-T-45. The fiberboard pad shall exceed the dimensions of the stacked stencils by 1/4-inch in length and width.

5.1.1.2 Intermediate packaging.

5.1.1.2.1 Single characters and numerals. A quantity of stencils of one description only, unit packaged as specified in 5.1.1.1.1, shall be packaged

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

in a snug-fitting paperboard box conforming to variety 1, style III or VIII, type G, class 1 of PPP-B-566 or type I, variety 1, class A, style 4 of PPP-B-676. Each box shall be securely closed in accordance with the appendix of the applicable box specification.

5.1.1.2.2 Legends. Twenty or fifty unit packages of stencils of one description only, unit packaged as specified in 5.1.1.1.2, shall be evenly stacked and then securely tied with cotton tape or twine.

5.1.2 Level B (civil agencies). Stencils shall be packaged in accordance with the applicable requirements specified in 5.1.1 (see 6.2).

5.1.3 Level C. Stencils shall be packaged to afford adequate protection against physical damage or deterioration during shipment from the supply source to the first receiving activity. The supplier may use his standard practice when it meets these requirements.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. Stencils of one description only, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, grade V2s of PPP-B-636. Each shipping container shall be closed, waterproofed, and reinforced in accordance with the appendix of the container specification. The weight of contents of each shipping container shall not exceed 65-pounds.

5.2.2 Level B. Stencils of one description only, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. Each shipping container shall be closed in accordance with method II as specified in the appendix of the container specification. The weight of contents of each shipping container shall not exceed 65-pounds.

5.2.2.1 When specified (see 6.2), the fiberboard shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with the appendix of the container specification.

5.2.3 Level C. Stencils, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with Uniform Freight Classification Rules or National Motor Freight Classification Rules, as applicable.

5.3 Palletization (military requirement). Unless otherwise specified (see 6.2), stencils of one description only, packed as specified in 5.2, shall be

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:21Z
Check the source to verify that this is the current version before use.

palletized in accordance with load type I of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer.

5.4 Marking.

5.4.1 Civil agencies. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with FED-STD-123.

5.4.2 Military requirements. In addition to any special marking required by the contract or order, interior packages, shipping containers, and palletized unit loads shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. Marking stencils covered by this specification are suitable for use with lacquers, synthetic enamels, or other finishing materials and are intended for use in motors vehicle identification, marking of aircraft, and to protect finished surfaces during the application of spray painting.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Type (see 1.2.1, 3.4.2.2 and 3.4.2.3).
(c) Quantity of legends per unit package desired (see 5.1.1.1.2).
(d) Inspection responsibility (for civil agencies only) if other than as specified herein; and administrative provisions for inspection records, when applicable (see 4.1).
(e) Selection of the applicable levels of packaging and packing (see 5.1 and 5.2).
(f) Agencies ordering type IV stencils should specify the desired legend, letter size, and spacing.
(g) When weather resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
(h) When palletization is not required for a military procurement (see 5.3).
(i) When level B packaging is required for civil agencies (see 5.1.2).

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:21Z
Check the source to verify that this is the current version before use.

MILITARY CUSTODIANS:

Army - GL
Air Force - 84

Review activities:

Army - MD, SM

User activities:

Army - AT, AV, ME
Navy - SA

Preparing activity:

Army - GL

CIVIL AGENCIES INTEREST:

GSA
FSS

HEW

VA
DMS

Project No. 7520-0148

☆U. S. GOVERNMENT PRINTING OFFICE : 1972 O - 482-192 (3272)

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 20 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.