UU-T-940B
July 30, 1975
SUPERSEDING
Fed. Spec. UU-T-940A
September 15, 1965

FEDERAL SPECIFICATION

TYPE CLEANER (SHEET FORM)

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE

1.1 This specification covers the requirements for type cleaner, for use in cleaning the type face of typewriters and similar office machines by a sheet form process.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

UU-P-63 - Paper, Blotting.
UU-P-121 - Paper, Bond and Writing; White and Colored.
PPP-B-566 - Boxes, Folding, Paperboard.
PPP-B-636 - Boxes, Shipping, Fiberboard.
PPP-B-676 - Boxes, Setup.

Federal Standard:

Fed. Std. No. 123 - Marking for Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specification:

MIL-P-116 - Preservation-Packaging, Methods Of.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

FSC 7510

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza., Chicago, IL 60606.)

3. REQUIREMENTS

3.1 Material and construction. The type cleaner shall be made of a flexible sheet backing coated on one side with flock fibers or other suitable material firmly bonded to the sheeting. This material shall be so positioned on the backing and be of sufficient depth to permit probing into the recesses of the type character when typed upon dislodging accumulated ink and dirt. A pressure-sensitive overcoating of adhesive shall then be applied creating a receptive surface capable of removing the dislodged ink and dirt. The adhesive overcoating shall not cause sticking of sheets to each other, to other objects, or to the machine being cleaned.

3.2 Performance.

3.2.1 Type cleaning ability. The imprints left by the type characters on the blotting paper shall be examined and shall be free of visible ink and dirt deposits after performance of test in 4.3.

3.3 Size. The type cleaner sheet size shall be 8-1/2 by 11 (+1/16 -0) inches and shall be perforated (width wise) into sections or strips, not less than six nor more than eight, to facilitate easy disposal of used portion.

3.4 Identification marking. Each envelope and sheets contained therein shall be marked to clearly identify the product and its manufacturer by name or trademark of such known character that the source of manufacturer can be readily determined.

3.5 Workmanship. The type cleaner shall be free from imperfections or defects which might affect serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Inspection for acceptance. Sampling and inspection shall be performed in accordance with the provisions of MIL-STD-105, except where otherwise indicated hereinafter.

4.2.1 Lot. For the purposes of sampling, a lot for acceptance, inspection, and tests shall consist of all type cleaners submitted for inspection and delivery at one time.

4.2.2 Examination of preparation for delivery. An examination shall be made to determine compliance with the packaging, packing, and marking requirements of section 5. Defects shall be scored in accordance with table I. The sample unit shall be one shipping container fully prepared for delivery. The inspection level shall be S-2 and AQL shall be 4.0 defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

TABLE I. Examination of preparation for delivery

Examine	Defect
Container	Not as specified.
Contents	Not as specified.
Marking	Omitted; incorrect; illegible; improper size, location, sequence or method of application.
Material	Component missing or damaged.
Workmanship	Bulging or distortion of containers. Cushioning inadequate or improper.

4.2.3 Examination of end item. A random sample of type cleaner shall be taken from each lot and examined for presence of defects listed in table II. The sample unit shall be one type cleaner sheet. The sample size shall be in accordance with inspection level S-2 and AQL shall be 2.5 percent defective.

TABLE II. Examination of end item

Examine	Defects
Size	Not as specified.
Perforations	Not width wise.
Strips	Less than 6 or more than 8 strips per sheet.
Identification marking	Not as specified.
Use instructions	Not printed on envelopes.
Stickiness	Sheets sticking together, to machine or to other objects.

4.2.4 Testing of the end item. The type cleaner shall be tested as specified in 4.3. The sample size, inspection level and AQL shall be the same as specified in 4.2.3.

4.3 Type cleaning test. Test typewriter shall be an International Business Machine, Fabric Ribbon Model C III electric "or equal" with elite type. The type shall be thoroughly cleaned prior to test. Install a new cotton offset black medium inked ribbon. Then with the typewriter impression indicator adjusted for maximum impact (setting #12), type the lower case letters "a", "e", and "g", six hundred times each on a sheet of 32-pound white bond paper conforming to the requirements for type III of UU-P-121. Do not allow ribbon to reverse during this operation as only a new ribbon surface is to be used during the test. With the impression indicator remaining in the maximum impact position, place typewriter in the stencil position and clean the "a", "e", and "g" type using the sample type cleaner limiting cleaning strokes to twenty five for each letter. With the typewriter still in the stencil position and still employing maximum impact, insert a piece of blotting paper conforming to the requirements for grade A of UU-P-63. Strike the blotting paper with the "a", "e", and "g" each ten times. The blotting paper shall then be inspected for compliance with 3.2.1.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C as specified (see 6.2).

5.1.1 Level A. Type cleaners shall be packaged three sheets to an envelope, twelve envelopes to a box, each box conforming to PPP-B-566 or PPP-B-676, style optional. Each box shall be waterproofed in accordance with MIL-P-116, Method IC-2.

5.1.2 Level B. Type cleaners shall be packaged as specified in 5.1.1 except that waterproofing shall not be required.

5.1.3 Level C. Type cleaners shall be packaged in accordance with the supplier's commercial practice.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. Twelve boxes, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to PPP-B-636, class weather-resistant V3c, style RSC. The container shall be closed and sealed in accordance with the appendix to PPP-B-636.

5.2.2 Level B. Twelve boxes, packaged as specified in 5.1, shall be packed in a box conforming to PPP-B-636, class domestic. Closure shall be in accordance with the appendix to PPP-B-636.

5.2.3 Level C. Type cleaners, packaged as specified in 5.1 shall be packed in containers to assure carrier acceptance and safe arrival at destination. The containers shall conform to the National Motor Freight Classification or Uniform Freight Classification Rules, as applicable.

5.3 Marking. In addition to 5.3.1 and any special marking required by the contract or order, unit and shipping containers shall be marked in accordance with Fed. Std. No. 123 or MIL-STD-129, as applicable (see 6.2).

5.3.1 Use instructions. Each unit package (envelope) shall be marked with instructions for use.

6. NOTES

6.1 Intended use. The type cleaner covered herein is intended to clean the metal type face on typewriters and other similar office machines.

6.2 Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Level of packaging and packing required (see 5.1 and 5.2).
(c) Marking required (see 5.3).

6.3 It is believed that this specification adequately describes the characteristics necessary to secure the desired material, and that normally no samples will be necessary prior to award to determine compliance with this specification. If, for any particular purpose, samples with bids are necessary, they should be specifically asked for in the invitation for bids and the particular purpose to be serviced by bid sample should be definitely stated, the specification to apply in all other respects.

MILITARY INTERESTS:

DOD has waived coordination interest in this specification.

User Activity:

Army - GL

Preparing activity:

GSA-FSS

CIVIL AGENCY COORDINATING ACTIVITIES:

GPO
GSA-FSS
VA-DMS

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See Section 2 of this specification to obtain extra copies and other documents referenced herein. Price 25 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.