L-R-00335A(GSA-FSS)
Amendment-2
September 16, 1971
SUPERSEDING
Amendment-1(GSA-FSS)
January 7, 1969

AMENDMENT

TO

INTERIM FEDERAL SPECIFICATION

RIBBON, FLAGGING, SURVEYOR'S, PLASTIC

This amendment was developed by the Standardization Division, Federal Supply Service, General Services Administration, Washington, D. C. 20406, based upon currently available technical information. The General Services Administration has authorized this amendment as a part of Interim Federal Specification L-R-00335A(GSA-FSS), dated August 24, 1966.

PAGE 1

Paragraph 1.2.2 Classes. Add new class as follows:

"Class 3 (type I only) - Color stripe (one side) Range: Blue and white, orange and white, red and white, yellow and white."

PAGE 2

Paragraph 2.2: Under the heading "American Society for Testing and Materials (ASTM) Standards," add the following method:

"D 2088 - Test for Low Concentration Lead."

After paragraph 3.1.2, insert new paragraph as follows:

3.1.3 Color pigments. Pigments for coloring types I and II flagging ribbons shall not contain lead (see 4.4.6).

PAGE 3

Table I. Thickness requirements - Add under indicated headings the following entries:

Type	Class	Grade	Thickness, inches	
			Minimum	Maximum
I	3	M	0.0019	0.0022
I	3	MH	0.003	0.004

Table II. Finished thickness requirements - Add under indicated headings the following entries:

Type	Class	Grade	Thickness, inches	
			Minimum	Maximum
I	3	M	0.0022	0.005
I	3	MH	0.004	0.006

Paragraph 3.4.1 Length. Delete first sentence, and substitute:

"Type I, classes 1 and 3, and the type II, class 1 ribbon shall be furnished in rolls of 100 yards minimum length of continuous strip."

After paragraph 3.4.2, insert new paragraph as follows:

3.4.2.1 Stripe width. The stripe width of the type I, class 3 ribbon shall be 9/16 plus or minus 1/16 inch with an angle of 45 plus or minus 1 degree. Stripes shall be printed on one side of the ribbon.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:09Z
Check the source to verify that this is the current version before use.

Table III. Color requirements. Make following changes in table:

Delete Type I, class 1 heading and substitute:

"Type I, class 1, and 3/4/:"

At end of table add following footnote 4/:

4/ Class 3 ribbon colors shall meet the applicable Munsell color notation, chart numbers

After paragraph 4.4.5.1, insert new paragraph as follows:

4.4.6 Test for presence of lead. A specimen of flagging ribbon shall be tested as specified in ASTM 2088 to determine conformance with 3.1.3.

GSA DC 72-4307

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:09Z
Check the source to verify that this is the current version before use.