NOTE: The document identifier and heading have been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.

INCH-POUND

MIL-PRF-27/322C
19 January 1989
SUPERSEDING
MIL-T-27/322B
2 April 1984

PERFORMANCE SPECIFICATION SHEET

TRANSFORMERS, POWER, 300 VOLT-AMPERES, 60 HERTZ, TF4S03YY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the transformer described herein shall consist of this specification and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-T-27.





FIGURE 1. Dimensions and configuration.


Ⓒ denotes changes

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.


Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:11Z
Check the source to verify that this is the current version before use.



DASH NUMBERS 07 THRU 24



DASH NUMBERS 01 THRU 06



CIRCUIT DIAGRAM

Inches	mm	Inches	mm
.005	0.13	.375	9.52
.016	0.41	.470	11.94
.031	0.79	.875	22.22
.062	1.57	1.063	27.00
.070	1.78	2.75	69.8
.080	2.03	3.50	88.9
.094	2.39	3.88	98.6
.188	4.78	4.69	119.1
.250	6.35	6.00	152.4

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Marking shall be on the sides of the case.
4. Unless otherwise specified, tolerance is ±.063 (1.60 mm).
5. Electrical values shall be marked as specified in table I.

FIGURE 1. Dimensions and configurations - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:11Z
Check the source to verify that this is the current version before use.

REQUIREMENTS (When numbers in parentheses, i.e., (1-2) are used, they indicate the winding and the extreme terminals of the winding.)

Electrical ratings:

Primary voltage (1-2) 115 volts ac, 50 to 60 hertz.

Primary dc resistance 0.5 ohms ±25 percent.

Secondary voltage (3-5): See table I.

Volt-ampere rating 200 volt-amperes.

Working voltage (1-2) 535 volts peak.

Design and construction:

Dimensions and configuration. See figure 1.

Duty cycle: Continuous.

Case Metal enclosed.

Material Steel.

Terminals Solderable terminals.

Dash numbers	Terminal type	Height (inches)	Diameter (inches)
01 through 06	hook	0.470 ±.031	0.080 ± 005
07 through 24	hook	0 375 ±.031	0.062 ±.005

Weight: 17.0 pounds, maximum.

Operating temperature range: -55°C to +130°C

Altitude: 10,000 feet.

Terminal strength MIL-STD-202, method 211, test condition A, 2.0 pounds.

Dielectric withstanding voltage (each winding) (at sea level): 1,500 volts rms.

Electrical characteristics:

Rated load. With 115 volts ac and 60 Hz across (1-2), and rated current in secondary, the voltage across (3-5), shall be as specified in table I.

Regulation: $\frac{\text{Voltage (no load)} - \text{Voltage (rated load)}}{\text{Voltage (rated load)}} \times 100$ shall not exceed 10 percent.

Polarity: Additive with terminals 2 and 3 connected.

Temperature rise: +35°C with 115 volts ac, 60 hertz across (1-2) at an ambient temperature of +95°C, full load terminals (3-5).

Shock (specified pulse): MIL-STD-202, method 213, test condition G.

Marking location: See figure 1.

Part or identifying number (PIN). M27/322-(dash number from table I).

Source: https://assist.dla.mil -- Downloaded: 202610-16T04:11Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical ratings.

Dash number	Secondary (3-5)		
	Voltage (volts) ±3 percent	Current 1/ (amperes)	DC resistance (ohms) ±25 percent
01	16.0	18.70	0.016
02	18.0	16.70	0.020
03	20.0	15.00	0.023
04	22.0	13.60	0.031
05	25.0	12.00	0.042
06	28.0	10.70	0.046
07	31.0	9.67	0.054
08	35.0	8.59	0.072
09	39.0	7.69	0.080
10	43.0	6.95	0.108
11	48.0	6.26	0.165
12	55.0	5.46	0.175
13	63.0	4.76	0.187
14	70 0	4.29	0.26
15	80.0	3.75	0.30
16	90.0	3.320	0.43
17	100	3.000	0.48
18	110	2.72	0.65
19	123	2.44	0.74
20	138	2.17	1.02
21	157	1.91	1.16
22	175	1.710	1.63
23	200	1.50	1.92
24	220	1.36	2.55

1/ For 50 Hz operation, reduce secondary current by 10 percent.

QUALITY ASSURANCE PROVISIONS:

Extent of Qualification:

Qualification testing and approval to M27/312-26, M27/316-30, and M27/322-24 shall be sufficient to grant qualification approval to MIL-T-27/312 through MIL-T-27/322, inclusive, all parts.

Qualification testing and approval to M27/322-24 shall be sufficient to grant qualification approval M27/322-01 through M27/322-24.

Source: https://assist.dla.mil -- Downloaded: 202610-16T04:11Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AR
Navy - OS, SH
Air Force - 11, 17, 99
DLA - ES

User activities
Army - ME
Navy - AS, MC
Air Force - 19

Preparing activity:
Army - ER

Agent:
DLA - ES

(Project 5950-0725-05)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:11Z
Check the source to verify that this is the current version before use.