NOTE: The document identifier and heading have been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.


MIL-PRF-27/326B
2 April 1984
SUPERSEDING
MIL-T-27/326A
14 January 1983


PERFORMANCE SPECIFICATION SHEET

TRANSFORMERS, POWER, 5 VA, 60 HZ, TF4S03EB


This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the transformer described herein shall consist of this specification and the latest issue of MIL-T-27.





TERMINAL DIMENSIONS



SEE NOTE 5

WORKING VOLTAGE 535 VOLTS PEAK

CIRCUIT DIAGRAM AND MARKING

INCHES	MM
.005	0.13
.016	0.45
.062	1.57
.063	1.60
.070	1.78
.125	3.18
.138	3.51
.188	4.78
.375	9.53
.875	22.23
1.250	31.75
1.375	34.93
1.812	46.02
1.938	49.23
2.438	61.93

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information.
3. Marking shall be on the sides of the case. Terminal identification shall be as shown on the figure.
4. Electrical values shall be marked as specified in table I.
5. For series output connect terminals 4 and 5 together. For parallel output connect pins 3 to 4 and 5 to 6.

FIGURE 1. Dimensions and configurations.

(B) denotes changes

FSC 5950

Source: https://assist.dla.mil -- Downloaded: 20261O-16T04:12Z
Check the source to verify that this is the current version before use.

REQUIREMENTS: (When numbers in parentheses, i.e., (1-2) are used, they indicate the winding and the extreme terminals of the winding.)

Electrical ratings:

Primary (1-2): 115 V rms, 50 to 65 Hz.

Primary dc resistance: 85 ohms ±25 percent.

Secondary: See table I.

Volt ampere: 5 VA.

Working voltage: 535 volts pk.

Design and construction:

Dimensions and configuration: See figure 1.

Duty cycle: Continuous.

Case: Metal enclosed.

Material: Steel.

Terminals: Solderable hook terminals.

Height: .375 ±.063 inch.

Diameter: .062 ±.005 inch.

Weight: 1.2 pounds, maximum.

Operating temperature range: -55°C to +130°C.

Altitude: 10,000 feet.

Terminal strength: MIL-STD-202, method 211, test condition A, 2 pounds.

Dielectric withstanding voltage (each winding, secondary winding shall be connected in parallel)

At sea level: 1500 V rms.

Electrical characteristics:

Rated load: With 115 V rms and 60 Hz in (1-2), and rated current in secondary, secondary voltage shall be as specified in table I within ±3 percent.

Regulation: $\frac{\text{Voltage (no load)} - \text{Voltage (rated load)}}{\text{Voltage (rated load)}} \times 100$ shall not exceed 12 percent

Polarity: Additive with terminals 2 and 3 connected and 5 and 4 connected.

Temperature rise: 40°C with 115 V rms, 60 Hz across (1-2) at an ambient temperature of 90°C.

Marking location: See figure 1.

Part number: M27/326-(dash number from table I).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:12Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical ratings.

Dash number	Secondary voltage (series) volts rms (3-6)	Secondary current (series) amperes (3-6)	Secondary voltage (parallel) volts rms (3-5)	Secondary current (parallel) amperes (3-5)	Secondary dc resistance each winding ohms ±25%
01	10.0	0.50	5.0	1.00	0.62
02	12.6	0.40	6.3	0.80	0.96
03	16.0	0.31	8.0	0.62	1.52
04	20.0	0.25	10.0	0.50	2.38
05	24.0	0.20	12.0	0.40	3.67
06	34.0	0.15	17.0	0.30	6.4
07	40.0	0.12	20.0	0.24	9.7
08	56.0	0.09	28.0	0.18	20.8
09	88.0	0.05	44.0	0.10	41
10	120.0	0.04	60.0	0.08	73

QUALITY ASSURANCE PROVISIONS·

Extent of qualification:

Qualification testing and approval to M27/326-10 and M27/331-08 shall be sufficient to grant qualification approval to MIL-T-27/326 through MIL-T-/331 inclusive, all parts.

Qualification testing and approval to M27/326-10 shall be sufficient to grant qualification approval to M27/326-01 through M27/326-10.

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AR
Navy - OS
Air Force - 11, 17, 99
DLA - ES

User activities:
Army - ME
Navy - AS, MC
Air Force - 19

Agent:
DLA - ES

Preparing activity:
Army - ER

(Project 5950-0623-42)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:12Z
Check the source to verify that this is the current version before use.