INCH-POUND
MIL-PRF-27/327E
w/AMENDMENT 2
5 February 2021
SUPERSEDING
MIL-PRF-27/327E
w/AMENDMENT 1
13 November 2015

PERFORMANCE SPECIFICATION SHEET

TRANSFORMERS, POWER, 15 VA, 60 HERTZ

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the transformer described herein shall consist of this specification and the latest issue of MIL-PRF-27.




FIGURE 1. Dimensions and configurations

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:12Z
Check the source to verify that this is the current version before use.

LTR	Dimensions	
	Inches	Millimeters
A	2.312 +.000, -.125	58.72 +.000, -3.18
B	1.688 ±.016	42.88 ±0.41
C	2.062 +.000, -.125	52.37 +.000, -3.18
D	1.438 ±.016	36.53 ±0.41
E	.875 ±.062	22.23 ±1.57
F	3.125 +.000, -.188	79.38 +.000, -4.78
G	.375 ±.063	9.53 ±1.60
H	.070 ±.005	1.78 ±.13
I	.062 ±.005	1.57 ±.13

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Marking shall be on the sides of the case. Terminal identification shall be as shown on the figure.
4. Electrical values shall be marked as specified in table I, except DCR.
5. For series output connect terminals 4 and 5 together. For parallel output connect pins 3 to 4 and 5 to 6.
6. The mounting surface can be painted.
7. Pin 7 not used for QPL products.
8. Black Dot by terminal 1.

FIGURE 1. Dimensions and configurations – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:12Z
Check the source to verify that this is the current version before use.

REQUIREMENTS: (When numbers in parentheses, i.e., (1-2) are used, they indicate the winding and the extreme terminals of the winding.)

Electrical ratings:

Primary voltage (1-2): 115 V rms, 50 to 65 hertz.

Primary dc resistance: 22.1 ohms ±25 percent.

Secondary: See table I.

Volt-ampere rating: 15 volt-amperes.

Working voltage: 535 volts peak.

Design and construction:

Dimensions and configuration: See figure 1.

Duty cycle: Continuous.

Case: Metal enclosed.

Material: Steel.

Terminals: Solderable hook terminals.

Terminal height: 0.375 ±0.063 inch.

Terminal diameter: 0.062 ±0.005 inch.

Weight: 2.2 pounds, maximum.

Operating temperature range: -55°C to +130°C; Maximum ambient temperature not to exceed 90˚C.

Altitude: 10,000 feet.

Terminal strength: MIL-STD-202-211, test condition A, 2.0 pounds.

Dielectric withstanding voltage (each winding, secondary winding shall be connected in parallel):

At sea level: 1,500 volts rms.

Electrical characteristics:

Rated load: With 115 volts ac and 60 Hz across (1-2), and rated current in secondary, secondary voltage shall be as specified in table I within ±3 percent.

Regulation: $\frac{\text{Voltage (no load) - Voltage (rated load)}}{\text{Voltage (rated load)}} \times 100$

Shall not exceed 10 percent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:12Z
Check the source to verify that this is the current version before use.

Polarity: Additive with terminals 2 and 3 connected and 5 and 4 connected.

Temperature rise: 40°C with 115 volts rms, 60 hertz across (1-2) at an ambient temperature of 90°C,

Marking location: See figure 1.

Part or Identification Number (PIN): M27/327-(dash number from table I).

TABLE I. Electrical ratings.

Dash number	Secondary voltage (series) volts rms	Secondary current (series) amperes (3-6)	Secondary voltage (parallel) volts rms (3-5)	Secondary current (parallel) amperes (3-5)	Secondary dc resistance each winding ohms ±25%
01	10.0	1.50	5.0	3.00	0.116
02	12.6	1.19	6.3	2.38	0.167
03	16.0	0.93	8.0	1.86	0.252
04	20.0	0.75	10.0	1.50	0.48
05	24.0	0.60	12.0	1.20	0.58
06	34.0	0.44	17.0	0.88	1.06
07	40.0	0.36	20.0	0.72	1.57
08	56.0	0.27	28.0	0.54	3.5
09	88.0	0.15	44.0	0.30	8.78
10	120.0	0.12	60.0	0.24	14.8

VERIFICATION:

Extent of Qualification:

Qualification testing and approval to M27/326-10 and M27/331-08 shall be sufficient to grant qualification approval to MIL-PRF-27/326 through MIL-PRF-27/331 inclusive, all parts.

Qualification testing and approval to M27/327-10 shall be sufficient to grant qualification approval M27/327-01 through M27/327-10.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:12Z
Check the source to verify that this is the current version before use.

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced documents.

MIL-PRF-27 MIL-PRF-27/326 MIL-PRF-27/328 MIL-PRF-27/329 MIL-PRF-27/330
MIL-PRF-27/331 MIL-STD-202-211

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5950-2020-026)

Review activities:
Army – AR, CR4
Navy - AS, MC, OS
Air Force - 19

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:12Z
Check the source to verify that this is the current version before use.