MIL-E-1/671B
2 August 1968
SUPERSEDING
MIL-E-1/671A
21 January 1959

MILITARY SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

TYPE 26D6

The complete requirements for procuring the electron tube described herein shall consist of this document and the latest issue of Specification MIL-E-1.

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

DESCRIPTION: Pentagrid converter, miniature

Outline	---	5-2 (EIA) (B)
Base	---	E7-1
Envelope	---	T5-1/2
Cathode	---	Coated unipotential

Base connections:

Pin No.	---	1	2	3	4	5	6	7
Element	---	g1	k, g5	h	h	p	g2, g4	g3

ABSOLUTE RATINGS:

Parameter:	Ef	Eb	Ec2+4	Ec1	Ec3	Pp	Pg2+4	Ic1	Ik	Ehk	(B) Alt
Unit:	Vdc	Vdc	Vdc	Vdc	Vdc	W	W	mAdc	mAdc	v	ft
Maximum:	29.2	330	110	---	---	1.1	1.1	0.5	14.0	100	(see
Minimum:	23.9	---	---	---	---	---	---	---	---	---	note 4)
TEST CONDITIONS:	26.5	26.5	26.5	0	-0.5	---	---	---	---	---	---

REQUIREMENT OR TEST:

GENERAL

3.2	Qualification - Required	E-50.3	Preheating
E-50.2	Holding period	5.	Preparation for delivery

(B) denotes technical changes only.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:32Z
Check the source to verify that this is the current version before use.

METHOD OR PARAGRAPH	REQUIREMENT OR TEST	CONDITIONS	AQL (PERCENT DEFECTIVE)	INSPECTION LEVEL OR CODE	SYMBOL	LIMITS MIN	LIMITS MAX	UNIT
	Quality conformance inspection, part 1							
1266	Total grid current	Eb = 250 Vdc; Ec3 = -2.0 Vdc; Ec2+4 = 100 Vdc (see note 1 or note 2 and note 5)	0.65	II	Ic3	0	-1.0	μAdc
1256	Electrode current (anode)	See note 1 or note 2	0.65	II	Ib	0.1	0.8	mAdc
1256	Electrode current (screen grid)	See note 1 or note 2	0.65	II	Ic2+4	1.0	2.2	mAdc
1236	Oscillator grid current	Zgk = 2,600 or note 2	0.65	II	Ic1	10	55	μAdc
1231	Emission	Eb = Ec1 = Ec2 = Ec3 = 15 Vdc (see note 5)	0.65	II	Is	50	---	mAdc
1326	Conversion transconductance (1)	See note 1 or 2	0.65	II	Sc	100	440	μmhos
(B)1201	Short and discontinuity detection		0.4	II	---	---	---	---
(B)Appendix D, 20(a), 30	Visual and mechanical inspection criteria		---	---	---	---	---	---
(B)Appendix D, 20(b)	Dimensions	Outline 5-2; dimensions A, C, D, and E	1.0	I	---	---	---	---
	Quality conformance inspection, part 2							
1211	Insulation of electrodes		6.5	L6	R	10	---	Meg
1031	Low-frequency vibration	Eb = 250 Vdc; Ec1 = Ec3 = -1.5 Vdc; Ec2+4 = 100 Vdc; Rp = 10,000 ohms	6.5	L6	Ep	---	300	mVac
1326	Conversion transconductance (2)	Ec3 = -6 Vdc (see note 1 or note 2)	6.5	L6	Sc	1	20	μmhos
(B)1336	Heater-cathode leakage		6.5	L6	Ink	---	20	μAdc
1301	Heater current		6.5	L6	If	64	76	mA
1306	Transconductance (oscillator)	Ec3 = 0 (see note 3)	6.5	L6	Sg1g2	2,500	6,000	μmhos
1331	Direct-interelectrode capacitance	Shield No. 316	6.5	Code E	Cg3-all Cp-all Cg3p	8.0 9.8 ---	9.0 18.2 0.3	pf pf pf
(B)2126	Glass strain		4.0	I	---	---	---	---
(B)1121	Base strain		---	---	---	---	---	---
(B)1105	Permanence of marking		---	---	---	---	---	---

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:32Z
Check the source to verify that this is the current version before use.

METHOD OR PARAGRAPH	REQUIREMENT OR TEST	CONDITIONS	AQL (PERCENT DEFECTIVE)	INSPECTION LEVEL OR CODE	SYMBOL	LIMITS MIN	LIMITS MAX	UNIT
	Quality conformance inspection, part 3							
4.7 and 1501	Life-test provisions (intermittent)(500 hours)	Group A; Eb = Ec2+4 = 50 Vdc; Ec1 = -1.5 Vdc; Ehk = +100 Vdc; Eg1 = 2.0 Vac	---	---	---	---	---	---
4.7.3	Life-test end points (intermittent) (500 hours)	Oscillator grid current Conversion trans-conductance (1)	--- ---	--- ---	Ic1 Gc	5 80	--- ---	µAdc µmhos

NOTES:

1. Insert a 20,000 ohms resistor and a suitable bypass capacitor in series with grid No. 1. Apply sufficient ac signal to produce 0.1 mAdc average grid current.
2. Rg1 = 2,000 ohms; Ec3 = 0. For equivalent test, use a 20 kHz Hartley Oscillator Coil whose resonant impedance is 19,400 ohms. Cathode tap at 13 percent of total turns from ground end. Use limits which correlate with those specified.
3. Anode and screen tied together at socket.
4. See 6.5.2.3 for reduced pressure (altitude), and for altitude, maximum peak voltage.
5. This test to be performed at the conclusion of the holding period.

Custodians:
Army - EL
Navy - EC
Air Force - 11

Review activities:
Army - EL
Navy - EC, SH
Air Force - 11, 85
DSA - ES

User activities:
Army - ME
Navy - AS, OS, MC, CG
Air Force - 19

Preparing activity:
Army - EL

(Project 5960-2211-29)

Source: https://assist.dla.mil -- Downloaded: 202640-15T13:32Z
Check the source to verify that this is the currentversion before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:32Z
Check the source to verify that this is the current version before use.

FOLD

Department of the Army
Headquarters
U.S.Army Electronics Command
Fort Monmouth, New Jersey 07703

POSTAGE AND FEES PAID

OFFICIAL BUSINESS

Commanding General
U.S.Army Electronics Command
ATTN: AMSEL-~~TD-SS~~
Fort Monmouth, New Jersey 07703

FOLD

To detach this form, cut along this line

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:32Z
Check the source to verify that this is the current version before use.

To detach this form, cut along this line

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION
MIL-E-1/671B Electron Tube, Receiving Type 26D6

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?
   ☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

ESC-PM 1068-68

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:32Z
Check the source to verify that this is the current version before use.