MIL-E-1/673A
27 September 1968
SUPERSEDING
MIL-E-1/673
23 March 1954

MILITARY SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

TYPE 35C5

The complete requirements for procuring the electron tube described herein shall consist of this document and the latest issue of Specification MIL-E-1.

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

DESCRIPTION: Pentode, miniature, beam power amplifier

Outline	---	5-3 (EIA) Ⓐ
Base	---	E7-1
Envelope	---	T5-1/2
Cathode	---	Coated unipotential

Base connections:

Pin No.	---	1	2	3	4	5	6	7
Element	---	k, g3	g1	h	h	g1	g2	p

ABSOLUTE-MAXIMUM RATINGS:

Parameter:	Ef	Eb	Ec1	Ec2	Pp	Pg2	Ⓐ Ehk	Ⓐ Alt
Unit:	V	Vdc	Vdc	Vdc	W	W	v	ft
Maximum:	38.5	150	---	125	5.0	1.1	100	(see note 1)
Minimum:	31.5	---	---	---	---	---	---	
TEST CONDITIONS:	35.0	110	-7.5	110	---	---	---	---

GENERAL:

Qualification - Required

Ⓐ denotes changes

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:33Z
Check the source to verify that this is the current version before use.

METHOD	REQUIREMENT OR TEST	CONDITIONS	AQL (PERCENT DEFECTIVE)	INSPECTION LEVEL OR CODE	SYMBOL	LIMITS MIN	LIMITS MAX	UNIT
	Quality conformance inspection, part 1							
1266	Total grid current	See note 2	0.65	II	Ic1	0	-3.0	µAdc
1256	Anode current		0.65	II	Ib	28	52	mAdc
1231	Emission	Eb = Ec1 = Ec2 = 20 Vdc (see note 2)	0.65	II	Is	90	---	mAdc
Ⓐ 1246	Audio frequency noise	Esig = 500 mVac; Rp = 2,000 ohms (see note 3)	0.65	II	---	---	---	---
1341	Power output	Esig = 5.3 Vac; Rp = 2,500 ohms	0.65	II	Po	1.1	---	W
Ⓐ 1201	Short and discontinuity detection		0.4	II	---	---	---	---
Ⓐ ---	Visual and mechanical inspection criteria		---	---	---	---	---	---
Ⓐ ---	Dimensions	Outline 5-3; dimensions A, C, D, and E	1.0	I	---	---	---	---
	Quality conformance inspection, part 2							
Ⓐ 1211	Insulation of electrodes		4.0	S3	R	10	---	Meg
1301	Heater current		6.5	S3	If	138	162	mA
Ⓐ 1336	Heater-cathode leakage		6.5	S3	Ihk	---	75	µAdc
1256	Electrode current (screen)		6.5	S3	Ic2	0	6.5	mAdc
1306	Transconductance		6.5	S3	Sm	4,400	7,200	µmhos
1031	Low-frequency vibration	Rp = 2,000 ohms; Ec1 = -15 Vdc	6.5	S3	Ep	---	1,000	mVac
Ⓐ 1121	Base strain		---	---	---	---	---	---
Ⓐ 2126	Glass strain		4.0	I	---	---	---	---
Ⓐ 1105	Permanence of marking		---	---	---	---	---	---
	Quality conformance inspection, part 3							
1501	Life-test provisions (intermittent) (500 hours)	Group A; Ebb = Ecc2 = 135 Vdc; Rg1 = 0.5 Meg; Rk = 250 ohms; Ehk = +100 Vdc; Ec1 = 0	---	---	---	---	---	---
---	Life-test end point	Power output	---	---	Po	0.8	---	W

Source: https://assist.dla.mil -- Downloaded: 202610-15T13:33Z
Check the source to verify that this is the current version before use.

NOTES:

1. See "Reduced pressure (altitude) rating," and altitude, maximum peak voltage.
2. This test to be performed at the conclusion of the holding period.
3. The rejection level shall be set at the VU meter reading obtained during calibration.

Custodians:
Army - EL
Navy - EC
Air Force - 11

Review activities:
Army - EL, MI
Navy - SH
Air Force - 11, 85
DSA - ES

User activities:
Army - AV, ME
Navy - AS, OS, MC, CG
Air Force - 19

Preparing activity:
Navy - EC

(Project 5960-2211-30)

☆ U. S GOVERNMENT PRINTING OFFICE: 1966-341-512/A-2010

Source: https://assist.dla.mil -- Downloaded: 202610-15T13:33Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:33Z
Check the source to verify that this is the current version before use.