MIL-E-1/694B
14 November 1968
SUPERSEDING
MIL-E-1/694A
21 January 1956

MILITARY SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

TYPE 6088

The complete requirements for procuring the electron tube described herein shall consist of this document and the latest issue of Specification MIL-E-1.

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

DESCRIPTION: Pentode, subminiature, power amplifier

Outline --- 2-1(EIA) Ⓑ

Base --- Pinch press, 5 leads in line

Envelope --- T2X3

Cathode --- Coated filament

Base connections:

Pin No.	---	1	2	3	4	5
Element	---	a (red dot)	g2	+f g3	g1	-f g3

ABSOLUTE-MAXIMUM RATINGS:

Parameter	Ef	Eb	Ec1	Ec2	Ik	Alt
Unit:	Vdc	Vdc	Vdc	Vdc	mAdc	ft
Maximum	1.5 (see note 1)	67.5	---	67.5	1.5	(see note 2)
Minimum:	1.0	---	---	---	---	---
TEST CONDITIONS:	1.25	45	-1.25	45	---	---

Ⓑ

GENERAL:

Qualification - Not required

Ⓑ denotes changes

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:34Z
Check the source to verify that this is the current version before use.

METHOD	REQUIREMENT OR TEST	CONDITIONS	AQL (PERCENT DEFECTIVE)	INSPECTION LEVEL OR CODE	SYMBOL	LIMITS MIN	LIMITS MAX	UNIT
	Quality conformance inspection, part 1							
1266	Total grid current (1)	Ec1 = -50 Vdc	0.65	II	Ic1	0	-1.0	µAdc
1256	Electrode current (anode)		0.65	II	Ib	450	900	µAdc
1256	Electrode current (screen grid)		0.65	II	Ic2	---	230	µAdc
1341	Power output (2)	Esig = 0.9 Vac; Rg1 = 5.0 Meg; Rp = 0.2 Meg; Ef = 1.0 Vdc (see note 3)	0.65	II	Po	5.5	---	mW
1201	Short and discontinuity detection		0.4	II	---	---	---	---
	Quality conformance inspection, part 2							
1116	Lead fatigue		4.0	S3	---	3	---	arcs
1301	Filament current		6.5	S3	If	17.5	22.5	mA
1306	Transconductance		6.5	S3	Sm	400	720	µmhos
1266	Total grid current (2)	Ec1 = -2.5 Vdc; Ec2 = Eb = 67.5 Vdc	6.5	S3	Ic1	0	-0.1	µAdc
1341	Power output (1)	Esig = 0.9 Vac; Rg1 = 5.0 Meg; Rp = 0.2 Meg	6.5	S3	Po	6.3	---	mW
2126	Glass strain		4.0	I	---	---	---	---
1211	Insulation of electrodes		4.0	S3	R	10	---	Meg
1119	Glass to lead seal strain		---	---	---	---	---	---
1105	Permanence of marking		---	---	---	---	---	---
	Quality conformance inspection, part 3							
1501	Intermittent life	Group A; Rg1 = 0.1 Meg min	---	---	---	---	---	---
---	Life-test end point (intermittent) (500 hours)	Power output (1)	---	---	Po	4.5	---	mW

NOTES:

1. Do not use series filament circuits.
2. See "Reduced pressure (altitude) rating," and altitude, maximum peak voltage.
3. This test is to be performed at the conclusion of the holding period.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:34Z
Check the source to verify that this is the current version before use.

Custodians:
Army - EL
Navy - EC
Air Force - 11

Review activities:
Army - EL
Navy - EC
Air Force - 11, 85
DSA - ES

User activities:
Army - ME
Navy - AS, OS, MC, CG
Air Force - 19

Preparing activity
Navy - EC

(Project 5960-2223-19)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:34Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:34Z
Check the source to verify that this is the current version before use.