MIL-E-1/767B
7 October 1968
SUPERSEDING
MIL-E-1/767A
22 April 1959

MILITARY SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

TYPE 6C6 1/ (B)

The complete requirements for procuring the electron tube described herein shall consist of this document and the latest issue of Specification MIL-E-1.

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

DESCRIPTION: Pentode, RF sharp cutoff

Outline	---	12-2 (EIA) (B)
Base	---	A6-7
Cap	---	C1-1, small
Envelope	---	ST-12
Cathode	---	Coated unipotential

Base connections:

Pin No.	---	1	2	3	4	5	6	Cap
Element	---	h	p	g2	g3	k	h	g1

ABSOLUTE-MAXIMUM RATINGS:

Parameter:	Ef	Eb	Ec1	Ec2	Ec3	Pg2	Pp	Ehk	Alt
Unit:	V	Vdc	Vdc	Vdc	Vdc	W	W	v	ft
Maximum:	6.9	330	---	140	0	0.11	0.8	100	10,000
Minimum:	5.7	---	---	---	---	---	---	---	---
TEST CONDITIONS:	6.3	250	-3	100	0	---	---	---	---

GENERAL:

Qualification - Not required

1/ Formerly JAN-6C6 (57)
(see note 2)

(B) denotes changes

Source: https://assist.dla.mil -- Downloaded: 202610-15T13:37Z
Check the source to verify that this is the current version before use.

METHOD	REQUIREMENT OR TEST	CONDITIONS	AQL (PERCENT DEFECTIVE)	INSPECTION LEVEL OR CODE	SYMBOL	LIMITS MIN	LIMITS MAX	UNIT
	Quality conformance inspection, part 1							
1266	Total grid current	See note 1	0.65	II	Ic1	0	-0.5	µAdc
1231	Emission	Eb = Ec1 = Ec2 = Ec3 = 30 Vdc (see note 1)	0.65	II	Is	45	---	mAdc
1256	Electrode current (1) (anode)		0.65	II	Ib	1.3	2.9	mAdc
1306	Transconductance		0.65	II	Sm	1,000	1,450	µmhos
1201	Short and discontinuity detection		0.4	II	---	---	---	---
	Quality conformance inspection, part 2							
1031	Low-frequency vibration	Rp = 10,000 ohms	6.5	S3	Ep	---	200	mAdc
1301	Heater current		6.5	S3	If	275	325	mA
(B) 1336	Heater-cathode leakage		6.5	S3	Ihk	---	20	µAdc
1256	Electrode current (2) (anode)	Ec1 = -8.0 Vdc	6.5	S3	Ib	0	25	µAdc
1256	Electrode current (screen)		6.5	S3	Ic2	0.2	1.0	mAdc
1331	Direct-interelectrode capacitance	Shield No. 310 Without shield Without shield	6.5	S3	Cgp Cin Cout	--- 4.0 4.6	0.007 6.0 8.4	pF pF pF
1101	Secureness of base, cap, or insert		6.5	S3	---	---	---	---
(B) 1111	Base pin solder depth	See note 3	6.5	S3	---	---	---	---
(B) 1211	Insulation of electrodes		4.0	S3	R	10	---	Meg
(B) 1105	Permanence of marking		---	---	---	---	---	---
	Quality conformance inspection, part 3							
1501	Intermittent life	Group A; Ehk = 100 V	---	---	---	---	---	---
---	Life-test end point (intermittent) (500 hours)	Transconductance	---	---	Sm	825	---	µmhos

NOTES:

1. This test to be performed at the conclusion of the holding period.
2. Tube type 57 is hereby deleted from this tube specification sheet. There is no known substitute for this tube type.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:37Z
Check the source to verify that this is the current version before use.

NOTES: -Continued

3. Applies to flexible leads as well as rigid leads.

Custodians:
Army - EL
Navy - EC
Air Force - 11

Review activities:
Army - EL, MU
Navy - SH
Air Force - 11, 85
DSA - ES

User activities:
Army - ME
Navy - AS, OS, MC, CG
Air Force - 19

Preparing activity:
Navy - EC

(Project 5960-2211-31)

☆ U. S. GOVERNMENT PRINTING OFFICE: 1968-341-512/A-2008

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:37Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:37Z
Check the source to verify that this is the current version before use.