A-A-342A
January 8, 1980
SUPERSEDING
A-A-342
June 12, 1979

COMMERCIAL ITEM DESCRIPTION

ADHESIVE, SEMI-SOLID, STICK FORM, WITH DISPENSERS

The General Services Administration has authorized the use of this commercial item description in lieu of Interim Federal Specification MMM-A-002015.

Salient characteristics:

The adhesive shall be a nontoxic, mold resistant, even-spreading material housed in an impact-resistant container with a cap. It shall have a pleasant odor and a smooth, uniform consistency. It shall be hard enough to prevent an excessive use rate and adhesive buildup which interferes with closure of the container, but not so hard as to prevent easy application. The cap and container shall not react with the adhesive and shall provide vapor-tight storage. The container shall have a mechanism which allows the adhesive stick to be mechanically advanced or retracted without contacting the adhesive.

Nonvolatile content. The adhesive shall have a minimum nonvolatile content of 40 percent when tested by the following procedure: Heat a 20-g sample at 105° C for 6 hours, cool in a desiccator, and weigh. Continue heating and weighing procedure, using a 30-minute heating period, until the weight remains constant.

Adhesion. Fibers of the paper shall remain embedded in the adhesive when bonded papers are separated 20 minutes and 24 hours after adhesive application. The two papers shall be joined using finger pressure for 10 seconds.

Freeze-thaw. The adhesive shall be stable to three freeze-thaw cycles. A cycle shall consist of cooling the adhesive to -29° C for 18 hours followed by 23° C for 6 hours.

Workmanship. The adhesive shall not discolor paper or photographs nor cause wrinkling, shrinking, or curling of the substrate to which it is applied.

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices and is the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Recovered materials. The manufacturer shall utilize recovered materials to the maximum extent practicable.

Packaging, packing, and marking. The adhesive sticks shall be packaged in accordance with normal commercial practice and packed in fiberboard boxes that will assure acceptance by common carrier and provide product protection against loss and damage during multiple shipments, handling, and storage. The shipping container shall be in compliance with National Motor Freight Classification or Uniform Freight Classification. Marking shall be as specified in the contract or order.

FSC 8030

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:07Z
Check the source to verify that this is the current version before use.