MILITARY SPECIFICATION

INDICATOR, RATE OF FLOW, FUEL, TOTALIZING 0-100,000 PPH, TYPE MA-8

This amendment forms a part of Military Specification MIL-I-25325A(USAF) dated 6 July 1961.

Page 2, paragraph 3.1: Delete and substitute:

"3.1 Preproduction. This specification makes provisions for preproduction testing."

Page 5, paragraphs 4.1 and 4.2: Delete and substitute:

"4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

"4.2 General specification. The inspection and testing of indicators shall be in accordance with MIL-I-7566 and as specified herein. For the purpose of this specification, the qualification tests in MIL-I-7566 shall be considered preproduction tests."

Page 8, paragraph 6.2, c and d: Delete and substitute:

"c. Levels of packaging and packing required and reinspection date markings."

Page 8, paragraph 6.3: Delete.

Page 9, notice paragraph: Delete.

Custodian:
Air Force - 11

Preparing activity:
Air Force - 11

FSC 6620

Source: https://assist.dla.mil -- Downloaded: 202640-20T04:22Z
Check the source to verify that this is the currentversion before use.