MILITARY SPECIFICATION
MANUAL, TECHNICAL: INTERMEDIATE MAINTENANCE INSTRUCTIONS
(Airborn Equipment)

This amendment forms a part of Military Specification MIL-M-25393A (USAF) dated 1 July 1969.

Page 4, Paragraph 3.8.3.1: Add new paragraph 3.8.3.1 as follows:

"3.8.3.1. Storage Inspection. For armament equipment, (Racks, Launchers, etc.), "Ready" and "Extended Storage" categories of inspection shall be explained and storage and maintenance requirements shall be provided. As a minimum, maintenance and inspection criteria shall be provided in chart form (See Figure 1) and the following text shall be included in Section V:

"5 - STORAGE INSPECTION. Different degrees of inspection are required based upon the type of storage:

a. Ready Storage: Equipment maintained in a completely ready status in anticipation of a relatively near term use requirement. This equipment may be positioned on the shelf, held in the shop, or may be installed in the next higher assembly or installation. The item may be pre-loaded with munitions and maintained in a munitions holding area or munitions storage igloo in preparation for installation on the aircraft. Equipment will be provided adequate protection from damage and the elements. Examples of ready storage would be DD 780 equipment receiving frequent use, and mobility contingency, or bare base assets requiring a high degree of readiness for immediate employment.

(1) Inspection Criteria: Inspection interval for items in this manual, placed in ready storage will be that deemed necessary by the IM/SM to assure serviceability in "ready-to-use" condition. For weapons release equipment the inspection frequency on items in ready storage will be a minimum of every eighteen months.

(2) Refer to table 5-X for Ready Storage Inspection and Maintenance Requirements.

b. Extended Storage: These items maintained in a ready condition for which a far-term-utilization requirement exists but for which no requirement exists for frequent exercises or immediate short term employment. Equipment placed in extended storage will be in a serviceable, ready to use condition. This category includes WRM assets.

(1) Inspection Criteria: An annual sampling inspection will be performed of 10 percent of assets in extended storage. Items inspected will be identified marked to prevent redundant inspection of the same items during future annual inspections. Subsequent annual inspections will be performed on those items which have acquired the longest calendar year time period since

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T04:39Z
Check the source to verify that this is the current version before use.

last inspection. In the event that deterioration of equipment is detected during any annual inspection, a determination will be made whether an inspection of all assets having corresponding packaging dates must be performed. For field organizations this determination will be made either by the organizational commander or maintenance supervisor. For AFLC depot organizations, this determination will be made by the Supply Inspector.

(2) Refer to table 5-X for Extended Storage Inspection and Maintenance Requirements.

(3) Storage and Packaging: Equipment placed in extended storage will meet the following criteria:

(a) Equipment will be packaged in accordance with TO 00-85-3.

(b) Outer containers will be fabricated in accordance with figure ____ of this TO.

(c) Packaged equipment must be warehoused in a covered structure which will provide protection from climatic elements.

(d) Units which have been subjected to prior use must meet all criteria outlined in table 5-X prior to being placed in Extended Storage.

(e) Items received from depot or in base supply assets, meeting the packaging requirements specified in (a) above will be considered as being in Extended Storage.

Page 6; Add Figure 1 as shown on Page 3.

Custodian:

Air Force - 16

Reviewer:

Air Force 01, 10, 70, 71, 80, 82, 84

Preparing Activity:

Air Force - 16

Project No.

TMSS F399

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T04:39Z
Check the source to verify that this is the current version before use.

Table 5-X Inspection and Maintenance Criteria

	NOMENCLATURE	INSPECT FOR	REPAIR	READY STORAGE	EXTERNED STORAGE
1.	All externally mounted	a. Damage, cuts, breaks, chafed & insulation. Proper installation	Repair or Replace	X	X
		b. Inspect for presence of Pro-Seal 777 potting compound (not applicable to MER-10A, 10N TER-9A, 15) see para 4-14A.			
2.	MER/TER Adapter	a. Visually inspect hangar (Fig 6-1-40 6-3-33) for security of attachment damage cracks and breaks in areas of attaching holes. Visually inspect block assembly (Fig 6-1-4-3) for security of attachment damage cracks and breaks in areas of attaching holes. Close inspection must be performed in area of top mounting bolt.	If there is any doubt of service-ability perform NDI inspection in accordance with para 4-41B.		
		b. Ejector units, lugs, and all external components for security of attachment.	Repair & secure as required.		
		c. All external surfaces and external components for damage, rust and corrosion.	Clean, lubricate & repair as required.	X	X

Figure 1. Sample Inspection and Maintenance Criteria Chart

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T04:39Z
Check the source to verify that this is the current version before use.