MILITARY SPECIFICATION

MANUALS, TECHNICAL: OVERHAUL INSTRUCTIONS AND INTERMEDIATE MAINTENANCE INSTRUCTIONS (For Engines)

1. SCOPE.

1.1 *Coverage.* This specification prescribes requirements for preparation of two types of technical manuals; one covering overhaul, and one covering intermediate maintenance (refer to 6.2.1) of engines (aircraft and non-aircraft). Coverage includes, but is not limited to; reciprocating, gas turbine (including turbo-prop and turbo-shaft), and liquid propellant rocket engines. The type(s) of manual(s) to be prepared will be specified by the procuring activity. Requirements set forth herein are applicable to both types of manual unless otherwise specified.

1.1.1 *Overhaul instructions.* Overhaul instruction manuals shall contain information required by depot level personnel for complete major overhaul of engines for return to zero time condition.

1.1.2 *Intermediate maintenance instructions.* Intermediate maintenance instruction manuals shall contain information required for maintenance and repair of engines (uninstalled) at field/base level activities. These manuals cover types of maintenance commonly referred to as intermediate maintenance, field maintenance, jet engine base maintenance (JEBM), etc. Organizational maintenance on installed engines will normally be covered in the end item (e.g., aircraft) manuals.

2. APPLICABLE DOCUMENTS.

2.1 The following documents, of the issue in effect on the date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

Military

MIL-M-4410	Manuals, Technical: Title Page and List of Effective Pages; Certificate of Destruction Page; Transmittal Notice; Reproduction Assembly Sheet; Photolithographic Negatives; Printing; and Binders
MIL-M-38730	Manuals, Technical: General Requirements for Preparation of
MIL-M-38780	Manuals, Technical: Nondestructive Inspection
MIL-M-38784	Manuals, Technical: General Requirements for Preparation of
MIL-P-38790	Printing Production of Technical Manuals: General Requirements for

STANDARDS

Military

MIL-STD-838	Lubrication of Military Equipment

PUBLICATIONS

Air Force-Navy Aeronautical Bulletin No. 275 — Guide for the Use of Lubricants, Compounds, and Fluids in Aircraft

(Copies of documents required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS.

3.1 *General.* The general manner of preparation shall be in accordance with MIL-M-4410, MIL-M-38730, MIL-M-38784, and MIL-P-38790. Inclusion of only unclassified information in the manual is desired. In the event insertion of classified information is essential, the provisions of MIL-M-38784 shall apply. (Compliance with MIL-M-38730 and MIL-M-4410 is necessary only when a specific requirement is not covered in MIL-M-38784 and MIL-P-38790, respectively.)

3.1.1 *Text.* Sound engineering principles and techniques, available engineering analyses, service experience, performance data on similar items, and

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T04:39Z
Check the source to verify that this is the current version before use.

all other reliability and maintainability data available shall be used in the preparation of specific instructions. For gas turbine engines, procedures shall cover, both or either, horizontal and vertical engine maintenance, as specified by the procuring activity, and in consonance with special tooling available.

3.1.1.1 *Special processes.* The manual shall include information on any special procedures or processes required under extreme temperature and humidity conditions within the limits established by the design specification.

3.1.1.2 *Reference to components.* Reference to components shall be by standard nomenclature. The principal noun in names of items shall be consistent with the drawing and be the same throughout the manual. Reference to part numbers shall be held to a minimum.

3.1.1.3 *Reference to other manuals.* Both the intermediate maintenance and overhaul manuals shall be complete within themselves without excessive cross reference to one another. Reference shall be made to other manuals as appropriate to avoid duplication of procedures exceeding two pages. For general shop practices and techniques, reference shall be made, when applicable, to the general procedures manuals, such as; TO 2-1-111, 1-1A-8, etc. Small exerpts of data from other manuals may be included if specifically required for continuity of procedures, clarity of text, and job performance.

3.1.1.4 *Lubrication.* The requirements of MIL-STD-838 and ANA Bulletin No. 275 are applicable.

3.1.2 *Illustrations and diagrams.* The requirements of MIL-M-38784 are applicable.

3.1.2.1 *Procedural illustrations.* Essential illustrations depicting mechanical operations shall be included in pertinent sections as necessary. It is not necessary to illustrate each step of a procedure, such as; removal of screws with an ordinary screwdriver, lifting off a cover after the screws have been removed, etc. Illustrations should supplement the text by clarifying procedures which are of a special nature, or are not obvious.

3.1.2.2 *Exploded views.* Exploded views shall be used for reference in disassembly and assembly instructions. Index numbers and a nomenclature list or legend, keyed to the index numbers, shall be used to identify each part. If the engine is of such a nature that it cannot be adequately illustrated by a single exploded view, separate subassembly exploded views shall be provided. In such cases, showing the complete engine exploded into its major subassemblies shall be shown first. Parts which attach and connect the major subassemblies together shall be shown on this illustration. These views and those in the illustrated parts breakdown shall be the same, with the sequence of key index numbers in the order of disassembly, insofar as practicable.

3.1.2.3 *Tool and test equipment illustrations.* Special (peculiar, uncommon) tools and test equipment shall be appropriately illustrated, either in use or by separate illustration, to convey recognition and how-to-use information. Standard tools and test equipment shall not be illustrated as such, nor shall self-evident or generally known uses be shown. Only uncommon or unusual uses, and connections for test purposes, need be illustrated in appropriate sections to avoid misunderstanding as to proper procedures. Unusual operations in checking fits, clearances, backlash, etc, shall be illustrated.

3.1.2.4 *Diagrams.* Diagrams of systems, such as fuel, oil, hydraulics, and internal wiring diagrams (schematics) shall be furnished when necessary and pertinent to the work described. Complex systems should be illustrated with schematics or block diagrams using tints, patterns, crosshatching, dots, colors, to the extent necessary for understanding of their operation by maintenance personnel.

3.2 *Arrangement.* Manuals shall be arranged in the following manner:

Front Matter

Section I	Introduction and General Information
Section II	Special Tools and Test Equipment
Section III	Dismantling and Disassembly
Section IV	Cleaning
Section V	Inspection, Repair and Replacement
Section VI	Assembly
Section VII	Accessories
Section VIII	Dimensional Limits and Torque Values
Section IX	Testing
Section X	Troubleshooting
Section XI	Preservation and Storage
Section XII	Propellant Characteristics and Safety Precautions (applicable to liquid propellant rocket engines only)
Section XIII	Afterburner Maintenance (or Overhaul) (applicable only to engines equipped with afterburners)
Section XIV	Difference Data Sheets (applicable to non-complex engines only)

Alphabetical Index

(When a section is not applicable, the section number of any applicable sections that follow, shall be moved up accordingly.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T04:39Z
Check the source to verify that this is the current version before use.

3.3 *Front matter.* Front matter shall consist of; title page, list of effective pages, table of contents, list of illustrations, and list of tables in accordance with the requirements of MIL-M-38784.

3.4 *Section I—Introduction and General Information.*

3.4.1 *Introduction.* The introduction shall be prepared in accordance with MIL-M-38784. It shall include any relevant information which may increase usability of the manual. Engines covered shall be identified by Government designation and manufacturer's type or model designation. For liquid propellant rocket engines, a caution shall be inserted directing attention to the provisions of Section XII prior to accomplishing maintenance action.

3.4.2 *General information.* General information to be used by maintenance personnel to further their understanding of the engine and its related systems shall be provided. A brief description shall reflect the engine's purpose and main features. A table of leading particulars shall be included. Appropriate illustrations or exploded views shall be provided. Information, such as; cylinder numbering system, compressor stages, combustion chamber arrangement, major sections, accessories, etc, shall be depicted. Each system of the engine, such as; fuel, lubrication, ignition, cooling, etc, shall be appropriately described, including illustrations (diagrams, schematics, etc), as necessary, to facilitate understanding. If the manual covers more than one model, significant differences shall be explained.

3.4.3 *Materials list.* A listing of consumable materials and expendable items required to accomplish intermediate maintenance or overhaul (dependent upon the type of manual) shall be provided when specified by the procuring activity. Nomenclature, material, specification number, Government Standard number, and item part number shall be given.

3.5 *Section II—Special Tools and Test Equipment.* This section shall list and illustrate the special tools and test equipment required for the work described. Overhaul manuals shall list all items required for complete major overhaul of the engine, whereas intermediate maintenance manuals shall list only those items required for intermediate (field level) maintenance. Items shall be selected from the list of Government approved tools and test equipment, if available; otherwise, the contractor's recommended tools and test equipment shall be shown. However, these recommendations shall be changed promptly, if necessary, to conform to the official Government list as soon as such information is available. Acceptable alternate tools and test equipment shall also be listed. Standard tools, such as screwdrivers, pliers, etc, shall not be listed; however, standard items of test equipment, such as voltmeters, oscilloscopes, etc, shall be listed, but not illustrated.

3.5.1 *Special tools and test equipment list.* Special tools and test equipment shall be listed in two formats. The list shall first be prepared as a "Functional tools list," followed by a "Numerical tools list." Tools shall be listed by part (tool) number and nomenclature which shall agree with the drawing. Test equipment shall be listed by type designator and nomenclature, using the AN type designation, if assigned, or the commercial or manufacturer's designation, if an AN type designator has not been assigned. If an alternate item can be used, it shall be listed and be so identified as an alternate. In the functional list, an alternate item shall be listed immediately following the item for which it is an alternate. In the numerical list, alternate items shall be listed numerically along with preferred items.

3.5.1.1 *Functional tools list.* In this list, tools and test equipment shall be arranged in functional groups based on the engine components or parts to which the tools are applicable. The groups shall be arranged in alphabetical order based upon the nomenclature of the component or part to which the tool group is applicable. Within each functional group, the tools and test equipment shall be listed in the order in which they are used within that group. The list shall be prepared in the following format.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T04:39Z
Check the source to verify that this is the current version before use.

FUNCTIONAL TOOLS LIST

Group Number	*Function Tool Nomenclature*	*Tool Number*	*Figure Number*	*Use and Application*
1	Accessory Case—Remove and install			
	Stand, Buildup	2809	2-37	Hold accessory case not mounted on engine
	Puller, Main driveshaft	21C3418	3-5	See para 3-27
2	Cylinder Assembly—Repair			
	Depressor, Valve spring	5276	3-16	See para 3-49 and 6-82
	Puller, Rocker shaft	287	3-17	See para 3-51

a. *Group number.* After the groups are listed in alphabetical sequence, a number shall be assigned to each. This becomes the tool group number which shall be in numerical sequence as listed.

b. *Function.* The tool group function is based on the nomenclature of the component or part to which the group applies. The function nomenclature shall be listed in alphabetical sequence and shall begin at the left margin of this column.

c. *Tool nomenclature.* Tools and test equipment shall be listed within each functional group in the order in which the tool is used. The nomenclature shall be listed indented approximately four characters in from the function title.

d. *Tool number.* The tool/test equipment part number or type designator shall be shown.

e. *Figure number.* This column shall reflect the number of the applicable illustration in which the tool/equipment is shown.

f. *Use and application.* The purpose of each item shall be stated. If use is described in the manual, reference to the applicable paragraph will suffice.

3.5.1.2 *Numerical tools list.* This list shall be a listing of all tools/test equipment in numerical sequence cross-referenced to the applicable group number. Tools shall be grouped and listed first, with the listing of test equipment following. The following format is recommended.

NUMERICAL TOOLS LIST

Tool Number	*Group Number*	*Tool Number*	*Group Number*	*Tool Number*	*Group Number*	*Tool Number*	*Group Number*

3.5.2 *Illustrations of special tools and test equipment.* Special tools and test equipment shall be illustrated in this section unless they are adequately illustrated in use in other sections of the manual.

3.5.3 *Tool and test equipment maintenance.* Required maintenance instructions for tools and test equipment, not covered in other manuals shall be included in this section. Instructions shall also be included for fabricating interconnecting cable assemblies, etc, required but not normally supplied with the equipment. Statements regarding local manufacture of tools must have prior approval of the procuring activity; then the manual shall refer to the applicable drawing(s) for fabrication instructions.

3.6 *Section III—Dismantling and Disassembly.*

3.6.1 *Dismantling.* This section shall contain procedures preliminary to inspection, repair, and replacement of engine parts specifically tailored to the level of repair to which the manual applies; i.e, the Intermediate Maintenance manual shall only provide coverage to the extent of repair authorized at intermediate (base) level; whereas the Overhaul manual shall contain complete disassembly instructions. Procedures shall include: removal of engine from shipping container, installation in stand, depreserving, and dismantling into major subassemblies.

3.6.2 *Disassembly.* Instructions shall be given for the disassembly of subassemblies into component parts. Special tools to be used, precautions to be observed, and critical dimensions, etc, to be recorded shall be prescribed.

3.7 *Section IV—Cleaning.* This section shall contain special cleaning instructions required. Existing manuals containing general cleaning methods and procedures shall be referenced. Specific instructions for various parts and subassemblies (i.e., bearings, valves, internal oil passages, etc) and

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T04:39Z
Check the source to verify that this is the current version before use.

cleaning methods (such as; special agents, ultrasonic, blowing out with compressed air, etc) shall be included. Precautions to be observed shall be listed. Cleaning instructions in connection with nondestructive inspection methods shall be included. Special tools, jigs, fixtures, etc, necessary during cleaning shall be indicated. Instructions relating to preservation of metal parts and surface treatment for accomplishment after cleaning, shall be provided.

3.8 *Section V—Inspection, Repair and Replacement.*

3.8.1 *Inspection.* Procedures shall include the required inspection methods, equipment and instructions for inspection of engine parts within the scope of the manual. Inspection instructions shall encompass; failures, wear, damage, corrosion, leakage, aging, burning, malfunctioning, deformation, and deterioration that can be expected to occur during service of the engine. Allowable service limits and adequate standards for determining when parts should be repaired or replaced shall be included.

3.8.1.1 Illustrations shall be used wherever necessary to augment inspection procedures. Accordingly, definitions, illustrations and limitations of descriptive terms, such as "scoring," "galling," etc, shall be included.

3.8.1.2 Procedures shall be included for performing special inspections required when the engine has operated beyond permissible limits, i.e., overspeed, sudden stoppage, etc.

3.8.1.3 Requirement for special inspection by nondestructive methods, such as; magnetic particle, ultrasonic, eddy-current, X-ray, liquid penetrant, etc, shall be specified. When such inspections are necessary, information required by that portion of MIL-M-38780 titled "Subsequent Sections" shall be provided.

3.8.2 *Repair and replacement.* Comprehensive instructions shall be provided for necessary repair and replacement operations to restore the engine to a completely satisfactory condition. Repair methods shall be specified for the correction of all deficiencies and conditions considered reparable within the scope of the level of maintenance to which the manual applies. Specific data shall be provided to adequately describe acceptable repairs, including material specifications for metals when pertinent to making repairs.

3.8.2.1 Application and operation of special tools and test equipment shall be described as they are required in repair and replacement operations.

3.8.2.2 Instructions shall specify use of approved corrosion-preventive compounds, neutralization, or other protection on parts and components.

3.8.3 *Table of limits.* A concise discussion shall be given of the Table of Limits as it applies to this section.

3.9 *Section VI—Assembly.*

3.9.1 *Assembly of subassemblies.* This section shall contain essential instructions for assembly of component parts into major subassemblies and final assembly of subassemblies to form a complete engine. Required corrosion-preventive action, special lubricants, gasket pastes, etc, shall be specified. Peculiar safetying methods and locking devices shall be emphasized. Methods for making checks for clearance, backlash, torque, etc, shall be described, and when necessary for clarity, illustrated. Appropriate tests for operation of a subassembly prior to final assembly shall be provided.

3.9.2 *Final engine assembly.* Instructions shall be given for final assembly of subassemblies and major sections to form a complete engine prior to performance test. Step-by-step procedures to check, align and adjust each assembly or subassembly shall be included.

3.10 *Section VII—Accessories.*

3.10.1 *Accessories minor repair—intermediate maintenance manuals.* This section shall contain step-by-step procedures for removing and installing individual engine accessories from an assembled basic engine; and provide instructions for inspections, adjustment, troubleshooting and minor repair. For complex accessories having separate manuals covering maintenance, suitable reference shall be made to applicable accessory publication numbers. This shall be done in tabular form, cross-referencing part number and nomenclature to publication number. Duplication of text contained in accessory manuals shall be kept to a minimum.

3.10.2 *Accessories overhaul—overhaul manuals.* This section shall contain complete instructions for overhauling those simple accessories installed on and considered a part of an engine, for which separate overhaul instructions are not available.

3.10.2.1 Separate overhaul instruction manuals are normally procured for major accessories. Suitable reference shall be made to applicable accessory publication numbers. This shall be done in tabular form, cross-referencing part number and nomenclature to publication number.

3.10.2.2 When it is necessary to provide data, because there is no separate manual, each accessory shall be treated as a separate entity and complete instructions shall be provided for disassembly, special cleaning, inspection, repair, assembly, and test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T04:39Z
Check the source to verify that this is the current version before use.

3.11 *Section VIII—Dimensional Limits and Torque Values.* This section shall contain dimensional limit and torque value information. It shall consist of introductory material, table(s) of limits, and chart(s) showing the limit points. The introductory material shall include definitions of unusual terms and abbreviations, including pinch fit, direction measured, etc.

3.11.1 *Dimensional limits table.* The table(s) of dimensional limits shall include all clearances, backlashes, endplays, spring pressures, torques, etc, arranged in numerical sequence by reference number. Reference numbers shall be so assigned that a numerical sequence of them will place the limits for particular areas of the engine, or for subassemblies, into groups. Limits contained in the table of limits shall not be stated in the text of other sections. The table(s) shall be cross-referenced to the chart on which the reference number is located. The table(s) shall be arranged as follows:

Reference Number	*Chart Number*	*Description*	*Minimum*	*Maximum*

3.11.2 *Reference charts.* The table of limits shall be supported by illustrations (charts) to show clearly all points of limits. Illustrations shall not show limit values but only reference numbers with leaders to the point of clearance.

3.11.3 *Torque values.* Special torque values for bolts, screws, studs, tubing and hose connectors, etc, shall be presented as a specific value according to individual application. Torque values (particularly internal application) may be included in the same table and reflected on the same chart with other limit points. Torque values for external application should normally be reflected on separate chart(s)/table(s).

3.12 *Section IX—Testing.*

3.12.1 *Final engine test.* This section shall contain instructions for conducting tests of the complete engine repaired/overhauled within the scope of the manual. Test data pertaining to specific testing conditions, test set up and operating procedures of applicable Aerospace Ground Equipment (AGE) shall be included. This section shall include the following:

a. Safety precautions.
b. Preparation for test.
c. Instrumentation requirements.
d. Engine static test and motoring procedures.
e. Engine starting, operating, and shutdown procedures.
f. Operating limits.
g. Level of testing following specific repairs.
h. Engine functional test and performance evaluation.
i. Test schedule.
j. Penalty schedule.
k. Fluid and electrical supply requirements.
l. Drainage requirements.
m. Preservation requirements.

3.12.1.1 If an item, such as a mobile engine test stand, has been provided for testing the engine, this section shall provide instructions for installation of the engine in the test stand.

3.12.1.2 Allowable engine performance data corrected to standard day atmospheric conditions shall be included. Performance evaluation charts or curves shall be provided. Correction charts shall be included to show correction factors for performance evaluation.

3.12.1.3 *Engine condition indication base line* (Refer to 6.3). If engine performance is to be evaluated through use of Aircraft Integrated Data System (AIDS), provisions shall be included for compilation of data and establishment of the engine condition indication base line. Data shall be presented in such a manner that diagnosis of mechanical or performance problems or trends toward potential problems may be evaluated through the use of AIDS. A copy of these data shall be maintained with the engine during maintenance for comparative use.

3.12.2 *Table of operating limits.* A table of operating limits shall be prepared with the following columnar arrangement:

OPERATING LIMITS

Item	*Limit*	*Remarks*

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T04:39Z
Check the source to verify that this is the current version before use.

3.12.3 *Test schedules and test procedures.* The sequence and method of accomplishing a functional test or performance evaluation of the engine shall be included. All checks and adjustments shall be described in detail with appropriate references to charts or curves. For performance evaluation, a test schedule shall be presented in tabular form.

3.12.4 *Penalty applications.* A table shall be included outlining the additional testing required for parts reinstalled or replaced following successful completion of a performance run. The table shall contain the following headings:

PENALTY APPLICATIONS

Part No.	Nomenclature	Reinstallation Test	Replacement Test	Remarks

3.12.4.1 A paragraph reading substantially as follows shall be inserted immediately following the Penalty Applications table:

> "Parts removed to gain access to other parts or areas shall invoke the same penalties, in accordance with the table of penalty applications, as parts removed to correct deficiencies and malfunctions. In event that more than one penalty is invoked, the most severe shall apply."

3.13 *Section X—Troubleshooting.* This section shall provide detailed instructions to determine, isolate, and remedy performance difficulties on the engine and engine systems. These instructions shall contain special techniques, methods, limits, and instrumentation requirements, as necessary, for effective troubleshooting. Instructions shall also be provided for locating and identifying malfunctions caused through interaction of integrated systems. A statement covering probable causes and an outline of definite procedures for correction shall be included. Procedures shall cover not only troubles most likely to occur, but also those of more infrequent and complex nature. Obvious remedies shall be omitted. When complete corrective action is too long to be stated briefly, appropriate reference shall be made to other paragraphs. A columnar or tabular arrangement of this information is preferred, which may be supplemented by test point schematics or block diagrams. For example, under a given trouble, column headings "Probable Cause" and "Correction" may be used. Information shall be arranged in the order of most likely occurrence. The sequence of steps required to detach or remove a component or unit shall be referenced when such removal is required.

3.13.1 *Engine condition indication* (Refer to 6.3). Provisions shall be presented in such a manner that diagnosis of mechanical or performance problems or trends toward potential problems may be evaluated through use of the engine portion of the Aircraft Integrated Data System (AIDS). Diagnostic provisions shall be included for each parameter measured by engine AIDS, including the method for a check of the engine base line performance condition indication.

3.14 *Section XI—Preservation and Storage.*

3.14.1 *Overhaul manuals.* This section shall include instructions for preserving the engine and preparation for storage. Reference shall be made, as required, to other applicable publications for information on specific procedures for preparation for storage. In addition, this section shall give the overall dimensions and weight of the shipping and storage container with engine packed for shipment. Information shall be provided for the prevention, recognition, and elimination of engine corrosion. Specific instructions shall be provided for the engine and equipment concerned and shall not duplicate information provided in general series manuals, which will be referenced as applicable.

3.14.2 *Intermediate maintenance manuals.* This section shall include instructions required for corrosion control and temporary storage of engines at field level.

3.15 *Section XII—Propellant Characteristics and Safety Precautions.* This section is applicable only to liquid propellant engines and will be omitted from manuals pertaining to other types of engines.

3.15.1 This section shall contain all essential information concerning propellants that may be used in the engine. Physical characteristics of each propellant that may be used shall be given, with emphasis on those characteristics which serve as identifying or distinguishing points.

3.15.2 All necessary safety precautions that must be observed in handling and using propellants, covering such items as clothing, fire contamination, containers, cleaning, passivating, etc. shall be given. Any danger signals shown by the propellant shall be explained fully and complete instructions given as to proper steps to take and avoid mishap. First

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T04:39Z
Check the source to verify that this is the current version before use.

aid action to be taken, in event of accident in handling propellants and oxidizers, shall be given.

3.16 *Section XIII—Afterburner Maintenance (or Overhaul).* (This section is applicable only to engines equipped with afterburners and will be omitted from manuals pertaining to other types of engines.) This section shall contain essential instructions for removal, installation, inspection, adjustment, and repair of afterburners. Extent of coverage, as well as section title, shall be commensurate with the type of manual, i.e., intermediate, maintenance or overhaul, being prepared.

3.17 *Section XIV—Difference Data Sheets.* For non-complex engines, Difference Data Sheets may be used, if required, to provide information on additional models of engines which constitute minor changes from the original design. These shall be the last section of the manual. Separate Difference Data Sheet(s) shall be prepared for each additional model.

3.17.1 *Format.* Requirements of MIL-M-38730 are applicable. Difference Data Sheet(s) for each model shall start on a right hand page. Page numbers shall run consecutively throughout the section. Pages shall be added as they are issued.

3.17.2 *Content.* Difference Data Sheets shall specify in the briefest practical form how maintenance or overhaul procedures for that model differ from the procedures for the representative model(s) contained in the preceding sections. Sheets shall contain the following data, as appropriate, on one or two pages, and shall not exceed four pages.

a. An external view of the model if it is significantly different from the one shown in Section I.

b. A table of leading particulars if the particulars are significantly different from those contained in Section I.

c. Illustrations which are essential for clarifying differences. Illustrations in preceding sections shall not be duplicated, but may be referenced if necessary. Reference shall not be made to illustrations on other Difference Data Sheets.

d. Brief coverage of subjects specified for the original model. The title of each of the preceding sections shall be listed in the same order of arrangement as in the manual. Appropriate statements shall be used to convey the similarity or explain the difference in procedures. Sentences shall be in short telegraphic style.

3.18 *Alphabetical Index.* When a manual exceeds 100 pages, an alphabetical index, prepared in accordance with MIL-M-38784, shall follow the last section of the manual.

4. QUALITY ASSURANCE PROVISIONS.

4.1 Quality assurance provisions shall be in accordance with MIL-M-38784 and MIL-P-38790.

5. PREPARATION FOR DELIVERY.

5.1 Packaging, packing, and marking for shipment shall be in accordance with MIL-M-38784 and MIL-P-38790.

6. NOTES.

6.1 *Intended use.* Manuals prepared in accordance with this specification are intended for use by maintenance personnel in accomplishing intermediate (field) level repair and overhaul of engines.

6.2 *Definitions.* The following definition is applicable to this specification.

6.2.1 *Intermediate maintenance.* The term "Intermediate Maintenance" is that maintenance which is the responsibility of, and performed by, designated maintenance activities for direct support of using organizations. Intermediate maintenance phases normally consist of calibration, repair or replacement of damaged or unserviceable parts, components, or assemblies. Intermediate maintenance is normally accomplished in fixed or mobile shops.

6.3 *Aircraft Integrated Data System (AIDS) requirement.* If use of Aircraft Integrated Data System is not required under the provisions of the contract, requirements for data relative thereto as set forth herein shall not apply.

6.4 *Ordering data.* Procurement documents should specify:

a. Title, number, and date of this specification.
b. Whether an overhaul manual is to be prepared (1.1).
c. Whether an intermediate maintenance manual is to be prepared (1.1).
d. Whether horizontal or vertical, or both, engine maintenance is required (3.1.1).
e. Whether a materials list is required (3.4.3).
f. Whether Aircraft Integrated Data System (AIDS) is applicable (6.3).

6.5 *Supersession data.* This specification supersedes the following: MIL-H-4884(USAF) dated 21 October 1954; MIL-H-5469A dated 15 January 1954; MIL-H-7985 dated 5 November 1952; and MIL-H-25396(USAF) dated 19 September 1955.

Custodian:
Air Force-16

Preparing Activity:
Air Force-16

Review Activities:
Air Force-01, 10, 11, 70, 71, 80, 82, 84

Project TMSS-F316

☆ U. S. GOVERNMENT PRINTING OFFICE: 1969-341-519/A-6233

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T04:39Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE AIR FORCE

UNITED STATES AIR FORCE
OFFICIAL BUSINESS

AFLC (MCMCP)
WRIGHT-PATTERSON AFB, OHIO 45433

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T04:39Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426 REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

AFLC-WPAFB-OCT 67 2M

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T04:39Z
Check the source to verify that this is the current version before use.