INCH-POUND

MS17343G
w/AMENDMENT 1
10 April 2024
SUPERSEDING
MS17343G
16 January 2013

MILITARY SPECIFICATION SHEET

CONNECTOR, RECEPTACLE, ELECTRICAL, WALL MOUNTING

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-22992.




FIGURE 1. Dimensions and configuration.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:07Z
Check the source to verify that this is the current version before use.




FIGURE 1. Dimensions and configuration - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:07Z
Check the source to verify that this is the current version before use.

Shell size	A Thread (plated) class 2A	D dia + .005 - .010	K + .005 - .020	L ± .020
12	0.8750-0.1P-0.2L-DS	.567	.938	.640
14	1.0000-0.1P-0.2L-DS	.692	.938	.640
16	1.1250-0.1P-0.2L-DS	.817	.938	.640
18	1.2500-0.1P-0.2L-DS	.942	.953	.625
20	1.3750-0.1P-0.2L-DS	1.068	.953	.625
22	1.5000-0.1P-0.2L-DS	1.192	.953	.625
24	1.7500-0.1P-0.2L-DS	1.317	1.047	.594
28	2.0000-0.1P-0.2L-DS	1.536	1.047	.594
32	2.2500-0.1P-0.2L-DS	1.786	1.111	.530
36	2.5000-0.1P-0.2L-DS	2.005	1.111	.530
40	2.7500-0.1P-0.2L-DS	2.255	1.111	.703
44	3.0000-0.1P-0.2L-DS	2.545	1.109	.703

Shell size	M + .010 - .000	Q max	QQ max	R (TP)	S + .021 - .020	T ± .005
12	.797	1.040	---	.906	1.188	.150
14	.797	1.040	1.590	.969	1.281	.150
16	.797	1.040	1.590	1.062	1.375	.150
18	.797	1.025	1.575	1.156	1.500	.177
20	.797	1.025	1.575	1.250	1.625	.177
22	.797	1.025	1.575	1.375	1.750	.177
24	.859	.931	1.481	1.562	2.000	.177
28	.859	.931	1.481	1.750	2.250	.177
32	.922	.867	1.417	1.938	2.500	.209
36	.922	.867	1.417	2.188	2.750	.209
40	.922	.867	1.417	2.375	3.000	.209
44	.922	NA	NA	2.625	3.250	.209

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:07Z
Check the source to verify that this is the current version before use.

FIGURE 1. Dimensions and configuration - Continued.

Shell size	V Thread (plated) class 2A LH	EE dia +.001 -.007	YY dia +.010 -.006	AAA	BBB
12	.7500-20 UNEF	.672	.647	.126 -.001, +.007	.063 -.001, +.007
14	.8750-20 UNEF	.797	.772		
16	1.0000-20 UNEF	.922	.897	.182 -.001, +.010	.108 -.001, +.010
18	1.1250-18 NEF	1.040	1.022		
20	1.2500-18 NEF	1.164	1.148		
22	1.3750-18 NEF	1.289	1.272		
24	1.6250-18 NEF	1.539	1.473	.260 -.001, +.010	.155 -.001, +.010
28	1.8750-16 UN	1.780	1.692		
32	2.0625-16 N	1.967	1.942		
36	2.3125-16 N	2.217	2.161		
40	2.6250-16 UN	2.530	2.411		
44	2.8750-16 UN	2.780	2.692		

FIGURE 1. Dimensions and configuration - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:07Z
Check the source to verify that this is the current version before use.

Shell size	CCC	DDD Socket insert location ± .030	EEE Pin insert location ± .030	Z max (see note 7)	Z min (size 0 contacts only)
12	.0035	.020	.729	.726	NA
14					
16	.007				
18				.711	
20					.780
22					
24				.617	.686
28					
32				.553	.622
36					
40					
44		.039	.744	.797	

FIGURE 1. Dimensions and configuration - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:07Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm	Inches	mm	Inches	mm	Inches	mm
.001	0.03	.622	15.80	.969	24.61	1.500	38.10	2.3125	58.74
.0035	0.089	.625	15.86	1.000	25.40	1.536	39.01	2.375	60.33
.005	0.13	.640	16.26	1.022	25.96	1.539	39.09	2.411	61.24
.006	0.15	.647	16.43	1.025	26.04	1.562	39.67	2.375	60.33
.007	0.18	.672	17.07	1.040	25.42	1.575	40.01	2.500	63.50
.010	0.25	.686	17.42	1.047	26.59	1.590	40.39	2.530	64.25
.020	0.51	.692	17.58	1.062	26.97	1.625	41.28	2.625	66.68
.021	0.53	.703	17.86	1.068	27.13	1.692	42.98	2.692	68.38
.030	0.76	.711	18.06	1.109	28.17	1.750	44.45	2.750	69.85
.031	0.79	.726	18.44	1.111	28.22	1.786	45.36	2.780	70.61
.039	0.99	.729	18.52	1.125	28.60	1.875	47.62	2.8750	73.020
.062	1.57	.750	19.05	1.148	29.16	1.938	49.23	3.000	76.20
.063	1.60	.764	19.40	1.156	29.36	1.942	49.33	3.125	79.38
.108	2.74	.772	19.61	1.164	39.57	1.967	49.96	3.250	82.55
.126	3.20	.780	19.81	1.188	30.18	2.000	50.80		
.141	3.58	.797	20.24	1.192	31.28	2.005	50.93		
.150	3.81	.817	20.75	1.250	31.75	2.0625	52.40		
.155	3.94	.859	21.82	1.272	32.31	2.161	54.89		
.177	4.50	.867	22.02	1.281	32.54	2.1885	55.60		
.182	4.62	.875	22.22	1.289	32.74	2.217	56.31		
.209	5.31	.897	22.78	1.317	33.45	2.250	57.15		
.260	6.60	.906	23.01	1.375	34.92	2.255	57.28		
.530	13.46	.922	23.42	1.375	34.93				
.553	14.06	.931	23.65	1.417	35.99				
.567	14.40	.938	23.83	1.473	37.41				
.594	15.09	.942	23.93	1.481	37.62				
.617	15.67	.953	24.21						

NOTES:

1. All dimensions are in inches.
2. Unless otherwise specified, tolerances are ± .016 inch (0.41 mm).
3. Metric equivalents are given for information only.
4. Maximum termination of grommet extension for sizes 12 and 16 contacts for class J.
5. Maximum termination of grommet extension for sizes 0, 4, and 8 contacts for class J.
6. Dimensions shall be maintained when inserts are pressed firmly against indicated shoulder.
7. For size 0 contacts only: Increase Z dimension by .312 inch (7.92 mm) for shell sizes 12 through 40, and increase Z dimension by .062 inch (1.57 mm) for shell size 44.


Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:07Z
Check the source to verify that this is the current version before use.

FIGURE 1. Dimensions and configuration - Continued.

REQUIREMENTS:

Design and construction: See figure 1.
Mates with plugs shown on MS17344 and covers shown on MS17349.
Class shall be designated by the letter C (pressurized), J (pressurized with grommet) or R (environmental resisting).
For shell size, insert arrangement, alternate position, contact size, spacing and service rating, see MIL-STD-1651.
Shell finish: See MIL-DTL-22992.

Part or Identifying Number (PIN) example:



Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:07Z
Check the source to verify that this is the current version before use.

Referenced documents. In addition to MIL-DTL-22992, this document references the following:

MS17344
MS17349
MIL-STD-1651

CONCLUDING MATERIAL

Custodians:
Army – CR
Navy – YD
Air Force – 85
DLA – CC

Preparing activity:
DLA – CC

Review activities:
Army – AR, MI
Navy – AS, CG, MC, OS, SH
Air Force – 19
NASA – NA

(Project 5935-2024-119)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:07Z
Check the source to verify that this is the current version before use.