


FED. SUP CLASS
2610





L PLAT TLR
REGULAR
(TYPICAL)(1)



EARTHMOVER
REGULAR
(TYPICAL)



EARTHMOVER
DIRECTIONAL TRACTION
(DIR TRTN)
(TYPICAL)



GRADER
RIBBED
(TYPICAL)

NOTES:

1. THE "TYPICAL" TREAD PATTERNS DEPICTED ARE SELECTED FROM THOSE PATTERNS COMMERCIALLY AVAILABLE. THEY ARE FOR ILLUSTRATIVE PURPOSES ONLY AND ARE NOT TO BE CONSTRUED AS REPRESENTING A SPECIFIC CONFIGURATION OR ANY PARTICULAR MANUFACTURER.
2. "TYPE CLASSIFICATIONS", AS FOLLOWS, ARE DEFINITIVE ONLY AND SHOULD NOT BE INTERPRETED AS LIMITING APPLICATION OF THE TIRE.

L PLAT TLR	LOW PLATFORM TRAILER
EARTHMOVER	EARTHMOVER
GRADER FB	ROAD GRADER FOR USE ON FLAT BASE RIM
GRADER DC	ROAD GRADER FOR USE ON DROP CENTER OR SEMI DROP CENTER RIM
AMPHIB VEH	AMPHIBIOUS VEHICLE

3. RATED LOADS ARE BASED ON SPEEDS OF 20 MILES PER HOUR MAXIMUM FOR L PLAT TLR TIRES, 30 MILES PER HOUR MAXIMUM FOR EARTHMOVER TIRES, AND 25 MILES PER HOUR MAXIMUM FOR GRADER FB AND GRADER DC TIRES.
4. THE "TUBE USED, MS DASH NO." REFERS TO MILITARY STANDARD MS 35392, INNER TUBE, PNEUMATIC TIRE.
5. THE "MEASURING RIM" IS THE "STANDARD RIM" OR "PREFERRED RIM" DESIGNATED IN THE TIRE AND RIM ASSOCIATION, INC. YEARBOOK.
6. "TIRE SECTION" IS THE WIDTH OF A NEW TIRE, INCLUDING NORMAL GROWTH DUE TO INFLATION AND INCLUDING NORMAL SIDEWALLS, BUT NOT INCLUDING PROTECTIVE SIDE RIBS, BARS, AND DECORATIONS.
7. MAXIMUM OVERALL TIRE WIDTHS MAY EXCEED MAXIMUM NEW TIRE SECTIONS BY 8% TO PROVIDE FOR PROTECTIVE SIDE RIBS OR BARS, AND FOR THE TIRE GROWTH.
8. DIMENSIONS SHOWN ARE IN INCHES AND ARE APPROXIMATE ONLY. THEY ARE NOT TO BE USED FOR INSPECTION PURPOSES.
9. EXCEPT AS SPECIFIED HEREIN, ALL TIRES MUST CONFORM TO THE INDICATED PROCUREMENT SPECIFICATION EVEN THOUGH THE PARTICULAR TIRE MAY NOT BE SHOWN THEREIN. PROCUREMENT OF MILITARY TYPE TIRES SHALL BE IN ACCORDANCE WITH MIL-T-46729 EXCEPT WHEN SMALL QUANTITIES ARE REQUIRED, PROCUREMENT SHALL BE IN ACCORDANCE WITH MIL-T-12459. DETERMINATION OF THE SPECIFICATION TO BE USED SHALL BE THE RESPONSIBILITY OF THE PROCURING ACTIVITY.
10. THE TIRE PART NUMBER CONSISTS OF THE MILITARY STANDARD NUMBER AND THE MS DASH NUMBER. EXAMPLE: MS 35390-1.
11. FOR LIMITED STANDARD ITEMS REQUIRED TO SUPPORT IN-SERVICE MATERIEL, REFER TO PAGE 6.
12. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.
13. FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER THE PROCUREMENT DOCUMENTS REFERENCED HEREIN.

(E)
CANCELLED AFTER 5 JANUARY 1973
USE THE LATEST PROCUREMENT SPECIFICATION

REVIEW ACTIVITY: ARMY-ME

APPROVED 28 DECEMBER 1955 REVISED (E) 5 JANUARY 1973

This military standard is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A. ARMY-AT Other Cust NAVY-YD AF-84	TITLE TIRE, PNEUMATIC: LOW PLATFORM TRAILER, EARTHMOVER, GRADER, AND AMPHIBIOUS VEHICLE	MILITARY STANDARD MS 35390
PROCUREMENT SPECIFICATION ZZ-T-1083 & SEE NOTE 9	SUPERSEDES:	SHEET 1 OF 6

DD FORM 1 SEP 67 672-1 (Coordinated)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 202610-23T17:22Z
Check the source to verify that this is the current version before use.

SIZE DESIGNATION	7.50-15	7.50-15	8.25-15	8.25-15	9.00-15
PLY RATING	10	12	12	14	12
TYPE CLASSIFICATION (2)	L PLAT TLR	L PLAT TLR	L PLAT TLR	L PLAT TLR	L PLAT TLR
TREAD TYPE	REGULAR	REGULAR	REGULAR	REGULAR	REGULAR
CORD MATERIAL	NYLON	NYLON	NYLON	NYLON	NYLON
RATED LOAD, LBS. MAX. (3)	3310	3660	4060	4450	4680
INFLATION PRESSURE, PSI	80	95	85	100	80
TUBE USED, MS DASH NO. (4)	-22	-22	-23	-23	-24
MEASURING RIM (5)	6.0, 6.00S	6.0, 6.00S	6.5, 6.50T	6.5, 6.50T	7.0, 7.00T
TIRE SECTION, INCHES (6)	8.40	8.40	9.20	9.20	10.10
DIAMETER, INCHES (MAX)	31.98	31.98	33.54	33.54	35.30
APPROX. LOADED RADIUS	14.1	14.1	15.5	15.5	16.3
PROCUREMENT SPEC. (9)	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083
MS DASH NO. (10)	-48	-1	-49	-2	-3
FIIN	294-9455	294-4944	294-4799	294-4800	294-4801

SIZE DESIGNATION	10.00-15	10.00-15	11.00-15	11.00-15	10.00-20
PLY RATING	14	14	16	16	12
TYPE CLASSIFICATION (2)	L PLAT TLR	L PLAT TLR	L PLAT TLR	L PLAT TLR	EARTHMOVER
TREAD TYPE	REGULAR	REGULAR	REGULAR	REGULAR	REGULAR
CORD MATERIAL	NYLON	NYLON	NYLON	NYLON	NYLON
RATED LOAD, LBS. MAX. (3)	5480	5480	6680	6680	4780
INFLATION PRESSURE, PSI	85	85	100	100	60
TUBE USED, MS DASH NO.(4)	-25	-25	-26	-26	-14
MEASURING RIM (5)	7.5, 7.50V	7.5, 7.50V	8.0, 8.00V	8.0, 8.00V	7.5, 7.50V
TIRE SECTION, INCHES (6)	10.82	10.82	11.47	11.47	10.82
DIAMETER, INCHES (MAX)	36.70	36.70	37.92	37.92	41.60
APPROX. LOADED RADIUS	16.9	16.9	17.6	17.6	19.9
PROCUREMENT SPEC. (9)	ZZ-T-1083	NOTE 9	ZZ-T-1083	NOTE 9	ZZ-T-1083
MS DASH NO. (10)	-4	-46	-5	-47	-50
FIIN	294-4804	752-9937	592-2421	878-3225	269-9540

SIZE DESIGNATION	10.00-20	14.00-20	12.00-24	16.00-25	18.00-25
PLY RATING	14	16	16	14	12
TYPE CLASSIFICATION (2)	EARTHMOVER	EARTHMOVER	EARTHMOVER	EARTHMOVER	AMPHIB VEH
TREAD TYPE	DIR TRTN	REGULAR	ND TRTN	DIR TRTN	SAND
CORD MATERIAL	NYLON	NYLON	NYLON	NYLON	NYLON
RATED LOAD, LBS. MAX. (3)	5250	8400	8320	9680	10650
INFLATION PRESSURE, PSI	70	60	70	35	20
TUBE USED, MS DASH NO. (4)	-14	-18	-105	-165	-166
MEASURING RIM (5)	7.5, 7.50V	10.0	8.5, 8.50V	11.25	10.00
TIRE SECTION, INCHES (6)	10.82	14.75	12.10	17.00	19.40
DIAMETER, INCHES (MAX)	42.42	49.04	49.34	59.12	60.85
APPROX. LOADED RADIUS	19.9	21.7	23.0	27.2	27.2
PROCUREMENT SPEC. (9)	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083	NOTE 9
MS DASH NO. (10)	-51	-52	-64	-9	-86
FIIN	227-0353	262-8777	269-9500	592-2424	792-1662

REVIEW ACTIVITY: ARMY-ME

APPROVED 28 DECEMBER 1955 REVISED (E) FOR CHANGE SEE SHEET 1

This military standard is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A.: ARMY-AT
Other Cust
NAVY-YD
AF-84

PROCUREMENT SPECIFICATION
ZZ-T-1083 & SEE NOTE 9

TITLE: TIRE PNEUMATIC:
LOW PLATFORM TRAILER, EARTHMOVER, GRADER, AND AMPHIBIOUS VEHICLE

SUPERSEDES:

MILITARY STANDARD
MS 35390

SHEET 2

Source: https://assist.dla.mil -- Downloaded: 2026-02-23 17:22Z
Check the source to verify that this is the current version before use.

SIZE DESIGNATION	18.00-25	18.00-25	21.00-25	21.00-25	21.00-25
PLY RATING	16	16	16	16	20
TYPE CLASSIFICATION (2)	EARTHMOVER	EARTHMOVER	EARTHMOVER	EARTHMOVER	EARTHMOVER
TREAD TYPE	REGULAR	DIR TRTN	DIR TRTN	DIR TRTN	REGULAR
CORD MATERIAL	NYLON	NYLON	NYLON	NYLON	NYLON
RATED LOAD, LBS. MAX. (3)	12620	12620	13640	13640	16120
INFLATION PRESSURE, PSI	40	40	30	30	40
TUBE USED, MS DASH NO. (4)	-166	-166	-167	TUBELESS	-167
MEASURING RIM (5)	13.00	13.00	15.00	15.00	15.00
TIRE SECTION, INCHES (6)	19.60	19.60	22.50	22.50	22.50
DIAMETER, INCHES (MAX)	62.70	64.06	69.36	69.36	67.84
APPROX. LOADED RADIUS	29.0	29.0	30.3	30.3	30.3
PROCUREMENT SPEC. (9)	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083
MS DASH NO. (10)	-53	-10	-12	-68	-54
FIIN	529-0513	262-8712	262-8687	555-2486	294-4654

SIZE DESIGNATION	21.00-25	23.5-25	23.5-25	24.00-25	24.00-25
PLY RATING	24	12	24	18	24
TYPE CLASSIFICATION (2)	EARTHMOVER	EARTHMOVER	EARTHMOVER	EARTHMOVER	EARTHMOVER
TREAD TYPE	DIR TRTN	DIR TRTN	REGULAR	DIR TRTN	DIR TRTN
CORD MATERIAL	NYLON	NYLON	NYLON	NYLON	NYLON
RATED LOAD, LBS. MAX. (3)	18370	11150	16760	18420	21340
INFLATION PRESSURE, PSI	50	25	50	35	45
TUBE USED, MS DASH NO. (4)	-167	TUBELESS	TUBELESS	-175	-175
MEASURING RIM (5)	15.00	19.50	19.50	17.00	17.00
TIRE SECTION, INCHES (6)	22.50	23.50	23.50	25.25	25.25
DIAMETER, INCHES (MAX)	69.36	64.06	62.70	74.26	74.26
APPROX. LOADED RADIUS	30.3	28.6	28.6	33.0	33.0
PROCUREMENT SPEC. (9)	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083
MS DASH NO. (10)	-13	-65	-66	-14	-55
FIIN	262-8714	580-3187	554-6244	262-8715	141-8624

SIZE DESIGNATION	26.5-25	26.5-25	21.00-29	24.00-29	29.5-29
PLY RATING	26	26	20	24	16
TYPE CLASSIFICATION (2)	EARTHMOVER	EARTHMOVER	EARTHMOVER	EARTHMOVER	EARTHMOVER
TREAD TYPE	DIR TRTN	REGULAR	DIR TRTN	DIR TRTN	DIR TRTN
CORD MATERIAL	NYLON	NYLON	NYLON	NYLON	NYLON
RATED LOAD, LBS. MAX. (3)	20970	20970	17510	23020	18600
INFLATION PRESSURE, PSI	50	50	40	45	25
TUBE USED, MS DASH NO. (4)	TUBELESS	TUBELESS	-176	-177	TUBELESS
MEASURING RIM	22.00	22.00	15.00	17.00	25.00
TIRE SECTION, INCHES (6)	26.5	26.5	22.5	25.25	29.5
DIAMETER, INCHES (MAX)	69.36	67.84	73.36	78.26	78.26
APPROX. LOADED RADIUS	30.6	30.6	32.1	34.7	34.8
PROCUREMENT SPEC. (9)	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083
MS DASH NO. (10)	-67	-87	-16	-17	-56
FIIN	580-3179	691-6669	262-8725	262-8724	580-7698

REVIEW ACTIVITY: ARMY-ME

This military standard is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

APPROVED 28 DECEMBER 1955 REVISED (E) FOR CHANGE SEE SHEET 1

Source: https://assist.dla.mil - Downloaded: 2026-10-23T17:22Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS
2610

SIZE DESIGNATION	29.5-29	29.5-29	29.5-29	24.00-33	27.00-33
PLY RATING	22	28	34	24	24
TYPE CLASSIFICATION (2)	EARTHMOVER	EARTHMOVER	EARTHMOVER	EARTHMOVER	EARTHMOVER
TREAD TYPE	DIR TRTN	DIR TRTN	DIR TRTN	REGULAR	DIR TRTN
CORD MATERIAL	NYLON	NYLON	NYLON	NYLON	NYLON
RATED LOAD, LBS. MAX. (3)	22620	26200	29490	24800	29890
INFLATION PRESSURE, PSI	35	45	55	45	40
TUBE USED, MS DASH NO. (4)	TUBELESS	TUBELESS	TUBELESS	-178	-179
MEASURING RIM (5)	25.00	25.00	25.00	17.00	22.00
TIRE SECTION, INCHES (6)	29.5	29.5	29.5	25.25	30.0
DIAMETER, INCHES (MAX)	78.26	78.26	78.26	80.58	88.84
APPROX. LOADED RADIUS	34.8	34.8	34.8	37.1	38.2
PROCUREMENT SPEC. (9)	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083
MS DASH NO. (10)	-44	-57	-45	-24	-18
FIIN	580-3208	554-6222	204-0433	294-4660	262-8723

SIZE DESIGNATION	30.00-33	36.00-41	44.5-45	44.5-45	65 INCH
PLY RATING	40	34	10	38	18
TYPE CLASSIFICATION (2)	EARTHMOVER	EARTHMOVER	SAND RIB	EARTHMOVER	EARTHMOVER
TREAD TYPE	DIR TRTN	DIR TRTN	RIBBED	DIR TRTN	DIR TRTN
CORD MATERIAL	NYLON	NYLON	NYLON	NYLON	NYLON
RATED LOAD, LBS. MAX. (3)	41700	55200	50870	72710	14550
INFLATION PRESSURE, PSI	50	35	35	45	35
TUBE USED, MS DASH NO. (4)	-168	-181	TUBELESS	TUBELESS	-169
MEASURING RIM (5)	22.00	26.00	37.00	37.00	25.00
TIRE SECTION, INCHES (6)	32.4	38.9	47.8	46.6	22.2
DIAMETER, INCHES (MAX)	94.66	114.0	114.0	118.5	64.1
APPROX. LOADED RADIUS	39.8	50.0	48.6	50.8	28.0
PROCUREMENT SPEC. (9)	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083
MS DASH NO. (10)	-58	-20	-92	-93	-59
FIIN	294-5097	592-2430			287-3170

SIZE DESIGNATION	14.00-20	7.50-24	9.00-24	10.00-24	12.00-24
PLY RATING	12	10	10	8	8
TYPE CLASSIFICATION (2)	GRADER DC	GRADER FB	GRADER FB	GRADER DC	GRADER DC
TREAD TYPE	DIR TRTN	RIBBED	RIBBED	DIR TRTN	DIR TRTN
CORD MATERIAL	NYLON	NYLON	NYLON	NYLON	NYLON
RATED LOAD, LBS. MAX.	5660	3220	4015	3640	4180
INFLATION PRESSURE, PSI	35	60	50	35	30
TUBE USED, MS DASH NO. (4)	-170	-171	-102	-172	-173
MEASURING RIM (5)	8.00T,8.00G	6.50TF	7.0,7.00T	7.5, 7.50V	8.00T,8.00TG
TIRE SECTION, INCHES (6)	14.25	8.40	10.1	10.82	12.3
DIAMETER, INCHES (MAX)	49.38	40.44	44.32	45.54	48.25
APPROX. LOADED RADIUS	22.3	19.4	20.5	21.6	21.7
PROCUREMENT SPEC. (9)	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083
MS DASH NO. (10)	-41	-36	-60	-31	-32
FIIN	640-2087	262-8654	275-8005	555-2519	555-2518

REVIEW ACTIVITY-ARMY-ME

APPROVED 28 DECEMBER 1955 REVISED (E) FOR CHANGE SEE SHEET 1

This military standard is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A. ARMY-AT Other Cust NAVY-YD AIR FORCE-84	TITLE TIRE PNEUMATIC: LOW PLATFORM TRAILER, EARTHMOVER, GRADER, AND AMPHIBIOUS VEHICLE	MILITARY STANDARD MS 35390
PROCUREMENT SPECIFICATION ZZ-T-1083 & SEE NOTE 9	SUPERSEDES:	SHEET 4

DD FORM SEP 67 672-1 (Coordinated)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 202610-23T17:22Z
Check the source to verify that this is the current version before use.

SIZE DESIGNATION	13.00-24	13.00-24	14.00-24	14.00-24	14.00-24
PLY RATING	8	12	8	12	12
TYPE CLASSIFICATION (2)	GRADER DC	GRADER DC	GRADER DC	GRADER DC	GRADER DC
TREAD TYPE	DIR TRTN	DIR TRTN	DIR TRTN	DIR TRTN	ND TRTN
CORD MATERIAL	NYLON	NYLON	NYLON	NYLON	NYLON
RATED LOAD, LBS. MAX. (3)	4410	5365	5190	6320	6320
INFLATION PRESSURE, PSI	25	35	25	35	35
TUBE USED, MS DASH NO. (4)	-174	-174	-57	-57	TUBELESS
MEASURING RIM (5)	8.00T,8.00TG	8.00T,8.00TG	8.00T,8.00TG	8.00T, 8.00TG	8.00T,8.00TG
TIRE SECTION, INCHES (6)	13.1	13.1	14.25	14.25	14.25
DIAMETER, INCHES (MAX)	50.56	50.56	53.38	53.38	53.38
APPROX. LOADED RADIUS	23.3	23.3	23.9	24.4	24.4
PROCUREMENT SPEC. (9)	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083
MS DASH NO. (10)	-21	-61	-33	-22	-69
FIIN	555-2520	640-2071	555-2521	640-2090	684-1872

SIZE DESIGNATION	16.00-24	16.00-24
PLY RATING	16	16
TYPE CLASSIFICATION (2)	GRADER DC	GRADER DC
TREAD TYPE	DIR TRTN	ND TRTN
CORD MATERIAL	NYLON	NYLON
RATED LOAD, LBS. MAX. (3)	9340	9340
INFLATION PRESSURE, PSI	40	40
TUBE USED, MS DASH NO. (4)	-165	-165
MEASURING RIM (5)	10.00VA	10.00VA
TIRE SECTION, INCHES (6)	17.3	17.3
DIAMETER, INCHES (MAX)	57.80	57.80
APPROX. LOADED RADIUS	26.5	26.5
PROCUREMENT SPEC. (9)	ZZ-T-1083	ZZ-T-1083
MS DASH NO. (10)	-90	-91
FIIN	580-3222	580-3223

REVIEW ACTIVITIES: ARMY-ME

APPROVED 28 DECEMBER 1955 REVISED (E) FOR CHANGE SEE SHEET 1

This military standard is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:22Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS
2610

SIZE DESIGNATION	10.00-15	8.25-15	8.25-20	11.00-20	11.00-20
PLY RATING	12	12	12	12	14
TYPE CLASSIFICATION (2)	L PLAT TLR	EARTHMOVER	EARTHMOVER	EARTHMOVER	EARTHMOVER
TREAD TYPE	REGULAR	ROCK LUG	ROCK LUG	REGULAR	ROCK LUG
CORD MATERIAL	NYLON	NYLON	NYLON	NYLON	NYLON
TUBE USED, MS DASH NO. (4)	-25	-23	-12	-15	-15
PROCUREMENT SPEC. (9)	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083
MS DASH NO. (10)	-71	-72	-73	-74	-75
FIIN	294-4802	294-5392	294-5396	269-9542	294-9475

SIZE DESIGNATION	13.00-24	16.00-21	16.00-21	16.00-24	16.00-24
PLY RATING	18	16	36	16	20
TYPE CLASSIFICATION (2)	EARTHMOVER	EARTHMOVER	EARTHMOVER	EARTHMOVER	EARTHMOVER
TREAD TYPE	ROCK LUG	REGULAR	SMOOTH	DIR TRTN	ROCK LUG
CORD MATERIAL	NYLON	NYLON	NYLON	RAYON	NYLON
TUBE USED, MS DASH NO. (4)	-106	TUBELESS	TUBELESS	-165	-135
PROCUREMENT SPEC. (9)	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083
MS DASH NO. (10)	-76	-62	-63	-89	-77
FIIN	294-9487	528-9709	294-5365	992-4433	269-9502

SIZE DESIGNATION	16.00-24	18.00-24	21.00-24	21.00-24	16.00-25
PLY RATING	24	16	20	20	24
TYPE CLASSIFICATION (2)	EARTHMOVER	EARTHMOVER	EARTHMOVER	EARTHMOVER	EARTHMOVER
TREAD TYPE	ROCK LUG	REGULAR	REGULAR	DIR TRTN	ROCK LUG
CORD MATERIAL	NYLON	NYLON	NYLON	NYLON	NYLON
TUBE USED, MS DASH NO. (4)	-135	-136	-167	-167	-165
PROCUREMENT SPEC. (9)	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083
MS DASH NO. (10)	-78	-26	-79	-28	-80
FIIN	294-9493	269-9544	269-9547	269-9550	294-9495

SIZE DESIGNATION	18.00-25	21.00-25	7.00-24	8.25-24	9.00-24
PLY RATING	24	20	10	10	10
TYPE CLASSIFICATION (2)	EARTHMOVER	EARTHMOVER	GRADER FB	GRADER FB	GRADER FB
TREAD TYPE	ROCK LUG	DIR TRTN	RIBBED	RIBBED	DIR TRTN
CORD MATERIAL	NYLON	NYLON	NYLON	NYLON	NYLON
TUBE USED, MS DASH NO. (4)	TUBELESS	-167	-199	-200	-102
PROCUREMENT SPEC. (9)	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083
MS DASH NO. (10)	-81	-82	-83	-37	-38
FIIN	528-9676	262-8810	262-8679	269-9525	262-8656

SIZE DESIGNATION	14.00-28	16.00-24	16.00-24	7.50-15	30.00-41
PLY RATING	8	12	12	4	28
TYPE CLASSIFICATION (2)	GRADER DC	GRADER DC	GRADER DC	GRADER DC	EARTMOVER
TREAD TYPE	DIR TRTN	DIR TRTN	ND TRTN	SMOOTH	DIR TRTN
CORD MATERIAL	NYLON	NYLON	NYLON	NYLON	NYLON
TUBE USED, MS DASH NO. (4)	-128	-165	TUBELESS	-157	-180
PROCUREMENT SPEC. (9)	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083	ZZ-T-1083
MS DASH NO. (10)	-84	-43	-70	-30	-19
FIIN	640-2091	640-2099	647-1137	051-0700	262-8720

ALL ITEMS ON THIS SHEET ARE INACTIVE FOR NEW DESIGN

AUTHORIZED FOR PROCUREMENT ONLY FOR SUPPORT OF IN-SERVICE MATERIEL

APPROVED 28 DECEMBER 1955 REVISED (E) FOR CHANGE SEE SHEET 1

REVIEW ACTIVITY: ARMY-ME

This military standard is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A. ARMY-AT Other Cust NAVY-YD AF-84	TITLE TIRE PNEUMATIC: LOW PLATFORM TRAILER, EARTHMOVER, GRADER, AND AMPHIBIOUS VEHICLE	MILITARY STANDARD MS 35390
PROCUREMENT SPECIFICATION ZZ-T-1083 & SEE NOTE 9	SUPERSEDES:	SHEET 6

DD FORM SEP 67 672-1 Obsoletes previous editions which may be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:22Z
Check the source to verify that this is the current version before use.

☆ U. S. GOVERNMENT PRINTING OFFICE: 1973 -714-541/3468