INCH-POUND
MIL-DTL-43826D
20 July 2026

SUPERSEDING
MIL-B-43826C
6 September 1989

DETAIL SPECIFICATION

BELT, INDIVIDUAL EQUIPMENT

This specification is approved for use by all Departments and Agencies of the Department of Defense (DoD).

1. SCOPE

1.1 Scope. This specification covers one type of adjustable individual equipment belt made from Camouflage Green 483 nylon webbing, plastic and miscellaneous metallic hardware.

1.2 Classification. The individual equipment belts will be of the following sizes as specified (see 6.2).

Medium - Waist under 30 inches
Large - Waist 30 inches or over

2. APPLICABLE PUBLICATIONS

2.1 General. The publications listed in this section are specified in sections 3 or 4 of this specification. This section does not include publications cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, users of this document are cautioned that they must meet all specified requirements of publications cited in sections 3 or 4 of this specification, whether or not they are listed.

2.2 Government publications.

Comments, suggestions, or questions on this document should be sent to trpsptctstandardiz@dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST online database at https://assist.dla.mil.

AMSC N/A FSC 8465

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:30Z
Check the source to verify that this is the current version before use.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these publications are those listed in the solicitation or contract (see 6.2).

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-DTL-32075 - Label: For Clothing, Equipage, and Tentage, (General Use)

(Copies of this specification are available online at https://quicksearch.dla.mil.)

2.2.2 Other Government publications. The following other Government publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these publications are those cited in the solicitation or contract (see 6.2).

U.S. ARMY DEVELOPMENTAL COMMAND - SOLDIER CENTER

2-2-309	-	Belt, Individual Equipment
2-2-498	-	Belt Assembly
2-2-499	-	Belt, Individual Equipment
2-2-506	-	Buckle, Side Release, 2-1/4 Inch
4-1-139	-	Keeper with slide
4-1-453	-	Belt Assembly

(Copies of these publications are available from the procuring activity.)

2.3 Non-Government publications. The following publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these publications are those cited in the solicitation or contract

AMERICAN SOCIETY FOR QUALITY (ASQ)

ASQ/ANSI Z1.4 - Sampling Procedures and Tables for Inspection by Attributes

(Copies of this publication are available online at https://www.asq.org.)

2.4 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection in accordance with 4.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:30Z
Check the source to verify that this is the current version before use.

3.2 Materials. The materials shall be as specified on Drawing 2-2-309 and all subsidiary drawings and parts lists (PLS) pertaining thereto.

3.2.1 Recycled, recovered, environmentally preferable, or biobased materials. Recycled, recovered, environmentally preferable, or biobased materials should be used to the maximum extent possible, provided that the material meets or exceeds the operational and maintenance requirements, and promotes economically advantageous life cycle costs.

3.3 Design and construction. The design and construction of the belt shall conform to the design, shape and dimensions shown on Drawing 2-2-309 and (PLS) as specified herein.

3.3.1 Setting of eyelet with washer. Holes shall be pre-punched or predrilled in the nylon webbing to receive the eyelets and shall be smaller than the outside diameter of the eyelet barrel so that the barrels shall be forced through the holes. The eyelets with washer shall be securely clinched in a manner that will prevent detachment from or cutting of the webbing. The eyelets shall be clinched without splitting.

3.3.2 Stitches, seams and stitching. All seams and stitching shall be as specified on the drawings.

3.3.2.1 Automatic stitching. Automatic stitching machines may be used to perform any of the stitch patterns provided the requirements for the stitch pattern, stitches per inch, and size and type of thread are met; and at least three or more tying, overlapping or back stitches are used to secure the ends of stitching.

3.3.2.2 Lubrication of thread. There shall be no lubrication of the thread prior to or during sewing.

3.3.2.3 Type 301 stitching. Ends of all stitching shall be backstitched or overstitched as specified on the drawings except where ends are turned under or caught in other seams or stitching. Thread tensions shall be maintained so that there will be no loose stitching resulting in loose bobbin or top thread or excessively tight stitching resulting in puckering of the materials sewn. The lock shall be imbedded in the materials sewn.

3.3.2.4 Repairs of type 301 stitching. Repairs of type 301 stitching shall be as follows:

a. When thread breaks or bobbin run-outs occur during stitching, the stitching shall be repaired by restarting the stitching a minimum of 1/2-inch back of the end of the stitching.
b. Thread breaks or two or more consecutive skipped or runoff stitches noted during inspection of the item (in-process or end item) shall be repaired by overstitching. The stitching shall start a minimum of 1/2-inch in back of the defective area, continue over the defective area, and continue a minimum of 1/2-inch beyond the defective area onto the existing stitching. Loose or excessively tight stitching shall be repaired by removing the defective stitching without damaging the materials and restitching in the required manner.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:30Z
Check the source to verify that this is the current version before use.

(When making the above repairs in a. and b., the ends of the stitching are not required to be backstitched.)

3.3.2.5 Thread ends. All thread ends that are visible on the finished item shall be trimmed to a maximum length of 1/4-inch.

3.3.3 Fusing of ends of nylon webbing. The ends of the nylon webbing shall be fused smooth in such a manner as to prevent sharp edges from forming. The apparatus used to fuse the webbing ends shall be capable of providing sufficient heat to fuse the cut ends of the webbing yarns together.

3.3.4 Setting of snap fasteners. A hole shall be pre-punched or predrilled through the materials to receive the button and eyelet components of the snap fasteners. The hole shall be smaller than the outside diameter of the button and eyelet barrels so that the barrel must be forced through the hole. The hole shall not be punched in the setting operation with the button or eyelet barrel. The fasteners shall be securely clinched without cutting the surrounding materials and no more than three splits shall occur in the button or eyelet barrels.

3.4 Label. The belt shall have a combination size and identification label. The label shall conform to type VI, class 5 of MIL-DTL-32075 except that the print shall be a minimum of 10 point and the color of the label shall be medium green (see 6.3). The size and attachment location of the label to the belt shall be as shown on Drawing 2-2-498. The contents of the label may read either across the belt or along the belt. The information required for the size shall include the waist dimension, for example the information required for the size medium belt shall be "size medium-waist under 30 inches".

3.4.1 Marking. The letters "US" shall be applied in the size characters and in the location shown on Drawing 2-2-498 and shall conform to type IV, class 9 of MIL-DTL-32075.

3.5 Workmanship. The end item shall conform to the quality of product established by this specification.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2).
b. Quality conformance inspection (see 4.3).

4.2 First article inspection. When a first article is required (see 3.1 and 6.2), it shall be examined for the defects specified in 4.3.1 and 4.3.2.

4.3 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with ASQ/ANSI Z1.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:30Z
Check the source to verify that this is the current version before use.

4.3.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced specification and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

TABLE I In process dimensional examination.

Examine	Defect	Classification	
		Major	Minor
Overall length of body	Not as specified exceeding tolerances:		
	- up to and including 1/4-inch		201
	- by more than 1/4-inch	101	
Location of eyelets	Any not located horizontally exceeding tolerances:		
	- up to and including 1/8-inch		202
	- by more than 1/8-inch	102	
	Any not located vertically as specified exceeding tolerances:		
	- up to and including 1/16-inch		203
	- by more than 1/16-inch	103	

4.3.2 End item visual examination. The end items shall be examined for the defects listed in Table II. The lot size shall be expressed in units of belts. The sample unit shall be one belt. (see 6.6).

TABLE II End item visual examination.

Examine	Defect	Classification	
		Major	Minor
Webbing	Not firmly and tightly woven; edges frayed or scalloped	104	
	Multiple floats		204
	Any cut, hole, tear or smash	105	
	Abrasion mark, slub, broken end or pick		205
	Ends not fused as specified (where required)		206
Metal hardware (general)	Broken or malformed failing to serve intended purpose, corroded area, burr or sharp edge	106	
	Finish omitted, partially omitted or not as specified:		
	-on brass components		207
	-on steel components	107	
	Not assembled as specified (unless otherwise classified herein)	108	
	Not specified type, size or style	109	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:30Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual examination – Continued.

Examine	Defect	Classification	
		Major	Minor
Eyelet	Insecurely clinched or clinched excessively tight, cutting fabric	110	
	Installed with scored side on outside of belt		208
	Not set with a scored setting		209
Snap fasteners	Any fastener not functioning properly i.e., fails to snap closed, to provide a secure closure, or to open freely	111	
NOTE:	The fasteners shall be snapped and unsnapped twice to determine whether parts of fastener separate freely and also effect a secure closure.		
	Clinched excessively tight, cutting adjacent material	112	
	Clinched loosely, permitting any component to rotate freely but not to the degree that any component can be expected to become detached during use		210
	Clinched loosely to the degree that components can be expected to become detached during use	113	
NOTE:	Incomplete roll of end of button or eyelet barrel is evidence of improper and insecure clinching.		
	Incorrect style	114	
	More than three splits in eyelet or button barrels		211
Seam and stitch type	Not specified seam or stitch type	115	
Stitch tension	Loose, resulting in a loose bobbin or top thread		212
	Tight, resulting in puckering of material		213
Stitches per inch	One stitch less than minimum specified		214
	Two or more stitches less than minimum specified	116	
	One or more stitches in excess of maximum specified		215
Thread breaks, skipped stitches, or runoffs	Not overstitched as specified		216
NOTE:	Thread breaks or two or more consecutive skipped or runoff stitches not overstitched shall be classified as open seams.		
Stitching ends	Not secured as specified		217
Belt buckle	Color not as specified		218
(plastic)	Color not molded in		219
	Broken, cracked or chipped	117	
	Any sink mark		220
	Any flash	118	
Stitching ends	Gates not trimmed as specified		221

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:30Z
Check the source to verify that this is the current version before use.

Belt buckle (plastic)	Surface not smooth		222
	Fasteners attached in reversed position or either component attached facing wrong direction	119	
	Any defect of belt fastener engaging the male and female components	120	
Component and assembly	Any component part or required operation omitted or not as specified (unless otherwise classified herein)	121	
	Any needle chew	122	
	Any mend, darn, patch or splice	123	
Marking	Omitted, incorrect, illegible, or misplaced, or size of characters not as specified, label not medium green		223
Cleanness	Any spot or stain clearly noticeable		224
Thread ends	Not trimmed to 1/4-inch maximum length		225

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the military service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful but is not mandatory.)

6.1 Intended use. The belt is worn by military personnel to carry various items of individual equipment, such as the water canteen and ammunition case which are suspended on the belt by keepers or by double hooks inserted through eyelets so spaced on the belt as to accommodate this equipment. The belt is also used in conjunction with the field pack suspenders, the suspender hooks being attachable to the top edge row of eyelets to help support the weight of the belt and its attached equipment.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number and date of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:30Z
Check the source to verify that this is the current version before use.

b. Size required (see 1.2).
c. Quantity
d. National Stock Number
e. Specific issue of individual documents referenced (see 2.2).
f. When a first article is required (see 3.1 and 4.3).
g. Name and address of the first article inspection facility; and the name and address of the Government activity responsible for conducting the first article inspection program.
h. Conformance inspection and acceptance quality limits (see 4.4)
i. Packaging required (see 5.1).

6.3 Color of label. The following cable numbers of the Standard Color Card of America are furnished for information and guidance as to the intensity of the shade of medium green desired for the label specified in 3.5:

Cable No. 70034
Cable No. 70130
Cable No. 70131

6.4 International standardization agreements. Certain provisions of this document are the subject of international standardization agreement as cited in NATO STANREC 4780. When amendment, revision, or cancellation of this document is proposed which will affect or violate the international agreement concerned, the preparing activity will take appropriate reconciliation action through international standardization channels including departmental standardization offices, if required.

6.5 Information. For access to information such as specification, patterns, drawings, shade standard samples of cloth, go to DLA Troop Support's Clothing and Textile website for their Specification/Drawing/Pattern Request Form: https://www.dla.mil/TroopSupport/ClothingandTextiles/SpecRequest.aspx. Complete the request form and then submit. Requests to use equivalent materials and/or components or to make changes to the pattern should be sent to the contracting officer for approval by the military services.

6.6 Subject term (key word) listing.

Ammunition case carrier
Canteen carrier
Equipment carrier
First aid carrier

6.7 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:30Z
Check the source to verify that this is the current version before use.

Custodians:
Army – GL
Navy – NU
Air Force – 11
DLA – CT

Review activities:
Army – MD
Navy – MC, YD

Preparing activity:
DLA – CT
(Project 8465-2026-002)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:30Z
Check the source to verify that this is the current version before use.