MIL-D-43807A
22 September 1977
SUPERSEDING
MIL-D-43807(GL)
14 September 1972

MILITARY SPECIFICATION

DISPENSER, FREEZE-DRIED COFFEE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers a counter model, self-contained freeze-dried coffee dispenser.

2. APPLICABLE DOCUMENTS

* 2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATION

FEDERAL

PPP-B-636 - Boxes, Shipping, Fiberboard

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads for 40" x 48" Pallets

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Natick Research and Development Command, Natick, MA 01760, by using the self-addressed standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 7310

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:24Z
Check the source to verify that this is the current version before use.

(Copies of specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

* 2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply:

AMERICAN SOCIETY OF TESTING AND MATERIALS (ASTM)

E 11 - Wire Cloth Sieves for Testing Purposes

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

NATIONAL SANITATION FOUNDATION (NSF)

Standard No. 18 - Manual Food and Beverage Dispensing Equipment

Listing of Food Service Equipment

(Application for copies should be addressed to the National Sanitation Foundation, NSF Building, Ann Arbor, MI 48105.)

UNDERWRITERS LABORATORIES INC.

UL 197 - Commercial Electric Cooking Appliances

(Application for copies should be addressed to the Underwriters Laboratories Inc., 207 East Ohio Street, Chicago, IL 60611; 333 Pfingsten Road, Northbrook, IL 60062; 1285 Walt Whitman Road, Melville, LI, NY 11746; 1655 Scott Blvd., Santa Clara, CA 95050; or 2602 Tampa East Blvd., Tampa, FL 33619.)

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:24Z
Check the source to verify that this is the current version before use.

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Traffic Department, 1616 P Street, N.W., Washington, DC 20036.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

* 3.1 Standard product. The dispenser delivered under this specification shall be the manufacturer's standard product except for changes necessary to meet specification requirements. All dispensers furnished under this specification for any one contract, including parts and assemblies thereof, shall be new and interchangeable.

* 3.2 Codes and standards. The complete dispenser shall conform to applicable requirements of NSF Standard No. 18 and UL 197, as applicable.

* 3.2.1 Compliance. Prior to approval of the first shipment, the contractor shall submit satisfactory evidence to the contracting officer or his authorized representative that the dispenser he proposes to furnish under this specification meets the applicable requirement, of NSF Standard No. 18 and UL 197, as follows:

* 3.2.1.1 NSF.

(1) Listing of the dispenser in the current edition of the NSF "Listing of Food Service Equipment" and display of the NSF seal on the finished dispenser, or

(2) A certification for the dispenser issued by NSF under their special one-time evaluation/certification service, or

(3) A certified test report from a recognized independent testing laboratory acceptable to the medical department of the service for which the dispensers are being procured, indicating that the dispensers have been tested and conform to NSF Standard No. 18.

* 3.2.1.2 UL. Acceptable evidence of meeting the requirements of UL 197 shall be the UL label, or listing mark, or a certified test report from a recognized independent testing laboratory, acceptable to the Government, indicating that the dispenser has been tested and conforms to the requirements of UL 197.

Source: https://assist.dla.mil -- Downloaded: 2026l0-21T22:24Z
Check the source to verify that this is the currentversion before use.

3.3 Materials. Materials not definitely specified shall be of the quality normally used by the manufacturer for freeze-dried dispensers, provided the complete item complies with all provisions of this specification (see 6.3).

3.4 Design and construction. The dispenser shall be designed for countertop or tabletop use and to be manually activated. The dispenser shall consist essentially of a water storage tank, aluminum container for freeze-dried coffee (product); two push-type switches, one push-type switch for coffee, and one push-type switch for water, drip-tray with grill; solenoid water valve; water heater; thermostat; plumbing; base; and the necessary controls and mixing devices to combine and dispense the water and product into the coffee supplier's recommended proportion for the hot-coffee drink. The entire unit shall be inclosed in a corrosion-resistant material cabinet. The base shall be provided with protectors to prevent damage to the surface dispenser it rests upon. Four 3/8-inch (37 mm) capped holes shall be provided in the dispenser base for counter-fastening. Unless otherwise specified (see 6.2), the contractor's standard dispenser dimensions are acceptable. The net weight of the dispenser not including the product and water, shall be not more than 50 pounds (22.7 kg). Dispenser, hot water storage tank, and fitting connections shall not leak when tested as specified in 4.4.1. The dispenser water supply connection shall be accessible from the outside of the cabinet. The dispenser shall be complete and ready for operation when connected to electrical and water supplies.

3.4.1 Water filter. When specified (see 6.2), a water filter conforming to specified requirements shall be provided.

3.4.2 Electrical characteristics. Unless otherwise specified (see 6.2), the dispenser shall operate on a nominal 120 volt, single-phase, 60 Hertz (Hz) system. Solenoids shall not exceed the manufacturer's specified operating temperatures. The electric cord shall extend 6 feet (1.8 m) and not more than 9 feet (2.7 m) from the cabinet.

3.4.3 Heating rate. The water in the tank shall be heated by heaters capable of heating a full tank of 60 $\pm$ 5° Fahrenheit (F) (16 $\pm$ 3° Celsius (C), water to 185 $\pm$ 5°F in 70 $\pm$ 5°F (85 $\pm$ 3°C in 21 $\pm$ 3°C) ambient, respectively, in less than 30 minutes with a maximum power rating of 1500 watts (w).

3.4.4 Operation. The dispenser controls and electrical components shall operate through a complete cycle without malfunction and controls shall not bind or show looseness when tested as specified in 4.4.1.

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:24Z
Check the source to verify that this is the currentversion before use.

3.4.5 Performance. The water heater and thermostat shall be capable of sustaining the heated water at 185 ± 5°F (85 ± 3°C) for a 100 six-ounce (177 ml) cup rate per hour or 1 cup per 36 seconds using supply water at 60 ± 5°F (16 ± 3°C) at 30 to 120 psig (207 to 827 kPa). Dry heat shall be directed into areas of product atmosphere exposure to preclude any bridging or preactivating of the product. Dispensing of a 6-ounce (177 ml) drink shall be performed in less than 10 seconds. At the finish of a draw of water or coffee, there shall be not more than 3 drops overrun of the liquid. The product throw shall be selected from an adjustable weight range between 1.5 ± 0.15 and 2.0 ± 0.20 grams per 6 ounces (177 ml) of water. The grain size of the product shall be such that the percent retained on the following ASTM E 11 sieves (U.S. standard sieves) after 5 minutes on a testing sieve shaker (RO-tap or equivalent) shall be as specified in table I.

TABLE I. Sieve requirements

Sieve number	Percent retained
8	None
12	20 max.
40	80 ± 5
pan	15 max.

3.4.6 Inclined operation. When specified for shipboard use (see 6.2), dispensers shall operate satisfactorily when the base is tilted at an angle of 15 degrees with no spillage of liquid when tested as specified in 4.4.4.

* 3.5 Marking. Identification instructions shall be permanently and legibly marked directly on the item or on an aluminum, brass, or stainless steel plate firmly affixed to the item. Marking shall be stamped, embossed, engraved or applied by photosensitive means. The plate thickness shall be not less than 0.012 inch (0.3 mm).

* 3.5.1 Identification plate. Each dispenser identification plate shall include the manufacturer's model and serial number, and name, trade name or trademark of such known character as to be readily identifiable. In addition, such information as required by UL 197, as applicable, shall appear on the identification plate.

* 3.6 Finish. Dispenser finishes shall be free from discoloration and stains. Stainless steel shall have a 2B or smoother finish.

Source: https://assist.dla.mil -- Downloaded: 202640-21T22:24Z
Check the source to verify that this is the currentversion before use.

* 3.7 Workmanship. All components and assemblies of the dispenser shall be free from dirt and other extraneous material, burrs, slivers, rough die, tool and grind marks, dents and cracks. Castings and molded parts if used, shall be free of sand, fins, pits, blowholes, and sprues. External surfaces shall be free from sharp edges and sharp corners.

* 3.7.1 Metal fabrication. Metal used in the fabrication of the dispensers shall be free from kinks. Forming and shearing shall not cause damage to the metal and the metal shall be free from trimming marks.

* 3.7.2 Welding. The surfaces of parts to be welded shall be free from rust, scale, paint, grease and other foreign matter. Welds shall be smooth and free from cracks, burn holes, undercuts or incomplete fusion. All scale and flux shall be removed from the finish weld area.

* 3.7.3 Fastening devices. Holes punched or drilled shall be free of burrs. Threaded fasteners shall not be broken, cracked or stripped and shall be drawn tight. Rivets, when used, shall fill the hole completely and the heads shall be in full contact with the surface of the member.

4. QUALITY ASSURANCE PROVISIONS

* 4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.2 Quality conformance inspection. Except as otherwise specified herein, sampling for inspection shall be performed in accordance with MIL-STD-105.

* 4.2.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced specifications and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

* 4.2.2 End item inspection. The lot shall consist of all dispensers offered for inspection at one time. The sample unit for this inspection shall be one completely assembled dispenser.

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:24Z
Check the source to verify that this is the current version before use.

* 4.2.2.1 Visual examination. Examination shall be made of the completely assembled dispenser for the defects listed in table II. The inspection level shall be II with an Acceptable Quality Level (AQL) of 2.5 for major defects and 6.5 for total defects, expressed in terms of defects per hundred units.

TABLE II. Classification of defects

Examine	Defect	Classification Major	Classification Minor
Standard product	Item not in accordance with manufacturer's standard product, except for changes necessary to comply with specification requirements	X	
Finish	Not in accordance with NSF	X	
	Edges and surfaces not smooth	X	
	Not free of discoloration or stains		X
	Stainless steel not 2B or better finish	X	
Construction and workmanship (general)	Component missing	X	
	Any wearing part not accessible for adjustment or replacement	X	
	Any component fractured or malformed	X	
	Any component misplaced or not in alignment	X	
	Any burr, sliver, sharp edge, rough die, tool, gouge, trim, or grind marks	X	
	Any component fractured, buckled, bent, dented, punctured, or malformed	X	
	Functioning component that is inoperative or will not operate as intended	X	
	Functioning component that required abnormal force to operate	X	
	Any adjustable assembly not properly adjusted to perform the intended function	X	
	Not fabricated of material specified	X	
	Water supply connection not accessible from outside of cabinet	X	

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:24Z
Check the source to verify that this is the currentversion before use.

TABLE II. Classification of defects (cont'd)

Examine	Defect	Classification Major	Minor
Construction and workmanship (general) (cont'd)	Base not protected to prevent damage to mounting surface	X	
	Drip tray and grill not provided	X	
	Mounting holes missing	X	
	Components not fully enclosed	X	
	Electric switches not as specified	X	
	Water valve not as specified	X	
	Heat not provided to exposed product	X	
	Dispensing directions not accessible from dispensing position	X	
Welding and brazing (when applicable)	Missing	X	
	Not continuous, not smooth, not uniform, burn holes, cracks, fissures, incomplete fusion	X	
	Not finished to blend to adjust surface	X	
	Not free from flux, scale, paint, or foreign material	X	
Threaded fasteners	Missing, stripped or cross-threaded, fractured	X	
	Loose		X
Rivets	Loose, not in full contact with members riveted	X	
Marking	Missing, not permanent, not legible, marking not as specified		X

4.2.2.2 Dimensional examination. Examination shall be made of the dispenser to determine compliance with dimensions specified. Any deviation from specified requirements shall constitute a defect. The inspection level shall be S-2 with an AQL of 4.0 expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:24Z
Check the source to verify that this is the current version before use.

* 4.2.2.3 End item testing. One production item, selected at random from the initial lot, shall be tested in accordance with 4.4.1 and 4.4.3. Any nonconformance shall be cause for rejection of the dispenser. The contractor shall perform tests on production units in accordance with 4.4.2 and when required 4.4.4 using an inspection level S-2 and an AQL of 2.5 expressed in terms of defects per hundred units.

* 4.2.3 Packaging inspection. An examination shall be made to determine that preservation-packaging, packing and marking as required by section 5 are complied with. Defects shall be as specified in table III. The sample unit shall be one shipping container fully prepared for delivery, except it need not be closed. The lot size shall be the number of shipping containers offered for inspection at one time. The inspection level shall be S-4 with an AQL of 6.5 defects expressed in terms of defects per hundred units.

TABLE III. Examination of packaging

Examine	Defect
Markings (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Components missing, damaged, or not as specified
Workmanship	Bulged or distorted containers, contents not immobilized with fiberboard inserts as specified

4.2.3.1 Examination of shipping containers. When shipping containers are required to be in accordance with PPP-B-636, examination for defects in closure, waterproofing, and reinforcing shall be in accordance with the appendix of PPP-B-636.

4.2.3.2 Examination of palletization. An examination shall be made to determine that palletization is in compliance with section 5. Defects shall be as specified in table IV. The sample unit for this examination shall be one palletized unit load ready for shipment. The lot shall be the number of palletized unit loads submitted for inspection at one time. The inspection level shall be S-1 with an AQL of 6.5 expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:24Z
Check the source to verify that this is the currentversion before use.

TABLE IV. Examination of palletization

Examine	Defect
Finished dimension	Length, width, or height exceeds specified maximum requirement
Palletization	Pallet pattern not as specified Interlocking of loads not as specified Load not bonded with required straps specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence or method of application

4.3 Certification examination. Certificates of compliance, certified test reports, approval labels or listing marks for codes and standards, as applicable, that are submitted as proof of conformance with the specified requirements shall be examined and validated.

4.4 Tests. Prior to performing tests specified herein, the dispensers to be tested shall be operated for a period of time recommended by the manufacturer for run-in and adjustment of the units.

4.4.1 Operational. Connect the dispenser to a 60 ± 5°F (16 ± 3°C) water supply in 70 ± 5°F (21 ± 3°C) ambient temperature and to a source of power having the same electrical characteristics as specified in 3.4.2. All controls and electrical components shall operate to insure that they function as specified in 3.4.4. During this test check for leaks in the hot water storage tank, at the fitting connections and where plumbing enters the water tank to determine conformance with the water tightness requirements of 3.4. Any nonconformance with specified requirements shall constitute failure of this test.

4.4.2 Heating rate and power consumption test. After the operational test specified in 4.4.1 is complete, connect an ammeter into the electrical supply line, and provide some means of measuring the water temperature in the hot water storage tank. Energize the dispenser, record the time for the water to heat to 185 ± 5°F (85 ± 3°C), and check this time for conformance with heat-up time requirements of 3.4.3. While the dispenser is heating, record the maximum amperage drawn, determine the electrical supply voltage, calculate the maximum wattage rating, and check this with the maximum wattage requirements of 3.4.3. Any nonconformance with specified requirements shall constitute failure of this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:24Z
Check the source to verify that this is the current version before use.

4.4.3 Performance test. With the water temperature stabilized at 185 ± 5°F (85 ± 3°C) draw 100 6-ounce (177 ml) cups for 1 hour recording the temperature at intervals to indicate any changes from the stabilized temperature. Adjust the dispenser for the minimum specified product throw (1.5 ± .15 grams per 6-ounces (177 ml)) of water; then determine the average weight of ten minimum product throws, the duration of each throw to be the time required for a 6-ounce (177 ml) draw of water. Repeat this average weight determination for the maximum specified draw (2.0 ± .20 grams) per 6-ounce (177 ml) of water. The average product throw for each adjustment shall be within the accuracy limits specified in 3.4.5. Draw continuously 1 gallon (3.8 liter) of water and test for solenoid overheating (see 3.4.2). Any nonconformance with specified requirements shall constitute failure of this test.

4.4.4 Inclined. The dispenser hot water storage tank shall be filled to 75 percent capacity with water. While in a fixed position, tilt the dispenser 15 degrees from vertical forward, backwards and sidewards and observe for spillage. Any nonconformance with specified requirements shall constitute failure of this test.

5. PACKAGING

5.1 Preservation-packaging. Preservation-packaging shall be level A or C, as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Disassembly. The extent of disassembly shall be determined by the manufacturer. This determination shall be based on the need for protection of parts susceptible to damage during transit or storage and for the reduction in cubage. Disassembly shall not be such that special skills or special tools are required to place the coffee dispenser in operation.

5.1.1.2 Packaging of coffee dispensers. The coffee dispenser shall be packaged in a snug-fitting fiberboard box conforming to style RSC, type CF, variety SW, or type SF, class domestic of PPP-B-636. Each box shall be securely closed with 2 inch (50.8 mm) minimum width gummed or pressure-sensitive paper tape.

5.1.2 Level C. The coffee dispensers shall be preserved-packaged to afford adequate protection against physical damage during shipment from the supply source to the first receiving activity. The package and the quantity per package shall be the same as that normally used by the supplier for retail distribution.

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:24Z
Check the source to verify that this is the current version before use.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

5.2.1 Level A packing. Each coffee dispenser including disassembled components, preserved-packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, type SF, grade V2s of PPP-B-636. Fiberboard inserts, fabricated from weather-resistant grade fiberboard, shall be used to immobilize the contents and prevent damage while in transit. Each fiberboard shipping container shall be closed in accordance with method III, waterproofed in accordance with method V and reinforced as specified in the appendix of PPP-B-636.

5.2.2 Level B packing. Each coffee dispenser including disassembled components, preserved-packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, type CF, variety SW, or type SF, class domestic, grade 200 of PPP-B-636. Fiberboard inserts fabricated of the same material as the container shall be used to immobilize the contents and prevent damage while in transit. Each fiberboard container shall be closed in accordance with method II of the appendix of PPP-B-636.

5.2.2.1 Weather-resistant shipping container. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with the method III as specified in the appendix of PPP-B-636.

5.2.3 Level C packing. The coffee dispensers, preserved-packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. The quantity per shipping container shall be the same as that normally used by the supplier for retail distribution. Containers shall be in accordance with Uniform Freight Classification or National Motor Freight Classification, as applicable.

5.3 Palletization. When specified (see 6.2), coffee dispensers packed as specified shall be palletized in accordance with load type I of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer.

5.4 Marking. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:24Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The dispensers intended for use in feeding areas to dispense hot coffee.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Electric system operation is other than specified (see 3.4).
(c) Dimensions, if other than specified (see 3.4).
(d) Water filter specifications, when required (see 3.4).
(e) Selection of the applicable levels of preservation-packaging and packing (see 5.1 and 5.2).
(f) When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
(g) When palletization is required (see 5.3).

6.2.1 Contract data requirements. Any data items to be delivered under any contract for the items covered by this specification should be specifically called for in the contract in accordance with the applicable regulations of the procuring activity.

6.3 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the specification (see 3.3).

6.4 Freeze-dried coffee dispenser water. Freeze-dried coffee dispensers require good quality water; free of undesirable impurities, tastes, or odors. If there is a water problem, professional advice should be solicited prior to procurement in order to determine a remedy by filtration or treatment.

6.5 Changes from previous issue. The outside margins of this specification have been marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Air Force - 99

Review activities:

Army - MD
DLA - GS

User activity:

Navy - SA

Preparing activity:

Army - GL

Project No. 7310-A584

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:24Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:24Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-D-43807A - Dispenser, Freeze-Dried Coffee

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:24Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
US ARMY NATICK RESEARCH and DEVELOPMENT COMMAND
NATICK, MASSACHUSETTS 01760

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
DRXNM-TD G

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD-314



Commander
US Army Natick Research and Development Command
ATTN: DRXNM-TD G
Natick, MA 01760

NATICK OP 1 JUL 77
FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:24Z
Check the source to verify that this is the current version before use.