MIL-G-43817A
16 December 1977
SUPERSEDING
MIL-G-43817
29 September 1972

MILITARY SPECIFICATION

GRILLS, FRANKFURTERS, ROLLER TYPE, ELECTRIC

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers two sizes of electrically heated roller-type frankfurter grills.

1.2 Classification. The frankfurter grills shall be of the following sizes as specified (see 6.2).

Size 1 - 350 frankfurters per hour
Size 2 - 600 frankfurters per hour

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein:

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Natick Research and Development Command, Natick, MA 01760 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 7310

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:25Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

PP-F-660 - Frankfurters, Chilled and Frozen.
PPP-B-636 - Boxes, Shipping, Fiberboard.
PPP-B-640 - Box, Fiberboard, Corrugated, Triple-Wall.

MILITARY

MIL-V-173 - Varnish, Moisture and Fungus Resistant (For Treatment of Communications, Electronic and Associated Equipment).

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection of Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of specifications, standards, and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply:

AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI)

C 73 - Dimensions of Caps, Plugs and Receptacles

(Application for copies should be addressed to the American National Standards Institute, 1430 Broadway, New York, NY 10019.)

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:25Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A 53 - Welded and Seamless Steel Pipe, Standard Specification for

A 167 - Stainless and Heat-Resisting Chromium-Nickel Steel Plate, Sheet, and Strip, Standard Specification for

A 176 - Stainless and Heat-Resisting Chromium Steel Plate, Sheet and Strip, Standard Specification for

A 264 - Stainless Chromium-Nickel Steel Clad Plate, Sheet and Strip, Standard Specification for

A 269 - Seamless and Welded Austenitic Stainless Steel Tubing for General Service, Standard Specification for

B 85 - Aluminum-Alloy Die Castings, Standard Specification for

B 209 - Aluminum-Alloy Sheet and Plate, Standard Specification for

B 456 - Electrodeposited Coatings of Nickel Plus Chromium, Standard Specification for

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

NATIONAL SANITATION FOUNDATION (NSF)

Standard No. 4 - Electric Commercial Cooking and Warming Equipment.

Listing of Food Service Equipment.

(Application for copies should be addressed to the National Sanitation Foundation, NSF Building, Ann Arbor, MI 48105.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Traffic Department, 1616 P Street, N.W., Washington, DC 20036.)

Source: https://assist.dla.mil -- Downloaded: 20260-21T22:25Z
Check the source to verify that this is the current version before use.

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

UNDERWRITERS LABORATORIES INC. (UL)

No. 197 - Commercial Electric Cooking Appliances.
No. 197-S1 - Commercial Electric Cooking Appliances for Marine Use.

(Application for copies should be addressed to the Underwriters Laboratories Inc., 207 East Ohio Street, Chicago, IL 60611; Walt Whitman Road, Melville, Long Island, NY 11749; or 1655 Scott Boulevard, Santa Clara, CA 95050.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Standard product. The frankfurter grills delivered under this specification shall be the manufacturer's current standard commercial product except for any changes necessary to comply with specification requirements.

3.2 Codes and standards. The complete frankfurter grills shall conform to applicable requirements of NSF Standard No. 4, UL 197 and UL 197-S1, as applicable.

3.2.1 Compliance. Prior to approval of first shipment, the contractor shall submit satisfactory evidence to the contracting officer or his authorized representative that the frankfurter grill he proposes to furnish under this specification meets the applicable requirement of NSF Standard No. 4 and UL 197, as follows:

3.2.1.1 NSF. Acceptable evidence of meeting the requirements of NSF shall be one of the following:

(1) Listing of the frankfurter grill in the current edition of the NSF "Listing of Food Service Equipment" and display of the NSF seal on the finished dispenser,

(2) A certification for the frankfurter grill issued by NSF under their special one-time evaluation/certification service.

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:25Z
Check the source to verify that this is the currentversion before use.

(3) A certified test report from a recognized independent testing laboratory acceptable to the medical department of the service for which the frankfurter grills are being procured, indicating that the dispensers have been tested and conform to NSF Standard No. 4.

* 3.2.1.2 UL. Acceptable evidence of meeting the requirements of UL 197 shall be the UL label or listing mark, or a certified test report from a recognized independent testing laboratory, acceptable to the Government, indicating that the frankfurter grill has been tested and conforms to the requirements of UL 197 and for shipboard use UL 197-S1.

* 3.3 Materials and components. Materials and components shall be as specified hereinafter. Materials not definitely specified shall be of the quality normally used by the manufacturer in the construction of grills of the type covered herein (see 6.3).

3.3.1 Stainless steel sheet and strip. Stainless steel sheet and strip shall conform to types 302 or 304 of ASTM A 167; or types 409, 410 or 430 of ASTM A 176.

3.3.2 Stainless steel seamless pipe and tube. Stainless steel seamless pipe and tube shall conform to ASTM A 269.

3.3.3 Stainless chromium-nickel steel clad plate, sheet, and strip. Stainless chromium-nickel steel clad plate, sheet and strip shall conform to ASTM A 264.

3.3.4 Welded and seamless steel pipe. Welded and seamless steel pipe shall conform to ASTM A 53.

3.3.5 Aluminum-alloy sheet and plate. Aluminum-alloy sheet and plate shall conform to types 3003, 5052 or 6061 of ASTM B 209.

3.3.6 Aluminum-alloy die castings. Aluminum-alloy die castings shall conform to ASTM B 85.

3.4 Design and construction. The grills shall be counter type as specified in 1.2. The grills shall be electrically operated and consist essentially of an outer shell or casing, an electric motor driven mechanism, driving rotating rollers, heating elements inside rollers, two heating systems, an electric temperature control assembly, cable and plug assembly, and a removable grease drip pan. Provision shall be made to prevent seeping of grease into drive mechanism. A sneeze guard shall be provided, unless otherwise specified (see 6.2). The grills shall not exceed a depth of 24 inches (609.6 mm) and a height of 10 inches (254 mm). The size 1 grills shall not exceed a length of 24 inches (609.6 mm) and the size 2 grills shall not exceed a length of 38 inches (965.2 mm). The grills shall have not less than eight rotating rollers and not less than half of the rollers shall be heated.

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:25Z
Check the source to verify that this is the currentversion before use.

3.4.1 Performance requirements. The completed grills shall operate without binding, erratic operation, vibration, overheating, failure of any part of component, or any evidence of malfunction, parts separation, breakage or any defect affecting the operation of the grills when tested as specified in 4.4.1. The size 1 machine shall have an hourly capacity of not less than 350 cooked frankfurters when tested as specified in 4.4.2. The size 2 grill shall have an hourly rate of not less than 600 cooked frankfurters when tested as specified in 4.4.2. Frankfurters shall conform to type 2, class 1, formula A, size 8-10 per pound (18-22 per kg) of PP-F-660. Starting temperature shall be 40°F (4.44°C) and frankfurters shall be considered cooked when the internal temperature reaches a minimum of 160°F (71.1°C). This internal temperature shall be reached without charring the surface of the frankfurters.

3.4.2 Outer shell or casing. The outer shell or casing shall be made of stainless steel conforming to 3.3.1 with a thickness not less than 20 gauge (nominal size 0.0375 inches (0.95 mm)), or cast aluminum conforming to 3.3.7, or chromium-nickel clad steel conforming to 3.3.3. When a flat cover is used on the outside of the cast aluminum side covers, the flat covers shall be made from aluminum conforming to 3.3.5. The outer shell or casing shall have not less than four non-slip supporting feet for counter protection.

3.4.3 Electrical requirements. Unless otherwise specified (see 6.2), the grills shall be designed for electric current operation on nominal system voltage of 120 volts, 60-hertz, alternating current. When 50-hertz operation is specified (see 6.2), a UL approved, 3-wire power supply cord compatible with item being furnished shall be provided without the attachment-plug cap. When specified for 50-hertz, the power-supply cord shall be provided with an attachment plug cap in accordance with ANSI C 73. The electrical system shall consist of a motor or motors, heating elements, heat controls, indicator light, "ON-OFF" switch or switches, two heating systems cable and plug assembly, and all the necessary wiring. The indicator lights and all controls and switches shall be clearly visible and easily accessible to the operator. Maximum kilowatt for size 1 shall be 1.25 kw and for size 2 shall be 1.80 kw, when tested as specified in 4.4.1. The grills may be designed with one or two motors at the manufacturer's option. The motor or motors shall drive the rotating rollers and shall be capable of continuous operation. The power supply cable shall be minimum two (2) feet (258 m) to six feet (1.82 m) long maximum.

3.4.3.1 Heating system. Each grill shall have two independently controlled heating systems. One system shall control the heat to the rear set of rollers and the other shall control the heat to the front set of rollers. A separate heat control shall be provided for each heating system. The heat control shall have a rotating dial with a minimum of three positive settings (low, medium, high) or it shall be an infinite type with a range from low to high when tested in accordance with 4.4.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:25Z
Check the source to verify that this is the current version before use.

3.4.3.2 Indicator lights and switches. An indicator light shall be provided with each heat control. The indicator light shall go "on" when the heating system is energized and "out" when the heat control or "ON-OFF" switch is in the "OFF" position. Each motor shall have an "ON-OFF" switch. When the switches are placed in the "OFF" position, all ungrounded lines shall be broken.

3.4.4 Rollers. Each grill shall have not less than eight rollers. The rollers shall be fabricated of stainless steel tube conforming to 3.3.2 or steel pipe conforming to 3.3.4 coated in accordance with 3.3.6. The rollers shall be removable for replacement or repair.

3.4.5 Sneeze guard. The sneeze guard shall be the manufacturer's standard commercial product. The sneeze guard shall be transparent and removable.

3.4.6 Grease drip pan. Each grill shall be provided with a grease drip pan removable without use of tools. The pan shall be fabricated of stainless steel conforming to 3.3.1 having a thickness not less than 22-gauge (0.0293 inches (0.74 mm)) or aluminum conforming to 3.3.5 having a thickness not less than 20-gauge (nominal 0.032 inches (0.81 mm)).

3.5 Fungus and moisture resistance of electrical components. When specified (see 6.2), the grills shall be treated for fungus and moisture resistance (see 4.3.1). The electrical circuitry, including all components and connections, shall be protected from the effects of moisture and fungus growth by an overall treatment with a varnish conforming to MIL-V-173 with the exception:

(a) Component or circuit elements which are inherently fungus and moisture resistant or which are hermetically sealed need not be treated.

(b) Component or circuit elements whose functions will be adversely affected by varnish shall not be treated.

3.6 Lubrication. Means shall be provided for lubricating bearings, shafts and other moving parts requiring lubrication. At the time of delivery, the grill shall be completely lubricated with the manufacturer's standard lubricant.

3.7 Repair and maintenance. Provision shall be made to allow access to permit adjustment, repair or replacement of electrical and other components.

* 3.8 Marking. Identification instructions shall be permanently and legibly marked directly on the item or on an aluminum, brass, or stainless steel plate firmly affixed to the item. Marking shall be stamped, embossed, engraved or applied by photosensitive means. The plate thickness shall be not less than 0.012 inch (0.3 mm).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:25Z
Check the source to verify that this is the current version before use.

3.8.1 Identification plate. Each frankfurter grill identification plate shall include the manufacturer's model and serial number, and name, trade name or trademark of such known character as to be readily identifiable. In addition, such information as required by UL 197 and UL 197-S1, as applicable, shall appear on the identification plate.

3.8.2 Marking of controls. Heat controls and indicator lights shall be marked "FRONT" or "REAR", as applicable. When multiple "ON-OFF" switches are used, they shall be marked "FRONT" or "REAR", as applicable.

* 3.9 Finish. Frankfurter grill finishes shall be free from discoloration and stains. Stainless steel shall have a No. 3 or smoother finish.

* 3.9.1 Electrodeposited coatings of nickel plus chromium. Electrodeposited coatings of nickel plus chromium shall conform to ASTM B-456.

3.10 Contract date requirements. Contract data requirements shall be as specified (see 6.2.1).

* 3.11 Workmanship. All components and assemblies of the frankfurter grill shall be free from dirt and other extraneous material, burrs, slivers, rough die, tool and grind marks, dents and cracks. Castings and molded parts if used, shall be free of sand, fins, pits, blowholes, and sprues. External surfaces shall be free from sharp edges and sharp corners.

3.11.1 Metal fabrication. Metal used in the fabrication of the frankfurter grill shall be free from kinks. Forming and shearing shall not cause damage to the metal and the metal shall be free from trimming marks.

* 3.11.2 Welding or soldering. The surfaces of parts to be welded or soldered, as applicable, shall be free from rust, scale, paint, grease and other foreign matter. Welds shall be smooth and free from cracks, burn holes, undercuts or incomplete fusion. All scale and flux shall be removed from the finish weld area. Soldering not adherent, dirty or evidence of pin holes in surfaces.

* 3.11.3 Fastening devices. Holes punched or drilled shall be free of burrs. Threaded fasteners shall not be broken, cracked or stripped and shall be drawn tight. Rivets, when used, shall fill the hole completely and the heads shall be in full contact with the surface of the member.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:25Z
Check the source to verify that this is the current version before use.

4.2 Quality conformance inspection. Except as otherwise specified herein, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.2.1 Components and materials inspection. In accordance with 4.1 above, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified or qualified in the specification or applicable purchase document.

4.2.2 End item inspection. The inspection lot shall consist of all grills of the same size offered for inspection at one time. The sample unit shall be one completely fabricated and assembled grill.

4.2.2.1 Visual examination. Examination shall be made of the grills for the defects listed in table I. The inspection level shall be level II with an acceptable quality level (AQL) of 2.5 for major defects and 6.5 for total defects expressed in terms of defects per hundred units.

TABLE I. Classification of defects

Examine	Defect	Classification Major	Minor
Standard product	Item not in accordance with manufacturer's standard product, except for changes necessary to comply with specification requirements	X	
Finish	Not in accordance with NSF	X	
	Edges and surfaces not smooth	X	
	Not free of discoloration or stains		X
	Stainless steel not No. 3 or better finish	X	
Construction and workmanship	Component missing	X	
	Any wearing part not accessible for adjustment or replacement	X	
	Any component fractured or malformed	X	
	Any component misplaced or not in alignment	X	
	Any burr, sliver, sharp edge, rough die, tool, gouge, trim, or grind marks	X	
	Any component fractured, buckled, bent, dented, punctured, or malformed	X	
	Functioning component that is inoperative or will not operate as intended	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:25Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects (cont'd)

Examine	Defect	Classification Major	Minor
Construction and workmanship (general) (cont'd)	Functioning component that required abnormal force to operate		X
	Any adjustable assembly not properly adjusted to perform the intended function		X
	Not fabricated of material specified	X	
Welding and brazing (when applicable)	Not continuous, not smooth, not uniform, burn holes, cracks, fissures, incomplete fusion	X	
	Not finished to blend with adjacent metal surfaces	X	
	Flux or scale not removed	X	
Soldering	Incomplete; not adherent	X	
	Dirty, pin holes, flux not removed	X	
Threaded fasteners	Missing, stripped or cross-threaded, fractured	X	
	Loose		X
Rivets	Loose, not in full contact with members riveted	X	
ON-OFF switches	Missing, not accessible to operator, not as specified	X	
Heat controls	Missing, not accessible to operator, not as specified	X	
Indicator lights	Missing, not as specified	X	
Motor	Not continuous operation type	X	
Cable and plug	Not as specified, missing	X	
Rollers	Less than 8 rollers, not as specified	X	
Sneeze guard (when specified)	Missing, not transparent, not removable	X	
Drip pan	Missing, not removable, not as specified	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:25Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects (cont'd)

Examine	Defect	Classification Major	Classification Minor
Lubrication	Means not provided for lubrication where required	X	
Marking	ON-OFF switches not marked FRONT or REAR when applicable	X	
	Heat controls not marked FRONT and REAR	X	
Identification marking	Missing, not permanent, not legible, marking not as specified	X	

4.2.2.2 Dimensional examination. An examination shall be made to determine compliance with dimensions specified in 3.4. Any nonconformance shall be classified a defect. The inspection level shall be S-4 with an AQL of 6.5 expressed in defects per hundred units.

* 4.2.2.3 End item testing. The first unit of production shall be tested as specified in 4.4.1 and 4.4.2. Every item shall be tested in accordance with 4.4.3. Failure to pass any test shall be cause for rejection.

* 4.2.3 Packaging inspection. An examination shall be made to determine that packing and marking as required by section 5 are complied with. Defects shall be as indicated in table II. The sample unit for this examination shall be one shipping container fully prepared for delivery, except that it need not be closed. The lot size shall be the number of containers offered for inspection at one time. The inspection level shall be S-4 with an AQL of 4.0, expressed in terms of defects per hundred units.

TABLE II. Examination of packaging

Examine	Defect
Markings	Omitted; incorrect; illegible; of improper size, location, sequence or method of application.
Materials	Components missing, damaged, defective, or not as specified.
Workmanship	Bulged or distorted containers.
Contents	Number of grills or sneezing guards per shipping container is more than required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:25Z
Check the source to verify that this is the current version before use.

4.2.3.1 Examination of shipping containers. When shipping containers are required to be in accordance with PPP-B-636 or PPP-B-640, examination for defects in closure, waterproofing and reinforcing shall be in accordance with the appendix of the applicable container specification.

* 4.3 Certification examination. Certificates of compliance, certified test reports, approval labels or listing marks for codes and standards, as applicable, that are submitted as proof of conformance with the specified requirements shall be examined and validated.

* 4.3.1 Certification for fungus and moisture resistance. When applicable (see 6.2), the manufacturer shall submit a certificate of compliance with the requirements of 3.6.

4.4 Tests.

4.4.1 Functional test. Connect the grill to an appropriate electrical power source. Activate the drive motor or motors, as applicable. Allow the grill to operate for a period of not less than one (1) hour. During the operation period set all heat controls for various heats. While operating stop and start the grill motor or motors at least ten times. Observe indicator lights to determine compliance with 3.5.2.2. Check to assure that heat controls operate corresponding heating systems as marked (see 3.4, 3.5.2.1, 3.5.2.2 and 3.9.2). Change the temperature setting on the heat controls at least ten times and observe to determine compliance with the requirements of 3.5.2.2. Observe all components for evidence of binding, erratic operation, unusual noise, excessive looseness, or any evidence of malfunctioning to determine compliance with the operational requirements of 3.4.1. Check for compliance with wattage requirements of 3.5.2. Any nonconformance to specified requirements shall constitute failure of this test.

4.4.2 Performance. Preheat grill in accordance with the manufacturer's standard procedure. Load grill to maximum capacity with frankfurters conforming to type 2, class 1, formula A, size 8-10 per pound (18-22 per kg) of PP-F-660. Starting temperature of the frankfurters shall be 40°F (4.44°C). Grill frankfurters until heated in accordance with 3.4.1. The internal temperature shall be taken at the midpoint of the longitudinal axis of the frankfurter using a quick reading temperature detecting device or a thermocouple probe. Repeat above procedure three consecutive times not allowing any recovery time between loadings. For the three consecutive loads, the rate of cooking shall not be less than required by 3.4.1. Observe for absence of grease seepage into drive mechanism (see 3.4). Any nonconformance to the requirements of 3.4 or 3.4.1 shall constitute failure of this test.

Source: https://assist.dla.mil -- Downloaded: 20260-21T22:25Z
Check the source to verify that this is the current version before use.

4.4.3 Operational test. Connect the grill to an appropriate electrical power source. Check to assure that motors are operating, indicator lights go "ON", and heating elements are heating the rollers. Observe grills for evidence of binding, erratic operation, unusual noise, excessive looseness, or any evidence of malfunctioning to determine compliance with operational requirements of 3.4.1. Any nonconformance to the requirements of 3.4.1 shall constitute failure of this test.

5. PACKAGING

* 5.1 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

* 5.1.1 Level A. One grill and one sneezing guard individually packed in a snug-fitting fiberboard shipping container conforming to style RSC, type SF, grade V2s of PPP-B-636, or class 2, style E of PPP-B-640, as applicable. Inner packing such as buffer pads, cell spacers, die-cut pads formed from scored sheets of the same material as the shipping container shall be used to provide clearance for projecting parts of the grill or sneeze guard, and to prevent damage from shock or vibration while in transit. Each shipping container shall be closed, waterproofed by means of tape and reinforced with flat strapping or tape banding in accordance with the appendix of the applicable container specification.

5.1.2 Level B. One grill and one sneeze guard shall be individually packed in a snug-fitting fiberboard shipping container conforming to style RSC, type CF (variety SW), or SF, class domestic, minimum grade 200 of PPP-B-636 or class 1, style E of PPP-B-640, as applicable. Inner packing as specified in 5.1.1 shall apply. Each shipping container shall be closed in accordance with applicable container specification.

5.1.2.1 Weather-resistant fiberboard containers. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636, or a class 2, style E of PPP-B-640, as applicable. Each shipping container shall be closed in accordance with the applicable container specification.

5.1.3 Commercial. The grills and sneeze guard shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with Uniform Freight Classification or National Motor Freight Classification, as applicable.

5.2 Marking. In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 202640-21T22:25Z
Check the source to verify that this is the currentversion before use.

6. NOTES

6.1 Intended use. The frankfurter grills covered by this specification are intended for use in Military dining facilities ashore and on Naval shipboard. Grills ordered with sneeze guards are for front counter use; grills ordered without sneeze guard are for back counter use.

* 6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Size of frankfurter grill required (see 1.2 and 6.1).
(c) Sneeze guard not required (see 3.4).
(d) When 50 Hz, operation is required and an ANSI electrical plug is required (see 3.4.3).
(e) When fungus and moisture treatment of electrical components is required (see 3.6 and 4.3.1).
(f) When grills are desinged for operation on other than 120 volts, 60 Hz, system (see 3.4.3).
(g) Selection of the applicable level of packing (see 5.1).
(h) When weather-resistant grade fiberboard shipping containers are required for level B shipment (see 5.1.2.1).

6.2.1 Contract data requirements. Any requirements for equipment manuals for the items covered by this specification should be included in DD Form 1423 Contract Data Requirements List, and cited in the contract.

6.3 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the specification (see 3.3).

6.4 Metric equivalents. Metric equivalents, indicated in parentheses throughout this document, are based on practices, conversion factors, and symbols specified in ASTM E 380 Standard for Metric Practice, and are for information only. In each instance, the value stated in US customary units shall be controlling.

6.5 Changes from previous issue. The outside margins of this specification have been marked with an asterisk (*) to indicate where changes (additions, modification, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:25Z
Check the source to verify that this is the currentversion before use.

Custodians:

Army - GL
Navy - YD
Air Force - 99

Review activities:

Army - MD
Navy - SA

User activities:

Navy - MC, MS
DLA - GS

Preparing activity:

Army - GL

Project No. 7310-0455

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:25Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:25Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE
MIL-T-83071 - Drills, Premarkers, Roller Type, Electric

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:25Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
US ARMY NATICK RESEARCH and DEVELOPMENT COMMAND
NATICK, MASSACHUSETTS 01760

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
DRXNM-TD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD-314



Commander
US Army Natick Research and Development Command
ATTN: DRXNM-TD
Natick, MA 01760

NATICK OP 1 JUL 77
FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:25Z
Check the source to verify that this is the current version before use.