29 September 1972

MILITARY SPECIFICATION

SLICING MACHINE, BUN

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope.- This specification covers one type of hand fed, counter mounted, electrically powered bun slicing machine.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

CC-M-636	-	Motor, Alternating-Current (Fractional Horsepower)
QQ-S-781	-	Strapping, Steel, Flat and Seals
PPP-B-601	-	Boxes, Wood, Cleated-Plywood
PPP-B-621	-	Boxes, Wood, Nailed and Lock Corner
PPP-T-45	-	Tape, Gummed, Paper, Reinforced and Plain for Sealing and Securing

MILITARY

MIL-B-121	-	Barrier Material, Greaseproofed, Waterproofed, Flexible
MIL-P-116	-	Preservation, Methods of

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:26Z
Check the source to verify that this is the current version before use.

MIL-STD-130 - Identification Marking of U.S. Military Property

MIL-STD-1186 - Cushioning, Anchoring, Bracing, Blocking and Waterproofing, with Appropriate Test Methods

(Copies of specifications, standards and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications.- The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on the date of invitation for bids or request for proposal shall apply:

American National Standards Institute (ANSI)

C73 - Dimensions of Caps, Plugs, and Receptacles

(Application for copies should be addressed to the American National Standards Institute, 1430 Broadway, New York, New York 10018.)

American Society for Testing and Materials (ASTM)

Designation ASTM A167-70 - Stainless and Heat-Resisting Chromium-Nickel Steel Plate, Sheet, and Strip.

Designation ASTM A176-71 - Stainless and Heat-Resisting Chromium-Steel Plate, Sheet and Strip.

Designation ASTM E18-67 - Rockwell Hardness and Rockwell Superficial Hardness of Metallic Materials.

(Applications for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pennsylvania 19103.)

Baking Industry Sanitation Standards Committee (BISSC)

Standard No. 13 - Bread, Cake and Roll Slicing, Wrapping, and Bagging Machines

Standard No. 29 - Electric Motors

(Application for copies should be addressed to the Bakery Industry Sanitation Standards Committee, 521 Fifth Avenue, New York, N.Y. 10017.)

National Motor Freight Traffic Association, Inc., Agent

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P. Street, N.W., Washington, D.C. 20036.)

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:26Z
Check the source to verify that this is the currentversion before use.

Uniform Classification Committee, Agent

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, Illinois 60606.)

Underwriters' Laboratories Inc., (UL)

Standard No. 73 - Motor-Operated Appliances

(Application for copies should be addressed to Underwriters' Laboratories, Inc., 207 East Ohio St., Chicago, Illinois 60611; 1655 Scott Blvd., Santa Clara, California 95050; 333 Pfingsten Road, Box 247, Northbrook, Illinois 60062; 1285 Walt Whitman Road, Melville, Long Island, New York 11746.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 First article.- When specified (see 6.2), the supplier shall furnish a sample for first article inspection and approval (see 4.2 and 6.3).

3.2 Standard product.- The bun slicing machines delivered under this specification shall be the manufacturer's current standard commercial product, except for any changes necessary to comply with specification requirements.

3.3 Standards compliance.-

3.3.1 Underwriters' Laboratories Standards (UL).- The bun slicing machines shall comply with the applicable requirements of UL Standard No. 73.

3.3.1.1 UL certification.- Prior to approval of the first article, if one is submitted, or prior to commencing production, the supplier shall submit to the contracting officer or his authorized representative satisfactory evidence that the bun slicing machines he proposes to furnish under this specification meet the requirements of UL Standard No. 73. Acceptable evidence of meeting the requirements of UL Standard No. 73 shall be the UL listing mark, or label, or a certified test report from a recognized independent testing laboratory acceptable to the Government indicating that the bun slicing machine has been tested and conforms to all applicable requirements of UL Standard No. 73.

3.3.2 Baking Industry Sanitary Standards (BISSC).- The bun slicing machines shall conform to the applicable requirements of BISSC Standards No. 13 and No. 29.

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:26Z
Check the source to verify that this is the currentversion before use.

3.3.2.1 BISSC certification.- The supplier shall submit satisfactory evidence to the contracting officer or his authorized representative that the bun slicing machine conforms to the applicable requirements of BISSC Standards 13 and 29, as follows:

(1) A photostatic copy of the current BISSC certificate of authorization for the bun slicing machine shall be submitted prior to the approval of the first article, if one is submitted, or prior to commencing production, or

(2) A certified test report from a recognized independent testing laboratory acceptable to the medical department of the service for which the bun slicing machines are being procured, indicating that the bun slicing machine has been tested and conforms to the applicable requirements of BISSC Standards 13 and 29, shall be submitted prior to the approval of the first article, if one is submitted, or prior to commencing production.

3.4 Materials.- Materials not definitely specified shall be of the quality normally used by the manufacturer in bun slicing machines.

3.4.1 Product zone material.- All surfaces of the bun slicing machine which the buns normally come in contact with, except the cutting blade, shall be made of stainless steel conforming to any chemical composition in the 300 series as specified in ASTM A167.

3.4.2 Cutting blade material.- The cutting blade shall be made of stainless steel conforming to ASTM A176.

3.5 Design and construction.- The bun slicing machine shall consist of a feeding chute tilted at a 25 to 35 degree vertical angle with the machine base and a circular cutting blade rotated by a electric motor. The motor shall be controlled by an ON-OFF switch provided with a safety guard cover located on the body of the bun slicing machine accessible to the operator. The feeding chute shall have adjustments for bun width and height, and thickness and depth of cut. The bun slicing machine shall be a counter model with 4 non-skid feet, and shall have envelope dimensions no greater than 36 inches wide, 15 inches deep and 25 inches high. No tools or excessive force shall be required to make adjustments on the bun slicing machine, and during adjustment, there shall be no binding or jamming of moving parts. The bun slicing machine shall be capable of slicing both soft and hard buns and rolls without jamming or stalling, and without tearing or crushing the buns or rolls. When the machine is switched on, the cutting blade shall rotate such that, within the chute, the cutting edge travels away from the bun inlet. The cutting teeth or serrations, as applicable, shall have their cutting edge facing the same direction as the blade travel.

3.5.1 Feeding chute.- The chute interior width shall be infinitely adjustable from a lower limit of no more than 1-1/4 inches to an upper limit of no less than 5 inches. The chute interior height shall be infinitely adjustable from a lower limit of no more than 1-3/4 inches to an upper limit of no less

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:26Z
Check the source to verify that this is the current version before use.

than 2-3/4 inches. The cutting blade height shall be infinitely adjustable from a lower limit of no more than 1/2 inch above the base of the chute to an upper limit of no less than 15/16 inch above the base of the chute.

3.5.2 Motor.- The motor shall be type I or II, style B1 or B2 of CC-M-636. The motor shall have a class A insulation and shall be operable from a 60 cycle, 120 volt alternating-current power source.

3.5.3 Cutting blade.- The cutting blade shall be made of the material specified in 3.4.2 and heat treated so that the hardness of the cutting blade, measured within 1/4 inch of the cutting edge, shall be not less than 50 nor more than 60 on the Rockwell C scale when tested as specified in 4.3.1.1.

3.5.4 Power supply cord.- When 50 hertz operation is specified (see 6.2), a UL approved, 3-wire power supply cord compatible with the bun slicing machine shall be provided without the attachment-plug cap. When specified for 50 hertz, the power supply cord shall be provided with an attachment-plug cap in accordance with ANSI C73.

3.6 Repair and maintenance.- Provisions shall be made to allow for service and replacement of the cutting blade and electric motor.

3.7 Marking for identification.- Each bun slicing machine shall be marked with the manufacturer's name, trade name, or trademark readily identifiable with the manufacturer. Marking shall be applied in a conspicuous location in accordance with MIL-STD-130.

3.8 Workmanship.- The bun slicing machines shall contain no sharp edges, dents, scratches, burrs or slivers, and shall be free from dirt, smudge, grease or other foreign matter. All bolt or rivet holes shall have burrs removed. Rivets shall be driven to completely fill the holes, with full sized heads neatly finished and in full contact with the surface of the member. Welds shall be continuous, smooth, free from porosity, cracks, burn holes, fractures and free of excess flux or splatter. Castings shall be sound and free of blowholes, shrinkage, porosity, warping or other defects that render the casting unsound.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:26Z
Check the source to verify that this is the current version before use.

4.2 First article inspection.- When a first article is required, it shall be examined for defects listed in table I, dimensions specified herein, and tested as specified in 4.4.1 and 4.4.2. The presence of any defect listed in table I, or any dimension not within specified requirements or failure to pass any test shall be cause for rejection of the first article.

4.3 Inspection.- Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise specified hereinafter.

4.3.1 Component and material inspection.- The supplier shall insure that all components and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards unless excluded, amended, modified or qualified in this specification or applicable purchase document.

4.3.1.1 Cutting blade hardness.- Sample cutting blades shall be tested for hardness in accordance with ASTM E18 to determine compliance with 3.5.3. The lot shall be all cutting blades offered for inspection at one time, and the sample unit shall be one cutting blade. The inspection level shall be level II with an AQL of 4.0 expressed in terms of defects per hundred units. Sample unit hardness not in conformance with 3.5.3 shall be considered a defect.

4.3.2 End item inspection.- The inspection lot shall consist of all bun slicing machines offered for inspection at one time. The sample unit shall be one completely fabricated bun slicing machine.

4.3.2.1 Visual examination.- The bun slicing machines shall be examined for defects in table I. The inspection level shall be level II with an acceptable quality level (AQL) of 2.5 for major defects and 6.5 for total defects, expressed in terms of defects per hundred units.

TABLE I.- Classification of defects

Examine	Defect	Classification Major	Minor
Standard product	Item not in accordance with manufacturer's standard product except for changes necessary to comply with specification requirements.	X	
Design and Construction	Chute width, height, and blade height not adjustable	X	
	On-off switch missing, or not provided with safety guard	X	
	Chute not at specified angle with machine base	X	

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:26Z
Check the source to verify that this is the current version before use.

TABLE I.- Classification of defects (cont'd)

Examine	Defect	Classification Major	Minor
Repair and Maintenance	No provisions for servicing and replacement of cutting blade and motor	X	
Marking for Identification	Missing, Illegible, not as specified		X
Workmanship	Scratches, dents, sharp edges, burrs or slivers	X	
	Dirt, smudge, grease or other foreign matter	X	
Riveting	Rivet heads not in full contact with joined surfaces	X	
	Not fully peened	X	
Welding	Not continuous, cracks, fractures, burn holes	X	
	Not smooth, excess flux or splatter	X	
Castings	Blowholes, shrinkage, porosity warping, or other defects affecting soundness	X	

4.3.2.2 Dimensional examinations.- Examination shall be made of the end items to determine compliance with dimensions specified. Any dimension not meeting specified requirements shall constitute a defect. The inspection level shall be S-2 with an AQL of 4.0 expressed in terms of defects per hundred units.

4.3.2.3 End item testing.- When a first article is not required, the initial unit of production shall be tested as specified in 4.4.1 and 4.4.2. Failure to pass either test shall be cause for rejection of the lot. Each production unit shall be tested in accordance with 4.4.2. Any nonconformance shall be cause for rejection of the unit.

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:26Z
Check the source to verify that this is the currentversion before use.

4.3.3 Standards compliance.- Proof of compliance with the requirements of 3.3.1 and 3.3.2 shall be submitted to the Government representative.

4.3.4 Examination of preparation for delivery.- An examination shall be made to determine that preservation and packaging, packing, and marking as required by section 5 of this specification are complied with. Defects shall be as indicated in table II. The sample unit shall be one shipping container fully prepared for delivery. The lot shall be the number of containers offered for inspection at one time. The inspection level shall be S-4 with an AQL of 6.5 defects expressed in terms of defects per hundred units.

TABLE II.- Examination of preparation for delivery

Examination	Defect
Markings	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Component missing, damaged or otherwise defective.
Preservation	Preservative improperly applied or missing.

4.3.4.1 Examination of shipping containers.- When shipping containers are required to be in accordance with PPP-B-601 or PPP-B-621, examination for defects in closure and strapping shall be in accordance with the applicable container specification. Examination for defects in cushioning, blocking and bracing, anchoring, and waterproofing shall be in accordance with MIL-STD-1186.

4.4 Tests.-

4.4.1 Functional test.- One dozen soft buns and one dozen hard rolls, each measuring between 1-1/2 inches and 5 inches in width, and between 1-3/4 inches and 2-3/4 inches in height shall be required for this test. The bun slicing machine chute shall be adjusted to allow the hard rolls to be sliced completely in half approximately 3/4 inch above the base of the roll. All adjustments made during this test shall be liberal to adjust for irregular baking uniformity. With the machine switched on, 6 hard rolls shall be fed in and sliced. The chute shall then be adjusted to allow the hard rolls to be sliced approximately 1/2 of the way through at a height approximately 1/2 inch above the base of the roll, and the remaining 6 hard rolls shall be fed into the operating bun slicing machine and sliced. The chute shall be adjusted to allow the soft buns to be sliced completely in half approximately 3/4 inch above the base of the bun, and 6 buns shall be fed into the operating bun slicing machine and sliced. The chute shall then be adjusted to allow the soft buns to be sliced approximately 1/2 of the way through at a height approximately 1/2 inch above the base of the

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:26Z
Check the source to verify that this is the currentversion before use.

bun, and the remaining 6 buns fed into the operating bun slicing machine and sliced. Noncompliance with the requirements of 3.5 shall constitute failure of this test.

4.4.2 Operational test.- The adjustments for chute interior width, interior height, and cutting blade height shall be checked to see that they allow adjustment between the limits specified in 3.5.1 without binding, excessive friction or excessive play. The bun slicing machine shall be connected to a compatible electrical source and shall be switched on. Rotation and cutting edge orientation of the slicing blade shall be observed for conformance with 3.5. Nonconformance with 3.5 and 3.5.1 shall constitute failure of this test.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.- Preservation and packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A.-

5.1.1.1 Preservation.- All exposed ferrous metal surfaces and the slicing knife shall be cleaned by process C-1, thoroughly dried, and coated with type P-14 preservative of MIL-P-116. All bearings and parts requiring lubrication shal be lubricated to capacity with the manufacturer's recommended lubricant containing a rust inhibitor.

5.1.1.2 Protection of preservative.- Surfaces from which preservative compound might be removed by contact with packaging and packing materials shall be covered or wrapped with greaseproof barrier material conforming to type I or II, grade A, class 1 or 2 of MIL-B-121. Barrier material shall be secured with tape conforming to type III, grade B of PPP-T-45, cotton tape or twine, or heat sealed when heat sealable barrier material is used.

5.1.2 Level C.- The bun slicing machine shall be preserved and packaged to afford adequate protection against corrosion, deterioration, and damage during shipment from the supply source to the first receiving activity. The supplier may use his standard practice when it meets this requirement.

5.2 Packing.- Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A.- Each bun slicing machine preserved and packaged as specified in 5.1, shall be packed in a shipping container conforming to overseas type, type 3 load of PPP-B-601, or class 2, style 2 or 4, type 3 load of PPP-B-621. Cushioning, blocking and bracing, or anchoring, and waterproofing shall be in accordance with MIL-STD-1186. Closure and strapping shall be in accordance with the applicable container specification and the strapping shall conform to class B of QQ-S-781.

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:26Z
Check the source to verify that this is the currentversion before use.

5.2.2 Level B.- Each bun slicing machine, preserved and packaged as specified in 5.1, shall be packed in a shipping container conforming to domestic type, style A or B, type 3 load of PPP-B-601, or class 1, style 2 or 4, type 3 load of PPP-B-621. The machine shall be provided with a full-length polyethylene shroud. Cushioning, blocking and bracing, or anchoring shall be in accordance with MIL-STD-1186.

5.2.3 Level C.- Bun slicing machines, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with Uniform Freight Classification Rules or National Motor Freight Classification Rules, as applicable.

5.3 Marking.- In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use.- The bun slicing machines are intended for use in garrison and shipboard feeding areas to slice rolls and buns.

6.2 Ordering data.- Procurement documents should specify the following:

a. Title, number, and date of this specification.

b. When a first article is required (see 3.1, 4.2 and 6.3).

c. Selection of the applicable levels of preservation and packaging and packing (see 5.1 and 5.2).

d. When 50 hertz operation is required and ANSI electrical plug is required (see 3.5.4).

6.2.1 Contract data requirements.- Any requirements for equipment manuals for the items covered by this specification should be included in DD Form 1423 Contract Data Requirements List, and cited in the contract.

6.3 First article.- When a first article is required, it shall be inspected and approved under the appropriate provisions of ASPR 7-104.55. The first article should be a preproduction sample. The first article should consist of one unit. The contracting officer should include specific instructions in all procurement instruments regarding arrangements for inspections and approval of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:26Z
Check the source to verify that this is the current version before use.

Custodians:

Army - GL
Navy - YD
Air Force - 84

Review activities:

Army - MD
Navy - SA

Preparing activity:

Army - GL

Project No. 7320-0502

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:26Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:26Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

Slicing Machine, Bun MIL-S-43818

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 20261O-21T22:26Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
U. S. ARMY NATICK LABORATORIES
NATICK, MASS. 01760

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD-314

U.S.MAIL

Commanding General
U. S. Army Natick Laboratories
ATTN: AMXRES-EQS
Natick, Massachusetts 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:26Z
Check the source to verify that this is the current version before use.