INCH-POUND

MIL-S-43828A
INTERIM AMENDMENT 2 (GL)
28 June 1991

MILITARY SPECIFICATION

STRAP, WEBBING, CARGO TIE DOWN, LIGHTWEIGHT PACK FRAME, M-1972

This interim amendment is approved for use within the Department of the Army, with MIL-S-43828A, dated 7 January 1983.

PAGE 1

2.1, under "SPECIFICATIONS, FEDERAL" Add: "TT-E-529 - Enamel Alkyd Semigloss".

Under "SPECIFICATIONS, MILITARY": Delete "MIL-E-480 - Enamel Baking, Pheno - or Urea Formaldehyde".

PAGE 2

2.1, under "STANDARDS, MILITARY": Delete "MIL-STD-1188 - Commercial Packaging of Supplies and Equipment".

* Under "STANDARDS, FEDERAL": Add "FED-STD-595 - Colors Used in Government Procurement".

2.2, after line 5: Add "D 3951 - Standard Practice for Commercial Packaging" and "D 1005 - Test Methods for Measurement of Dry-Film Thickness of Organic Coating Using Micrometers".

PAGE 3

* 3.3.3, line 3: After "Part No. 3837,": Add "Brookside Part No. SP920; ITW Waterbury Part No. 917".

3.3.3.1: Delete "Type I or II of MIL-E-480" and substitute "Type II of TT-E-529".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:31Z
Check the source to verify that this is the current version before use.

Add new paragraph:

* "3.3.3.2 Epoxy powder coating. As an alternate to the coating, zinc plating, and enameling specified in 3.3.3.1, the surfaces may be prepared and coated as follows:

a. The rivets and two lever components of the fastener shall be prepared for coating by mechanical means. The surfaces shall be thoroughly and uniformly textured by sand blasting with 80-grit aluminum oxide. Prepared surfaces shall be kept clean during the subsequent handling. Handling to be clean-gloved hands or by clean implements. The surfaces shall be retained in a clean environment. The surface shall be epoxy coated not more than 8 hours after sand blasting.

b. The finish coating shall be lusterless green (olive green) No. 34087 of FED-STD-595, electrodeposited epoxy powder coating conforming to H.B. Fuller Company, Kativo Powder No. IF-3561 or equal.

c. The electrodeposited epoxy powder coating shall be baked in accordance with commercial practice.

d. The thickness of the baked coating shall be 0.003 $\pm$ 0.001 inch when tested as specified in ASTM D 1005.

e. The final coating shall be smooth and uniform in appearance, and free from wrinkles and streaks (see 4.4.1.1)."

3.3.4, line 3: Delete "Part No. 3837" and substitute "Part No. 3838, Brookside Part No. SP950".

3.3.4.1, after "3.3.3.1": Add "or 3.3.3.2".

PAGE 5

* 4.4.1.1: After "steel hook" insert "and preparation for and thickness of epoxy powder coating (see 3.3.3.2).".

PAGE 7

4.4.3, line 4: Delete "with the exception that it need not be closed".

Delete the fourth sentence.

PAGE 8

5.1.2: Delete "MIL-STD-1188" and substitute "ASTM D 3951".

5.2.1, line 3, after "PPP-B-636.": Add "The inside dimensions shall approximate 15-1/4 inches in length, 9 inches in width and 15-1/4 inches in depth. Approximate dimensions are furnished as a guide only."

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:31Z
Check the source to verify that this is the current version before use.

PAGE 9

5.2.2, line 3, after "PPP-B-636,": Add "The inside dimensions shall approximate 15-1/4 inches in length, 9 inches in width and 15-1/4 inches in depth."

5.2.3, line 2: Delete "MIL-STD-1188" and substitute "ASTM D 3951".

5.3: Delete and substitute:

"5.3 Palletization. When specified (see 6.2), straps, packed as specified in 5.2, shall be palletized on a 4-way entry pallet in accordance with primary and secondary straps in accordance with bonding means C and D or film bonding means F or G. Pallet patterns shall be pattern number 15 as specified in the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course."

5.4, line 3, after "MIL-STD-129": Add "or ASTM D 3951 as applicable".

PAGE 10

Add new paragraph:

* "6.8 International standardization agreement. Certain provisions of this specification are the subject of international standardization agreement as cited in NATO, STANAG No. 2311. When amendment, revision, or cancellation of this specification is proposed that will modify the international agreement concerned, the preparing activity will take appropriate action through international standardization channels including departmental standardization offices, to change the agreement or make other appropriate accommodations."

NOTE: The margins of this amendment are marked with asterisks to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in there notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Preparing activity:

Army - GL

(Project 8465-A088)

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:31Z
Check the source to verify that this is the current version before use.