MILITARY SPECIFICATION SHEET

PIN-RIVET, THREADED, TYPE VI (PROTRUDING SHEAR HEAD), CLASS 1
(7075 ALUMINUM, 45 KSI Fsu AND 75 KSI Ftu)

This specification sheet is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the pin-rivet, threaded described herein shall consist of this document and the issue in effect of MIL-P-87988.




FIGURE 1. PIN-RIVET, THREADED, TYPE VI (PROTRUDING SHEAR HEAD) CLASS 1 (7075 ALUMINUM, 45 KSI Fsu AND 75 KSI Ftu)

DISTRIBUTION STATEMENT A. Approved for public release; distribution unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:28Z
Check the source to verify that this is the current version before use.

NOTES:

1. Dimensions in inches to be met after application of final coating or surface finish, unless otherwise specified.
2. Concentricity "A" to "D" diameter within .010 FIM.
3. Parts identified with HI-Shear HL22 or M87988/1 are interchangeable in accordance with TABLE III.
4. Hole preparation in accordance with NAS618. (Information only)

1/ 5. Evidence of broken edge across points.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:28Z
Check the source to verify that this is the current version before use.

TABLE I. DASH NUMBERS AND DIMENSIONS

DIA NO.	NOM SIZE	THREAD (MODIFIED)	ØA	B REF	ØD	ØTD	G REF	H	R RAD	S CHAMFER REF	SOCKET				DOUBLE SHEAR POUNDS MIN	TENSION POUNDS MIN
											M HEX	T DEPTH	V MAX DRILL DEPTH	ØY		
5	5/32	.1640-32 UNJC-3A	.262 .242	.312	.1635 .1625	.1595 .1570	.030	.060 .045	.025 .015	.031 x 45°	.0645 .0635	.135 .115	.165	1/	1,760	940
6	3/16	.1900-32 UNJF-3A	.315 .295	.325	.1895 .1885	.1840 .1810	.035	.074 .055	.025 .015	.031 x 45°	.0806 .0791	.135 .115	.175	.119 .104	2,540	1,240
8	1/4	.2500-28 UNJF-3A	.412 .387	.395	.2495 .2485	.2440 .2410	.045	.090 .080	.025 .015	.031 x 45°	.0967 .0947	.150 .130	.200	.142 .122	4,500	2,170
10	5/16	.3125-24 UNJF-3A	.505 .475	.500	.3120 .3110	.3060 .3020	.055	.110 .100	.030 .020	.047 x 45°	.1295 .1270	.170 .150	.240	.180 .160	7,050	3,020
12	3/8	.3750-24 UNJF-3A	.600 .565	.545	.3745 .3735	.3680 .3640	.065	.135 .125	.030 .020	.047 x 45°	.1617 .1582	.200 .180	.279	.217 .197	10,100	4,370
14	7/16	.4375-20 UNJF-3A	.676 .565	.635	.4370 .4360	.4310 .4260	.075	.155 .145	.030 .020	.047 x 45°	.1930 .1895	.230 .210	.318	.253 .233	13,800	6,000
16	1/2	.5000-20 UNJF-3A	.770 .735	.685	.4995 .4985	.4930 .4880	.085	.180 .170	.030 .020	.047 x 45°	.2242 .2207	.260 .240	.363	.289 .269	18,000	7,600

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:28Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

1. Material. 7075 Aluminum alloy (UNS A97075) in accordance with QQ-A-225/9 or QQ-A-430.

2. Protective coating and surface treatment

   All pins shall be anodized in accordance with MIL-A-8625 Type II, Class 1.


   Lubricant:
   B - Solid film lubricant in accordance with MIL-L-46010 TYPE I.
   C - Cetyl alcohol lubricant in accordance with MIL-L-87132 Type I, Grade B.

3. Heat treatment. Age to T6 condition in accordance with MIL-H-6088.

4. Surface texture. Unless otherwise specified, all surfaces shall have a 125 microinch finish.


5. Part number. The part number consists of the letter "M", the basic number of this specification sheet, followed by a lubricant code letter, the first number indicates nominal diameters in thirty-seconds of an inch taken from TABLE I, the grip dash number indicates maximum grip length in sixteenths of an inch taken from TABLE II.

   Example: M87988/1B8-8

   M87988/1B8-8 indicates: Pin-Rivet, Threaded, Type VI (Protruding Shear Head), Class 1 (7075 Aluminum, 45 KSI Fsu and 75 KSI Ftu); anodized; solid film lubricant; 8/32 nominal diameter; 8/16 maximum grip length.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:28Z
Check the source to verify that this is the current version before use.



HEAD MARKING SHALL BE .010 MAXIMUM DEEP. FOR DASH 5,6 AND 8 SIZES ONLY, MARK MANUFACTURER IDENTIFICATION AND M PLUS SLASH SHEET (M1). FOR DASH 10 AND ABOVE, MARK MANUFACTURER IDENTIFICATION PLUS BASIC PART NUMBER (M87988/1-) AND DIAMETER.

TABLE II. GRIP AND LENGTH DIMENSIONS

GRIP DASH NO.	MAX GRIP ±.005	LENGTH ±.010[a/]						
		DIAMETER DASH NUMBER AND THREAD SIZE						
		5 .1640-32	6 .1900-32	8 .2500-28	10 .3125-24	12 .3750-24	14 .4375-20	16 .5000-20
1	.062	.375						
2	.125	.437	.450	.520	.625	.670	.760	.810
3	.188	.500	.513	.583	.688	.733	.823	.873
4	.250	.562	.575	.645	.750	.795	.885	.935
5	.312	.625	.638	.708	.813	.858	.948	.998
6	.375	.687	.700	.770	.875	.920	1.010	1.060
7	.438	.750	.763	.883	.938	.984	1.073	1.123
8	.500	.812	.825	.895	1.000	1.045	1.135	1.185
9	.562	.875	.888	.958	1.063	1.108	1.198	1.248
10	.625	.937	.950	1.020	1.125	1.170	1.260	1.310
11	.688	1.000	1.013	1.083	1.188	1.233	1.323	1.373
12	.750	1.062	1.075	1.145	1.250	1.295	1.385	1.435
13	.812	1.125	1.138	1.208	1.313	1.358	1.448	1.498
14	.875	1.187	1.200	1.270	1.375	1.420	1.510	1.560
15	.938	1.250	1.263	1.333	1.438	1.483	1.573	1.623
16	1.000	1.312	1.325	1.395	1.500	1.545	1.635	1.685
17	1.062	1.375	1.388	1.458	1.563	1.608	1.698	1.748
18	1.125	1.437	1.450	1.520	1.625	1.670	1.760	1.810
19	1.188	1.500	1.513	1.583	1.688	1.733	1.823	1.873
20	1.250	1.562	1.575	1.645	1.750	1.795	1.885	1.935
21	1.312	1.625	1.638	1.708	1.813	1.858	1.948	1.998
22	1.375	1.687	1.700	1.770	1.875	1.920	2.010	2.060
23	1.438	1.750	1.763	1.833	1.938	1.983	2.073	2.123
24	1.500	1.812	1.825	1.895	2.000	2.045	2.135	2.185
25	1.562	1.875	1.888	1.958	2.063	2.108	2.198	2.248
26	1.625	1.937	1.950	2.020	2.125	2.170	2.260	2.310
27	1.688	2.000	2.013	2.083	2.188	2.233	2.323	2.373
28	1.750	2.062	2.075	2.145	2.250	2.295	2.385	2.435
29	1.812	2.125	2.138	2.208	2.313	2.358	2.448	2.498
30	1.875	2.187	2.200	2.270	2.375	2.420	2.510	2.560
31	1.938	2.250	2.263	2.333	2.438	2.483	2.573	2.623
32	2.000	2.312	2.325	2.395	2.500	2.545	2.635	2.685

a/ Nominal length equals maximum grip plus "B". See Figure 1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:28Z
Check the source to verify that this is the current version before use.

TABLE III. INTERCHANGEABILITY

MILITARY PART NUMBER	HI-SHEAR EQUIVALENT PART NUMBER
M87988/1B5-( )	HL22D-5-( )
M87988/1C5-( )	HL22-5-( )
M87988/1B6-( )	HL22D-6-( )
M87988/1C6-( )	HL22-6-( )
M87988/1B8-( )	HL22D-8-( )
M87988/1C8-( )	HL22-8-( )
M87988/1B10-( )	HL22D-10-( )
M87988/1C10-( )	HL22-10-( )
M87988/1B12-( )	HL22D-12-( )
M87988/1C12-( )	HL22-12-( )
M87988/1B14-( )	HL22D-14-( )
M87988/1C14-( )	HL22-14-( )
M87988/1B16-( )	HL22D-16-( )
M87988/1C16-( )	HL22-16-( )
M87988/1B indicates anodized and solid film lubricant.	HL22D indicates anodized and solid film lubricant.
M87988/1C indicates anodized and cetyl alcohol lubricant.	HL22 indicates anodized and cetyl alcohol lubricant.

Custodians:
Army - AV
Navy - AS
Air Force - 99

Review activities:
Army - GL
DLA - IS
NSA - NS

User activities:

Preparing activity:
Air Force - 82

Agent:
DLA - IS

(Project 5320-0542)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:28Z
Check the source to verify that this is the current version before use.