NOTICE
OF CHANGE

INCH-POUND

MIL-STD-1179D
NOTICE 3
9 November 1992

MILITARY STANDARD

LAMPS, REFLECTORS AND ASSOCIATED SIGNALING EQUIPMENT FOR MILITARY VEHICLES

To all Holders of MIL-STD-1179D:

1. The following pages of MIL-STD-1179D have been revised and supersede the page listed:

New Page	Date	Superseded Page	Date Reprinted Without Change
23	14 April 1986	23	
24	14 April 1986	24	17 June 1992

2. RETAIN THIS NOTICE AND INSERT BEFORE TABLE OF CONTENTS.

3. Holders of MIL-STD-1179D will verify that the changes indicated herein have been entered. This notice will be retained as a check sheet. This issuance is a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or cancelled.

Custodian:
Army - AT

User Activities:
Navy - YD, MC
Air Force - 99

Preparing Activity:
Army - AT

(Project 23GP-0019)

DISTRIBUTION STATEMENT A. Approved for public release; Distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T23:23Z
Check the source to verify that this is the current version before use.

Reprinted without Change https://assist.dla.mil -- Downloaded: 2026-10-23T23:23Z
Check the source to verify that this is the current version before use.

TABLE IV. Lighting equipment location for tactical military trucks, trailers and truck tractors of 80 or more inches overall width (see 3.21).

Item	Location on Trucks	Trailers	Truck-tractors	Height above road surface measured from center of item on vehicle at curb weight
Head lamps	On the front, at the same height, 1 on each side of the vertical centerline; as far apart as practicable.		Same as trucks	Not less than 22 inches, nor more than 54 inches.
Tail lamps	On the rear - 1 on each side of the vertical centerline at the same level, as far apart as practicable (see 4.6.1.2).	Sames as trucks	Same as trucks	Not less than 15 inches, nor more than 72 inches.
Stop lamps	On the rear - 1 on each side of the vertical centerline at the same level, and as far apart as practicable.	Same as trucks	Same as trucks	Not less than 15 inches, nor more than 72 inches.
Reflex reflectors	On the rear - 1 red on each side of the vertical centerline, at the same level, as far apart as practicable.	Same as trucks	Same as trucks	Not less than 15 inches, nor more than 60 inches.
	On each side - 1 red as far to the rear as practicable, and 1 amber as far to the front as practicable.	Same as trucks	On each side - 1 amber as far to the front as practicable.	Not less than 15 inches, nor more than 60 inches.

TABLE IV. Lighting equipment location for tactical military trucks, trailers and truck tractors of 80 or more inches overall width (see 3.21) - Continued.

Item	Location on Trucks	Trailers	Truck-tractors	Height above road surface measured from center of item on vehicle at curb weight
Side marker lamps	On each side - 1 red as far to the rear as practicable, and 1 amber as far to the front as practicable.	Not less than 15 inches and on the rear of trailers not more than 60 in (see 4.6.1.6).	On each side - 1 amber as far to the front as practicable.	Not less than 15 inches.
Back-up lamps	On the rear.			No requirement.
Turn signal lamps	At or near the front 1 amber on each side of the vehicle centerline, at the same level, as far apart as practicable.		Same as trucks	On the front - not less than 15 inches, nor more than 83 inches.
	On the rear, 1 red or amber on each side of the vertical centerline at the same height and as far apart as practicable. The turn signal may be part of the stoplight assembly.	Same as trucks	Same as trucks	On the rear - not less than 15 inches, nor more than 83 inches.

Downloaded from assist.dla.mil -- Downloaded: 2026-10-23T23:23Z
Check the source to verify that this is the current version before use.