

FED. SUP CLASS
5935



STYLE "P"- PIN INSERT



STYLE"S"- SOCKET INSERT

Class D & L environment resistant

Class L inactive for design after 23 Mar 76

NOTES:
1. Dimensions are in inches.
2. Unless otherwise specified, tolerance is ±.016.
3. Dimensions and tolerancing in accordance with ANSI Y14.5-1973.
4. MIL-C-5015 crimp contact connectors are intermateable with corresponding solder contact connectors.
5. Unless otherwise shown, corresponding features of style "S" and "P" are identical.
6. For insert arrangements see MIL-STD-1651.
7. For design feature purposes, this standard takes precedence over procurement documents referenced herein.
8. Referenced documents shall be of the issue in effect on date of invitations for bid.

Ⓓ DENOTES CHANGES

APPROVED 14 Jun 71 REVISED Ⓐ 31 Oct 72 Ⓑ 17 DEC 75 Ⓒ 23 MAR 76 Ⓓ 9 April 1979

User activities:

Review activities:

This military standard is approved for use by Naval Air Systems Command, NAVY AS , Department of the Navy , and is available for use by all Departments and Agencies of the Department of Defense.

P.A Navy - AS Other Cust	International interest	TITLE CONNECTORS, PLUG, ELECTRIC, 90° ASSEMBLY, CRIMP CONTACT, AN TYPE	MILITARY STANDARD MS3408(NAVY)
Procurement Specification MIL-C-5015		SUPERSEDES	PAGE 1 OF 6

DD FORM 1 MAY 73 672 (Limited coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

PROJECT NO. 5935-ND66-4

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:04Z
Check the source to verify that this is the current version before use.

This military standard is approved for use by Naval Air Systems Command, NAVY AS , Department of the Navy , and is available for use by all Departments and Agencies of the Department of Defense.

Review activities:

User activities:

SIZE	L - MAX 16 & 12 CONTACTS	L - MAX 8, 4 & 0 CONTACTS
8S	2.475	
10S	2.500	
10SL	2.555	
12S	2.555	
12	2.625	
14S	2.615	
14	2.685	
16S	2.695	
16	2.765	3.165
18	2.810	3.210
20	2.875	3.275
22	2.935	3.335
24	2.995	3.395
28	3.160	3.560
32	3.250	3.650
36	3.375	3.775
40	3.510	3.910
44	3.635	4.035
48	3.760	4.160

EXAMPLE OF PART NO.: MS3408D 22-5SW

MS3408 D 22 - 5 S W

- MS3408 — Basic part number
- D — Class D & L
- S — Material designator S - Stainless steel. Leave blank for aluminum alloy.
- 22 — Shell size
- 5 — Insert arrangement
- S — Contact designator A, B, D, E, P, S
- W — Alternate insert position W, X, Y, or Z. - Leave blank for normal position.


APPROVED 14 Jun 71 REVISED Ⓓ FOR CHANGES SEE SHEET 3

P.A Navy - AS Other Cust	International interest	TITLE CONNECTORS, PLUG, ELECTRIC, 90° ASSEMBLY, CRIMP CONTACT, AN TYPE	MILITARY STANDARD MS3408(NAVY)
Procurement Specification MIL-C-5015		SUPERSEDES:	PAGE 2 OF 6

DD FORM 1 MAY 73 672 (Limited coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:04Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS
5935



(D) REQUIREMENTS:
1. Connector and backshell shall be of the same material and finish in accordance with MIL-C-5015.
2. Connector, backshell and ancillary hardware shall conform to the dissimilar metal compatibility requirements of MIL-STD-454, Requirement 16.

NOTES:
1. Dimensions are in inches.
2. Unless otherwise specified, tolerance is ±.016.
3. For size 8, 4 and 0 contacts, add .375 to overall length.
4. Unit package shall be marked with class DJ part number only. Connector shall be marked with class D part number.
5. This assembly is available only with class D or DS connector plug for jacketed cable.
6. Unless otherwise shown, corresponding features of pin and socket contact connectors are identical.
7. MIL-C-5015 crimp contact, front and rear release connectors and solder contact connectors are intermateable.
8. Dimensions and tolerances in accordance with ANSI Y14.5-1973.
9. Referenced documents shall be of the issue in effect on date of invitations for bid.
10. For design feature purposes, this standard takes precedence over procurement documents referenced herein.

APPROVED 14 Jun 71 REVISED (D) FOR CHANGES SEE SHEET 3

User activities:

Review activities:

This military standard is approved for use by Naval Air Systems Command, NAVY AS , Department of the Navy , and is available for use by all Departments and Agencies of the Department of Defense.

P.A Navy - AS Other Cust	International interest	TITLE CONNECTORS, PLUG, ELECTRIC, 90° ASSEMBLY, CRIMP CONTACT, AN TYPE	MILITARY STANDARD MS3408(NAVY)
Procurement Specification MIL-C-5015		SUPERSEDES.	PAGE 3 OF 6

DD FORM 1 MAY 73 672 (Limited coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:04Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS
5935

ASSEMBLY NO.	CONNECTOR PLUG NO.	BACKSHELL ASSEMBLY NO.	A CABLE ENTRY MAX.	A CABLE ENTRY MIN.	B THREAD CLASS 2	C DIA MAX.	E MAX.	H MAX.	L MAX.	Q MAX.
MS3408DJ 10AXX	MS3406D -10S-XX	MS3188B -04A	.312	.125	.625-24UNEF	.969	.957	3.125	3.000	2.500
10BXX	-10S-XX	-09A	.437	.250			1.145	3.125	3.812	3.250
10DXX	-10S-XX	-05A	.375	.250			1.145	2.500	3.062	2.500
11AXX	-10SL-XX	-04A	.312	.125			.957	3.125	3.000	2.500
11BXX	-10SL-XX	-09A	.437	.250			1.145	3.125	3.812	3.250
11DXX	-10SL-XX	-05A	.375	.250	.625-24UNEF	.969	1.145	2.500	3.062	2.500
13AXX	-12S-XX	-06A	.312	.125	.750-20UNEF	1.062	.957	3.125	3.000	2.500
13BXX	-12S-XX	-71A	.625	.350			1.332	3.312	4.188	3.562
13DXX	-12S-XX	-08A	.500	.350			1.332	2.500	3.188	2.500
13EXX	-12S-XX	-07A	.437	.250			1.145	3.125	3.062	2.500
12AXX	-12-XX	-06A	.312	.125			.957	3.125	3.000	2.500
12BXX	-12-XX	-71A	.625	.350			1.332	3.312	4.188	3.562
12DXX	-12-XX	-08A	.500	.350			1.332	2.500	3.188	2.500
12EXX	-12-XX	-07A	.437	.250	.750-20UNEF	1.062	1.145	3.125	3.062	2.500
15AXX	-14S-XX	-09A	.437	.250	.875-20UNEF	1.156	1.145	3.138	3.188	2.688
15BXX	-14S-XX	-50A	.750	.500			1.551	3.500	4.375	3.625
15DXX	-14S-XX	-10A	.575	.350			1.332	2.312	3.250	2.688
15EXX	-14S-XX	-74A	.312	.125			.957	3.188	3.125	2.625
14AXX	-14-XX	-09A	.437	.250			1.145	3.188	3.188	2.688
14BXX	-14-XX	-50A	.750	.500			1.551	3.500	4.375	3.625
14DXX	-14-XX	-10A	.575	.350			1.332	2.812	3.250	2.688
14EXX	-14-XX	-74A	.312	.125	.875-20UNEF	1.156	.957	3.188	3.125	2.625
17AXX	-16S-XX	-12A	.700	.500	1.000-20UNEF	1.250	1.551	2.938	3.562	2.812
17BXX	-16S-XX	-51A	.937	.625			1.770	3.688	4.688	3.750
17DXX	-16S-XX	-11A	.437	.250			1.145	3.312	3.375	2.812
17EXX	-16S-XX	-40A	.625	.350			1.332	3.312	3.438	2.812
16AXX	-16-XX	-12A	.700	.500			1.551	2.938	3.562	2.812
16BXX	-16-XX	-51A	.937	.625			1.770	3.688	4.688	3.750
16DXX	-16-XX	-11A	.437	.250			1.145	3.312	3.375	2.812
16EXX	-16-XX	-40A	.625	.350	1.000-20UNEF	1.250	1.332	3.312	3.438	2.812
18AXX	-18-XX	-13A	.625	.350	1.125-18UNEF	1.344	1.332	3.438	3.625	2.875
18BXX	-18-XX	-52A	.750	.500			1.551	3.500	3.625	2.875
18EXX	-18-XX	-41A	.312	.125			.957	3.438	3.625	2.875
18FXX	-18-XX	-42A	.437	.250	1.125-18UNEF	1.344	1.145	3.438	3.625	2.875
20AXX	-20-XX	-15A	.625	.350	1.250-18UNEF	1.469	1.332	3.438	3.625	2.875
20BXX	-20-XX	-54A	.750	.500			1.551	3.500	3.625	2.875
20EXX	-20-XX	-55A	1.250	.875			2.113	4.062	4.938	3.875
20EXX	-20-XX	-43A	.437	.250			1.145	3.438	3.625	2.875
20GXX	-20-XX	-16A	.904	.625	1.250-18UNEF	1.469	1.770	3.250	3.750	2.875
22AXX	-22-XX	-56A	.625	.350	1.375-18UNEF	1.594	1.332	3.562	3.875	3.000
22BXX	-22-XX	-17A	.750	.500			1.551	3.625	3.875	3.000
22DXX	-22-XX	-57A	.937	.625			1.770	3.688	3.938	3.000
22EXX	-22-XX	-58A	1.250	.875			2.113	4.062	4.938	3.875
MS3408DJ 22FXX	MS3406D -22-XX	MS3188B -44A	.312	.125	1.375-18UNEF	1.594	.957	3.562	3.875	3.000

APPROVED 14 Jun 71 REVISED Ⓓ FOR CHANGES SEE SHEET 3

User activities:

Review activities:

This military standard is approved for use by Naval Air Systems Command, NAVY AS , Department of the Navy , and is available for use by all Departments and Agencies of the Department of Defense.

P.A Navy - AS	International interest	TITLE CONNECTORS, PLUG, ELECTRIC, 90° ASSEMBLY, CRIMP CONTACT, AN TYPE	MILITARY STANDARD
Other Cust			MS3408(NAVY)
Procurement Specification MIL-C-5015		SUPERSEDES:	PAGE 4 OF 6

DD FORM 1 MAY 73 672 (Limited coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:04Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS
5935

ASSEMBLY NO.	CONNECTOR PART NO.	BACKSHELL ASSEMBLY NO.	A CABLE ENTRY MAX.	A CABLE ENTRY MIN.	B THREAD CLASS 2	C DIA. MAX.	E MAX.	H MAX.	L MAX.	Q MAX
MS3408 22GXX	MS3060 -22-XX	MS3138 -9GA	.937	.250	1.375-18UNEF	1.594	1.385	3.562	3.875	3.000
22HXX	-22-XX	-13A	1.029	.875	1.375-18UNEF	1.594	2.113	3.562	4.062	3.000
24AXX	-24-XX	-19A	.750	.500	1.500-18UNEF	1.719	1.551	3.625	3.875	3.000
24BXX	-24-XX	-59A	.937	.625	↑	↑	1.770	3.688	3.938	3.000
24EXX	-24-XX	-73A	1.250	.875			2.113	4.062	4.313	3.875
24FXX	-24-XX	-96A	.625	.350	↓	↓	1.332	3.562	3.875	3.000
24GXX	-24-XX	-20A	1.144	.875	1.500-18UNEF	1.719	2.113	3.562	4.062	3.000
28AXX	-28-XX	-60A	.750	.500	1.750-12UNS	1.969	1.551	3.750	4.125	3.125
28BXX	-28-XX	-21A	.937	.625	↑	↑	1.770	3.875	4.125	3.125
28DXX	-28-XX	-61A	1.250	.875	↓	↓	2.113	4.062	4.313	3.125
28EXX	-28-XX	-22A	1.375	1.000	1.750-18UNS	1.969	2.363	3.875	4.312	3.125
32AXX	-32-XX	-23A	.937	.625	2.000-12UNS	2.219	1.770	4.125	4.625	3.500
32BXX	-32-XX	-24A	1.250	.875	↑	↑	2.113	4.312	4.625	3.500
32DXX	-32-XX	-62A	1.375	1.000	↓	↓	2.363	4.438	4.625	3.500
32EXX	-32-XX	-25A	1.625	1.250	2.000-12UNS	2.219	2.770	4.375	4.875	3.500
36AXX	-36-XX	-63A	1.250	.875	2.250-16UN	2.469	2.113	4.312	4.938	3.688
36BXX	-36-XX	-27A	1.375	1.000	↑	↑	2.363	4.438	4.938	3.688
36DXX	-36-XX	-64A	1.625	1.250			2.770	4.688	5.062	3.688
36EXX	-36-XX	-29A	1.840	1.437			3.020	4.375	5.188	3.688
36FXX	-36-XX	-97A	.750	.500	↓	↓	1.551	4.000	4.938	3.688
36GXX	-36-XX	-26A	.937	.625	2.250-16UN	2.469	1.770	4.062	4.938	3.688
40AXX	-40-XX	-65A	1.250	.875	2.500-16UN	2.719	2.113	4.312	5.688	4.438
40BXX	-40-XX	-30A	1.375	1.000	↑	↑	2.363	4.438	5.688	4.438
40DXX	-40-XX	-66A	1.625	1.250			2.770	4.688	5.812	4.438
40EXX	-40-XX	-31A	1.840	1.437	↓	↓	3.020	4.375	5.938	4.438
40FXX	-40-XX	-40A	.750	.500	2.500-16UN	2.719	1.551	4.000	5.688	4.688
44AXX	-44-XX	-67A	1.250	.875	2.750-16UN	2.969	2.113	4.312	5.688	4.938
44BXX	-44-XX	-33A	1.375	1.000	↑	↑	2.363	4.438	5.688	4.938
44DXX	-44-XX	-68A	1.625	1.250			2.770	4.688	5.812	4.938
44EXX	-44-XX	-34A	1.840	1.437	↓	↓	3.020	4.375	5.938	4.938
44FXX	-44-XX	-32A	.937	.625	2.750-16UN	2.969	1.770	4.062	5.688	4.938
48AXX	-48-XX	-69A	1.250	.875	3.000-16UN	3.219	2.113	4.312	5.688	4.938
48BXX	-48-XX	-36A	1.375	1.000	↑	↑	2.363	4.438	5.688	4.938
48DXX	-48-XX	-70A	1.625	1.250	↓	↓	2.770	4.688	5.812	4.938
MS3408 48EXX	MS3060 -48-XX	MS3138 -37A	1.840	1.437	3.000-16UN	3.219	3.020	4.375	5.938	4.938

APPROVED 14 Jun 71 REVISED (D) FOR CHANGES SEE SHEET 3

This military standard is approved for use by Naval Air Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

Review activities: NAVY AS

User activities:

PA Navy - AS	Procurement Interest	TITLE CONNECTORS, PLUG, ELECTRIC, 90° ASSEMBLY, CRIMP CONTACT, AN TYPE	MILITARY STANDARD
Other Cust			MS3408(NAVY)
Procurement Specification MIL-C-5015		SUPERSEDES	PAGE 5 OF 6

DD FORM 1 MAY 73 672 (Limited coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:04Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS
5935

SUPERSESSION DATA

Buships Dwg. RE49D2041 Part number	Superseded by Part number
10-214810-**	MS3408DJ10A**
811-**	11A**
812-**	13A**
813-**	12A**
814-**	15A**
815-**	14A**
816-**	17E**
817-**	16E**
818-**	18A**
820-**	20B**
822-**	22B**
824-**	24D**
828-**	28B**
832-**	32B**
836-**	36B**
840-**	40D**
10-214844-**	MS3408DJ44E**

EXAMPLE OF PART NO.: MS3408DJ 18A11PY

MS3408	DJ	18	A	11	P	Y
Basic part number	Class DJ	Material designator S - Stainless steel. Leave blank for aluminum alloy.	Shell size	Designator for sealing range of MS3188 backshell	Insert arrangement	Contact designator	Alternate insert position W, X, Y, or Z. - Leave blank for normal position.

APPROVED 14 Jun 71 REVISED (D) FOR CHANGES SEE SHEET 3

P.A Navy - AS Other Cust	International interest	TITLE CONNECTORS, PLUG, ELECTRIC, 90° ASSEMBLY, CRIMP CONTACT, AN TYPE	MILITARY STANDARD MS3408(NAVY)
Procurement Specification MIL-C-5015		SUPERSEDES:	PAGE 6 OF 6

DD FORM 1 MAY 73 672 *(Limited coordinated)* PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

User activities:

Review activities:

This military standard is approved for use by Naval Air Systems Command, NAVY AS , Department of the Navy , and is available for use by all Departments and Agencies of the Department of Defense.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:04Z
Check the source to verify that this is the current version before use.