INCH-POUND

MIL-A-27198B(USAF)
AMENDMENT 1
15 MARCH 1994

MILITARY SPECIFICATION

ALTIMETER, PRESSURE AAU-7/A

This amendment forms a part of MIL-A-27198B (USAF), dated 29 December 1987, and is approved for use by the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Under SPECIFICATIONS, Federal delete "PPP-B-601"; "PPP-B-636" entirely and add: "PPP-B-1672 Boxes Shipping, Reusable With Cushioning".

Under SPECIFICATIONS, Military, add: "MIL-B-121 Barrier Material, Greaseproofed Waterproofed Flexible".

Under Beneficial block line 3 delete "MMEDO" and add: "TICLA".

PAGE 2

Under STANDARDS, Federal, add: "FED-STD-101 Preservation, Packaging And Packing Materials: Test Procedures".

Under STANDARDS, Military delete "MIL-STD-794" entirely and add: "MIL-STD-2073-1 DOD Material Procedures For Development And Application Of Packaging Requirements." Change "MIL-STD-143" to "MIL-STD-970.

Delete "2.2" entirely.

PAGE 3

Line 3 delete "MIL-STD-143" and add: "MIL-STD-970".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:09Z
Check the source to verify that this is the current version before use.

PAGE 23

Delete "section 5" entirely and add:

"5. PACKAGING

5.1 Preservation-packaging. Unless otherwise specified by the contracting activity, item shall be packaged in Quantity Unit Pack (QUP) of one each. Each item will be provided a preservation method IC-1 In Accordance With (IAW) MIL-P-116.

5.1.2 Cleaning. Item shall be cleaned IAW MIL-P-116 C-1 process.

PAGE 24

5.1.3 Drying. Immediately after cleaning, the item shall be dried following any one or combination of the drying procedures listed in MIL-P-116. The drying procedures employed shall not be injuries to the item.

5.1.4 Level A. Item shall be preserved IAW MIL-P-116 and MIL-STD-2073-1 to provide a method IC-1.

5.1.5 Level C. Item shall be individually preserved in a manner that will afford adequate protection against corrosion, deterioration, and physical damage during shipment from the supply source to the first receiving activity as specified in MIL-P-116 AND MIL-STD-2073-1.

5.2 Packing. Packing shall be level "A", "B", or "C", as specified (see 6.2).

5.2.1 Container-cushioning. Unit container requirements shall conform to MIL-B-121, barrier material, unless otherwise specified by the contracting activity. Unit containers shall be large enough to allow for application of sufficient cushioning/ wrap material, between the item and unit container. Item cushioning/wrap material shall be off sufficient density and thickness to protect the unit container from punctures. Intermediate/shipping containers shall be large enough to allow for application of sufficient cushioning material, between the unit container and intermediate/shipping container. Cushioning material shall be of sufficient density and thickness to insure shock transmission does not exceed peak values in G's established for the item.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:09Z
Check the source to verify that this is the current version before use.

5.2.2 Level A. Fiberboard containers do not meet Level "A" container criteria.

5.2.3 Level B. Item will be preserved as specified in 5.1 and shall be packed in exterior containers conforming to PPP-B-1672, weather-resistant unless otherwise specified by the contracting activity. Exterior container shall be uniform shape, size and minimum tare and cube, consistent with the protection required. Closure shall be in accordance with appropriate PPP-B-1672 procedures, as specified by Special Packaging Instructions (SPI), and contracting activity.

5.2.4 Level C. Item will be packed in such a manner that will afford adequate protection against physical damage during direct domestic shipment from the supply source to the first receiving activity. These packs shall conform to MIL-STD-2073-1.

5.3 Marking. Unit, intermediate, and exterior containers shall be marked IAW special markings required by the contracting activity, SPI and MIL-STD-129.

5.4 Inspection and Test. Test of methods of preservation shall be accomplished in accordance with section 4 of MIL-P-116 to insure compliance with section 5 of this specification. Packaging tests shall be conducted IAW rough handling as specified in FED-STD-101.

Under 6. NOTES. add: "(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)"

6.2 Delete line 1 entirely and add: Acquisition requirements. Acquisition documents must specify the following:"

Add: "6.2.e. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1)".

Custodian:
AIR FORCE -99

Preparing Activity:
AIR FORCE -71

Project Number:
6610-F379

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:09Z
Check the source to verify that this is the current version before use.