MILITARY SPECIFICATION

INDICATOR, POSITION, VARIABLE NOZZLE

This amendment forms a part of MIL-I-27191B(USAF), dated 1 Nov 1979, and is approved for use within the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Delete "2.1" and add: "2.1 Government documents."

Add: "2.1.1 Specification standards, and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation."

Under SPECIFICATIONS, Federal, add: "PPP-B-601 Boxes, Wood, Cleated Plywood."

Delete address on lines 3 and 4 of beneficial comments block and add: "Oklahoma City Air Logistics Center/MMEDO, Tinker AFB OK 73145-5990."

Under SPECIFICATIONS, Military, delete "MIL-E-5272."

Under STANDARDS, Military, add: "MIL-STD-810C Environmental Test Methods and Engineering Guidelines."

Add: 2.2. Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

ASTM D3951 packaging, Commerical

(Application for copies should be addressed to: ASTM, 1916 Race St, Philadelphia PA 19103.)

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services."

Add: "2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:06Z
Check the source to verify that this is the current version before use.

Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained."

PAGE 7

Add: "4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsiblity of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material."

Delete "4.4.3.2 and add new "4.4.3.2 Vibration failure. The indicator shall be subjected to the vibration test of MIL-STD-810C Method 514.2, procedure I. The test shall follow curve C of figure 514.2-2 to a maximum freg of 52 Hz. The test shall be conducted while the indicator is being operated on 28v dc and while the blubs are illuminated with 5V power.

PAGE 9

Delete Section 5 in its entirety and add:

"5. Packaging

5.1. Preservation-packaging: Preservation-packaging shall be level A, C, or industrial as specified. (see 6.2)

5.1.1. Level A.

5.1.1.1. Cleaning. Indicator shall be cleaned in accordance with process C-1 of MIL-P-116.

5.1.1.2. Drying. Indicator shall be dried in accordance with process D-4 of MIL-P-116.

5.1.1.3. Preservation-application. Not applicable.

5.1.1.4. Unit packaging. Unless otherwise specified by the contracting activity, each indicator shall be packaged in quantity unit packs of one each in accordance with Method 1C1 of MIL-P-116. Overbox completd pack in PPP-B-636 container. Apply sufficient cushioning material between bag and unit container of a type, density, and thickness to insure shock transmission does not exceed peak values in G's established for the indicator when completed packs are subjected to the rough handling drop tests of MIL-P-116.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:06Z
Check the source to verify that this is the current version before use.

5.1.2 Level C. Each indicator shall be clean, dry, and individually packaged in a manner that will afford adequate protection against corrosion, deterioration, and physical damage during shipment from supply source to the first receiving activity.

5.1.3. Industrial. The Industrial preservation of indicator shall be in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, C, or Indsutrial as specified (see 6.2).

5.2.1. Level A. Indictor packaged as specified in 5.1.1 shall be packed in shipping containers confrming to PPP-B-601, Styles A or B, Class overseas, unless otherwise specified by the contracting activity. Insofar as practical, exterior shipping container shall be of uniform shape, size, minimum tare and cube consistent with the protection required.

5.2.2. Level B. Indicator packaged as specified in 5.1.1. shall be packed in shipping containers conforming to PPP-B-636, class weather-resistent, unless otherwise specified by the contracting activity. Other requirements as specified in 5.2.1. apply.

5.2.3. Level C. Packing shall be applied which affords protectin from domestic shipment from the supply source to the first receiving activity for immediate use. This level shall conform to applicable carrier rules and regulations.

5.2.4. Industrial. The packaged indicator shall be packed in accordance with ASTM D3951.

5.3. Marking. In addition to any other markings required by the contract or order (see 6.2), interior and exterior containers shall be marked in accordance with MIl-STD-129."

PAGE 11

6.3 Line 12 and 13 delete "HQ AFLC CASO/LODS, Federal Center, Battle Creek, MI 49016" and add: "Oklahoma City Air Logistics Center/MMEDO, Tinker AFB OK 73145-5990."

Custodian
Air Force -99

Preparing activty:
Air Force -71

Project No
6620-F424

Source: https://assist.dla.mil -- Downloaded: 202610-20T11:06Z
Check the source to verify that this is the currentversion before use.