INCH-POUND

MIL-S-8805/47E
AMENDMENT 1
31 August 1998

MILITARY SPECIFICATION SHEET

SWITCHES, SENSITIVE, SPDT, LEVER, 25 AMPERES, HERMETIC

This amendment forms a part of MIL-S-8805/47E, dated 10 October 1972, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Figure 1, centerline to centerline dimension 1.000±.002, delete and substitute:

"1.000 REF"

Figure 1, bottom left side, delete MS25011-3 configuration.

PAGE 2

After Operating characteristics, add the following:

"Part or Identifying Number (PIN): See table I."

Table I, delete and substitute the following:

"TABLE I. Operating characteristics 1/

PIN	A Maximum free position	B Maximum pretravel	Operating position	Maximum differential travel	Minimum overtravel	Actuating force	Minimum release force
	inch	inch	inch	inch	inch	oz	oz
MS25011-1 2/	.600	.065	.53	.020	.010	16 ± 8	4
MS25011-2 2/	.610	.085	.53	.020	.010	25 ± 3	4
MS25011-3 3/	.790	.065	.72	.020	.010	16 ± 6	4
MS25011-4	.790	.065	.72	.020	.010	16 ± 6	4

1/ ±20 percent variation from specified values acceptable after test.
2/ MS25011-1 and MS25011-2 - inactive for new design.
3/ MS25011-3 has been canceled without replacement.

DISTRIBUTION STATEMENT A Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:10Z
Check the source to verify that this is the current version before use.

Table II, delete and substitute:

"Table II. Electrical ratings

PIN	Load	Current capacity (amperes)		
		28 Vdc	115 Vac, 60 Hz	120 Vdc
MS25011-1 MS25011-2	Resistive Inductive	25 10	1 1	1 .5
MS25011-4	Resistive Inductive	25 8	1 1	.5 .5

"

Material, delete and substitute:

"Material: Phenolic terminal block may be type CFG in accordance with ASTM D 5948-96."

Table III, delete and substitute:

"Table III. Group submission

Examination or test	Basic switch	Other switch	Extent of approval
Qualification inspection table of MIL-S-8805 (except operating characteristics in group VI shall be tested immediately preceding short circuit, rather than as the final test).	MS25011-2 1/ and MS25011-4 (all sample units)	MS25011-1 1/ (2 sample units) 1. Visual and mechanical examination 2. Operating characteristics	All

1/ MS25011-1 and MS25011-2 are inactive for new design."

Custodians:
Army - CR
Navy - EC
Air Force - 85

Preparing activity:
DLA - CC

(Project 5930-1649)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:10Z
Check the source to verify that this is the current version before use.