INCH-POUND

MIL-S-8805/47E
AMENDMENT 2
27 January 1999
SUPERSEDING
AMENDMENT 1
31 August 1998

MILITARY SPECIFICATION SHEET

SWITCHES, SENSITIVE, SPDT, LEVER, 25 AMPERES, HERMETIC

This amendment forms a part of MIL-S-8805/47E, dated 10 October 1972, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

FIGURE 1, centerline to centerline dimension “1.000 ±.002”, delete and substitute “1.000 REF”.

FIGURE 1, bottom left side, delete “MS25011-3 configuration”.

PAGE 2

After operating characteristics, add: "Part or Identifying Number (PIN): See table I."

* TABLE I, delete and substitute:

“TABLE I. Operating characteristics. 1/

PIN	A Maximum free position	B Maximum pretravel	Operating position	Maximum differential travel	Minimum overtravel	Actuating force	Minimum release force
	Inch	Inch	Inch	Inch	Inch	oz	oz
MS25011-1 2/	.600	.065	.53	.020	.010	16 ±8	4
MS25011-2 2/	.610	.085	.53	.020	.010	25 ±3	4
MS25011-3 3/	.790	.065	.72	.020	.010	16 ±6	4
MS25011-4	.610	.085	.53	.020	.010	25 ±3	4

1/ ±20 percent variation from specified values acceptable after test.
2/ MS25011-1 and MS25011-2 - inactive for new design.
3/ MS25011-3 has been canceled without replacement.”

TABLE II, delete and substitute:

"TABLE II. Electrical ratings.

PIN	Load	Current capacity (amperes)		
		28 V dc	115 V ac, 60 Hz	120 V dc
MS25011-1	Resistive	25	1	1
MS25011-2	Inductive	10	1	.5
MS25011-4	Resistive	25	1	.5
	Inductive	8	1	.5

“

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:10Z
Check the source to verify that this is the current version before use.

Material, delete and substitute: "Material: Phenolic terminal block may be type 94V-O in accordance with UL94."

* Quality assurance, delete and substitute:

"Quality assurance:
Group B: Explosion test not applicable
Group B: Not applicable to inactive part numbers."

* TABLE III, delete and substitute:

"TABLE III. Group submission.

Examination or test	Basic switch 1/	Other Switch	Extent of approval
Qualification inspection table of MIL-S-8805 (except operating characteristics in group VI shall be tested immediately preceding short circuit, rather than as the final test).	MS25011-2 2/ and MS25011-4 (all sample units)	MS25011-1 2/ (2 sample units) 1. Visual and mechanical examination 2. Operating characteristics	All

1/ MS25011-1 and MS25011-2 are inactive for new design.
2/ Qualification testing of MS25011-4 may be waived if testing is performed on MS25011-2."

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - CR
Navy - EC
Air Force - 85

Preparing activity:
DLA - CC

(Project 5930-1673)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:10Z
Check the source to verify that this is the current version before use.