INCH-POUND

MIL-S-8805/50B
16 June 1993
SUPERSEDING
MIL-S-8805/50A
10 February 1971

MILITARY SPECIFICATION SHEET

SWITCH, SENSITIVE, ROLLER-LEVER, WATERTIGHT

Inactive for new design after 10 February 1971

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation MIL-S-8805






FIGURE 1. Dimensions and configuration

(B) denotes changes

DISTRIBUTION STATEMENT A Approved for public release, distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:11Z
Check the source to verify that this is the current version before use.





Inches	mm	Inches	mm	Inches	mm	Inches	mm
.005	0 13	.098	2.49	.562	14 ?	.875	22.23
010	0 25	.125	3.18	.565	14.35	.938	23.83
.015	0.38	.193	4 90	575	14.61	1.031	26.19
.025	0.64	.250	6.35	.594	15.09	1 125	28.58
.031	0 79	.281	7 14	.621	15.77	1.219	30.96
.047	1.19	.312	7 92	.655	16.64	1.281	32.54
.062	1.57	.375	9.53	.656	16.66	1.312	33.32
.070	1.78	.422	10.72	.708	17.98	1.563	39.70
.080	2.03	.438	11.13	725	18.42	1.781	45.24
.085	2 16	.500	12.70	.805	20.45	1.875	47.63
.094	2.39	.554	14.07	.812	20.62	2 562	65 07

NOTES
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ±.015, except ±.005 for ferrule and seal gland
4. The "A" pin shall be permanently indicated with a circle.
5. One hole on small end of gland shall be permanently marked with a circle, to be mounted on "A" pin
6. The circuit and the terminal arrangement shall be marked on the switch case.
(B) 7. The dimensions of the electrical conduit coupling nut shall be in accordance with AN3054-8 Alternative base metals and protective finishes, as approved by the qualifying activity, may be used

FIGURE 1 Dimensions and configuration - Continued

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:11Z
Check the source to verify that this is the current version before use.

REQUIREMENTS

Dimensions and configuration: See figure 1

Enclosure design. 3 (watertight).

Temperature characteristic 2 (-65°C to +125°C)

(B) Shock: 50 g's, sawtooth, in accordance with method 213, test condition G, MIL-STD-202

Sinusoidal vibration grade: 1 (10 to 500 Hz).

Material:

(B) Ferrule: Deep drawn steel gauge number 22 (.031 inch), plated to resist corrosion.

Seal gland. Silicone rubber

Weight: 7.0 ounces maximum

Operating characteristics

Actuating force 4 0 +2, -0 pounds

Pretravel. 100 ±.031 inch.

(B) Overtravel. .250 inch minimum

(B) Movement differential: .062 +.025, - 010 inch

(B) Full overtravel force: 11 +4, -3 pounds.

(B) Coincidence of operating and releasing points: In switches having more than one moving contact, the moving contacts shall open and close together within .015 inch of actuator travel as measured at the roller axis.

Contact resistance: Not applicable.

Mechanical endurance: 200,000 cycles

Electrical endurance: 100,000 cycles.

Electrical ratings See table I

TABLE I. Electrical ratings

Load	Sea level	
	28 V dc	115 V ac, 400 Hz
	Amperes	Amperes
Resistive	15	
Inductive	10	10
Lamp	5	10 6

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:11Z
Check the source to verify that this is the current version before use.

Qualification

Group submission See table II

(B) Quality conformance

Group B inspection. Not applicable

Part or Identifying Number (PIN): See table III.

TABLE II. Qualification inspection - group submission.

Examination or test	Basic switch	Other switch samples	Extent of approval
Qualification inspection table of MIL-S-8805, groups I, II, III, V, VI, VII, and VIII	MS25040-3	MS25040-1, -2, and -4 Two sample units each, visual and mechanical examination	All

TABLE III. Part or Identifying Number (PIN)

PIN	Contact arrangement
MS25040-1	2 circuit
MS25040-2	SPDT
MS25040-3	4 circuit
MS25040-4	DPDT

CONCLUDING MATERIAL

Custodians
Army - ER
Navy - EC
Air Force - 85

Review activities
Army - GL, MI
Navy - AS, OS, SH
Air Force - 99
DLA - ES

User activities
Army - AR
Navy - MC
Air Force - 19

Preparing activity
Navy - EC

Agent
DLA - ES

(Project 5930-1545)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:11Z
Check the source to verify that this is the current version before use.