INCH-POUND
MIL-M-24784/1(SH)
6 September 1994

ASSOCIATED DETAIL SPECIFICATION

MANUAL, TECHNICAL CHANGE PACKAGE REQUIREMENTS

This specification is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification sets forth the development requirements for changes to technical manuals in support of modifications to weapon systems and equipments, and correction of technical deficiencies.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

MILITARY

MIL-M-24784 - Manual, Technical: General Acquisition and Development Requirements.
MIL-M-24784/2 - Manual, Technical Revision Requirements.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Document Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, SEA 03R42, Naval Sea Systems Command, 2531 Jefferson Davis Hwy, Arlington, VA 22242-5160 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N6946 AREA TMSS
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 20261O-20T02:15Z
Check the source to verify that this is the current version before use.

2.2 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 General. The change package shall conform to the format of the basic manual, and shall incorporate all approved information (for example, engineering change proposals, ship alterations, ordnance alterations, machine alterations, field changes, and so forth). The changes shall also incorporate all advance change notices (see 6.3.1) and outstanding deficiencies that have been resolved by the Government. A change package shall not affect more than 25 percent of the total pages in the published manual.

3.2 Change package content. Each change package shall include the following:

(a) A replacement title page.
(b) A replacement list of effective pages.
(c) An instruction sheet.
(d) As applicable, replacement pages for the table of contents, general information page(s), lists of abbreviations or symbols, system and component diagrams, and text.

3.3 Cover and title page. In accordance with Appendix C of MIL-M-24784, the title page (and cover, if required) of changed manuals shall be updated to:

(a) Reflect the current distribution statement (see 6.3.3), warning (if required), and destruction notice. A new title page shall be supplied with the distribution statement centered, one-fourth inch below the SYSCOM seal.
(b) Indicate the change letter and date in addition to the original date of the publication, that is, CHANGE A 15 July 1994. The change identification shall be entered below the original publication date in the lower right-hand corner of the page.
(c) Indicate the current supersession notice.

3.4 List of effective pages. On the list of effective pages, above the listing of pages contained in the manual, shall be a list of all published change identification numbers, letters, and dates. The current change shall be included in this list.

3.5 Change instruction sheets. The change instruction sheet shall provide instructions for inserting new and revised pages, and for disposing of superseded pages (see figure 1-1). The instruction sheet shall be the first page of a change package. The instruction sheet shall include the following, as applicable:

(a) "Change Instruction Sheet" shall appear at the top of each page (below the basic technical manual identification number).

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:15Z
Check the source to verify that this is the current version before use.

(b) The technical manual change identification number shall appear on the top-left of each change instruction sheet page, but below the page identifier (that is, "Change Instruction Sheet"). The change shall be identified with a permanent identification number assigned by the Government (see 3.12 for interim changes).

(c) The security classification shall be located on all pages of classified interim or permanent changes and shall appear on the top (above the manual identification number) and bottom center of each page.

(d) The total number of pages included in the change shall be indicated on the first page for the instruction sheet.

(e) If other than the change date, a statement shall be included indicating when the change is in effect. If it supersedes an earlier change, a statement of that fact shall be given.

(f) If an equipment change is involved (field or production change), a statement shall be included indicating the purpose of the change and the extent (serial numbers or conditions of application) to which it applies to the equipment population and identify the alteration by number.

(g) When the equipment nomenclature has been changed because of a production or field change to the equipment, the nomenclature references in the text and illustrations need not be modified merely to include the new nomenclature providing that information equivalent to the following is included as general information:

"Unless otherwise specified, all references in the manual to Radar Set AN/SPS-10 apply equally to Radar Set AN/SPS-10A."

(h) If an equipment change does not effect the entire equipment population, the change shall be developed so that it will describe both the effected and uneffected equipment.

(i) When the change applies to the entire equipment population, the change shall cover only the modified equipment. A note shall be included in the first paragraph of the instruction sheet to the effect that maintenance support activities shall not dispose of the superseded pages until it is established that all of the equipment population has been modified.

(j) Instructions shall be concise and clear, illustrations and diagrams corrected, as applicable, and replacement pages provided.

(k) The instructions shall be followed by a statement that the change instruction sheet shall be inserted in the manual immediately following the front cover and title page for reference purposes.

(l) The instructions shall specify the deleted or added pages and include information for completing the change record page.

(m) The method used to identify new and changed material shall be explained.

(n) For changes pertaining to equipment modifications, the user shall be instructed not to insert a change in a manual until the modification has been accomplished.

(o) Printed matter shall be arranged on the page so that all copy is readable when bound in the manual.

(p) A bar-coded stock number for the change package shall appear in the lower left-hand corner of the first page.

Source: https://assist.dla.mil -- Downloaded: 2026l0-20T02:15Z
Check the source to verify that this is the currentversion before use.

3.6 Replacement pages. Changes to an existing manual shall be issued in the form of replacement pages. The change shall be developed in accordance with this specification, development details of MIL-M-24784, and style, format and content of the applicable associated detail specification. Pages shall be revised only when significant technical changes are required.

(a) Replacement pages shall include all corrections issued in previous changes in addition to all other outstanding corrections required (see 6.2).
(b) Changes made to any given page of the manual shall require a complete check and correction of associated pages that reflect the subject change.
(c) A change letter for the change shall be used to identify changes and will be assigned by the Government.
(d) When the published change package is available, the change pages shall be inserted (by the supplier) into the basic manuals to be shipped with the equipment.
(e) The publication identification number shall appear at the top of each replacement page and shall remain the same as the basic manual.
(f) When the RDC of the change is submitted for review and acceptance, the new change package publication identification number and change letter shall be requested from the Government.
(g) When a change is made to a maintenance dependency chart (MDC), the entire chart shall be reprinted, including the backup page. Markings shall be the same as for all changed pages.
(h) As necessary, indexes shall be updated to reflect changes and shall be issued as replacement pages.
(i) Change pages shall be developed and punched or drilled to the exact size and dimensions of the pages they replace.

3.6.1 Additions. All paragraphs and pages shall be added and numbered as follows:

3.6.1.1 Numbering of added material. When paragraphs, illustrations, tables, and pages are added by a change, existing paragraphs, illustrations, tables, and pages shall be renumbered. If this involves renumbering more than 10 paragraphs or will effect more than five pages, the following method shall be used:

(a) When paragraphs are added at the end of a sequence, the next consecutive number shall be used.
(b) When paragraphs are added in the middle of a sequence, paragraphs shall be numbered by adding an alpha character (for example, 2.4A, 2.4B, 2.4.1A, and so forth), to the preceding paragraph number.
(c) Added illustrations, tables, and pages shall be numbered by adding a decimal (for example, figure 3-2.1, page 3-26.1, and so forth).
(d) When it is necessary to add an illustration, table, and page between items which have already been added by the preceding method, an alpha character shall be used (for example, a page added between 3-26.2 and 3-26.3 would be 3-26.2A).
(e) Pages shall not be added between a right-hand (odd numbered) and a left-hand (even numbered) page.

Source: https://assist.dla.mil -- Downloaded: 2026l0-20T02:15Z
Check the source to verify that this is the currentversion before use.

(f) When new material is to be added to a right-hand page, any overrun shall be carried to the left-hand page. The overrun from the left-hand page shall be placed on the added page.

(g) Where material is to be added to a right-hand page (for example, 2-5) and adequate blank space is available on the preceding left-hand page (for example, 2-4), material at the top of 2-5 shall be moved to the bottom of 2-4 and the new material added to 2-5.

3.6.1.2 Multisheet illustration. Sheets added to a set of multisheet illustrations which fall between existing sheets shall be assigned the preceding number plus a decimal number. For example: if a sheet is added between sheets 2 and 3, the added sheet becomes 2.1. If possible, the new sheet shall be added after the last sheet and be assigned the next consecutive number.

3.6.1.3 Index number. Where a change to an illustration adds index numbers between existing numbers, the added numbers shall be the same as the preceding index number with an added decimal number, for example, 22.1, 22.2, and so forth.

3.6.2 Deletions.

3.6.2.1 Deleted paragraphs, steps, illustrations, tables. Where a change deletes a paragraph, step, substep, illustration, or table without substituting another, the space formerly occupied by the paragraph, step, substep, illustration, or table can be used for other instructions, allowing for sufficient space to provide 1/4 inch above and below a sentence such as "4-2 (Deleted.)". The table of contents, list of illustrations, list of tables and index shall be changed as necessary.

3.6.2.2 Deleted pages. When page number continuity is broken by deletion of a page and a blank page results, a statement indicating the deletion shall be placed in the bottom margin (right or left corner, or centered, as space permits) of the preceding page or top margin of the succeeding page. For example:

"All data on page ....., including Figure ..... deleted."

This also applies when two back to back pages are deleted. The statement shall be used only if the same manual change affects a preceding or succeeding page. A preceding or succeeding page shall not be changed merely to add this statement. In such instances, the list of effective page listings will be adequate.

3.6.3 Changes to Illustrations. When changes are made to illustrations, the original artwork shall be used unless the development of new artwork is less expensive. Sheets added to a set of multisheet illustrations which fall between existing sheets shall be assigned the preceding number plus a decimal number. For example: if a sheet is added between sheets 2 and 3, the added sheet becomes 2.1. If possible, the new sheet shall be added after the last sheet and be assigned the next consecutive number. If a callout is deleted from an illustration, the word "(Deleted)" in parentheses shall be placed after the appropriate number in the legend.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:15Z
Check the source to verify that this is the current version before use.

3.6.4 Change symbols for illustrations. Changes to line drawings, charts, illustrations, graphs, diagrams, and schematics shall be indicated by shading and screening to highlight the area containing the changed information (see MIL-M-24784, figure 85). Extensively changed presentations shall be indicated by a screen border around the effected area. For minor changes not suitable for shading or screening, a miniature pointing hand shall be used.

3.6.5 Change page numbering and sequence. Change pages which replace pages in the manual shall carry the same number as the page they replace. Where the reverse side of the page in the manual is uneffected by the change, the replacement page shall carry both the change page and its unchanged back-up page. Added pages shall be numbered by adding sequential decimal numbers to the preceding page number (for example, 12.1, 22.1, 22.2). Added pages may be printed on one side only if the addition of a back-up page would disrupt the sequence of the presentation within the volume or part.

3.6.6 Blank page number. A blank page shall be assigned a number but it shall appear on the preceding or following page. For example: if page 10 of Chapter 1 is blank, page 9 shall bear the number 1-9/(1-10 blank); if page 9 of Chapter 1 is blank, page 10 shall bear the number (1-9 blank)/1-10. When applicable, an added page, such as 1-10.1, shall show that 1-10.2 is blank.

3.7 Change designator. Each page containing changed or added material shall bear the words "Change ___" placed at the bottom of the page in the same corner and on the same line as the page number. The change designator shall begin approximately 1/2-inch to the right of the page number for an even numbered page, and end approximately 1/2-inch to the left of the page number for an odd numbered page (see figure 1-2). This change designator requirement is also applicable to all added pages, including those placed at the end of a manual.

3.8 Change symbols for text and tables. Changes (except as noted below) to the text and tables (including new material on added pages) shall be indicated by a vertical line in the margin extending the entire area of the material effected (outer margin for double column material, margin opposite binding edge for single column material) (see figures 1-1 and 1-2). Exception: pages with emergency markings (black diagonal lines around three edges) shall have the vertical line symbols placed along the inner margins for single column; for double column, the vertical line symbols which apply to the outside column shall be placed in the gutter between columns. Previous change symbols on a page shall be deleted when a page is subsequently changed. Symbols shall show current changes only. The vertical line change symbol shall be 6-point in width. It may be reduced 10 percent in width to allow for automatic composing equipment use providing it remains legible and obvious. If the composing equipment used is incapable of producing a vertical line, change symbols such as a number sign "#", plus sign "+", black circle or black square, or the letter "C", "R", or "X" may be used in lieu of the vertical line, if approved by the Government. The meaning of these symbols shall be explained in the change instruction sheet or foreword, preface or introduction of the manual. Change symbols are not required for:

(a) Introductory material.
(b) Indexes where the change cannot be identified.
(c) Blank space resulting from the deletion of text, an illustration or part of an illustration, or a table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:15Z
Check the source to verify that this is the current version before use.

(d) Correction of minor inaccuracies such as spelling, punctuation, relocation of material, renumbered paragraphs, and so forth, unless such correction changes the meaning of instructive information or procedures.
(e) Replacement or addition of a complete part, chapter, or section.

3.9 Numbering of changes. Each change package to a manual shall be lettered, as specified by the Government, in sequence and dated (see MIL-M-24784). Identification of changes after each revision of a manual shall begin over again with the letter A as applicable. The change date shall be the date at which the final material to be included was received (copy freeze date).

3.10 Final reproducible copy (FRC). FRC shall be furnished for altered and additional pages. Copy shall be furnished for both sides of the page on which the change is made.

3.11 Rapid action changes. When specified, rapid action changes shall be provided. Printed pages from the manual may be used for the changed and unchanged pages, if legible and applicable. Only changed paragraphs, tables, or illustrations need to be developed and mounted in the proper place (size permitting) on the existing printed page. Copy shall be furnished for both sides of the page on which a change is made, even though change is made to one side only. Pages removed from the printed manual to be used without change shall be pasted to bond paper of the same size as the manual. Unchanged portions of pages may also be mounted and used in conjunction with the new material. Unless otherwise specified, front matter (title page, list of effective pages, change instruction sheet, and so forth) shall be provided as a part of the change package.

3.12 Interim changes. Interim changes are temporary changes. Each interim change package shall be provided with a complete set of front matter. Interim changes shall be followed up by the issue of a permanent change page package.

3.12.1 Pen-and-ink corrections. Pen-and-ink corrections are interim changes and are not acceptable unless this change process is specified by the Government. Unless specified elsewhere, pen-and-ink corrections for a minor change is prohibited.

3.12.2 Advanced changes. As specified, change pages or pen-and-ink corrections shall be developed to correct an urgent deficiency.

3.12.3 Change instruction sheet. A "T" shall be entered in the front of the interim change package identification number. This change number shall be assigned by the Government.

3.12.4 Deleted paragraph. When a paragraph is to be deleted, the number of the page on which it appears shall be stated, followed by a statement that the paragraph is rescinded. For example:

"Page 3. Paragraph 2-1 is rescinded."

Source: https://assist.dla.mil -- Downloaded: 20260-20T02:15Z
Check the source to verify that this is the current version before use.

3.12.5 Changes to tabular material. When interim changes are made in lengthy tabular material, deletions, additions, and substitutions shall be listed in page sequence and the page number on which each change occurs shall be shown. For example:

"Page B-15, Appendix B.

The following are deleted from the list of classes:

Page B-15.	5133 Drills, Counterbores and Countersinks
	5905 Resistors
Page B-16.	6115 Generators and Generators Sets

The following changes are made in the columns indicated:

Page B-21.	The description of class 4010 is changed to read "Chain and Wire Rope".
Page B-27.	Class number "2960", appearing between class 2930 and 2940, is corrected to read "2935"."

3.12.6 Interim additions. The number of the page where the added material would appear if it were incorporated into the existing manual shall be stated, followed by a statement to the effect that the material is being added. This shall be followed by the number, title, and text of the new paragraph. For example:

"Page 3-14. Paragraph 3.5.1A and 3.5.1B are added after 3.5.1.

Paragraph 3.5.1A - Refer to S0005-XX-XXX-XXX for coaxial connector repair procedures.

Paragraph 3.5.1B - Refer to S0005-XX-XXX-XXX for LRU checkout and trouble-shooting procedures."

3.12.7 Text supersession. The number of the page on which the paragraph appears shall be stated, followed by a statement to the effect that the paragraph is superseded. This shall be followed by the number, title, and text of the superseding paragraph. For example:

"Page 1-6. Paragraph 1.2 is superseded as follows:

1.2	RECORD AND REPORT FORMS.
1.2.1	Depreservation Guide. STD Form XXXX, Depreservation Guide for Engineer Equipment.
1.2.2	Other Forms. For other record and report forms applicable to operator, crew and organizational maintenance, refer to S0005-XX-XXX-XXX."

Source: https://assist.dla.mil -- Downloaded: 20260-20T02:15Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of Sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.2 Quality control. Unless otherwise specified, the quality conformance inspection, Government inspection, validation, verification, technical manual quality assurance (TMQA) program reviews, technical manual evaluation records and rejection requirements shall be in accordance with MIL-M-24784.

5. PACKAGING

5.1 Packaging requirements. Unless otherwise specified (see 6.2), the packaging and preservation requirements for delivery of book plans, review draft copies, preliminary technical manuals, final reproducible copy, technical manuals, replenishment materials, changes and revisions shall be in accordance with MIL-M-24784.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. Technical publication change packages in accordance with this specification are intended for use in the installation, operation, maintenance, repair, and logistics support of modified weapon equipment and systems or for accomplishment of assigned missions.

6.2 Acquisition requirements. Acquisition documents must specify the following:

(a) Title, number, and date of this specification (or any TMCR referencing this specification).
(b) Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1).

Source: https://assist.dla.mil -- Downloaded: 20260-20T02:15Z
Check the source to verify that this is the current version before use.

(c) When a change to a technical manual is required to support an equipment or system, changes must be specified only when they pertain to technical manual corrections resulting from a hardware change or modification. They may also be specified if it has been determined that significant omissions of technical data or information has been identified. Do not specify a change to correct minor or editorial corrections. When changes are justified on the above basis, the change must include the correction of all outstanding temporary or interim changes and may include minor changes (see 3.1). Whenever the number of change pages is estimated to exceed approximately 25 percent of the total number of pages in the manual, an update revision must be specified in accordance with MIL-M-24784/2.
(d) When the existing cover or title page requires the addition of a current distribution statement, warning, and destruction notice (see 3.3).
(e) Applicable change letter (see 3.3) and technical manual identification number (see 3.5).
(f) The equipment or system models, configurations, and components to be covered (see 3.5).
(g) When change symbols other than vertical lines are permitted (see 3.8).
(h) When rapid action changes are required (see 3.11).
(i) Availability of existing final reproducible copy or printed pages (see 3.11).
(j) When interim changes are required (see 3.12). Note: NAVSEA is prohibited from issuing pen-and-ink changes, except for urgent corrections.
(k) When advanced changes are required for urgent corrections (see 3.12.2).
(l) The Government must specify the number of weeks for review of the draft copy.
(m) When preservation, packing, and marking are other than as specified (see Section 5. PACKAGING).
(n) For classified equipment, attach a DD Form 254 specifying the following:

(1) Security classification.
(2) Downgrading and declassification notification.
(3) Areas requiring security protection.

6.3 Definitions. The words or phrases used throughout this specification must be as defined in MIL-M-24784 and the following.

6.3.1 Advance change notice (ACN). A controlled interim change to selected portions of a technical manual. An ACN is used to correct urgent deficiencies that impact personnel safety, impact mission accomplishment, or could result in damage to or permanent degradation of the equipment.

6.3.2 Copy freeze date. The copy freeze date is a date specified by the Government after which no additions, deletions, or changes will be accepted to the publication material. Additions, deletions, and changes after that date will be accumulated for development of a subsequent change or revision of the publication.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:15Z
Check the source to verify that this is the current version before use.

6.3.3 Distribution statement. A statement used in marking a technical document to denote the conditions of its availability for distribution, release, or disclosure. This statement will be provided by the Government upon request.

6.4 Subject term (key word) listing.

Associated detail specification
Change package
Final reproducible copy
Technical manual
Validation
Verification

Review activities:
Navy - EC

Preparing activity:
Navy - SH
(Project TMSS-N242-01)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:15Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:15Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the comment number and revision letter should be given.

2. The submitter of this form must complete blocks 4, 5, 6, and 7.

3. The preparing activity must provide a reply within 30 days from receipt of this form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-M-24784/1(SH)	2. DOCUMENT DATE (YYMMDD) 940906

3. DOCUMENT TITLE
MANUAL, TECHNICAL CHANGE PACKAGE REQUIREMENTS

4. NATURE OF CHANGE (identity paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

A. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) DSN (if applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

A. NAME Technical Point of Contact (TPOC) MR. MICKEY ANDER, SEA 04TD3 ADDRESS ALL CORRESPONDENCE AS FOLLOWS:	b. TELEPHONE (Include Area Code) (1) Commercial: DSN: TPOC: 703-602-8701 8-332-8701
c. ADDRESS (Include Zip Code) COMMANDER, NAVAL SEA SYSTEMS COMMAND ATTN: SEA 03R42 2531 JEFFERSON DAVIS HIGHWAY ARLINGTON, VA 22242-5160	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403 Falls Church, VA 22041-3466 Telephone 703-756-2340 DSN 289-2340

Source: https://assist.dla.mil -- Downloaded: 202610-20T02:15Z
Check the source to verify that this is the current version before use.