TT-C-598B
AMENDMENT-2
March 17, 1970
SUPERSEDING
AMENDMENT-1
January 28, 1969

FEDERAL SPECIFICATION

CALKING COMPOUND, OIL AND RESIN BASE TYPE
(FOR MASONRY AND OTHER STRUCTURES)

This amendment which forms a part of Federal Specification TT-C-598B, dated March 12, 1965, was approved by the commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

PAGE 1

Paragraph 1.2.1, line 2: After "types" add "as specified (see 6.2)".

Paragraph 2.1, under "Federal Standards": Delete reference to Fed. Std. No. 102.

Paragraph 3.3, line 1: After "specified" add "(see 6.2)".

After paragraph 3.10 add the following:

3.11 Fill. The fill when tested as prescribed in 4.3.11 shall consist of 1/12 gallon net content (volume) in approximately 1/10 gallon cartridge.

PAGE 3

Paragraph 4.3.4, line 15: Delete "groud" and substitute "ground".

PAGE 5

Paragraph 4.3.10, line 12: Delete "vertical" and substitute "horizontal". Line 14: After "pockets" add footnote "1/". Add the following footnote at bottom of page:

1/ If the sample under test is cartridge-packed, the portion of calking used to fill the rheometer tube shall be extruded from a filled newly opened cartridge using a conventional calking gun. If the compound cannot be extruded because of hardened portions blocking the passage of the calking through the nozzle, the Extrusion Test shall be regarded as failed; and the procedure stopped at this point .

PAGE 6

After paragraph 4.3.10: Add the following:

4.3.11 Fill. Determine the weight per gallon of the material in accordance with method 4184 of the Fed. Std. Test Method No. 141. The method of calculation for fill is as follows:

$$\text{Fill} = \frac{\text{gross weight - tare}}{\text{Weight per gallon}}$$

Paragraph 5: Delete first paragraph referencing Fed. Std. No. 102.

Paragraph 5.1.1.1.1.1: Delete and substitute the following:

5.1.1.1.1.1 Type I. The compound shall be unit packaged in 1 pint or 1 gallon round cans conforming to PPP-P-704, type II, class 3, 4, or 5, or cartridges (see 6.2). The container must be resistant to moisture for a period of not less than one year. When the cartridge is utilized, the inner ply of the tube shall be compatible with the product packaged.

FSC 8030

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:17Z
Check the source to verify that this is the current version before use.

Paragraph 5.1.1.1.1.3: Delete and substitute the following:

5.1.1.1.1.3 Intermediate packaging (applicable to cartridges supplied under type I only). Ten (10) cartridges shall be packaged in a close-fitting box conforming to PPP-B-636, W5c. The box shall be closed and waterproof sealed in accordance with the appendix to the box specification.

Paragraph 5.2, title: Delete "Packaging" and substitute "Packing".

Paragraph 5.2.1: Delete and substitute the following:

5.2.1 Level A. The intermediate packages of cartridges or cans of compound shall be packed in close-fitting boxes conforming to PPP-B-585, class 3; PPP-B-591, class II; PPP-B-601, overseas type; PPP-B-621, class 2; PPP-B-636, class weather-resistant or PPP-B-640, class 2, style A. The boxes shall be closed, waterproof sealed, and strapped in accordance with the appendix to the applicable box specification. The gross weight of the triple wall fiberboard box and the wood boxes shall not exceed 200 pounds. The gross weight of the PPP-B-636 fiberboard box shall not exceed the weight limitations of the box specification.

PAGE 7

Paragraph 5.3: Delete.

Paragraph 6.2,"(d)": After "required" add "for Level A (see 5.1.1.1.1.1, 5.1.1.1.1.2" "(f)": Delete.

PAGE 8

Paragraph 6.4: Delete.

☆ U. S. GOVERNMENT PRINTING OFFICE : 1970 O - 395-531 (4525)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:17Z
Check the source to verify that this is the current version before use.