INCH-POUND

MIL-B-63469 (AR)
AMENDMENT 8
16 FEBRUARY 1990
SUPERSEDING
AMENDMENT 7
1 JULY 1987

# MILITARY SPECIFICATION

## BODY ASSEMBLIES, GENERAL PURPOSE GRENADE: M73 AND M75 (PRACTICE)

This Amendment forms a part of Military Specification MIL-B-63469(AR), dated 2 August 1982, and is approved for use within the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of defense.

PAGE 1

2.1.1, Add "MIL-STD-1169 Packaging, Packing, and Marking for Shipment of Inert Ammunition Components".

PAGE 3

* 4.3.1, Add "Retaining Ring and Cone Assembly 9335706 32".

PAGE 5

TABLE I: Welded Tubing: Add

| | | | |
|---|---|---|---|
| "Hydrostatic Test | 1 | 3.3 | 4.5.4" |

Body, M75: Add

| | | | |
|---|---|---|---|
| "Hardness Test | 15 | 3.2 | 4.4.2.9". |

PAGE 6

* TABLE I: Under Body Assembly, M73 General Purpose Grenade (Dwg.9335701), delete:

| | | | |
|---|---|---|---|
| "Pushout Force of Cone to Ring | 32 | 3.2 | 4.5.7" |

AMSC N/A FSC 1330



DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:57Z
Check the source to verify that this is the current version before use.

* Add:

| | | | |
|---|---|---|---|
| "Retaining Ring and Cone Assembly (Dwg. 9335706) | | | |
| Pushout Force of Cone to Ring | 32 | 3.2 | 4.5.7 |
| Examination for defects | 32 | 3.2 | 4.4.2.11" |

PAGE 12

* 4.4.2.5, Delete "Smallest Inside Diameter" and substitute "Fuze Well Diameter" in three places.

PAGE 13

4.4.2.6, Delete in its entirety and substitute included page 3 (13a).

PAGE 14

4.4.2.7, Major 102: Delete "Large Inside Diameter" and substitute "Depth to Datum Diameter".

PAGE 15

* 4.4.2.8, Major 102: Delete "visual" and substitute "4.5.9".

Delete Major 105 in its entirety and substitute:

| | | | |
|---|---|---|---|
| "Yellow band missing or improper | 0.40% | 3.2 | Visual" |

Add Majors 108 and 109:

| | | | |
|---|---|---|---|
| "108 Excess paint in fuze cavity | 0.40% | 3.2 | 4.5.9 |
| 109 Internal staking surface diameter (Note 7) | 0.40% | 3.2 | Gage" |

Page 16

4.4.2.9, Add Major 105:

| | | | |
|---|---|---|---|
| "105 Hardness test | 0.40% | 3.2 | Gage". |

Add Minor 204:

| | | | |
|---|---|---|---|
| "204 Location of bore rider slot | 0.65% | 3.2 | Gage". |

PAGE 17

4.4.2.10, Major: Delete "None Defined".



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

## CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63469 (AR)
AMENDMENT 8

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER 9335705 |
|---|---|---|---|---|---|
| 4.4.2.6 | Cap | | | | NEXT HIGHER ASSEMBLY 9335704 |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| CRITICAL | None defined | | | | |
| MAJOR | | | | | |
| 101 | Angle | | 0.40% | 3.2 | Gage |
| 102 | Overall Height | | 0.40% | 3.2 | Gage |
| MINOR | | | | | |
| 201 | Small inside diameter | | 0.65% | 3.2 | Gage |
| 202 | Evidence of poor workmanship | | 0.65% | 3.5 | Visual |

NOTES:



AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil - Downloaded: 2026-10-23T02:57Z
Check the source to verify that this is the current version before use.

Add Major 101, 102, and Minor 206:

| | | | | |
|---|---|---|---|---|
| "101 | Excess paint in fuze cavity | 0.40% | 3.2 | 4.5.9 |
| 102 | Internal staking surface diameter (Note 11) | 0.40% | 3.2 | Gage |
| 206 | Brown band missing or improper | 0.65%(a) | 3.2 | 4.5.9". |

* Add new paragraph 4.4.2.11 inclosed as Page 17a of this specification.

Add note to note block:

"(a) Minor 206 is not applicable to Simulator Grenade".

PAGE 18

4.5.1, Line 21: delete ".003R" and substitute ".010R".

PAGE 19

4.5.5, Delete in third line, "air" and substitute "air or nitrogen".

PAGE 20

* 4.5.7, Delete in its entirety and substitute:

"4.5.7 Pushout force of cone to retaining ring. Apply a load circumferentially to the cone and in such a direction as to test the strength of the cone to the retaining ring. If any assembly fails to comply with the requirement specified on drawing 9335706, the lot represented by the sample shall be rejected."

* 4.5.8, Delete "After completion of test 4.5.7" and substitute "After completion of test 4.5.6".

Add 4.5.9:

"4.5.9 Paint inspection. Visual standards approved by the Government shall be used to determine acceptability. The painted part shall be visually examined and compared with the visual standards. Any part that is outside the range of the visual standards shall be classed defective."

5.4, Delete first line "5.4 Shipping. When components from more than one lot are" and substitute first line "5.4 Shipping. Palletize in accordance with MIL-STD-1169, Level B. When components from more than one lot are".



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:57Z
Check the source to verify that this is the current version before use.

## CLASSIFICATION OF DEFECTS & TESTS



| PARAGRAPH | TITLE | SHEET | DRAWING NUMBER |
|---|---|---|---|
| 4.4.2.11 | Retaining Ring and Cone Asembly | 1 OF 1 | 9335706 |
| | | | NEXT HIGHER ASSEMBLY: 9334115 |

| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
|---|---|---|---|---|---|
| Critical | None defined. | | | | |
| Major | | | | | |
| 101 | Pushout force of cone to ring. | 32 | | 3.2 | 4.5.7 |
| Minor | | | | | |
| 201 | Evidence of poor workmanship | | 0.65% | 3.5 | Visual |

REMARKS

AMSMC Form 1570, 1 Feb 85 — Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:57Z
Check the source to verify that this is the current version before use.

PAGE 21

6.1, Delete in its entirety and substitute:

"6.1 Intended use. The M73 Body Assembly is intended for use in the M73 General Purpose Grenade. The M75 Body Assembly is intended for use in the M75 General Purpose Practice Grenade and the Simulator Grenade".

6.3, Delete "US Army Armament Research and Development Command, ATTN: DRDAR- QAF-I" and substitute "Armament Research, Development and Engineering Center, US Army Armament, Munitions and Chemical Command, ATTN: AMSMC-QAF-I(D)".

The margins of this amendment are marked with an asterisk or vertical lines to indicate Where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1330-A337)



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:57Z
Check the source to verify that this is the current version before use.