MILITARY
SPECIFICATION

MIL-C-55076(SigC)
Amendment 2
15 May 1963

COMPUTER, HUMIDITY-TEMPERATURE CP-223( )/UM

1. Paragraph 2.1 Under Specifications, Federal- Add:

QQ-S-781	Strapping, Flat; Steel
PPP-F-320	Fiberboard, Sheet, Stock and Cut Shapes
PPP-B-636	Boxes, Fiber

2. Paragraph 4.6.2 - Change table as follows:

a. Column (3) Relative Humidity Line - Humidity Plate, change first item "95" to "100".

b. Column (4) Temperature Marking

(1) Change first item "±25" to "+10".

(2) Change second item "±25" to "+25".

3. Delete Section 5 and replace with the following:

5. PREPARATION FOR DELIVERY

5.1 Preservation and Packaging. -

5.1.1 Level A. - Each Computer, Humidity-Temperature CP-223( )/UM shall be preserved and packaged in accordance with the procedures specified for the designated methods as prescribed in Specification MIL-P-116 and described in the following paragraphs.

5.1.1.1 Computer, Humidity-Temperature CP-223( )/UM and Technical Literature. - Each Computer and each technical literature shall be packaged together Method 1C-6 as follows: Cushion each computer and each technical literature together between two (2) sheets of fiberboard, Type CF, Class Domenstic, conforming to Specification PPP-F-320. Inclose the cushioned computer and technical literature within a close-fitting, Class d bag conforming to Specification MIL-B-117. Heat seal to effect closure.

5.1.1.2 Intermediate Container. - Place twenty (20) unit packages, packaged as specified in 5.1.1.1, within a close-fitting fiberboard box, Type 1, Class 2, conforming to Specification PPP-B-636. Seal the box closure in accordance with the appendix of the box specification.

FSC 6660

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:20Z
Check the source to verify that this is the current version before use.

3. Delete Section 5 and replace with the following:(cont'd)

5.1.2 Level C. - Computer, Humidity-Temperature CP-223( )/UM shall be preserved and packaged in accordance with commercial practice and in a manner that will afford protection against corrosion, deterioration and physical damage during shipment to the first receiving activity.

5.1.3 Package Performance. - Package testing shall be performed in accordance with the requirements of Specification MIL-P-116. The rough handling and functional test will be required only when invoked in the bid request or contract.(See 6.1(d)(2)f.

5.2 Packing.-

5.2.1 Level A. - Eight (8) each intermediate containers packaged as specified in 5.1.1.2 shall be packed in a Class 2 nailed wood box or Class 2, Type III, Style A, cleated plywood box conforming to Specification PPP-B-621 or PPP-B-601, respectively. Fabricate the box to fit the contents snugly. Closure shall be in accordance with the applicable box specification or appendix thereto.

5.2.1.1 Metal Strapping.- Metal strapping conforming to Specification QQ-S-781, Type I, Class b, shall be applied to the wooden shipping container in accordance with the requirements of the applicable box specification and appendix thereof.

5.2.2 Level B. - Eight (8) each intermediate containers shall be packed as specified in 5.2.1 except the nailed wood box shall be Class 1 and the cleated plywood box shall be Type IV, Class 1.

5.2.3 Level C.- Computer, Humidity-Temperature CP-223( )/UM shall be packed in shipping containers of the type, size and kind commonly used for the purpose, in a manner that will insure acceptance by common carrier and safe delivery at destination. Shipping containers shall comply with the Rules or Regulations of the common carrier applicable to the mode of transportation.

5.3 Marking. - Interior packages and exterior shipping containers shall be marked in accordance with the applicable requirements of Military Standard MIL-STD-129.

4. Paragraph 6.1 Add as new sub-paragraph:

6.1(d)(2)f If rough handling and functional tests are required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:20Z
Check the source to verify that this is the current version before use.