MIL-C-63999(A
AMENDMENT 3
3 JUNE 1985
SUPERSEDING
AMENDMENT 2
25 January 19

MILITARY SPECIFICATION

CARTRIDGE, CALIBER .50, BALL, PLASTIC
PRACTICE: M858

This Amendment forms a part of Military Specification MIL-C-63999(AR), dated 16 August 1983, and is approved for by the US Army Armament, Munitions and Chemical Command an available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

3.9: Delete "2750" and "50"; Substitute "2790" and "80" respectively.

PAGE 4

3.11: Delete "600 yards" and substitute "150 meters"

PAGE 5

Table I, Defect 2: Delete "0" for acceptance number and subst "1"; delete "1" for rejection number and substitute "2".

PAGE 7

Table II, Note 3/: Delete "600 yards" and substitute "150 met

PAGE 8

4.4.1.1: Delete in its entirety.

PAGE 9

* 4.4.2.1: Add the following criticals:

"2.	Case split in K, L or M location 1/	100%	3.3	Visua
3.	Case split in I, S or J location when loss of powder occurs 1/	100%	3.3	Visua
4.	Perforated case 1/	100%	3.3	Visua
5.	Cocked primer 1/	100%	3.3	Visua
6.	Inverted primer 1/	100%	3.3	Visua

FSC

DISTRIBUTION STATEMEMT A. Approved for public release; distribution is unli

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

* Delete: Majors 106, 107 and 110 in their entirety.

* Major 109: Delete "Split case 1/ .40" and substitute "Case split in I, S or J location 1/ 100%"

PAGE 10

4.4.2.1: Delete note 3/ in its entirety and substitute the following:

"3/ Failure of the cartridges in the first sample to compl with the applicable requirement shall require testing a second sample consisting of double the quantity of cartridges used in the first tests. Failure of the cartridge in the second sample to comply with the applicable requiremen shall be cause for rejection of the lot."

4.4.2.1: Add: "Major 124. Gap, Max, for 360° between metal head and plastic body .40 3.3 Gage"

* After Note 4/ add: "After the required number of readings have been recorded for velocity and chamber pressure, only action time readings shall be continued to be recorded."

PAGE 12

Table III, Defect 2: Delete "0" for first sample and substitut "1"; delete "1" for cumulative and substitute "2".

PAGE 14

4.5.7: Delete "...for pressure measurement." and substitute: "..for pressure measurement at mid-case position."

PAGE 15

6.5: Delete in its entirety and substitute the following:

"6.5 Contract data requirements. When warranted, requirements for reports of the results of examination and testing shall be specified on DD Form 1423 included in the contract."

6.6: Delete in its entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, correction deletions) from the previous issue were made. This was done convenience only and the government assumes no liability whatsoever for any inaccuracies in these notations. Bidders contractors are cautioned to evaluate the requirements of th document based on the entire content irrespective of the mar notations and relationship to the previous amendment.

Custodian:
Army-AR

Preparing activ
Army-AR

(Project 1305-A

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:08Z
Check the source to verify that this is the current version before use.