Metric
DOD-P-63245A (AR)
AMENDMENT 1
9 MARCH 1982

MILITARY SPECIFICATION

PROJECTILE, HE, 155MM, XM795
METAL PARTS ASSEMBLY

This amendment forms a part of Military Specification DOD-P-63245A (AR) dated 28 September 1981 and is approved for use by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

Delete "XM795" wherever it appears and substitute: "M795".

PAGE 20

4.4.2.7: Add Critial defect 4:

"4. Missing base plate, broken base plate weld or perforated base plate 100% Visual."

PAGE 28

4.5.3.4, line 5: Delete the words "but need not include experience."

PAGE 30

4.5.10: Delete in its entirety and substitute:

"4.5.10 Magnetic particle inspection. The procedures for performing this test utilizing the wet flourescent method shall be as specified in Specification MIL-I-6868 after hydro test, for indirect magnetization by the continuous method. The suspension shall be applied to the entire body inside and outside. The body shall be drained, then thoroughly inspected inside and outside, after inducing a circular magnetic field and then a longitudinal magnetic field in a darkened area under the ultraviolet light which will produce adequate flourescence of the magnetic particles. The solids content of the suspension shall be maintained at a level recommended by the manufacturer. The suspension shall be checked at the start of each days' production and at intervals of not over 4 hours continuous operation, utilizing the procedures and the equipment prescribed by specification MIL-I-6868. When performing the test for the solids content of suspension, if it is determined that it does not comply, all assemblies that have been accepted since the last satisfactory test shall be retested after the suspension has been brought to the proper level. After acceptance, the body assembly shall be demagnetized and cleaned, then stamped as required by

FSC 1320

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:29Z
Check the source to verify that this is the current version before use.

the applicable drawing. The magnetic particle test shall be performed on equipment that complies with the requirements of Specification MIL-I-6867. The operator(s) of the equipment and the inspectors making the determination shall be certified in accordance with MIL-STD-410."

Custodian:
Army - AR

Preparing activity:
Army - AR

(Project: 1320-A631)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:29Z
Check the source to verify that this is the current version before use.