MILITARY SPECIFICATION

FUZE, M934 SERIES, ACTUATORS FOR

This Amendment forms a part of Military Specification MIL-F-63051A (AR) dated 1 July 1985, and is approved for use within the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

Add new paragraph 3.4.8.6 as follows:

3.4.8.6 Moisture Resistance.

PAGE 8

Change the following under GROUP III Bruceton Analysis, subsection Test (All-Fire):

Test (All-Fire): Delete "-40" and substitute "40".

Add new note 5/ as follows:
5/ Arming Actuator P/N 9282665 only

PAGE 12

Add new group as follows:

EXAM or TEST	TEMPERATURE	2/	3/	Reg. Para.	Para. Ref.
GROUP XIII 5/	-40 AMB +140	0	20		
Lead-to-Lead Resistance (Pre-Fire)	20			3.4.3	4.5.3
Insulation Resistance (Pre-Fire)	20			3.4.4.1	4.5.4
Moisture Resistance	20			3.4.8.6	4.5.17
Lead-to-Lead Resistance	20			3.4.3	4.5.3
All Fire Characteristic/ Exhibited Force	20			3.4.6, 3.4.7	4.5.6, 4.5.7
Insulation Resistance (Post-Fire)	20			3.4.4.2	4.5.4
Lead-to-Lead Resistance (Post-Fire) 4/	20			3.4.3	4.5.16

PAGE 15

4.4.2.2 Delete paragraph 4.4.2.2 (page 15) in it's entirety and substitute the following page:

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:07Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.2	Actuator, Arming Actuator, Abort	1	1	9282665/9282666
				NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Environmental Exposure Sequence	1/	0.65%	3.4.8	
MAJOR					
101	Mechanical Shock (Groups A&B) 2/		0.65%	3.4.8.2	4.5.9 (Visual)
102	Sinusoidal Vibration (Groups A&B) 2/		0.65%	3.4.8.3	4.5.10 (Visual)
103	Random Vibration (Groups A&B) 2/		0.65%	3.4.8.4	4.5.11 (Visual)
104	Acceleration (Groups A&B) 2/		0.65%	3.4.8.5	4.5.12 (Visual)
105	Moisture Resistance 4/		0.65%	3.4.8.6	4.5.17 (Visual)
106	Lead-to-Lead Resistance (Pre-Fire) 2/		0.65%	3.4.3	4.5.3 (Ambient)
107	Insulation Resistance (Pre-Fire) 2/		0.65%	3.4.4	4.5.4 (Ambient)
108	No-Fire Characteristic (+140°F)		0.65%	3.4.5	4.5.5
109	All-Fire Characteristic/ Exhibited Force (-50°F)			3.4.6, 3.4.7	4.5.6, 4.5.7
110	Pin Protrusion/Retraction (Post-Fire)		0.65%	3.2	Gage
111	Insulation Resistance (Post-Fire)		0.65%	3.4.4.2	4.5.4 (+140°F)
112	Lead-to-Lead Resistance (Post-Fire) 3/		0.65%	3.4.3	4.5.16 (Ambient)

NOTES:
1/ Number of sample units per 4.4.2/ sample exposed to all test listed.
2/ Samples divided into 2 equal groups, A&B. "A" units tested at +140°F; "B" units tested at -50°F.
3/ Abort actuator P/N 9282666 only
4/ Arming actuator P/N 9282665 only

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:07Z
Check the source to verify that this is the current version before use.

PAGE 18

Add new paragraph 4.5.17 as follows:

4.5.17 Moisture Resistance. Moisture resistance shall be performed in accordance with MIL-STD-202, Method 106, tailored such that sections 3.5 to 3.6.3 inclusive, are excluded from the tests due to the fact that these are one time devices.

Custodian:
Army-AR

Preparing Activity:
Army-AR
(Project 1336-A545)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:07Z
Check the source to verify that this is the current version before use.