MILITARY SPECIFICATION

GRENADES, GP: M42 AND M46, INERT LOADING, ASSEMBLING AND PACKING

This Amendment forms a part of Military Specification MIL-G-70477 (AR) dated 15 February 1985, and is approved for use by the US Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 11

* 4.4.2.5: Note a: delete in its entirety and substitute:

"For each test randomly select 50 samples per lot or select 2 samples per machine at the start of production each day and 2 samples per machine after every 4 hours of production or portion thereof. Reject on 1 or more failures."

PAGE 12

* 4.4.2.6, Critical Defect 1: Add "(Grenade Cap, Fuze, Tape Stiffener Assembly) after "illegible".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:31Z
Check the source to verify that this is the current version before use.

PAGE 15

4.4.3.1: Delete in its entirety and substitute with the following:

"4.4.3.1 Weight of inert filler of body loading assembly (dwg: 9381453 or 9381456) Major defect. The weight of the inert material of the body loading assembly shall be determined on one assembly from each body loading machine at the start of production each day, and after every one hour of production or portion thereof. If the weight of any body loading assembly fails to comply with the drawing requirement, the body loading assemblies produced since the last satisfactory check shall be rejected. In addition, the necessary adjustments shall be made to the machine which will be verified by determining the weight of inert filler of two consecutively produced body loading assemblies. Testing shall be in accordance with paragraph 4.5.2."

4.5.2: Delete in its entirety and substitute with the following:

"4.5.2 Weight of inert filler of body loading assembly The following procedure shall be used to determine the weight of the inert filler of the body loading assembly.

a. Prior to assembly, weigh body assembly with lead cup in air (grams).
b. Load with inert filler using normal production methods.
c. Weigh the assembly in air (grams).
d. Calculate the weight of inert filler in air (c) - (a).

The body assemblies with lead cup inserted shall be randomly selected prior to loading and identified as test samples. Each sample shall be marked clearly with its weight and the applicable inert material consolidation machine number. The samples must be retrieved after powder consolidation but prior to cone insertion."

PAGE 18

* 4.5.4.1: Delete first sentence "The sample assemblies . . . ".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:31Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1330-A261)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:31Z
Check the source to verify that this is the current version before use.