MILITARY SPECIFICATION

MOUNTING, MT-3802( )/ARC

Page 1

2.1 Delete: "MIL-T-5422 Testing, Environmental, Aircraft Electronic Equipment".

Page 4

3.10 Add the following: "The service condition tests shall not affect the isolation efficiency (transmissibility and resonance) of the item."

3.10.1: Delete and substitute:

"3.10.1 Temperature-Vibration combination. (See 4.6.1). - The unit(s) shall meet the performance requirements (using dummy load) when subjected to specified temperature-vibration requirements."

3.10.5 Delete and substitute:

"3.10.5 Vibration (See 4.6.5). - The unit(s) shall meet the vibration requirements for equipment category (s), ~~Method 5.4.1 of MIL-STD-810.~~"

Add new sub-paragraph 3.10.7:

"3.10.7 Dust (See 4.6.7). - The unit(s) shall show no evidence of operational degradation after being subjected to a Dust test conducted in accordance with Method 510 of MIL-STD-810."

Page 6

4.3, Line 5: Insert Roman Numeral "I" preceding RomanNumeral "II".

4.5.1: Delete first sentence and substitute: "Each unit of each lot of equipment shall be inspected for conformance to all the inspection and test requirements of TABLE I. Each lot will be subject to verification utilizing the procedures of MIL-STD-105 using the general inspection levels and the AQL's indicated in TABLE I."

FSC 5810

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:02Z
Check the source to verify that this is the current version before use.

Page 7

TABLE I: - Under Insp Para column: Delete Numbers 4.11, 4.8 and 4.12 and substitute respectively "4.10, 4.7 and 4.11".

TABLE III: Under Subgroup I add "Dust".

Under Rqt Para add "3.10.7".

Under Insp Para add "4.6.7".

Page 9

4.6, Line 2: Change "MIL-T-5422" to "MIL-STD-810".

Lines 5 and 6: Change "temperature-altitude, humidity, fungus and salt spray tests" to "Temperature-Vibration, Humidity, Fungus, Salt-Spray, and Dust Test".

Line 6: Delete "No defects shall be allowed" and substitute "All units, excluding those subjected to the vibration test of Paragraph 4.6.5 shall be subjected to a resonance search in accordance with Method 514.1 of MIL-STD-810, and the results recorded. Following the service condition tests except those of Paragraph 4.6.1 and 4.6.5, a resonance search shall be conducted to verify that the isolation efficiency is within specified requirements. No defects shall be allowed."

4.6.1: Delete and substitute:

"4.6.1 Temperature-Vibration combination. - The test unit(s) with dummy load shall be tested over an operating temperature range of -54°C to 71°C using test Methods 501 and 502 of MIL-STD-810. A resonance search as specified by Method 514.1 of MIL-STD-810 shall be performed at the temperature extremes, to ascertain changes in the resonant frequencies and transmissibility of the test item."

4.6.2: Delete and substitute:

"4.6.2 Relative humidity. - The unit(s) shall be subjected to the test of Method 507 of MIL-STD-810, Procedure II."

4.6.4, Line 2: Change "MIL-T-5422" to "MIL-STD-810".

4.6.5: Delete and substitute:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:02Z
Check the source to verify that this is the current version before use.

4.6.5 Vibration. The unit(s) using dummy load, shall be subjected to the Test Procedure I, Curve Z, Method 5.14.1 of MIL-STD-810 and meet the vibration transmissibility requirements per MIL-C-172 as modified per Drawing SM-C-349413."

4.6.6: Delete and substitute:

4.6.6 Shock, Equipment. - The unit(s) shall be subjected to the test of Method 516, Procedure I and III of MIL-STD-810. The shock pulses shall be in accordance with Figure 546-2 for Flight Vehicle Equipments."

Add new sub-paragraph 4.6.7: -

"4.6.7 Dust. - The unit(s) shall be subjected to the Dust test specified in Method 510 of MIL-STD-810 to determine compliance with 3.10.7."

CUSTODIAN:
Army - EL

Preparing Activity
Army - EL
Project No. 5810-A016

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:02Z
Check the source to verify that this is the current version before use.